



MyBox: Easy Tools Set

User Guide – Data Tools

Author: Mara

Version: 6.6.2

Date: 2022-11-30

Contents

1 Introduction.....	8
1.1 Main Interface.....	8
1.2 Resources Addresses.....	9
1.3 Documents.....	10
1.4 Menu of Tools.....	11
2 Data in Two-dimensional Storage Structure.....	12
2.1 Data Objects.....	12
2.2 Functions Menu.....	13
2.3 Define Columns	14
2.3.1 Interface of Columns Management.....	14
2.3.2 Types of Columns.....	15
2.3.3 Format of Column.....	16
2.3.3.1 Format for Numbers.....	16
2.3.3.2 Format for Datetime/Date.....	17
2.3.3.3 Format for Era.....	18
2.3.3.4 Define Enumeration.....	19
2.3.4 Handle Invalid Values.....	19
2.4 Usages of Columns.....	20
2.4.1 Load Data.....	20
2.4.2 Display Data.....	20
2.4.3 Controls for editing	21
2.4.4 Edit Data Cell.....	22
2.4.5 Save Data.....	24
2.4.6 Calculate Data.....	24
2.4.7 Sort Data.....	25
2.4.8 Color of Column.....	25
2.5 Edit Data.....	26
2.5.1 Mode "Table".....	26
2.5.2 Mode "CSV".....	27
2.5.3 Save and Recover.....	28
2.6 View Data.....	29
2.6.1 View Html.....	29
2.6.2 View CSV.....	30
2.7 Define Data Attributes.....	31
2.8 Row Expression.....	32
2.8.1 Usages of Row Expression.....	32
2.8.2 Edit Row Expression.....	32
2.8.3 Calculate Row Expression.....	33
2.8.4 Examples.....	33
2.9 Row Filter.....	34
2.9.1 Usages of Row Filter	34
2.9.2 Edit Row Filter.....	34
2.9.3 Exmaples.....	35

2.10 Group Rows.....	36
2.10.1 Before and after Grouping.....	36
2.10.2 Usages of grouping.....	36
2.10.3 Group by Equal Values.....	37
2.10.3.1 Way of Grouping.....	37
2.10.3.2 Implementation of Grouping.....	37
2.10.3.3 Results of Grouping.....	38
2.10.4 Group by Value Ranges.....	39
2.10.4.1 Way of Grouping.....	39
2.10.4.2 Split Date/Era.....	40
2.10.4.3 Edit List of “Start-End”.....	41
2.10.4.4 Implementation of Grouping.....	42
2.10.4.5 Results of Grouping.....	42
2.10.5 Group by Conditions.....	43
2.10.5.1 Way of Grouping.....	43
2.10.5.2 Implementation of Grouping.....	43
2.10.5.3 Results of Grouping.....	44
2.10.6 Group by Row Number.....	45
2.10.6.1 Way of Grouping.....	45
2.10.6.2 Implementation of Grouping.....	45
2.10.6.3 Results of Grouping.....	46
2.11 Modify Data.....	47
2.11.1 Add Rows.....	48
2.11.2 Set Values.....	49
2.11.3 Delete.....	50
2.11.4 Set styles / Mark Abnormal Values.....	51
2.11.4.1 Manage Styles.....	51
2.11.4.2 Data Scope.....	52
2.11.4.3 Define Styles.....	53
2.11.4.4 Apply Styles.....	54
2.11.5 Paste Content in System Clipboard.....	55
2.11.6 Paste Content in MyBox Clipboard.....	56
2.12 Trim Data.....	57
2.12.1 Copy/Filter/Query/Convert.....	58
2.12.2 Sort.....	59
2.12.3 Transpose	60
2.12.4 Normalization	61
2.12.5 Split/Group.....	62
2.13 Data Calculation.....	63
2.13.1 Row Expression.....	64
2.13.2 Descriptive Statistic	65
2.13.3 Statistic in Groups.....	66
2.13.3.1 Options of Calculation.....	66
2.13.3.2 Grouped Data.....	67
2.13.3.3 Statistic Data.....	67
2.13.3.4 Data in Chart.....	68

2.13.3.5 XY Chart.....	69
2.13.3.6 Pie Chart.....	70
2.13.4 Simple Linear Regression	71
2.13.4.1 Base of Implementation.....	71
2.13.4.2 Options of Calculation.....	71
2.13.4.3 Regression	71
2.13.4.4 Model.....	72
2.13.4.5 Fitted Chart.....	73
2.13.4.6 Residual Chart.....	74
2.13.5 Simple Linear Regression - Combination	75
2.13.6 Multiple Linear Regression.....	76
2.13.6.1 Regression.....	76
2.13.6.2 Model.....	77
2.13.7 Multiple Linear Regression - Combination.....	78
2.13.8 Frequency Distributions	79
2.13.9 Values Percentage	80
2.14 Data Charts.....	81
2.14.1 XY Chart.....	82
2.14.1.1 Data.....	82
2.14.1.2 Bar Chart.....	83
2.14.1.3 Stacked Bar Chart.....	83
2.14.1.4 Line Chart.....	84
2.14.1.5 Scatter Chart.....	84
2.14.1.6 Bubble Chart.....	85
2.14.1.7 Area Chart.....	86
2.14.1.8 Stacked Area Chart.....	86
2.14.1.9 Parameters of Data in Chart.....	87
2.14.1.10 Layout.....	88
2.14.1.11 Category Axis.....	89
2.14.1.12 Number Axis.....	90
2.14.2 Pie Chart.....	91
2.14.3 Box-and-whisker Chart	92
2.14.3.1 Way of Calculation	92
2.14.3.2 Options of Calculation	93
2.14.3.3 Statistic Data.....	93
2.14.3.4 Options of Chart.....	94
2.14.4 Self Comparison Bars Chart	95
2.14.4.1 Way of Calculation.....	95
2.14.4.2 Options of Calculation	95
2.14.4.3 Options of Chart.....	95
2.14.5 Comparison Bars Chart	97
2.14.5.1 Way of Calculation.....	97
2.14.5.2 Options of Calculation	97
2.14.5.3 Options of Chart.....	97
2.14.6 XYZ Chart.....	99
2.14.6.1 3-D Scatter.....	100

2.14.6.2 Surface Chart.....	101
2.14.7 Locations Distribution.....	103
2.14.7.1 Options of Data.....	103
2.14.7.2 Data in Map.....	103
2.14.7.3 Options of Map.....	104
2.14.7.4 Options of Playing.....	105
2.15 Group Charts.....	106
2.15.1 General Manufacture.....	107
2.15.1.1 Group Data.....	107
2.15.1.2 Results of Grouping.....	108
2.15.1.3 Display Options of Chart.....	109
2.15.1.4 Options of Playing.....	109
2.15.2 Group Data – XY Chart.....	110
2.15.2.1 Specific Options to Generate Chart.....	110
2.15.2.2 Specific Options to Display Chart.....	110
2.15.3 Group Data – Pie Chart.....	111
2.15.3.1 Specific Options to Generate Chart.....	111
2.15.4 Group Data – Box-and-whisker Chart.....	112
2.15.4.1 Specific Options to Generate Chart.....	112
2.15.4.2 Specific Options to Display Chart.....	112
2.15.5 Group Data – Self Comparison Bars Chart.....	113
2.15.5.1 Specific Options to Generate Chart.....	113
2.15.5.2 Specific Options to Display Chart.....	113
2.15.6 Group Data – Comparison Bars Chart.....	114
2.15.6.1 Specific Options to Generate Chart.....	114
2.15.6.2 Specific Options to Display Chart.....	114
2.16 Input Data.....	115
2.16.1 Load Contents in System Clipboard	115
2.16.2 Import Examples.....	116
2.16.2.1 Personal Data.....	116
2.16.2.2 Statistic Data of China.....	117
2.16.2.3 Data of Regression	118
2.16.3 Location Data.....	119
2.17 Output Data.....	120
2.17.1 Export.....	121
2.17.1.1 Data Source.....	121
2.17.1.2 Formats of Targets.....	122
2.17.1.3 Target Files.....	122
2.17.2 Convert to Database Table.....	123
2.18 Manage Data.....	124
2.19 Splice Data.....	125
2.20 Data File.....	126
2.20.1 CSV File.....	126
2.20.2 Text File.....	127
2.20.3 Excel File.....	128
2.20.4 Convert/Split Data Files in Batch.....	129

2.20.5 Merge Data Files	130
2.21 Data in System Clipboard.....	131
2.22 Data in MyBox Clipboard.....	132
2.23 Matrix.....	133
2.23.1 Edit and Manage Matrices.....	133
2.23.2 Unary Matrix Calculation.....	134
2.23.3 Binary Matrices Calculation.....	135
2.24 Database Tables.....	136
2.24.1 Manage Database Tables.....	136
2.24.2 Limitations of SQL Identifier.....	137
2.24.3 Database SQL.....	138
2.24.4 SQL Query.....	139
3 Script and Expression.....	140
3.1 JShell(Java interactive coding tool).....	140
3.1.1 About JShell.....	140
3.1.2 Run Jshell in GUI.....	140
3.2 JEXL(Java Expression Language).....	142
3.2.1 About JEXL.....	142
3.2.2 Run JEXL in GUI.....	142
3.3 Javascript	144
4 Math Function.....	145
4.1 Define Math Functions.....	145
4.2 Calculate Math Function.....	145
4.3 Data Set.....	147
4.4 XY Chart of Unary Function.....	148
4.5 XYZ Chart of Binary Function.....	149
5 Data of Location.....	150
5.1 Data Constraints.....	150
5.1.1 Invalid Value.....	150
5.1.2 Coordinate System:.....	150
5.1.3 Coordinate Values.....	150
5.1.4 Time.....	150
5.1.4.1 Date Formats.....	150
5.1.4.2 Era	150
5.1.4.3 Examples	151
5.2 Data Operations.....	151
5.3 Map Data.....	152
5.4 Geography Code.....	154
5.4.1 Data Definition.....	154
5.4.2 Data Constraints.....	154
5.4.3 Edit Data.....	154
5.4.4 Define Condition.....	154
5.4.5 Import Data.....	154
5.4.5.1 Predefined Data.....	154
5.4.5.2 CSV Format.....	155
5.4.5.3 Data from geoname.org:.....	155


MyBox User Guide – Data Tools v6.6.2

5.4.6 Settings	155
5.5 Location in Map.....	157
5.6 Location Tools.....	158
6 Others.....	159
6.1 Create Barcodes.....	159
6.2 Decode Barcodes.....	159
6.3 Message Digest.....	159
6.4 Encode/Decode Base64.....	159
6.5 Extract ttf files from ttc file.....	159

1 Introduction

This is desktop application based on JavaFx to provide simple and easy functions. It's free and open sources.

1.1 Main Interface



1.2 Resources Addresses


Contents	Link
Project Main Page	https://github.com/Mararsh/MyBox/
Source Codes and Compiled Packages	https://github.com/Mararsh/MyBox/releases
Submit Software Requirements and Problem Reports	https://github.com/Mararsh/MyBox/issues
Data	https://github.com/Mararsh/MyBox_data
Documents	https://github.com/Mararsh/MyBoxDoc
Mirror Site	https://sourceforge.net/projects/mara-mybox/files/
Cloud Storage	https://pan.baidu.com/s/1fWMRzym_jh075OCX0D8yA#list/path=%2F

The screenshot shows the GitHub repository page for [Mararsh / MyBox](https://github.com/Mararsh/MyBox). The page includes a header with various icons, a search bar, and navigation links like Pull requests, Issues, Marketplace, and Explore. Below the header, there's a main content area with tabs for Code, Issues (41), Pull requests, Discussions, Actions, Projects, Wiki, Security, Insights, and Settings. The Code tab is selected. A red circle highlights the 'Code' button in the top right of this section. The main content area shows a list of commits for branch master, with one commit highlighted: 'Mararsh a6.5.9' (790ff01, 5 hours ago, 573 commits). Below the commits is a file tree for README.md. At the bottom right, a red circle highlights the 'Releases' section, which shows a latest release 'v6.5.8' (18 days ago) and '+ 88 releases'.

1.3 Documents

Name	Version	Time	English	Chinese
Development Logs	6.6.2	2022-11-30	html	html
Shortcuts	6.5.6	2022-6-11	html	html
Functions list	6.6.2	2022-11-30	html	html
Packing Steps	6.3.3	2020-9-27	html	html
Development Guide	2.1	2020-8-27	PDF	PDF
User Guide - Overview	6.6.2	2022-11-30	html PDF odt	html PDF odt
User Guide - Data Tools	6.6.2	2022-11-30	html PDF odt	html PDF odt
User Guide - Document Tools	6.6	2022-9-28	html PDF odt	html PDF odt
User Guide - Image Tools	6.6	2022-9-28	html PDF odt	html PDF odt
User Guide - File Tools	6.6	2022-9-28	html PDF odt	html PDF odt
User Guide - Network Tools	6.6	2022-9-28	html PDF odt	html PDF odt
User Guide - Media Tools	6.6	2022-9-28	html PDF odt	html PDF odt
User Guide - Development Tools	6.6.2	2022-11-30	html PDF odt	html PDF odt
Examples - Notes	6.6.1	2022-11-16	html	html
Examples - Information in Tree	6.6.1	2022-11-16	html	html
Examples - Favorite Address	6.6.1	2022-11-16	html	html
Examples - SQL	6.6.1	2022-11-16	html	html
Examples - JShell	6.6.1	2022-11-16	html	html
Examples - JEXL	6.6.1	2022-11-16	html	html
Examples - JavaScript	6.6.1	2022-11-16	html	html
Examples - Math Function	6.6.1	2022-11-16	html	html
Examples - Row Filter	6.6.1	2022-11-16	html	html
About - Color	6.6.1	2022-11-16	html	html
About - Coordinate System	6.6.1	2022-11-16	html	html
About - Media	6.6.1	2022-11-16	html	html
About - Data Analysis	6.6.1	2022-11-16	html	html
Palette - Common Web Colors	6.6.1	2022-11-16	html	html
Palette - Chinese Traditional Colors	6.6.1	2022-11-16	html	html
Palette - Japanese Traditional Colors	6.6.1	2022-11-16	html	html
Palette - Colors from colorhexa.com	6.6.1	2022-11-16	html	html
Palette - MyBox Colors	6.6.1	2022-11-16	html	html

1.4 Menu of Tools



2 Data in Two-dimensional Storage Structure

2.1 Data Objects

1. Following objects can be edited in consistent way:

- Data files, including CSV File, Excel file, texts file.
- Data of MyBox Clipboard
- Matrices
- Database tables.

2. Data are represented as two-dimensional storage structure:

- "Columns" define dimensions of data in horizontal direction.
- "Rows" save values of data in vertical direction..
- Data should be in same width. That is all rows have equal number of columns.

Tabl...	Data ...	age					
1	1	59					
2	2	48					
3	3	72					
4	4	24					
5	5	50					
6	6	23					
7	7	36					
8	8	66					
9	9	60					
10	10	29	1	30	85	180	93.4
11	11	22	1	18.6	97	114	57.6
12	12	56	2	28	85	184	144.8
13	13	53	1	23.7	92	186	109.2
14	14	50	2	26.2	97	186	105.4

2.2 Functions Menu

Hover or click button “Functions” top pop Functions Menu.

The screenshot shows the MyBox Data Tools interface with a CSV file named "DiabetesPrediction_en.csv" loaded. The "Edit" tab is selected in the top navigation bar. A context menu is open over a table cell, with the "Data" option highlighted and circled in blue. The "Data" menu contains options like Save, Recover, Refresh, Open, Create data, Load content in system clipboard, Export, Convert to database table, Modify, Trim, Calculation, Charts, Examples, and a checked checkbox for "Pop when mouse hovering".

Index	Glucose	B.P.	Skin	Insulin	B.F.	Age	Class
1	1	59				255	185
2	2	48				56	4.55
3	3	72					
4	4	24					
5	5	50					
6	6	23					
7	7	36					
8	8	66	2	26.2	114		
9	9	60	2	32.1	83	179	119.4
10	10	29	1	30	85	180	93.4
11	11	22	1	18.6	97	114	57.6
12	12	56	2	28	85	184	144.8
13	13	53	1	23.7	92	186	109.2
14	14	50	2	26.2	97	186	105.4

Selected: 0 Rows: 50/442 Page size 50 / Page 1 / 9

2.3 Define Columns

2.3.1 Interface of Columns Management


Under tab “Columns”, add/delete/change columns in table view:

1. Column names should not be null nor duplicated.
2. Click table cell to edit value directly.
3. Select one row and click button “Edit” to open edit window.
4. Can rename all columns with sequence numbers.
5. Can set random colors.
6. Can adjust orders of columns.
7. Click button "OK" to apply modifications of columns to "Table" of current data.
8. Click button "Cancel" to discard modifications of columns and pick data from "Table" of current data.
9. When changes have not been saved, if modifications have not been applied to data, “**” is displayed in tab header, or else “*” is displayed in tab header.

Ta...	Index	Column name	Type	Color	Width	Editable	Not null	Separat...
<input type="checkbox"/>	1	age	Double	[Color Box]	61	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
<input type="checkbox"/>	2	sex	Short	[Color Box]	100	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
<input type="checkbox"/>	3	BMI(body mass index)	Double	[Color Box]	-----	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
<input checked="" type="checkbox"/>	4	BP(average blood pressure)	Double	[Color Box]	0x9E556AFF	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
<input type="checkbox"/>	5	S1(blood serum measurement 1)	Double	[Color Box]	#9E556A	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
<input type="checkbox"/>	6	S2(blood serum measurement 2)	Double	[Color Box]	-6400662	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
<input type="checkbox"/>	7	S3(blood serum measurement 3)	Double	[Color Box]	sRGB: 158 85 106 100%	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
<input type="checkbox"/>	8	S4(blood serum measurement 4)	Double	[Color Box]	HSB: 343 46% 62%	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
<input type="checkbox"/>	9	S5(blood serum measurement 5)	Double	[Color Box]	Adobe RGB: 141 86 105	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
<input type="checkbox"/>	10	S6(blood serum measurement 6)	Double	[Color Box]	Apple RGB: 137 64 87	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
<input type="checkbox"/>	11	disease progression one year after ...	Double	[Color Box]	ECI RGB: 148 93 115	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>

2.3.2 Types of Columns

1. Types of columns include: String, Double, Float, Long, Integer, Short, Boolean, Datetime, Date, Era, Longitude, Latitude, Enumeration, Color.
2. This attribute is used to display, edit, calculate, and save data.
3. Longitude and Latitude are defined together generally.




2.3.3 Format of Column

1. This attribute is mainly for display. When data are inputted/edited, formats are not applied automatically and original inputs are kept.
2. In some interfaces, like "Copy" or "Export", options "Save date/time/era and numbers as columns' formats" can be checked.


2.3.3.1 Format for Numbers

To numbers, format can be: group in thousands, group in ten thousands, scientific notation, and no format.




2.3.3.2 Format for Datetime/Date

To Datetime/Date, following are supported in formats: MM/dd/yy, yy-MM-dd, milliseconds, time zone, T separator, patch century, etc..




2.3.3.3 Format for Era

To Era, following are supported in formats: MM/dd/yy, yy-MM-dd, milliseconds, time zone, T separator, patch century, prefix/suffix of “AD” and “BC” in Chinese and English,etc..



2.3.3.4 Define Enumeration

To Enumeration, list of values can be defined.



2.3.4 Handle Invalid Values

1. How columns handle invalid values, including: skip, count as empty, and count as zero.
2. In some context, “count as empty” equals to “skip”.
3. This attribute is only used for display or calculation. When data are inputted/edited, invalid values are not handled automatically.

2.4 Usages of Columns

Principle of column usages is “Most tolerability and least manufacture”.

2.4.1 Load Data

When load data, types of columns are not checked, and original values are read and imported.

2.4.2 Display Data

1. Parse values as columns' types.
2. Handle invalid values as columns' definitions.
3. Rewrite values as columns' formats.
4. Displayed values may be different from current actual values.
5. Example, Column type is Double and value “abc” is read:
 - If count invalid as zero, then display it as zero(actual value is still “abc”).
 - If skip or count invalid as empty, then display it as “abc”.

Table r...	Data...	year_	populatio...	male(ten t...	female(te...	urban(ten ...	rural(ten t...	
<input type="checkbox"/>	1	1949	5,4167	28,145	26022	5765	48402	
<input type="checkbox"/>	2	1950	5,5196	28,669	26527	6169	49027	
<input type="checkbox"/>	3	1951	5,6300	29,231	27069	6632	49668	
<input type="checkbox"/>	4	1952	5,7482	29,833	27649	7163	50319	
<input checked="" type="checkbox"/>	5	1953	58796	30,468	28328	7826	50970	
<input type="checkbox"/>	6	1954	6,0266	31,242	29024	8249	52017	
<input type="checkbox"/>	7	1955	6,1465	31,809	29656	8285	53180	
<input type="checkbox"/>	8	1956	6,2828	32,536	30292	9185	53643	
<input type="checkbox"/>	9	1957	6,4653	33,469	31184	9949	54704	
<input type="checkbox"/>	10	1958	6,5994	34,195	31799	10721	55273	
<input type="checkbox"/>	11	1959	6,7207	34,890	32317	12371	54836	
<input type="checkbox"/>	12	1960	6,6207	34,283	31924	13073	53134	
<input type="checkbox"/>	13	1961	6,5859	33,880	31979	12707	53152	
<input type="checkbox"/>	14	1962	6,7296	34,517	32778	11659	55636	


2.4.3 Controls for editing

- To Boolean, checkbox is provided.
- To Enumeration, list view is provided with selections.
- To Color, palette is provided.
- To Longitude and Latitude, map can be popped to locate coordinate.

Edit CSV File : CSV - 943 - d:\tmp\mybox-data-6.5.9\data\HeartFailure_en.csv *

Table r...	Data...	age	anaemia	creatinine...	diabetes	ejection fr...	high bloo...	platelets(k...	
<input type="checkbox"/> 1	1	61-80	<input type="checkbox"/>	582	<input type="checkbox"/>	20	<input checked="" type="checkbox"/>	265000	1
<input type="checkbox"/> 2	2	41-60	<input type="checkbox"/>	7861	<input type="checkbox"/>	38	<input type="checkbox"/>	263358.03	1
<input type="checkbox"/> 3	3	61-80	<input type="checkbox"/>	146	<input type="checkbox"/>	20	<input type="checkbox"/>	162000	1
<input type="checkbox"/> 4	4	41-60	<input checked="" type="checkbox"/>	111	<input type="checkbox"/>	20	<input type="checkbox"/>	210000	1
<input type="checkbox"/> 5	5	61-80	<input checked="" type="checkbox"/>	160	<input checked="" type="checkbox"/>	20	<input type="checkbox"/>	327000	2
<input checked="" type="checkbox"/> 6	6	81-...	<input checked="" type="checkbox"/>	47	<input type="checkbox"/>	40	<input checked="" type="checkbox"/>	204000	2
<input type="checkbox"/> 7	7	1-20	<input checked="" type="checkbox"/>	246	<input type="checkbox"/>	15	<input type="checkbox"/>	127000	1
<input type="checkbox"/> 8	8	21-40	<input checked="" type="checkbox"/>	315	<input checked="" type="checkbox"/>	60	<input type="checkbox"/>	454000	1
<input type="checkbox"/> 9	9	41-60	<input type="checkbox"/>	157	<input type="checkbox"/>	65	<input type="checkbox"/>	263358.03	1
<input type="checkbox"/> 10	10	61-80	<input checked="" type="checkbox"/>	123	<input type="checkbox"/>	35	<input checked="" type="checkbox"/>	388000	9
<input type="checkbox"/> 11	11	81-100	<input checked="" type="checkbox"/>	81	<input type="checkbox"/>	38	<input checked="" type="checkbox"/>	368000	4
<input type="checkbox"/> 12	12	61-80	<input type="checkbox"/>	231	<input type="checkbox"/>	25	<input checked="" type="checkbox"/>	253000	0
<input type="checkbox"/> 13	13	41-60	<input checked="" type="checkbox"/>	981	<input type="checkbox"/>	30	<input type="checkbox"/>	136000	1
<input type="checkbox"/> 14	14	41-60	<input checked="" type="checkbox"/>	168	<input type="checkbox"/>	38	<input checked="" type="checkbox"/>	276000	1

Selected: 1 Rows: [1-50]50/299 Page size 50 Page 1 /6



2.4.4 Edit Data Cell

- When user clicks a data cell in table view, editing is started. Its original value is displayed, while both type and format of column are ignored.
- While user inputs and modifies the value, value in the edit control is checked by column type:
 - If value is invalid, then edit control is displayed in abnormal color.
 - If value is valid, then edit control is displayed in normal color.
 - The value is always kept as what user has inputted.
- When focus leaves the data cell, value in the edit control is checked:
 - If value is not changed, then no checking of column type nor saving.
 - If value is changed, then check the changed value as column type:
 - To invalid value, discard it, and then restore and display original value.
 - To valid value, submit and save as new value, and then display saved value as type and format of the column.

4. Example, column type is Double, count invalid as empty, and decimal scale is 2. When read “abc”:
 - The data cell is displayed as “abc”.
 - User modifies it as “abc123”:
 - While user inputs the change, the text field is always in abnormal color.
 - After user clicks Enter or other control, this data cell comes back as “abc” in normal color.
 - User modifies it as “123.4567”:
 - While user inputs the change, the text field is always in normal color.
 - After user clicks Enter or other control, this data cell is saved as “123.4567” and displayed as “123.46”.
5. Other data cells are not affected. That is, data cells are always in original values if they are not changed.

MyBox Edit CSV File : CSV - 943 - d:\tmp\mybox-data-6.5.9\data\HeartFailure_en.csv

Window Document Image Data File Media Network Settings Recent Accessed Development Help

Columns Attributes View Edit Table CSV

Selected: 1 Rows: [1-50]50/299 Page size 50 Page 1 /6

Table r...	Data...	age	anaemia	creatinine...	diabetes	ejection fr...	high bloo...	platelets(k...	...
<input type="checkbox"/>	1	75	<input type="checkbox"/>	582	<input type="checkbox"/>	20	<input checked="" type="checkbox"/>	265000	1
<input type="checkbox"/>	2	55	<input type="checkbox"/>	7861	<input type="checkbox"/>	38	<input type="checkbox"/>	263358.03	1
<input type="checkbox"/>	3	65	<input type="checkbox"/>	146	<input type="checkbox"/>	20	<input type="checkbox"/>	162000	1
<input type="checkbox"/>	4	50	<input checked="" type="checkbox"/>	111	<input type="checkbox"/>	20	<input type="checkbox"/>	210000	1
<input type="checkbox"/>	5	65	<input checked="" type="checkbox"/>	160	<input checked="" type="checkbox"/>	20	<input type="checkbox"/>	327000	2
<input type="checkbox"/>	6	90	<input checked="" type="checkbox"/>	47	<input type="checkbox"/>	40	<input checked="" type="checkbox"/>	204000	2
<input checked="" type="checkbox"/>	7	75	<input checked="" type="checkbox"/>	246abd	<input type="checkbox"/>	15	<input type="checkbox"/>	127000	1
<input type="checkbox"/>	8	60	<input checked="" type="checkbox"/>	315	<input checked="" type="checkbox"/>	60	<input type="checkbox"/>	454000	1
<input type="checkbox"/>	9	65	<input type="checkbox"/>	157	<input type="checkbox"/>	65	<input type="checkbox"/>	263358.03	1
<input type="checkbox"/>	10	80	<input checked="" type="checkbox"/>	123	<input type="checkbox"/>	35	<input checked="" type="checkbox"/>	388000	9
<input type="checkbox"/>	11	75	<input checked="" type="checkbox"/>	81	<input type="checkbox"/>	38	<input checked="" type="checkbox"/>	368000	4
<input type="checkbox"/>	12	62	<input type="checkbox"/>	231	<input type="checkbox"/>	25	<input checked="" type="checkbox"/>	253000	0
<input type="checkbox"/>	13	45	<input checked="" type="checkbox"/>	981	<input type="checkbox"/>	30	<input type="checkbox"/>	136000	1
<input type="checkbox"/>	14	50	<input checked="" type="checkbox"/>	168	<input type="checkbox"/>	38	<input checked="" type="checkbox"/>	276000	1
<input type="checkbox"/>	15	49	<input checked="" type="checkbox"/>	80	<input type="checkbox"/>	30	<input checked="" type="checkbox"/>	427000	1
<input type="checkbox"/>	16	82	<input checked="" type="checkbox"/>	379	<input type="checkbox"/>	50	<input type="checkbox"/>	47000	1

2.4.5 Save Data

1. Values are written into file of CSV/Texts/Excel as strings.
2. Values are written into database table as nearest types:

Column Type of MyBox	Data Type of JDBC
String	VARCHAR
Double	DOUBLE
Float	FLOAT
Long	BIGINT
Integer	INT
Short	SMALLINT
Boolean	BOOLEAN
Datetime	TIMESTAMP
Date	DATE
Era	BIGINT
Longitude	DOUBLE
Latitude	DOUBLE
Enumeration	VARCHAR
Color	VARCHAR

Notice: derby does not support negative date, so Ear is saved as long.

3. All values in Matrix are saved as Double.

2.4.6 Calculate Data

1. Data are handled as original values, without concern about types and formats of columns.
2. Values are parsed as need. Example, if the calculation requires double values, then try to convert values as doubles.
3. If value conversion fails, then invalid value is handled as definition of column.
4. Calculation itself can define how to handle invalid values. Definition of calculation priors to definition of column.
5. Both column and calcultion can define decimal scale. Definition of calculation priors to definition of column.
6. Example, Column type is String, and descriptive statistic is running against it:
 - Try to convert each value as double.
 - If “count invalid value as zero”, then invalid values are calculated into “Count”, and participate in calculations of “Mean” and “Sum”.
 - If “skip invalid value”, then invalid values are not involved in any calculation.
 - If “count invalid value as empty”, then invalid values cause results of all calculations as invalid(Double.NaN).

2.4.7 Sort Data

1. For any calculations involved in sorting, data will be translated into a temporary database table, and be sorted by database system.
2. Results of sorting are related to columns' types. Example, string “124” is smaller than string “18”, while number “124” is bigger than number “18”.

2.4.8 Color of Column

Column color is mainly used for data charts.

When chart is generated, elements in it are displayed in colors as their columns' definitions.. Then user can set chart in random colors.

2.5 Edit Data

2.5.1 Mode "Table"

"Table" is the master edit mode:

1. Its modifications are applied to other panes automatically.
2. It is the final data to save.
3. To string values, except for text file, multiple lines can be edited and saved:
 - When the value is single line(not contain line break):
 - Text field is shown when click the data cell.
 - Write "\n" as line break in the value and commit the change(return or click other place).
 - When the value contains line breaks:
 - Text area is shown when click the data cell.
 - Write the text in multiple lines directly.

Table r...	Data...	SepalLeng...	SepalWidt...	PetalLeng...	PetalWidt...	Species
<input type="checkbox"/> 1	1	5.1	3.5	1.4	0.2	Iris-setosa
<input type="checkbox"/> 2	2	4.9	3	1.4	0.2	Iris-setosa
<input checked="" type="checkbox"/> 3	3	4.7	3.2	1.3	0.2	Iris-setosa multiple lines
<input type="checkbox"/> 4	4	4.6				Iris-setosa
<input type="checkbox"/> 5	5	5				
<input type="checkbox"/> 6	6	5.4				
<input type="checkbox"/> 7	7	4.6				
<input type="checkbox"/> 8	8	5				
<input type="checkbox"/> 9	9	4.4				
<input type="checkbox"/> 10	10	4.9				
<input type="checkbox"/> 11	11	5.4				
<input type="checkbox"/> 12	12	4.8				
<input type="checkbox"/> 13	13	4.8				
<input type="checkbox"/> 14	14	4.3				
<input type="checkbox"/> 15	15	5.8				

Selected: 0 Rows: [1-50]50/150 Page size 50 Page 1 /3

2.5.2 Mode "CSV"

"CSV" is the assist edit mode.

1. Click button "OK" to apply its modifications to "Table".
2. Click button "Cancel" to discard its modifications and pick data from "Table".
3. Click button "Delimiter" to pick data from "Table" and apply new delimiter while its modifications are discarded.
4. If value contains delimiter or line break, it should be surrounded by quotes.

MyBox Edit CSV File : CSV - 947 - d:\tmp\mybox-data-6.5.9\data\IrisSpecies_en.csv *

Window Document Image Data File Media Network Settings Recent Accessed Development Help

SepalLengthCm,SepalWidthCm,PetalLengthCm,PetalWidthCm,Species


5.1,3.5,1.4,0.2,Iris-setosa
4.9,3.0,1.4,0.2,Iris-setosa
4.7,3.2,1.3,0.2,"Iris-setosa
multiple lines"
4.6,3.1,1.5,0.2,"a,b,c,contains delimiter"
5.0,3.6,1.4,0.2,Iris-setosa
5.4,3.9,1.7,0.4,Iris-setosa
4.6,3.4,1.4,0.3,Iris-setosa
5.0,3.4,1.5,0.2,Iris-setosa
4.4,2.9,1.4,0.2,Iris-setosa
4.9,3.1,1.5,0.1,Iris-setosa
5.4,3.7,1.5,0.2,Iris-setosa
4.8,3.4,1.6,0.2,Iris-setosa
4.8,3.0,1.4,0.1,Iris-setosa
4.3,3.0,1.1,0.1,Iris-setosa
5.8,4.0,1.2,0.2,Iris-setosa
5.7,4.4,1.5,0.4,Iris-setosa
5.4,3.9,1.3,0.4,Iris-setosa
5.1,3.5,1.4,0.3,Iris-setosa
5.7,3.8,1.7,0.3,Iris-setosa

If a value contains delimiter or line break, it should be surrounded by quotes.

Selected: 0 Rows: [1-50]50/150 Page size 50 Page 1 /3

2.5.3 Save and Recover

1. When changes are not saved, * is displayed in tab header.
2. Click button "Save" to write modifications to file and database:
 - Changes of rows in "Table", including modify/add/delete/sort, affect rows of current page in file.
 - Changes in "Columns" tab, including modify/add/delete/sort, affect all rows in file.
 - Changes of attributes and columns are saved in database.
3. Click button "Recover" to discard all modifications and load data from file and database.



2.6 View Data

2.6.1 View Html

1. View data of current data.
2. Options: Form, Title, Column Names, Row Numbers.

MyBox Edit CSV File : CSV - 947 - d:\tmp\mybox-data-6.5.9\data\IrisSpecies_en.csv *

Window Document Image Data File Media Network Settings Recent Accessed Development Help

Form Title Column name Row number

Columns* Attributes **View** Edit*

d:\tmp\mybox-data-6.5.9\data\IrisSpecies_en.csv

Row number	SepalLengthCm	SepalWidthCm	PetalLengthCm	PetalWidthCm	Species
Row1	5.1	3.5	1.4	0.2	Iris-setosa
Row2	4.9	3	1.4	0.2	Iris-setosa
Row3	4.7	3.2	1.3	0.2	Iris-setosa multiple lines
Row4	4.6	3.1	1.5	0.2	a,b,c,contains delimiter
Row5	5	3.6	1.4	0.2	Iris-setosa
Row6	5.4	3.9	1.7	0.4	Iris-setosa
Row7	4.6	3.4	1.4	0.3	Iris-setosa
Row8	5	3.4	1.5	0.2	Iris-setosa
Row9	4.4	2.9	1.4	0.2	Iris-setosa

H2

Selected: 0 Rows: [1-50]50/150 Page size 50 ▾ Page 1 ▾ /3

Html CSV

2.6.2 View CSV

1. View data of current data.
2. Options: Form, Title, Column Names, Row Numbers.
3. Set delimiter.

The screenshot shows the MyBox Data Tools interface for viewing CSV files. The main window displays the contents of 'IrisSpecies_en.csv' located at 'd:\tmp\mybox-data-6.5.9\data\'. The toolbar at the top includes various icons for file operations and data analysis. The 'View' button in the toolbar is circled in blue. To the right, a vertical sidebar has tabs for 'HTML' and 'CSV', with 'CSV' also circled in blue. A small 'MyBox: Set of Easy Tools' dialog box is open in the center, titled 'Text delimiter', showing various options for setting the delimiter character. The bottom of the screen shows standard navigation controls for selecting rows and pages.

Selected: 0 Rows: [1-50]50/150 Page size 50 Page 1 /3

	SepalLengthCm	SepalWidthCm	PetalLengthCm	PetalWidthCm	Species
1	5.1	3.5	1.4	0.2	Iris-setosa
2	4.9	3	1.4	0.2	Iris-setosa
3	4.7	3.2	1.3	0.2	"Iris-setosa
multiple lines"					
4	4.6	3.1	1.5	0.2	a,b,c,contains delimiter
5	5	3.6	1.4	0.2	Iris-setosa
6	5.4	3.9	1.7	0.4	Iris-setosa
7	4.6	3.4	1.4	0.3	Iris-setosa
8	5	3.4	1.5	0.2	Iris-setosa
9	4.4	2.9	1.4	0.2	Iris-setosa
10	4.9	3.1	1.5	0.1	Iris-setosa
11	5.4	3.7	1.5	0.2	Iris-setosa
12	4.8	3.4	1.6	0.2	Iris-setosa
13	4.8	3	1.4	0.1	Iris-setosa
14	4.3	3	1.1	0.1	Iris-setosa
15	5.8	4	1.2	0.2	Iris-setosa
16	5.7	4.4	1.5	0.4	Iris-setosa
17	5.4	3.9	1.3	0.4	Iris-setosa
18	5.1	3.5	1.4	0.3	Iris-setosa

2.7 Define Data Attributes

Data name, decimal scale, and maximum value of random.

The screenshot shows the MyBox Data Tools application window. The title bar reads "Edit CSV File : CSV - 7 - d:\tmp\mybox-data-6.5.9\data\SouthGermanCredit_en.csv". The menu bar includes "Window", "Document", "Image", "Data", "File", "Media", "Network", "Settings", "Recent Accessed", "Development", and "Help". The toolbar features various icons for file operations like Open, Save, Print, and Find. The main area has tabs for "Columns" and "Attributes", with "Attributes" currently selected. A sub-toolbar below the tabs includes icons for "View", "Edit", and "Delete". The central workspace displays the following configuration for the CSV file:

- ID**: 7
- Data type**: CSV
- Data name**: South German credit
- Decimal scale**: 2
- Maximum value of random**: 1000
- Description** (in a text box):

http://archive.ics.uci.edu/ml/datasets/South+German+Credit
700 good and 300 bad credits with 20 predictor variables. Data from 1973 to 1975. Stratified sample from actual credits with bad credits heavily oversampled. A cost matrix can be used.
- Update time**: 2022-09-28 11:17:37
- File details** (in a scrollable pane):
 - File: d:\tmp\mybox-data-6.5.9\data\SouthGermanCredit_en.csv
 - File size: 46.934 KB
 - File modify time: 2022-09-28 11:17:35
 - Charset: UTF-8
 - Delimiter: ,
 - First line defines the columns' names: Yes
 - Lines number in file: 1000
 - Columns number: 21
 - Current page: 1 / 20
 - Rows range in page: 1 - 50 (50)
 - Page modify time: 2022-09-28 11:17:40

At the bottom, there are buttons for "Selected: 0", "Rows: 50/1000", "Page size: 50", "Page: 1 / 20", and navigation arrows.

2.8 Row Expression

2.8.1 Usages of Row Expression


JavaScript expression can be data values when manufacture/trim/calculate data or generate chart.

2.8.2 Edit Row Expression

1. If the script is blank, then return empty string.
2. It can include any valid elements which Nashorn can parse(ECMAScript 5.1).
3. It should be a value finally.
4. It can include following placeholders:

```
#{{TableRowNumber}}
#{{DataRowNumber}}
#{{<column_name>}}
#{{<column_name>- <statistic-name>}}
```

5. All valid placeholders are listed in left.
6. To save the script, click "Edit" button.
7. Hover or click button “Examples” to paste example codes.
8. Hover or click button “Histories” to paste codes in histories.



2.8.3 Calculate Row Expression

When MyBox evaluates the expression:

1. Placeholders are replaced with actual values of each data row.
2. Statistic values are calculated by all data.
3. '#{xxx}' is handled as string while #{{xxx}} is handled as number.
4. When handles all pages, script fails when it includes “#{TableRowNumber}” .

2.8.4 Examples

expression	meaning
#DataRowNumber} % 2 == 0	data row number is even
#TableRowNumber} % 2 == 1	odd rows in current page
Math.abs(#{v1}) + Math.PI * Math.sqrt(#{v2})	calculation
'#{v1}'.replace(/hello/ig, 'Hello')	replace all “hello”(case-insensitive) as “Hello” in column “v1”
'#{v1}'.toLowerCase()	lower case of value of column “v1”
'#{v1}'.split(',')	split value of column “v1” by comma
#{v1} - #{v1-Mean}	difference between value of column “v1” and mean of column “v1”
new Date('#{time}'.replace(/-/g,'/')).getFullYear()	year of value of column “time”


2.9 Row Filter

2.9.1 Usages of Row Filter

“Row Filter” is special “Row Expression”, and can be condition to filter data rows.

2.9.2 Edit Row Filter

1. It should be boolean value("true" or "false") finally.
2. Can set maximum rows to take.
3. Can be saved in tree.



2.9.3 Examples

Expression	meaning
<code>#{{DataRowNumber}} % 2 == 0</code>	data row number is even
<code>#{{TableRowNumber}} % 2 == 1</code>	odd rows in current page
<code>Math.abs(#{{v1}}) >= 0</code>	value of column “v1” is number
<code>#{{v1}} > 0</code>	value of column “v1” is larger than zero
<code>#{{v1}} - #{{v2}} < 100</code>	difference between values of “v1” and “v2” is less than 100
<code>'#{{v1}}' == ''</code>	value of column “v1” is null or empty
<code>'#{{v1}}'.length > 0</code>	value of column “v1” is not empty
<code>'#{{v1}}'.search(/Hello/ig) >= 0</code>	value of column “v1” includes “Hello”(case-insensitive)
<code>'#{{v1}}'.startsWith('Hello')</code>	value of column “v1” starts with “Hello”
<code>var array = ['A', 'B', 'C'];array.includes('#{{v1}}')</code>	value of column “v1” is one of “A”, “B”, “C”
<code>#{{v1}} < #{{v1-Mean}}</code>	value of column “v1” is less than mean of column “v1”
<code>new Date('#{{time}}'.replace(/-/g,'/')).getTime() > new Date('2016/05/19 09:23:12').getTime()</code>	value of column “time” is later than '2016/05/19 09:23:12'

2.10 Group Rows

2.10.1 Before and after Grouping

1. Before grouping, rows can be filtered. That is, objects of grouping are filtered rows.
2. In order to implement sorting and statistic with database system, data are converted as temporary database table automatically before grouping.
3. Sorting condition and maximum data number of each group can be set for grouped data.

2.10.2 Usages of grouping

With grouped data, following can be handled:

1. Add grouping information in source data, which are 2 new columns: Group Number and Group Parameter.
2. Split data into multiple files of groups.
3. Calculate descriptive statistic of groups.
4. Display following types of charts in sequence of groups dynamically: XY chart, pie chart, comparison bars chart, self comparison bars chart, box-and-whisker chart.

2.10.3 Group by Equal Values

2.10.3.1 Way of Grouping

Select several columns and put rows into same group when they have same values of these columns.

MyBox Split/Group - CSV - 942 - d:\tmp\mybox-data-6.5.9\data\DiabetesPrediction_en.csv

Split/Group

Data Row filter Group Options

By Equal values Value range Conditions Rows range

Group by

	Table r...	Column	
<input checked="" type="checkbox"/>	1	age	
<input checked="" type="checkbox"/>	2	sex	
<input type="checkbox"/>	3	BMI(body mass index)	
<input type="checkbox"/>	4	BP(average blood pressure)	
<input type="checkbox"/>	5	S1(blood serum measurement 1)	
<input type="checkbox"/>	6	S2(blood serum measurement 2)	
<input type="checkbox"/>	7	S3(blood serum measurement 3)	
<input type="checkbox"/>	8	S4(blood serum measurement 4)	
<input type="checkbox"/>	9	S5(blood serum measurement 5)	

Groups are generated against the filtered data rows as following:

- Select some columns.
- Rows are divided into same group when they have equal values of these columns.

2.10.3.2 Implementation of Grouping

1. Convert data as a temporary database table
2. Execute SQL of “group by”.

2.10.3.3 Results of Grouping

1. Complete: Each row belongs to a group.
 2. Non-intersect: Each row only belongs to one group.

My Box Edit CSV File : CSV - 949 - d:\tmp\mybox-data-6.5.9\generated\Progression_Prediction_of_Diabetes_Equal_values_age_sex.csv

Table r...	Data...	Group	Equal values_age_sex	age	sex	BMI(body ...	BP(averag...
<input type="checkbox"/> 1	1	1	{sex=1, age=19.0}	19	1	23.2	75
<input type="checkbox"/> 2	2	1	{sex=1, age=19.0}	19	1	25.3	83
<input type="checkbox"/> 3	3	1	{sex=1, age=19.0}	19	1	19.2	87
<input type="checkbox"/> 4	4	2	{sex=1, age=20.0}	20	1	22.9	87
<input type="checkbox"/> 5	5	3	{sex=2, age=20.0}	20	2	24.2	88
<input type="checkbox"/> 6	6	3	{sex=2, age=20.0}	20	2	22.1	87
<input type="checkbox"/> 7	7	4	{sex=1, age=21.0}	21	1	24.2	76
<input type="checkbox"/> 8	8	4	{sex=1, age=21.0}	21	1	20.1	63
<input type="checkbox"/> 9	9	5	{sex=1, age=22.0}	22	1	19.9	75
<input type="checkbox"/> 10	10	5	{sex=1, age=22.0}	22	1	19.3	82
<input type="checkbox"/> 11	11	5	{sex=1, age=22.0}	22	1	23	73
<input type="checkbox"/> 12	12	5	{sex=1, age=22.0}	22	1	18.6	97
<input type="checkbox"/> 13	13	6	{sex=1, age=23.0}	23	1	18.8	78
<input type="checkbox"/> 14	14	6	{sex=1, age=23.0}	23	1	29	90
<input type="checkbox"/> 15	15	6	{sex=1, age=23.0}	23	1	22.6	89
<	16	7	{sex=1, age=23.0}	23	2	18	78
>							

Selected: 0 Rows: [1-50]50/442 Page size 50 Page 1 /9


2.10.4 Group by Value Ranges

2.10.4.1 Way of Grouping

Select one column and divide data by value ranges of this column.

Following 3 selections can be for the split:

- Interval of values
- Number of split
- List of "StartValue-EndValue"




Groups are generated against the filtered data rows as following:

- Select a column and divided rows into groups by ranges of its values.
- Value ranges can be defined by following ways:
 - Size of split(Value interval)
 - Number of split
 - List of "startValue-endValue"
- Type of the selected column is ignored. Its data are parsed as double values.

2.10.4.2 Split Date/Era

When split rows of date/era:

1. Values of the column are converted as milliseconds.
2. Time unit can be set.
3. For items of “Start-End”, ranges should be in valid formats of date/era.



2.10.4.3 Edit List of “Start-End”

1. Add/Delete/Update start-end items in table.
2. Set whether includes “start”/“end” for “start-end” items.

MyBox Split/Group - CSV - 82 - D:\tmp\mybox-data\mybox-data-6.6.2\generated\Chinese_Historical_Capitals_...

Split/Group

Data Row filter Group Options

By Equal values Value range Conditions Rows range

Column **Start time**

Value interval Number of split Start-end list

Start	End	Include "start"	Include "end"	
2022-02-01 00:00:00	2022-08-30 00:00:00	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	
2022-05-30 16:23:08	2022-11-30 16:23:12		<input checked="" type="checkbox"/>	
2022-12-01 00:00:00	2022-12-31 00:00:00	<input checked="" type="checkbox"/>		

Groups are generated against the selected column.

- Select a column and devide rows into groups.
- Value ranges can be defined by
 - Size of split(Value interval)
 - Number of split
 - List of "startValue-endValue"
- Type of the selected column is

Value range

Column: Start time

Start  Include ...

End  Include ...

2.10.4.4 Implementation of Grouping

- Convert data as a temporary database table.
- Ignore type of selected column, and parse its values as double.
- Calculate maximum value and minimum value of this column.
- Count ranges of each group.
- Compose query statements for each group. The conditions are like “column-name \geq start-value-of-range AND column-name $<$ end-value-of-range”.

2.10.4.5 Results of Grouping

- If split as size or number, then:
 - Complete: Each row belongs to a group.
 - Non-intersect: Each row only belongs to one group.
- If split as start-end list, then:
 - Possible incomplete: Some rows may not belong to any group.
 - Possible intersect: Some rows may belong to several groups.

MyBox Edit CSV File : CSV - 951 - d:\tmp\mybox-data-6.5.9\generated\Progression_Prediction_of_Diabetes_Range_age.csv

Window Document Image Data File Media Network Settings Recent Accessed Development Help

Columns* Attributes View Edit

Table CSV

Table r... Data... Group Range_age age sex BMI(body ...) BP(averag... S1(blood ...) S2(blood ...)

Table r...	Data...	Group	Range_age	age	sex	BMI(body ...)	BP(averag...)	S1(blood ...)	S2(blood ...)
<input type="checkbox"/>	20	1	[19,27)	20	2	24.2	88	126	72.2
<input type="checkbox"/>	21	1	[19,27)	26	1	18.8	83	191	103.6
<input type="checkbox"/>	22	1	[19,27)	23	2	18	78	171	96
<input type="checkbox"/>	23	1	[19,27)	19	1	25.3	83	225	156.6
<input type="checkbox"/>	24	1	[19,27)	25	2	22.6	85	130	71
<input type="checkbox"/>	25	1	[19,27)	19	1	23.2	75	143	70.4
<input type="checkbox"/>	26	1	[19,27)	25	2	23.5	88	143	80.8
<input type="checkbox"/>	27	2	[27,35)	29	1	30	85	180	93.4
<input type="checkbox"/>	28	2	[27,35)	34	2	24.7	118	254	184.2
<input type="checkbox"/>	29	2	[27,35)	31	1	29.7	88	167	103.4
<input type="checkbox"/>	30	2	[27,35)	30	2	25.2	83	178	118.4
<input type="checkbox"/>	31	2	[27,35)	32	1	30.5	89	182	110.6
<input type="checkbox"/>	32	2	[27,35)	32	2	25.4	90.33	153	100.4
<input type="checkbox"/>	33	2	[27,35)	33	1	25.3	85	155	85
<input type="checkbox"/>	34	2	[27,35)	27	1	19.6	78	128	68

Selected: 0 Rows: [1-50]50/442 Page size 50 Page 1 /9

2.10.5 Group by Conditions

2.10.5.1 Way of Grouping

Define some row filters and data rows are divided in groups by these row filters.

The screenshot shows the 'Split/Group' dialog box from the MyBox Data Tools. The title bar reads 'My Box Split/Group - CSV - 942 - d:\tmp\mybox-data-6.5.9\data\DiabetesPrediction_en.csv'. The main area is titled 'Split/Group' and contains a toolbar with four buttons: 'Data', 'Row filter' (selected), 'Group', and 'Options'. Below the toolbar, there's a section labeled 'By' with three radio buttons: 'Equal values', 'Value range', and 'Conditions' (selected). There are also three icons: a double arrow, a sunburst, and a rose. A table below lists six row filters:

Expression	Reverse	Maxim...	
<code>#{age} < 20</code>	false	-1	
<code>#{age} < 45</code>	false	-1	
<code>#{age} < 60</code>	false	-1	
<code>#{age} < 70</code>	false	-1	
<code>#{age} < 85</code>	false	-1	
<code>#{age} > 85</code>	false	-1	

At the bottom right of the dialog are two icons: a red swirl and a red rose. The text below the dialog states: 'Groups are generated against the filtered data rows as following:' followed by a list of steps.

Groups are generated against the filtered data rows as following:

- Define some row filters.
- Rows are divided in groups by these row filters.

2.10.5.2 Implementation of Grouping

1. Convert data as a temporary database table.
2. For each row filter, scan data rows to pick out group members which satisfy condition.

2.10.5.3 Results of Grouping

- Possible incomplete: Some rows may not belong to any group.
- Possible intersect: Some rows may belongs to several groups.

MyBox Edit CSV File : CSV - 953 - d:\tmp\mybox-data-6.5.9\generated\Progression_Prediction_of_Diabetes_Condition.csv

Window Document Image Data File Media Network Settings Recent Accessed Development Help

Columns Attributes View Edit

Table CSV

Selected: 0 Rows: [1-50]50/1374 Page size 50 Page 1 /28


Table r...	Data...	Group	Condition	age	sex	BMI(body ...	BP(averag...
1	1	1	<code>#{age} < 20</code>	19	1	19.2	87
2	2	1	<code>#{age} < 20</code>	19	1	25.3	83
3	3	1	<code>#{age} < 20</code>	19	1	23.2	75
4	4	2	<code>#{age} < 45</code>	24	1	25.3	84
5	5	2	<code>#{age} < 45</code>	23	1	22.6	89
6	6	2	<code>#{age} < 45</code>	36	2	22	90
7	7	2	<code>#{age} < 45</code>	29	1	30	85
8	8	2	<code>#{age} < 45</code>	22	1	18.6	97
9	9	2	<code>#{age} < 45</code>	34	2	24.7	118
10	10	2	<code>#{age} < 45</code>	38	1	25.4	84
11	11	2	<code>#{age} < 45</code>	41	1	24.7	83
12	12	2	<code>#{age} < 45</code>	35	1	21.1	82
13	13	2	<code>#{age} < 45</code>	25	2	24.3	95
14	14	2	<code>#{age} < 45</code>	25	1	26	92
15	15	2	<code>#{age} < 45</code>	31	1	29.7	88
16	16	2	<code>#{age} < 45</code>	20	2	25.0	82

2.10.6 Group by Row Number

2.10.6.1 Way of Grouping

Divide data rows by their row numbers. Following 3 selections can be for the split:

- Size of split(interval of row numbers)
- Number of split
- List of "StartNumber-EndNumber"



2.10.6.2 Implementation of Grouping

1. Convert data as a temporary database table.
2. Count range of row numbers for each group.
3. Scan data rows, and set groups as row numbers.

2.10.6.3 Results of Grouping

- If split as size or number, then:
 - Complete: Each row belongs to a group.
 - Non-intersect: Each row only belongs to one group.
- If split as start-end list, then:
 - Possible incomplete: Some rows may not belong to any group.
 - Possible intersect: Some rows may belong to several groups.

MyBox Edit CSV File : CSV - 955 - d:\tmp\mybox-data-6.5.9\generated\Progression_Prediction_of_Diabetes_DataRowNumber.csv

Table r...	Data...	Group	DataRowNumber	age	sex	BMI(body ...	BP(averag...
<input type="checkbox"/>	1	1	[1,55]	58	1	25.7	99
<input type="checkbox"/>	2	1	[1,55]	65	2	27.9	103
<input type="checkbox"/>	3	1	[1,55]	34	1	25.5	93
<input type="checkbox"/>	4	1	[1,55]	46	1	24.9	115
<input type="checkbox"/>	5	1	[1,55]	35	1	28.7	97
<input type="checkbox"/>	6	2	[56,110]	37	1	21.8	84
<input type="checkbox"/>	7	2	[56,110]	37	1	30.2	87
<input type="checkbox"/>	8	2	[56,110]	41	1	20.5	80
<input type="checkbox"/>	9	2	[56,110]	60	1	20.4	105
<input type="checkbox"/>	10	2	[56,110]	66	2	24	98
<input type="checkbox"/>	11	2	[56,110]	29	1	26	83
<input type="checkbox"/>	12	2	[56,110]	37	2	26.8	79
<input type="checkbox"/>	13	2	[56,110]	41	2	25.7	83
<input type="checkbox"/>	14	2	[56,110]	39	1	22.9	77
<input type="checkbox"/>	15	2	[56,110]	67	2	24	83

Selected: 0 Rows: [51-100]50/442 Page size 50 Page 2 /9

2.11 Modify Data

Hover or click button “Function” to select functions under menu item “Modify”.

The screenshot shows the MyBox Data Tools interface with a CSV file named "DiabetesPrediction_en.csv" open. The "Modify" function menu is displayed as a context menu over a table selection. The menu includes options like Add rows, Set values, Delete, Set Styles / Mark Abnormal Values, Paste content in System Clipboard, Paste content in MyBox Clipboard, Trim, Calculation, Charts, Group Charts, and Examples. A checkbox for "Pop when mouse hovering" is checked, and a note at the bottom says "Close(ESC/F6 Or click anywhere outside the object)".

Index	Glucose	B.P.	Skin	Insulin	B.F.	Age
1	1	59				90
2	2	48				11
3	3	72				83
4	4	24				85
5	5	50				180
6	6	23				93.4
7	7	36	2	22	90.4	42
8	8	66	2	26.2	119.4	43
9	9	60	2	32.1	119.4	46
10	10	29	1	30	119.4	46
11	11	22	1	18.6	119.4	46
12	12	56	2	28	119.4	46
13	13	53	1	23.7	119.4	46
14	14	50	2	26.2	119.4	46
15	15	61	1	24	119.4	46

Selected: 0 Rows: [1-50]50/442 Page size 50 Page 1 /9

2.11.1 Add Rows

1. Select where to add new rows: Front, End, Above some row, Below some row.
2. Set rows number to be added.
3. Set values for new rows. Edit controls are provided as types of columns:
 - o If data contains both Longitude and Latitude, display button “Location”.
 - o For datetime, date, or era, display button “Example”.
 - o For boolean, display selection buttons.
 - o For enumeration, display value list.
 - o For color, display button “Color”.

Edit CSV File

Add rows

Front End Above Below


Table row

Rows number

DataRowNumber	<input type="button" value="Location"/>
Start time	2022-11-14
End time	2022-11-14
color	<input type="color" value="#FF0000"/> <input type="color" value="#00FFFF"/>
marked	<input type="radio"/> true <input checked="" type="radio"/> false
Longitude	115.3125
Latitude	30.14513
Altitude	
Coordinate System	CGCS2000(China Geodetic Coordinate System) <input type="button" value="▼"/>
Comments	CGCS2000(China Geodetic Coordinate System)
	GCJ-02(China encrypted coordinate)
	WGS-84(GPS)
	BD-09(Baidu encrypted coordinate)
	Mapbar coordinate

2.11.2 Set Values

1. Select data rows. Row filter can be set.
2. Select columns to be set.
3. Select way to set values:
 - o Constant: 0, 1, blank, or inputted value
 - o Random, random of non-negative
 - o Add prefix, append suffix, set decimal scale, or add sequence numbers
 - o When selected data are square, whose rows number equals to columns number, they can be set as following: gaussian distribution, identify matrix, upper triangular matrix, lower triangular matrix.
 - o Row expression
4. If handle all pages of data file, then auto-backup before set values.



2.11.3 Delete

1. Select data rows. Row filter can be set.
2. Option: Whether continue when error.
3. If handle all pages of data file, then auto-backup before delete.

MyBox Delete - CSV - 786 - d:\tmp\mybox-data-6.5.9\data\ChinaPopulation_en.csv

Delete

Data Row filter Options

Rows Selected Current page All pages 

<input type="checkbox"/> Table row	<input checked="" type="checkbox"/> Data row	Select some to handle, or select none to handle all in table: n(te... rural(ten ...)						
<input type="checkbox"/> 1	<input checked="" type="checkbox"/>	1	167	28,145	26,022	5,765	48,402	
<input type="checkbox"/> 2	<input checked="" type="checkbox"/>	2	1950	55,106	38,669	26,527	6,169	1,027
<input type="checkbox"/> 3	<input checked="" type="checkbox"/>	3	1951	52,896	30,168	28,328	6,266	49,668
<input type="checkbox"/> 4	<input checked="" type="checkbox"/>	4	1952	57,482	29,833	27,649	7,163	50,319
<input type="checkbox"/> 5	<input checked="" type="checkbox"/>	5	1953	52,896	30,168	28,328	6,266	50,970
<input type="checkbox"/> 6	<input checked="" type="checkbox"/>	6	1954	57,482	31,803	29,030	8,285	53,780
<input type="checkbox"/> 7	<input checked="" type="checkbox"/>	7	1955	61,483	33,803	30,292	9,185	53,643
<input type="checkbox"/> 8	<input checked="" type="checkbox"/>	8	1956	61,483	34,517	32,178	11,658	55,636
<input type="checkbox"/> 9	<input checked="" type="checkbox"/>	9	1957	61,483	34,517	32,178	11,658	55,726
<input type="checkbox"/> 10	<input checked="" type="checkbox"/>	10	1958	61,483	34,517	32,178	11,658	55,273
<input type="checkbox"/> 11	<input checked="" type="checkbox"/>	11	1959	61,483	34,517	32,178	11,658	54,836
<input type="checkbox"/> 12	<input checked="" type="checkbox"/>	12	1960	61,483	34,517	32,178	11,658	54,181
<input type="checkbox"/> 13	<input checked="" type="checkbox"/>	13	1961	61,483	34,517	32,178	11,658	54,704
<input type="checkbox"/> 14	<input checked="" type="checkbox"/>	14	1962	61,483	34,517	32,178	11,658	55,636
<input type="checkbox"/> 15	<input checked="" type="checkbox"/>	15	1963	69,172	35,533	33,639	11,646	57,526
<input type="checkbox"/> 16	<input checked="" type="checkbox"/>	16	1964	70,499	36,142	34,357	12,950	57,549

Selected: 0 Rows: 60/73 Page size 50  Page 1  /2     

2.11.4 Set styles / Mark Abnormal Values

2.11.4.1 Manage Styles

1. Add/Edit/Delete/Rename styles.
 2. Define title and sequence number of the style.
 3. Set whether the style marks abnormal values.

My Box Set Styles / Mark Abnormal Values - CSV - 63 - d:\tmp\mybox-data-6.5.9\data\ChinaPopulation_en.csv

Set Styles / Mark Abnormal Values

Seq...	Abnormal ...	Title	From	To
1.0		Analyse of Female	1	-1
2.0		Analyse of Male	1	-1
3.0	✓	Abnormal of Fem...	25	-1
4.0	✓	Abnormal of Male	25	-1

< >

Page 1 /1

Page size 50 Rows: 4/4 Selected: 1

ID: 7

Base Data Filter Style

Sequence 3.0

Title Abnormal of Female

This rule defines abnormal values

2.11.4.2 Data Scope

Define conditions to determine which data cells to apply the style:

1. Range of data rows
2. Column names.
3. Row filter.

Notice, data of a row number may be changed when some rows are added or deleted. Example, when insert 2 rows before "row 6", original "row 12" becomes "row 14" while current "row 12" was "row 10".

So "row number" is not right way to locate a specific data row while rows number is changing. A way to refer special rows is the expression composed of column values.

Seq...	Abn...	Title	From	+/-
1.0		Analyse of Female	1	-
2.0		Analyse of Male	1	-
3.0	<input checked="" type="checkbox"/>	Abnormal of Fem...	25	-
4.0	<input checked="" type="checkbox"/>	Abnormal of Male	25	-

ID: 7

Base Data Filter Style

DataRowNumber

From Blank, zero, or negative means no limitation to row number

To Blank, zero, or negative means the last row

Columns to be calculated (No selection means all)

year_population at year-end(ten thousand)
 male(ten thousand) female(ten thousand)
 urban(ten thousand) rural(ten thousand)

Page 1 /1
 Page size 50 Rows: 4/4
 Selected: 1

2.11.4.3 Define Styles

1. Font color, font size, background color, bold, etc.
2. More values in format of JavaFx CSS.

Set Styles / Mark Abnormal Values - CSV - 63 - d:\tmp\mybox-data-6.5.9\data\ChinaPopulation_en.csv

Set Styles / Mark Abnormal Values

Seq...	Abn...	Title	From	To
1.0		Analyse of Female	1	-1
2.0		Analyse of Male	1	-1
3.0	✓	Abnormal of Fem...	25	-1
4.0	✓	Abnormal of Male	25	-1

< >

Page 1 /1

Page size 50 Rows: 4/4 Selected: 1

ID: 7

Base Data Filter Style

Font color Default Set

Background color Default Set

Font size ▾ Bold

More

[JavaFX CSS Reference Guide](#)

2.11.4.4 Apply Styles

When load data page, all styles of the data are applied to the rows one by one in order of their sequence numbers(from small to large).

When data scopes of styles are interlaced, style with larger number overrides the one with smaller number for the interlaced part.

The screenshot shows a CSV file named "ChinaPopulation_en.csv" being edited in MyBox Data Tools. The interface includes a toolbar with various icons for file operations, a menu bar with "Window", "Document", "Image", "Data", "File", "Media", "Network", "Settings", "Recent Accessed", "Development", and "Help". Below the menu is a toolbar with icons for search, filter, sort, and other data manipulation. The main area displays a table with the following data:

Table	Data	year_	populatio...	male(ten t...)	female(te...)	urban(ten ...)	rural(ten t...)
24	24	1972	87,177	44,813	42,364	14,935	72,242
25	25	1973	89,211	45,876	43,335	15,345	73,866
26	26	1974	90,859	46,727	44,132	15,595	75,264
27	27	1975	92,420	47,564	44,856	16,030	76,390
28	28	1976	93,717	48,257	45,460	16,341	77,376
29	29	1977	94,974	48,908	46,066	16,669	78,305
30	30	1978	96,259	49,567	46,692	17,245	79,014
31	31	1979	97,542	50,192	47,350	18,495	79,047
32	32	1980	98,705	50,785	47,920	19,140	79,565
33	33	1981	100,072	51,519	48,553	20,171	79,901
34	34	1982	101,654	52,352	49,302	21,480	80,174
35	35	1983	103,008	53,152	49,856	22,274	80,734
36	36	1984	104,357	53,848	50,509	24,017	80,340

At the bottom, there are buttons for selecting rows (0-73), setting page size (50), navigating pages (1-2), and other document controls.

2.11.5 Paste Content in System Clipboard

1. Read contents in System Clipboard.
2. Guess delimiter and parse data.
3. User can select a delimiter to parse data.
4. Select how to parse:
 - CSV parser: Values can contain delimiter and line break. But not support parsing “Blanks” and “Regular Expression”.
 - Text parser: Values can not contain delimiter and line break. Support parsing “Blanks” and “Regular Expression”.
5. Select whether first line defines column names.
6. Based on parsed data, select rows and columns to be pasted.
7. Select location to paste data: row and column in target data.
8. Select the way to paste data: Replace, Insert Above, or Append Below.

Paste content in System Clipboard : CSV - 957 - d:\tmp\mybox-data-6.5.9\AppData\Temp\2022-11-14_15-42-45-08...

Table r...	Data...	C...	Co...	Col+
<input type="checkbox"/> 1	1	age	sex	BMI(bod
<input checked="" type="checkbox"/> 2	2	59	2	32.1
<input checked="" type="checkbox"/> 3	3	48	1	21.6
<input type="checkbox"/> 4	4	72	2	30.5
<input checked="" type="checkbox"/> 5	5	24	1	25.3
<input checked="" type="checkbox"/> 6	6	50	1	23
<input type="checkbox"/> 7	7	23	1	22.6
<input checked="" type="checkbox"/> 8	8	36	2	22
<input type="checkbox"/> 9	9	66	2	26.2
<input type="checkbox"/> 10	10	60	2	32.1

If a value contains delimiter or line break, it should be surrounded by quotes.

2.11.6 Paste Content in MyBox Clipboard

1. Select data item in MyBox Clipboard.
2. Select rows and columns to be pasted.
3. Select location to paste data: row and column in target data.
4. Select the way to paste data: Replace, Insert Above, or Append Below.

Paste content in MyBox Clipboard : MyBox Clipboard - 1089 - ChinaPopulation_zh.csv

Table row	ID	Type	Name
<input checked="" type="checkbox"/> 1	1089	MyBox ...	ChinaPopu
<input type="checkbox"/> 2	1086	MyBox ...	ChinaPopu
<input type="checkbox"/> 3	1085	MyBox ...	ChinaPopu
<input type="checkbox"/> 4	1083	MyBox ...	ChinaPopu
<input type="checkbox"/> 5	1082	MyBox ...	ChinaPopu
<input type="checkbox"/> 6	1063	MyBox ...	a
<input type="checkbox"/> 7	6	MyBox ...	b

Location to paste

Table row 1

Column year_

Rows Selected Current page All pages

Columns

Table row	Data row	源行号	年	年末总人
1	1	源行号	年	年末总人
✓ 2	2	1	1949	54,167
✓ 3	3	2	1950	55,196
✓ 4	4	3	1951	56,300
5	5	4	1952	57,482
6	6	5	1953	58,796

Replace
Insert above
Append below

Page 1 /1 Rows: 7/7 Selected: 1

Page size 50

2.12 Trim Data

However or click button “Function” and select functions under menu item “Trim”.

My Box Edit CSV File : CSV - 944 - d:\tmp\mybox-data-6.5.9\data\ChinaPopulation_en.csv

Window Document Image Data File Media Network Settings Recent Accessed Development Help

Columns Attributes View Edit

Table r... Data... year_ populatio... male(ten t... fe

1 1 1949

2 2 1950

3 3 1951

4 4 1952

5 5 1953

6 6 1954

7 7 1955 61465 31809 29

8 8 1956 62828 32536 30

9 9 1957 64653 33469 31 184 9949 54704

10 10 1958 65994 34195 31799 10721 55273

11 11 1959 67207 34890 32317 12371 54836

12 12 1960 66207 34283 31924 13073 53134

13 13 1961 65859 33880 31979 12707 53152

14 14 1962 67296 34517 32778 11659 55636

15 15 1963 69172 35533 33639 11646 57526

16 16 1964 70100 36142 34257 12050 57740

Selected: 0 Rows: [1-50]50/73 Page size 50 /2

Columns Attributes View Edit


Data Modify Trim Calculation Charts Group Charts Examples

Pop when mouse hovering

Close(ESC/F6 Or click anywhere outside the object)

2.12.1 Copy/Filter/Query/Convert

1. Select data rows. Row filter can be set.
2. Select columns to be copied.
3. Select whether:
 - Copy row numbers
 - Copy column names
 - Save date/time/era and numbers as columns' formats
4. Results can be written as external data, including: new csv/excel/text file, matrix, system clipboard, MyBox clipboard, database table, json, xml, html, or pdf.
5. When handle rows for current page or selected ones, results can be written in current page: insert, append, or replace data in defined location of the table.



2.12.2 Sort

1. Select data rows. Row filter can be set.
2. Select columns to sort and whether descending.
Data type of column affects sorting results.
3. Maximum rows number of results can be set.
4. Select columns to be copied.
5. Select whether copy row number or column name.
6. Results can be written as external data, including: new csv/excel/text file, matrix, system clipboard, MyBox clipboard, database table, json, xml, html, or pdf.
7. When handle rows for current page or selected ones, results can be written in current page: insert, append, or replace data in defined location of the table.

Sort - CSV - 83 - D:\tmp\mybox-data\mybox-data-6.6.2\data\ChinaGDP_en.csv

Sort

Data Row filter Options

Order by(Column type affects sorting results)

<input type="checkbox"/> Table r...	Sort		
<input type="checkbox"/> 1	year_-Descending		
<input type="checkbox"/> 2	year_-Ascending		
<input checked="" type="checkbox"/> 3	gross national income(GNI hundred million yuan)-Descending		
<input type="checkbox"/> 4	gross national income(GNI hundred million yuan)-Ascending		
<input type="checkbox"/> 5	gross domestic product(GDP hundred million yuan)-Descending		

Maximum sorted rows to take(Empty/zero/negative to unlimit)

Columns to be copied (No selection means all)

year_ gross national income(GNI hundred million yuan)
 gross domestic product(GDP hundred million yuan)
 value-added of first industry(VA1 hundred million yuan)
 value-added of secondary industry(VA2 hundred million yuan)
 value-added of tertiary industry(VA3 hundred million yuan) GDP per capita(yuan)

Row number Column name

Target

External

Name

In table Insert above Append below Replace

2.12.3 Transpose

1. Select data rows. Row filter can be set.
2. Select columns to be calculated.
3. Select whether:
 - Copy row number
 - Copy column name
 - Set first column as column names.
4. Results can be written as external data, including: new csv/excel/text file, matrix, system clipboard, MyBox clipboard, database table, json, xml, html, or pdf.
5. When handle rows for current page or selected ones, results can be written in current page: insert, append, or replace data in defined location of the table.

Transpose - CSV - 83 - D:\tmp\mybox-data\mybox-data-6.6.2\data\ChinaGDP_en.csv

Transpose

Data Row filter Options

Columns to be calculated (No selection means all)

year_ gross national income(GNI hundred million yuan)
 gross domestic product(GDP hundred million yuan)
 value-added of first industry(VA1 hundred million yuan)
 value-added of secondary industry(VA2 hundred million yuan)
 value-added of tertiary industry(VA3 hundred million yuan) GDP per capita(yuan)

Row number Column name First column as column names

Target

External CSV XLS TXT Matrix JSON XML HTML PDF

Name: Gross domestic product(GDP) of China

In table Insert above Append below Replace

2.12.4 Normalization

1. Select data rows. Row filter can be set.
2. Select columns to be calculated.
3. Select objects: According to Columns/rows/all.
4. Select algorithms: MinMax(Range can be set), sum(L1), Zscore(L2).
5. To non-numeric, skip or count as zero.
6. Select columns to be copied.
7. Results can be written as external data, including: new csv/excel/text file, matrix, system clipboard, MyBox clipboard, database table, json, xml, html, or pdf.
8. When handle rows for current page or selected ones, results can be written in current page: insert, append, or replace data in defined location of the table.

Normalize - CSV - 84 - D:\tmp\mybox-data\mybox-data-6.6.2\data\IrisSpecies_en.csv

Normalize

Data **Row filter** **Options**

Columns to be calculated (No selection means all)

SepalLengthCm SepalWidthCm PetalLengthCm PetalWidthCm Species

According to Columns Rows All

Algorithm MinMax L1(Sum) L2(Z-Score)

Range , (-1,1) [0.0,1.0]

Row number Column name

Decimal scale

To invalid number Skip Count as zero

Columns to be copied

SepalLengthCm SepalWidthCm PetalLengthCm PetalWidthCm Species

Target

External

Name

In table Insert above Append below Replace

2.12.5 Split/Group

1. Select data rows. Row filter can be set.
2. Set parameters of grouping.
3. Select columns to be copied.
4. Set sort conditions and maximum data rows in each group.
5. Select whether include row numbers.
6. Select target:
 - All groups in single file
 - One file for each group
 - Database table

MyBox Split/Group - CSV - 958 - d:\tmp\mybox-data-6.5.9\data\ChinaGDP_en.csv

Split/Group

Data Row filter Group Options

Columns to be copied (No selection means all)

year_ gross national income(GNI hundred million yuan)
 gross domestic product(GDP hundred million yuan)
 value-added of first industry(VA1 hundred million yuan)
 value-added of secondary industry(VA2 hundred million yuan)
 value-added of tertiary industry(VA3 hundred million yuan) GDP per capita(yuan)

Order by(Column type affects sorting results)

Table r...	Sort	+
<input type="checkbox"/> 1	year_-Descending	
<input type="checkbox"/> 2	year_-Ascending	
<input checked="" type="checkbox"/> 3	gross national income(GNI hundred million yuan)-Descending	
<input type="checkbox"/> 4	gross national income(GNI hundred million yuan)-Ascending	
<input type="checkbox"/> 5	gross domestic product(GDP hundred million yuan)-Descending	

Maximum rows in each group(Empty/zero/negative to unlimit)

Row number

Target All groups in single file One file for each group Database Table

2.13 Data Calculation

Hover or click button “Function” to select functions under menu item “Calculation”.


The screenshot shows the MyBox Data Tools interface with a CSV file named 'ChinaGDP_en.csv' loaded. The main window displays a table with columns: Table r..., Data..., year_, gross nati..., gross do..., va... (partially visible). A context menu is open over the first row of the table. The menu is organized into sections: Data, Modify, Trim, Calculation, Charts, Group Charts, Examples, and a settings section. The 'Descriptive statistics' option under the Calculation section is highlighted with a blue background. At the bottom of the interface, there are navigation buttons for rows (Selected: 0, Rows: [1-50]50/70), page size (Page size: 50), page number (Page: 1, /2), and other document-related icons.

Table r...	Data...	year_	gross nati...	gross do...	va...
1	1	1952	679.1	679.1	34
2	2	1953	679.1	679.1	34
3	3	1954	679.1	679.1	34
4	4	1955	679.1	679.1	34
5	5	1956	679.1	679.1	34
6	6	1957	679.1	679.1	34
7	7	1958	679.1	679.1	34
8	8	1959	679.1	679.1	34
9	9	1960	679.1	679.1	34
10	10	1961	679.1	679.1	34
11	11	1962	679.1	679.1	34
12	12	1963	1248.5	1248.5	477.5
13	13	1964	1469.9	1469.9	559
14	14	1965	1734	1734	651.1
15	15	1966	1888.7	1888.7	702.2
16	16	1967	1704.2	1704.2	711.2

Selected: 0 Rows: [1-50]50/70 Page size: 50 Page: 1 /2

2.13.1 Row Expression

1. Select data row. Data filter can be set.
2. Select columns to be copied.
3. Input row expression and its name.
4. Results can be written as external data, including: new csv/excel/text file, matrix, system clipboard, MyBox clipboard, database table, json, xml, html, or pdf.
5. When handle rows for current page or selected ones, results can be written in current page: insert, append, or replace data in defined location of the table.



2.13.2 Descriptive Statistic

1. Select data rows. Data filter can be set.
2. Select columns to be calculated.
3. Select statistic items:
 count, sum, mean, geometric mean, sum of squares, mode, skewness, population variance, sample variance, population standard deviation, sample standard deviation, minimum(Q0), lower quartile(Q1), median(Q2), upper quartile(Q3), maximum(Q4), upper extreme outlier line(E4), upper mild outlier line(E3), lower mild outlier line(E2), lower extreme outlier line(E1)
4. Select objects: According to columns/rows/all.
5. Set decimal scale.
6. To non-numeric: skip or count as zero
7. Results can be written as external data, including: new csv/excel/text file, matrix, system clipboard, MyBox clipboard, database table, json, xml, html, or pdf.
8. When handle rows for current page or selected ones, results can be written in current page: insert, append, or replace data in defined location of the table.

MyBox Descriptive statistics - CSV - 84 - D:\tmp\mybox-data\mybox-data-6.6.2\data\IrisSpecies_en.csv

Descriptive statistics

Data Row filter Options

Columns to be calculated (No selection means all)

SepalLengthCm SepalWidthCm PetalLengthCm PetalWidthCm Species

Descriptive statistics

Count Summation Mean Geometric mean Sum of squares
 Population variance Sample variance Population standard deviation Sample standard deviation
 Skewness
 Minimum(Q0) Lower quartile(Q1) Median(Q2) Upper quartile(Q3) Maximum(Q4)
 Upper extreme outlier line(E4) Upper mild outlier line(E3) Lower mild outlier line(E2)
 Lower extreme outlier line(E1) Mode

According to Columns Rows All

Decimal scale 2

To invalid number Skip Count as zero

Target

External CSV XLS TXT JSON XML HTML PDF

Name Iris species

In table Insert above Append below Replace

2.13.3 Statistic in Groups

2.13.3.1 Options of Calculation

1. Select data rows. Data filter can be set.
2. Set parameters of grouping.
3. Select columns to be calculated.
4. Select statistic items. “Count” is always selected.
5. Set decimal scale.
6. To invalid numbers: set as blank or zero.

Statistic in groups - CSV - 958 - d:\tmp\mybox-data-6.5.9\data\ChinaGDP_en.csv

Data **Row filter** **Group** **Options**

Columns to be calculated (No selection means all)

year_ gross national income(GNI hundred million yuan)
 gross domestic product(GDP hundred million yuan)
 value-added of first industry(VA1 hundred million yuan)
 value-added of secondary industry(VA2 hundred million yuan)
 value-added of tertiary industry(VA3 hundred million yuan)
 GDP per capita(yuan)

Descriptive statistics

Count Summation Mean Geometric mean
 Sum of squares
 Population variance Sample variance
 Population standard deviation Sample standard deviation
 Skewness
 Minimum(Q0) Lower quartile(Q1) Median(Q2)
 Upper quartile(Q3) Maximum(Q4)
 Upper extreme outlier line(E4) Upper mild outlier line(E3)
 Lower mild outlier line(E2) Lower extreme outlier line(E1)
 Mode

Decimal scale

To invalid number Set as blank Set as zero

Display all data in chart

Group Data **Statistic data** **Chart data**

Data...	id	group_id	range_year_
1	1	1	[1952,1961)
2	2	1	[1952,1961)
3	3	1	[1952,1961)
4	4	1	[1952,1961)
5	5	1	[1952,1961)
6	6	1	[1952,1961)
7	7	1	[1952,1961)
8	8	1	[1952,1961)
9	9	1	[1952,1961)
10	10	2	[1961,1970)
11	11	2	[1961,1970)
12	12	2	[1961,1970)
13	13	2	[1961,1970)
14	14	2	[1961,1970)
15	15	2	[1961,1970)
16	16	2	[1961,1970)

Selected: 0 Rows: [1-20]20/70 Page size
 Page /4

2.13.3.2 Grouped Data

After data are grouped, 2 columns are added: “Group id”, “Group Parameter”.

Statistic in groups - CSV - 958 - d:\tmp\mybox-data-6.5.9\data\ChinaGDP_en.csv

Data...	id	group_id	range_year_	year_	gross_nati...	gross_do...	value_add...	value_a...
1	1	1	[1952,1961)	1952	679.1	679.1	342.9	141.1
2	2	1	[1952,1961)	1953	824.4	824.4	378	191.6
3	3	1	[1952,1961)	1954	859.8	859.8	392	210.8
4	4	1	[1952,1961)	1955	911.6	911.6	421	221.5
5	5	1	[1952,1961)	1956	1030.7	1030.7	443.9	280.4
6	6	1	[1952,1961)	1957	1071.4	1071.4	430	316.6
7	7	1	[1952,1961)	1958	1312.3	1312.3	445.9	483.6
8	8	1	[1952,1961)	1959	1447.5	1447.5	383.8	616.7
9	9	1	[1952,1961)	1960	1470.1	1470.1	340.7	652.6
10	10	2	[1961,1970)	1961	1232.3	1232.3	441.1	393.5

Selected: 0 Rows: [1-20]20/70 Page size 20 Page 1 /4

2.13.3.3 Statistic Data

Based on grouped data, calculate statistic values for each group.

Statistic in groups - CSV - 958 - d:\tmp\mybox-data-6.5.9\data\ChinaGDP_en.csv

Data...	id	group_id	range_year_	column_name	group_count	group_sum	group_mean	grc +
1	1	1	[1952,1961)	gross national i...	9	9606.9	1067.43	103
2	2	1	[1952,1961)	gross domestic...	9	9606.9	1067.43	103
3	3	1	[1952,1961)	value-added of...	9	3578.2	397.58	395
4	4	1	[1952,1961)	value-added of...	9	3114.9	346.1	303
5	5	1	[1952,1961)	value-added of...	9	2913.9	323.77	311
6	6	1	[1952,1961)	GDP per capita...	9	1527	169.67	166
7	7	2	[1961,1970)	gross national i...	9	14235.9	1581.77	155
8	8	2	[1961,1970)	gross domestic...	9	14235.9	1581.77	155
9	9	2	[1961,1970)	value-added of...	9	5480.7	608.97	597

Selected: 0 Rows: [1-20]20/48 Page size 20 Page 1 /3

2.13.3.4 Data in Chart

1. Statistic data are trimmed into columns and rows for chart.
2. If select “Display all data in chart”, then data of all pages are displayed in chart. Or else only data of current page are displayed in the chart.

Statistic in groups - CSV - 958 - d:\tmp\mybox-data-6.5.9\data\ChinaGDP_en.csv


Data...	Group id	Range_year_	Group_Count	gross national income(GNI hundred million yuan)_Sum	gross i +
1	1	[1952,1961)	9	9606.9	1067.43
2	2	[1961,1970)	9	14235.9	1581.77
3	3	[1970,1979)	9	25829.7	2869.97
4	4	[1979,1988)	9	64024.4	7113.82
5	5	[1988,1997)	9	315828.2	35092.02
6	6	[1997,2006)	9	1064800.3	118311.14
7	7	[2006,2015)	9	3822494.2	424721.58
8	8	[2015,2021]	7	6296896.8	899556.69

Selected: 0 Rows: [1-8]8/8 Page size 20 Page 1 /1

2.13.3.5 XY Chart

Statistic data of groups can be displayed as XY chart:


1. Select columns to be displayed
2. Select statistic values to be displayed.
3. Select category axis: group parameter, or group id.
4. Select type of XY chart.
5. Select whether transpose the chart.
6. Set maximum data number in the chart.



2.13.3.6 Pie Chart

Groups and their “Count” are displayed as Pie chart.

1. Select category axis: group parameter, or group id.
2. Set maximum data number in the chart.



2.13.4 Simple Linear Regression

2.13.4.1 Base of Implementation

This tool is based on Apache Commons Math.

The regression does not store data, so calculation itself has not memory limitation when handle lots of rows.

2.13.4.2 Options of Calculation

1. Select data rows. Data filter can be set.
2. Select one column as independent variable.
3. Select another column as dependent variable. It should not be the same column of independent variable.
4. Set desired significance level(alpha).
5. Select whether includes intercept.
6. Select whether display all data in chart.
7. Set decimal scale.

2.13.4.3 Regression

Display values status of regression steps in table, including number of observations, slope, intercept, coefficient of determination(R-Square), correlation coefficient(R), mean of squared error(MSE) , sum of squared errors(SSE), total sum of squares(SSTO), sum of squares about regression(SSM/SSR), etc.

N...	income	happiness	Slope(b1)	Intercept(b0)	Coeffici...	Pearson
1	3.8626	2.3145	NaN	NaN	NaN	NaN
2	4.6399	3.7379	1.8314	-4.7594	1	1
3	2.1347	0.2687	1.3514	-2.6845	0.9874	0.9937
4	6.5013	4.3748	0.9625	-1.45	0.9171	0.9577
5	3.6512	2.1558	0.9579	-1.4127	0.9183	0.9583
6	2.2865	1.8936	0.8249	-0.715	0.8447	0.9191
7	4.7489	4.903	0.9204	-0.8517	0.7453	0.8633
8	5.4592	4.8335	0.975	-0.9964	0.7754	0.8806

2.13.4.4 Model

1. Display fitted linear model.
2. Display data status of last regression step.
3. Input value for independent variable, and generate predicted value.

Simple linear regression - CSV - 784 - d:\tmp\mybox-data-6.5.9\data\IncomeHappiness_en.csv

About linear regression Decimal scale 4

Model Regression Fitting Residual

Linear model: happiness = 0.2222 + 0.7097 * income

Independent variable: income = Predict

Dependent variable: happiness =

Last status

Name	Value
Row number	477
Number of observations	477
income	4.4981
happiness	1.9071
Slope(b1)	0.7097
Intercept(b0)	0.2222
Coefficient of determination(R-Square)	0.7517
Pearson's product moment correlation coefficient(R)	0.867
Mean of squared error(MSE)	0.5057

DIV


2.13.4.5 Fitted Chart

1. When handle all data rows(all pages), option to display all values in chart.

When display all values in chart, need concern memory limitation when load lots of data.

Or else only values in current page will be displayed in chart while all pages involve regression, and no memory limitation.

2. Set parameters of plot, X axis and Y axis.
3. Options to display fitted points, fitted line, or model description in chart.
4. Options to display data labels.
5. Set random colors to fitted points/line.
6. Fitted chart can be popped.
7. Html including fitted chart and its data can be created.
8. Display fitted chart's data in table.



2.13.4.6 Residual Chart


1. X axis can be set as: predicted value, independent variable, or actual value.

2. Option whether standardize residuals.

When standardize residuals, upper line and lower line of Sigma2(95%) will be displayed.

3. Set random color to points and lines.

4. Display residual chart's data in table.



2.13.5 Simple Linear Regression - Combination

This tool helps to generate data of simple linear regression:

1. Select some columns as candidates of independent variables.
2. Select some columns as candidates of dependent variables.
3. Select options like decimal scale, alpha, whether include intercept.
4. When click button "OK":

- Make pairs from candidates : one as independent variable and another as dependent variable.
 - Calculate the regression models.
 - Sort the modes by their coefficient of determination(R-Square) in descending order.
5. Select one model and click button "View" to view its regression data, fitting chart, and residual chart.

The screenshot shows the MyBox Data Tools interface for a simple linear regression analysis. The left panel contains two sections: 'Candidates of independent variables' and 'Candidates of dependent variables'. The independent variables section includes checkboxes for age, sex, BMI, BP, and six serum measurements (S1-S6), with 'disease progression one year after baseline' checked. The dependent variables section includes checkboxes for all listed variables, with 'disease progression one year after baseline' checked. Below these are settings for 'Decimal scale' (8) and 'Desired significance level(alpha)' (0.05), and a checkbox for 'Intercept(b0)'. The right panel is titled 'About data analysis' and shows a table with columns: Data..., Dependen..., Independ..., Coeffi..., Pearson..., and Model. The table lists 12 rows of data, with the first row highlighted. A message at the bottom of the right panel says 'Double click selected item to view'.

Data...	Dependen...	Independ...	Coeffi...	Pearso...	Model
3	disease pr...	BMI(body ...	0.34392...	0.58645...	disease progression one year
9	disease pr...	S5(blood s...	0.32022...	0.56588...	disease progression one year
4	disease pr...	BP(averag...	0.19490...	0.44148...	disease progression one year
8	disease pr...	S4(blood s...	0.18528...	0.43045...	disease progression one year
7	disease pr...	S3(blood s...	0.15585...	0.39478...	disease progression one year
10	disease pr...	S6(blood s...	0.14629...	0.38248...	disease progression one year
5	disease pr...	S1(blood s...	0.04495...	0.21202...	disease progression one year
1	disease pr...	age	0.03530...	0.18788...	disease progression one year
6	disease pr...	S2(blood s...	0.03029...	0.17405...	disease progression one year
2	disease pr...	sex	0.00185...	0.043062	disease progression one year

2.13.6 Multiple Linear Regression

2.13.6.1 Regression

This tool helps to generate data of multiple linear regression based on Apache Commons Math:

1. Select some column as independent variables, whose data should be numbers.
2. Select a column as dependent variable, whose data should be numbers.
3. Select whether include intercept.

4. Click button "OK":

- Tool normalizes involved data by Z-Score.
- Tool calculates multiple linear regression by Ordinary Least Squares(OLS).
- Results include intercept, coefficients, R-Square, adjusted R-Square.

The screenshot shows the 'About data analysis' window for a multiple linear regression model. The left panel displays the configuration for the independent variables, and the right panel shows the resulting model statistics.

Independent variable (No selection means all)

- age
- sex
- BMI(body mass index)
- BP(average blood pressure)
- S1(blood serum measurement 1)
- S2(blood serum measurement 2)
- S3(blood serum measurement 3)
- S4(blood serum measurement 4)
- S5(blood serum measurement 5)
- S6(blood serum measurement 6)
- disease progression one year after baseline

Dependent variable: disease progressio... ▾

Normalize L2(Z-Score)
Regression Ordinary Least Squares(OLS)
 Intercept(b0)

All data are involved in memory. Too many data may cause out of memory.

About data analysis


Model | Regression

Decimal scale: 3

Name	Value
Dependent variable	disease progression one year after baseline
Independent variable	[age, sex, BMI(body mass index), BP(average blood pressure), S1(blood serum measurement 1), S2(blood serum measurement 2), S3(blood serum measurement 3), S4(blood serum measurement 4), S5(blood serum measurement 5), S6(blood serum measurement 6)]
Number of observations	442
Intercept(b0)	0.0
Coefficients	[-0.006, -0.148, 0.321, 0.2, -0.489, 0.294, -0.062, 0.109, 0.464, 0.042]
Coefficient of determination(R-Square)	0.518
Adjusted R squared	0.507
Standard Error	0.702
Variance	1.0

2.13.6.2 Model

User can input values of independent variables and predict value of dependent variable.



2.13.7 Multiple Linear Regression - Combination

This tool helps to generate data of multiple linear regression based on Apache Commons Math:

1. Select some columns as candidates of independent variables.
2. Select some columns as candidates of dependent variables.

3. Select whether include intercept.
4. When click button "OK", the tool does following:
 - Make combination of candidates as independent variables and dependent variable .
 - Calculate the regression models.
 - Sort the modes by their adjusted coefficient of determination(R-Square) in descending order.
5. Select one model and click button "View" to view its regression data

Multilpe linear regression - Combination - CSV - 996 - d:\tmp\mybox-data-6.5.9\data\DiabetesPrediction_standardized_en.csv

Data	Filter	Options	About data analysis					
			Data...	Dependen...	Independent variable	Adjus...▼	Coeffici...	Coeff +
19	disease pr...	[sex, BMI(body mass index), ...]	0.50767...	0.51771...	[-0.14]			
18	disease pr...	[sex, BMI(body mass index), ...]	0.50764...	0.51657...	[-0.14]			
10	disease pr...	[age, sex, BMI(body mass index), ...]	0.50656...	0.51774...	[-0.00]			
9	disease pr...	[age, sex, BMI(body mass index), ...]	0.50650...	0.51657...	[-0.00]			
26	disease pr...	[BMI(body mass index), ...]	0.49165...	0.499727	[0.348]			
27	disease pr...	[BMI(body mass index), ...]	0.49099...	0.50023...	[0.344]			
16	disease pr...	[sex, BMI(body mass index), ...]	0.48634...	0.49332...	[-0.14]			
17	disease pr...	[sex, BMI(body mass index), ...]	0.48585...	0.49401...	[-0.14]			
7	disease pr...	[age, sex, BMI(body mass index), ...]	0.48525...	0.49342...	[0.010]			
8	disease pr...	[age, sex, BMI(body mass index), ...]	0.48477...	0.49411...	[0.010]			
24	disease pr...	[BMI(body mass index), ...]	0.471218	0.47721...	[0.376]			
25	disease pr...	[BMI(body mass index), ...]	0.47023...	0.47744...	[0.376]			
34	disease pr...	[BP(average blood pressure), ...]	0.41056...	0.41991...	[0.238]			
33	disease pr...	[BP(average blood pressure), ...]	0.40788...	0.41594...	[0.256]			
15	disease pr...	[sex, BMI(body mass index), ...]	0.39582...	0.40267...	[-0.04]			
13	disease pr...	[sex, BMI(body mass index), ...]	0.39568...	0.39979...	[-0.06]			
14	disease pr...	[sex, BMI(body mass index), ...]	0.39519...	0.40068...	[-0.06]			
23	disease pr...	[BMI(body mass index), ...]	0.39507...	0.40056...	[0.490]			
4	disease pr...	[age, sex, BMI(body mass index), ...]	0.39477...	0.40026...	[0.023]			
6	disease pr...	[age, sex, BMI(body mass index), ...]	0.39463...	0.40287...	[0.015]			
5	disease pr...	[age, sex, BMI(body mass index), ...]	0.39407...	0.40094...	[0.017]			
21	disease pr...	[BMI(body mass index), ...]	0.39324...	0.39599...	[0.488]			
		..						

Double click selected item to view

2.13.8 Frequency Distributions

1. Select data row. Data filter can be set.
2. Select one column to count frequency.
3. Option whether case-insensitive

4. Set decimal scale.
5. Results can be written as external data, including: new csv/excel/text file, matrix, system clipboard, MyBox clipboard, database table, json, xml, html, or pdf.
6. When handle rows for current page or selected ones, results can be written in current page: insert, append, or replace data in defined location of the table.

The screenshot shows a data table on the left and a configuration dialog on the right.

Data Table:

town	town_Count	town_Count percentage
Beverly	2	3.33
Danvers	4	6.67
Hamilton	1	1.67
Lynn	22	36.67
Lynnfield	2	3.33
Marblehead	3	5
Middleton	1	1.67
Nahant	1	1.67
Peabody	9	15
Salem	7	11.67
Sargus	4	6.67
Swampsc...	2	3.33
Topsfield	1	1.67
Wenham	1	1.67

Frequency Distributions Dialog:

- Column:** town
- Case-insensitive:** checked
- Decimal scale:** 2
- Target:**
 - External:** CSV (selected), XLS, TXT, HTML, JSON, XML, Star, Database, Cache
 - Name:** BostonHousingPrices_en.csv
- In table:** options for Insert above, Append below, Replace

2.13.9 Values Percentage

1. Select data row. Data filter can be set.
2. Select columns to be calculated.
3. Select objects: According to columns/rows/all.
4. Set decimal scale.

5. To negative values: skip, zero, or absolute value.
6. To non-numeric, skip or count as zero.
7. Select columns to be copied
8. Results can be written as external data, including: new csv/excel/text file, matrix, system clipboard, MyBox clipboard, database table, json, xml, html, or pdf.
9. When handle rows for current page or selected ones, results can be written in current page: insert, append, or replace data in defined location of the table.

.6-DataTools-zh.odt - OpenOffice Writer

编辑(E) 视图(V) 插入(I) 格式(O) 表格(A) 工具(T) 窗口(W) 帮助(H)

MyBox Edit Excel File : Excel - Food consumption of China *

Window Document Image Data File Media Network Settings Recent Accessed Development Help

Source row number item year 2020 year 2020_Percent... year 2019 year 2019_Percent...

Source row number	item	year 2020	year 2020_Percent...	year 2019	year 2019_Percent...
Row1	food consumption per capita(kil...	141.2	36.2	130.1	35.12
Row2	cooking oil consumption per ca...	10.4	2.67	9.5	2.56
Row3	vegetables				
Row4	meat consu				
Row5	poultry con				
Row6	aquatic pro				
Row7	eggs consu				
Row8	milk consu				
Row9	fruits consu				
Row10	sugar consu				
Column-Summation					

Value percentage - CSV - 64 - d:\tmp\mybox-data-6.5.9\data\ChinaFoods_en_en.csv

Percentage

Data Row filter Options

Columns to be calculated (No selection means all)

item year 2020 year 2019 year 2018 year 2017 year 2016
 year 2015 year 2014 year 2013

According to Columns Rows All

Decimal scale 2

To negative Skip Count as zero Absolute value

To invalid number Skip Count as zero

Columns to be copied

item year 2020 year 2019 year 2018 year 2017 year 2016
 year 2015 year 2014 year 2013

2.14 Data Charts

Hover or click button “Function” to select functions under menu item “Charts”.

The screenshot shows the MyBox Data Tools interface. A CSV file named "DiabetesPrediction_standardized_en.csv" is open. A context menu is displayed over a selected row in a table. The "Charts" option is highlighted in blue. Other chart types shown include XY chart, Pie chart, Box-and-whisker chart, Self comparison bars chart, Comparison bars chart, XYZ chart, and Location distribution.

Table r...	Data...	age	sex	BMI(body ...	Bl
1	1	0.038075906	0	0.0616962...	0
2	2	-0.001882...	0	-0.051474...	0
3	3	0.08529890...	0	0.0444512...	0
4	4	-0.089062...	0	0.0444512...	0
5	5	0.00538306...	0	0.0444512...	0
6	6	-0.092695...	0	0.0444512...	0
7	7	-0.045472...	0	0.0444512...	0
8	8	0.06350367...	0	0.0444512...	0
9	9	0.04170844...	0	0.0444512...	0
10	10	-0.070900...	0	0.0444512...	0
11	11	-0.096328...	0	0.0444512...	0
12	12	0.027178291	0	0.0175059...	0
13	13	0.016280676	0	-0.028840...	0
14	14	0.00538306	0	-0.001894...	0
15	15	0.045340983	0	-0.025606...	0


Selected: 0 Rows: [1-50]50/442 Page size 50 Page 1 /9

2.14.1 XY Chart

2.14.1.1 Data


1. Select data rows. Data filter can be set.
2. Select type of XY Chart.

3. Select one column as "Category Axis", to define data names.
4. Select several columns as "Value Axis". Different value series are shown in different colors or shapes.
5. By default, "Category Axis" is the horizontal axis and "Number Axis" is the vertical axis.
6. To invalid data:, skip or count as zero.
7. When display all data rows(all pages), need concern memory limitation.
8. Click button “Menu” to set parameters of chart.
9. Click button “Pop” to display current chart as image in popped window.
10. Click button “Data” to display data of the chart in data table.
11. Click button “Html” to display data of the chart in html page.




2.14.1.2 Bar Chart

1. Represents data size with bars' heights.
2. "Category" column is always counted as strings.




2.14.1.3 Stacked Bar Chart

1. Represents data size with bars' heights.
2. "Category" column is always counted as strings.




2.14.1.4 Line Chart

1. Represents data trend with lines connecting points.
2. "Category" column can be counted as strings or numbers.



2.14.1.5 Scatter Chart


1. Represents data distribution with symbols.
2. "Category" column can be counted as strings or numbers.



2.14.1.6 Bubble Chart


1. Represents data size with circles of different radius:
2. "Category Column" and "Value Column" define coordinates of data.

3. Select several columns as "Size Columns" to defines data size.
4. All columns should be numbers. Size columns should be non-negative.




2.14.1.7 Area Chart

1. Represents data size with area size.
2. "Category" column is always counted as strings.



2.14.1.8 Stacked Area Chart


1. Represents data size with area size.
2. "Category" column is always counted as strings.



2.14.1.9 Parameters of Data in Chart


1. Options about label: not display, point, value, category, etc.
2. Location of labels.

3. Font size of labels.
4. Decimal scale.




2.14.1.10 Layout

Set parameters of plot: title, font size, location of legend, zero-lines, grid lines, line width, etc.




2.14.1.11 Category Axis

Set parameters of category axis: label, font size, location, tick, count values as string or number, coordinate, etc.



2.14.1.12 Number Axis


Set parameters of number axis: label, font, location, tick, coordinate, etc.



2.14.2 Pie Chart

Data numbers are represented as percentages with a circle divided into segments.

1. Select data rows. Data filter can be set.
2. Select one column as "Category Axis", to define data names..
3. Select another column as "Number Axis". Values should be non-negative.
4. When display all data rows(all pages), need concern memory limitation
5. Click button “Menu” to set parameters of chart.
6. Click button “Pop” to display current chart as image in popped window.
7. Click button “Data” to display data of the chart in data table.
8. Click button “Html” to display data of the chart in html page.



2.14.3 Box-and-whisker Chart

2.14.3.1 Way of Calculation

Box-and-whisker chart represents data distribution:

1. Sort data according to column/row/all in ascending order.
2. Following items can show aggregation and discreteness of data:

Minimum $Q_0 = \text{in } 0\%(\text{start}) \text{ of the data list}$

Lower quartile $Q_1 = \text{in } 25\% \text{ of the data list}$

Median $Q_2 = \text{in } 50\%(\text{middle}) \text{ of the data list}$

Upper quartile $Q_3 = \text{in } 75\% \text{ of the data list}$

Maximum $Q_4 = \text{in } 100\%(\text{end}) \text{ of the data list}$

3. Following values can be used to mark outliers of data:

Lower extreme outlier line $E_1 = Q_1 - 3 * (Q_3 - Q_1)$

Lower mild outlier line $E_2 = Q_1 - 1.5 * (Q_3 - Q_1)$

Upper mild outlier line $E_3 = Q_3 + 1.5 * (Q_3 - Q_1)$

Upper extreme outlier line $E_4 = Q_3 + 3 * (Q_3 - Q_1)$

4. Following values can be referred for discreteness:

Mean = average of the data list


2.14.3.2 Options of Calculation

1. Select data rows. Data filter can be set.
2. Select objects: According to columns, rows(select category column), or all.
3. Select columns to be calculated.

4. Set conditions of sorting, and maximum data number to take.
5. To invalid values: skip, or count as zero.

2.14.3.3 Statistic Data


Generated statistic data can be viewed and edited.



2.14.3.4 Options of Chart

1. Box width
2. Whether display outliers lines or mean
3. Whether display connection lines of values, and whether dotted lines

4. Whether transpose
5. Maximum data number in chart
6. Random colors
7. Click button “Menu” to set parameters of chart.
8. Click button “Pop” to display current chart as image in popped window.
9. Click button “Data” to display data of the chart in data table.
10. Click button “Html” to display data of the chart in html page.



2.14.4 Self Comparison Bars Chart

2.14.4.1 Way of Calculation

Self comparison bars show difference between data and reference values. Bars are calculated by following rulers:

1. If value is zero, no bar
2. When compare as absolute values:

maximum_value = maximum_absolute_value_of_column/row/all

percentage = absolute_value / maximum_value

width = maximum_width * percentage

color = If value is larger than zero, color_of_column.

If value is less than zero, inverted_color_of_column

3. When compare as range of minimum and maximum:

maximum_value = maximum_value_of_column/row/all

minimum_value = minimum_value_of_column/row/all

percentage = (value - minimum_value) / (maximum_value - minimum_value)

width = maximum_width * percentage

color = color_of_column

2.14.4.2 Options of Calculation

1. Select data rows. Data filter can be set.
2. Select columns to be calculated.
3. Select columns to be copied.
4. Set conditions of sorting, and maximum data number to take.
5. Select how to handle invalid data.
6. Set decimal scale.
7. When display all data rows(all pages), need concern memory limitation.

2.14.4.3 Options of Chart

1. Select objects to compare: columns/rows/all.
2. Select comparison way: absolute values, or range of minimum and maximum.
3. Set maximum width of bars.
4. Set maximum data number in chart.
5. Select whether display row numbers, values, percentages, categories, calculated values.
6. Edit data in chart.
7. Edit html of chart.

MyBox User Guide – Data Tools v6.6.2

Self comparison bars chart - CSV - 944 - d:\tmp\mybox-data-6.5.9\data\ChinaPopulation_en.csv

Data Filter Options

Columns to be calculated (No selection means all)

year_ population at year-end(ten thousand) male(ten thousand) female(ten thousand) urban(ten thousand) rural(ten thousand)

Columns to be copied

year_ population at year-end(ten thousand) male(ten thousand) female(ten thousand) urban(ten thousand) rural(ten thousand)

Order by (Column type affects sorting results)

Table r...	Sort
<input type="checkbox"/> year_ Descending	
<input type="checkbox"/> 2 year_-Ascending	
<input checked="" type="checkbox"/> 3 population at year-end(ten thousand)	
<input type="checkbox"/> 4 population at year-end(ten thousand)	

Maximum sorted rows to take (Empty/zero/negative)

Decimal scale 2

To invalid number Skip Count as zero

All data are involved in memory. Too many data may out of memory.

Compare

Columns Rows All

According to

Absolute value Range of min and max

Maximum width 80

Maximum data in chart (Empty/zero/negative to unlimit)

100

Row number Value Percentage Others Calculated values

CSV - 944 - d:\tmp\mybox-data-6.5.9\data\ChinaPopulation_en.csv - Self comparison bars chart Column comparison

male(ten thousand)	female(ten thousand)	year_	male(ten thousand)	female(ten thousand)
Max absolute: 72357.0	Max absolute: 68969.0			
99%	99%	2021	72311	68949
100%	99%	2020	72357	68855
99%	100%	2019	72039	68969
99%	99%	2018	71864	68677
99%	99%	2017	71650	68361
98%	98%	2016	71307	67925
97%	97%	2015	70857	67469
97%	97%	2014	70522	67124
96%	96%	2013	70063	66663

2.14.5 Comparison Bars Chart

2.14.5.1 Way of Calculation

Comparison bars show difference between two series of data. Bars are calculated by following rulers:

1. If value is zero, no bar
2. When compare as absolute values:

maximum_value = maximum_absolute_value_of_value_columns

percentage = absolute_value / maximum_value

width = maximum_width * percentage

color = If value is larger than zero, color_of_column.

If value is less than zero, inverted_color_of_column

3. When compare as range of minimum and maximum:

maximum_value = maximum_value_of_value_columns

minimum_value = minimum_value_of_value_columns

percentage = (value - minimum_value) / (maximum_value - minimum_value)

width = maximum_width * percentage

color = color_of_column

2.14.5.2 Options of Calculation

1. Select data rows. Data filter can be set.
2. Select one column as category column(unnecessary).
3. Select two columns to be compared.
4. Select columns to be copied.
5. Set conditions of sorting, and maximum data number to take.
6. Set decimal scale.
7. When display all data rows(all pages), need concern memory limitation.

2.14.5.3 Options of Chart

1. Select comparison way: absolute values, or range of minimum and maximum.
2. Set maximum width of bars.
3. Set maximum data number in chart.
4. Select whether display row numbers, values, percentages, categories, calculated values.
5. Edit data in chart.
6. Edit html of chart.

Comparison bars chart - CSV - 944 - d:\tmp\mybox-data-6.5.9\data\ChinaPopulation_en.csv

Data **Filter** **Options**

Category column **year_**

Value column **male(ten thousand)**

Value column **female(ten thousa...**

Columns to be copied

year_ population at year-end(ter
 male(ten thousand) female(ten t
 urban(ten thousand) rural(ten th

Order by(Column type affects sorting res

Table r...

1 year_-Descending
 2 year_-Ascending
 3 population at year-end(te
 4 population at year-end/te

Maximum sorted rows to take(Empty/zero)

Decimal scale **2**

All data are involved in memory. Too ma
out of memory.

According to
 Absolute value
 Range of min and max

Maximum width **80**

Maximum data in chart(Empty/zero/negative to unlimit)
100

Row number Value Percentage Category
Others Calculated values

**CSV - 944 - d:\tmp\mybox-data-
6.5.9\data\ChinaPopulation_en.csv -
Comparison bars chart**


Maximum: 72357.0 Minimum: 26022.0

male(ten thousand)	year_	female(ten thousand)	urban(ten thousand)	rural(ten thousand)
99%	2021	92%	91425	49835
100%	2020	92%	90220	50992
99%	2019	92%	88426	52582
98%	2018	92%	86433	54108
98%	2017	91%	84343	55668
97%	2016	90%	81924	57308
96%	2015	89%	79302	59024
96%	2014	88%	76738	60908
95%	2013	87%	74502	62224
94%	2012	86%	72175	63747

H2

2.14.6 XYZ Chart

1. Base on [echarts-gl](#), 3D charts can be displayed in html with technic of WebGL.
2. Webview of JavaFX does not support WebGL, so generated html will be displayed by system web browser.
3. Please make sure your system web browser supports WebGL and does not limit local JavaScript files.



2.14.6.1 3-D Scatter

1. Select data rows. Data filter can be set.
2. Select data axes:
 - o Select one column as axis X. Select as string or number.
 - o Select one column as axis Y. Select as string or number.
 - o Select several columns as axis Z. Select as string or number.
3. Select other columns to be popped in labels
4. Set parameters of the chart: projection, color, width, height, whether dark, point size.

XYZ chart - CSV - 942 - d:\tmp\mybox-data-6.5.9\data\DiabetesPrediction_en.csv

XYZ chart

Data **Filter** **Options**

Axis X age Count values as strings

Axis Y BMI(body mass in... Count values as strings

Axis Z (No selection means all) Count values as strings

sex BP(average blood pressure) S1(blood serum measurement 1) S2(blood serum measurement 2)
 S3(blood serum measurement 3) S4(blood serum measurement 4) S5(blood serum measurement 5)
 S6(blood serum measurement 6) disease progression one year after baseline

Other values to be popped

age sex BMI(body mass index) BP(average blood pressure) S1(blood serum measurement 1)
 S2(blood serum measurement 2) S3(blood serum measurement 3) S4(blood serum measurement 4)
 S5(blood serum measurement 5) S6(blood serum measurement 6)
 disease progression one year after baseline

Type Scatter chart Surface chart

Projection Perspective Orthographic

Color Column Gradient Random

Width px

Height px

Dark mode

Point size

Notice: A html file will be generated to display the chart.
 Please make sure your system web browser supports WebGL and does not limit local JavaScript files.

2.14.6.2 Surface Chart

1. Select data rows. Data filter can be set.
2. Select data axes:
 - Select one column as axis X. Select as string or number.
 - Select one column as axis Y. Select as string or number.
 - Select one column as axis Z. Select as string or number.
3. Select other columns to be popped in labels.
4. Set parameters of the chart: projection, color, width, height, whether dark, wire frame.

XYZ chart - CSV - 942 - d:\tmp\mybox-data-6.5.9\data\DiabetesPrediction_en.csv

XYZ chart

Data **Filter** **Options**

Axis X BMI(body mass in... Count values as strings

Axis Y S5(blood serum m... Count values as strings

Axis Z disease progressio... Count values as strings

Other values to be popped
 age sex BMI(body mass index) BP(average blood pressure) S1(blood serum measurement 1)
 S2(blood serum measurement 2) S3(blood serum measurement 3) S4(blood serum measurement 4)
 S5(blood serum measurement 5) S6(blood serum measurement 6)
 disease progression one year after baseline

Type Scatter chart Surface chart

Projection Perspective Orthographic

Color Column Gradient Random

Width px

Height px

Dark mode Wire frame


Notice: A html file will be generated to display the chart.
 Please make sure your system web browser supports WebGL and does not limit local JavaScript files.





Progression Prediction of Diabetes - Surface chart

Axis X: "BMI(body mass index)" Axis Y: "S5(blood serum measurement 5)" Axis Z: "disease progression one year after baseline"



2.14.7 Locations Distribution

Display location data in map dynamically.

2.14.7.1 Options of Data

1. Select data rows. Data filter can be set.
2. Select one column for each of the following: Label, Longitude, Latitude, and Size.
3. Select other columns to be displayed in popped labels.
4. Select coordinate system of data.
5. Set conditions of sorting, and maximum data number to take.

2.14.7.2 Data in Map


Data referred by map are displayed in table.

Data...	Country	Longitude	Latitude	
1	Myth-Shui Ren	112.55699	34.87973	Unknown
2	Myth-Fu Hsi	109.18939	34.224677	Unknown
3	Myth-Nu Wa	111.107528	35.126412	Unknown
4	Myth-Shen Nun...	113.772655	26.489902	Unknown
5	Myth-Yellow Em...	113.730529	34.395562	Unknown
6	Myth-Shao Hao	118.822224	34.30994	穷桑 (江苏省)
7	Myth-Zhuan Xu	115.071879	34.445656	帝丘 (河南省)
8	Myth-Emperor Ku	115.65637	34.414172	毫 (河南省)
9	Myth-Yao	111.518976	36.088005	唐 (山西省)
10	Myth-Shun	110.329194	34.831075	蒲坂 (山西省)
11	Xia Dynasty	111.220456	35.141363	安邑 (山西省)
12	Xia Dynasty	113.050492	34.453667	阳城 (河南省)
13	Xia Dynasty	113.488478	34.140701	阳翟 (河南省)
14	Xia Dynasty	111.007528	35.026412	安邑 (山西省)
15	Xia Dynasty	112.693124	34.69775	斟鄩 (河南省)
16	Xia Dynasty-Ho...	112.789612	34.90797	鉏/穷石 (河南省)
17	Xia Dynasty	114.28185	34.8138	老丘 (河南省)
18	Xia Dynasty	114.392392	36.097577	西河 (河南省)
19	Shang Dynasty	115.65537	34.454172	亳 (河南省)

Selected: 0 Rows: [1-20] 20/163 Page size 20 Page


2.14.7.3 Options of Map

1. Map type: TianDi map, or GaoDe map.
2. Select projection and size of map.
3. Set image and text of markers.
4. Select whether pop information.
5. Select controls of map.



2.14.7.4 Options of Playing

1. Select timer:
 - Delay: After display current frame, wait for defined time, and then display next frame.
 - Interval: Keep defined time between current frame and next frame.
2. Select whether: Loop, Reverse, Accumulate, Move Center, Link.
3. Auto-play.
4. Display specific frame.
5. Buttons of navigation.
6. Snapshot:
 - Select background color and dpi.
 - Snap frame by frame, and display them in “Edit Images List”.
7. Set maximum data number in chart.



2.15 Group Charts

Hover or click button “Function” to select functions under menu item “Group Charts”.

The screenshot shows the MyBox Data Tools interface with a CSV file named "ConcreteCompressiveStrength_en.csv" loaded. The window title bar reads "Edit CSV File : CSV - 1003 - d:\tmp\mybox-data-6.5.9\data\ConcreteCompressiveStrength_en.csv". The menu bar includes Window, Document, Image, Data, File, Media, Network, Settings, Recent Accessed, Development, and Help. Below the menu is a toolbar with icons for various functions. The main area displays a table with data from the CSV file. A context menu is open over the table, with the "Edit" tab selected. The "Group Charts" option is highlighted in blue, indicating it is the active function. Other options in the menu include Data, Modify, Trim, Calculation, Charts, Examples, and a checkbox for "Pop when mouse hovering". At the bottom of the interface, there are buttons for navigating through the data, selecting rows, and setting page size and page number.

Table r...	Data...	Cement(kg)	Blast Furn...	Fly Ash(kg)	V
1	1	540	0	0	16
2	2	540	0	0	16
3	3	333	143	0	22
4	4	333	143	0	22
5	5				
6	6				
7	7				
8	8				
9	9				
10	10	475	0	0	228
11	11	199	132	0	192
12	12	199	132	0	192
13	13	428	48	0	228
14	14	190	190	0	228
15	15	304	76	0	228


Selected: 0 Rows: [1-50]50/1030 Page size 50 Page 1 /21

2.15.1 General Manufacture

After data are grouped, generate one chart for each group, and display them in sequence dynamically.

2.15.1.1 Group Data

1. Select data rows. Data filter can be set.
2. Set conditions of grouping.
3. Set specific options to generate chart.
4. Set conditions of sorting, and maximum data number to pick.
5. Set decimal scale, and how to handle invalid values.



2.15.1.2 Results of Grouping

After calculation, grouped data are displayed in table.

My Box Group Data - XY chart - CSV - 944 - d:\tmp\mybox-data-6.5.9\data\ChinaPopulation_en.csv

Data Row filter Group Options

Category column year_

Value columns (No selection means all)

year_ population at year-end(ten thousand)
 male(ten thousand) female(ten thousand)

urban(ten thousand) rural(ten thousand)

Order by(Column type affects sorting results)

Table r...
Sort

1 year_-Descending
 2 year_-Ascending

3 population at year-end(ten thousand)
 4 population at year-end(ten thousand)

<
Maximum rows in each group(Empty/zero/negative)
>

Decimal scale 2

To invalid number Set as blank Set as zero

Row number

XY chart Group Data

Data...	id	group_id	range_year_	year_	male_...	fer...
1	1	1	[1949,1958)	1957	33469	311
2	2	1	[1949,1958)	1956	32536	302
3	3	1	[1949,1958)	1955	31809	296
4	4	1	[1949,1958)	1954	31242	290
5	5	1	[1949,1958)	1953	30468	283
6	6	1	[1949,1958)	1952	29833	276
7	7	1	[1949,1958)	1951	29231	270
8	8	1	[1949,1958)	1950	28669	265
9	9	1	[1949,1958)	1949	28145	260
10	10	2	[1958,1967)	1966	38189	363
11	11	2	[1958,1967)	1965	37128	354
12	12	2	[1958,1967)	1964	36142	343
13	13	2	[1958,1967)	1963	35533	336
14	14	2	[1958,1967)	1962	34517	327
15	15	2	[1958,1967)	1959	34890	323

Selected: 0 Rows: [1-20]20/73 Page size 20


1 /4

2.15.1.3 Display Options of Chart

1. Specific display options of chart.
2. Set maximum data number displayed in chart.

2.15.1.4 Options of Playing

1. Select timer:
 - Delay: After display current frame, wait for defined time, and then display next frame.
 - Interval: Keep defined time between current frame and next frame.
2. Select whether: Loop, Reverse, Accumulate, Move Center, Link.
3. Auto-play.
4. Display specific frame.
5. Buttons of navigation.
6. Snapshot:
 - Select background color and dpi.
 - Snap frame by frame, and display them in “Edit Images List”.




2.15.2 Group Data – XY Chart

2.15.2.1 Specific Options to Generate Chart

1. Select one column as category axis.
2. Select several columns as value axis.

2.15.2.2 Specific Options to Display Chart


1. Type of XY chart
2. Whether transpose



2.15.3 Group Data – Pie Chart

2.15.3.1 Specific Options to Generate Chart

1. Select one column as category axis.
2. Select one column as value axis.




2.15.4 Group Data – Box-and-whisker Chart

2.15.4.1 Specific Options to Generate Chart

1. Select several columns to be calculated.

2.15.4.2 Specific Options to Display Chart

1. Box width
2. Whether display outliers lines or mean
3. Whether display connection lines of values, and whether dotted lines
4. Whether transpose
5. Maximum data number in chart



2.15.5 Group Data – Self Comparison Bars Chart

2.15.5.1 Specific Options to Generate Chart

1. Select several columns to be calculated.
2. Select columns to be copied.

2.15.5.2 Specific Options to Display Chart

1. Select objects to compare: columns/rows/all.
2. Select comparison way: absolute values, or range of minimum and maximum.
3. Set maximum width of bars.
4. Set maximum data number in chart

Group Data - Self comparison bars chart - CSV - 944 - d:\tmp\mybox-data-6.5.9\data\ChinaPopulation_en.csv

Self comparison bars chart

Delay: 500 Milliseconds
 Loop Reverse
Frame: 5 [1... /10

Snapshot

Background:
DPI: 96

Calculated values

CSV - 944 - d:\tmp\mybox-data-6.5.9\data\ChinaPopulation_en.csv - Self comparison bars chart
Group id5 - [1977,1984) Column comparison

urban(ten thousand)	rural(ten thousand)	year_	urban(ten thousand)	rural(ten thousand)
Maximum: 22274.0	Maximum: 80734.0			
Minimum: 16669.0	Minimum: 78305.0			
100%	100%	1983.0	22274	80734
85%	76%	1982.0	21480	80174
62%	65%	1981.0	20171	79901
44%	51%	1980.0	19140	79565
32%	30%	1979.0	18495	79047
1%	29%	1978.0	17245	79014

2.15.6 Group Data – Comparison Bars Chart

2.15.6.1 Specific Options to Generate Chart

1. Select one column as category column(unnecessary).
2. Select two columns to be compared.
3. Select columns to be copied.

2.15.6.2 Specific Options to Display Chart

1. Select comparison way: absolute values, or range of minimum and maximum.
2. Set maximum width of bars.
3. Set maximum data number in chart

Group Data - Comparison bars chart - CSV - 944 - d:\tmp\mybox-data-6.5.9\data\ChinaPopulation_en.csv

Comparison bars chart

Delay Interval
500 Milliseconds
Loop Reverse

Frame 5 [1... /10

Row number Value Percentage Category
Others Calculated values

CSV - 944 - d:\tmp\mybox-data-6.5.9\data\ChinaPopulation_en.csv - Comparison bars chart Group id5 - [1977,1984]

Max absolute: 80734.0

urban(ten thousand)	year_	rural(ten thousand)	urban(ten thousand)	rural(ter thousand)
27%	1983.0	100%	22274	80734
26%	1982.0	99%	21480	80174
24%	1981.0	98%	20171	79901
23%	1980.0	98%	19140	79565
22%	1979.0	97%	18495	79047
21%	1978.0	97%	17245	79014
20%	1977.0	96%	16669	78305

* Links and controls may be unresponsive when html page is editable.

2.16 Input Data

2.16.1 Load Contents in System Clipboard

1. Read contents in System Clipboard.
 2. Guess delimiter and parse data.
 3. User can select a delimiter to parse data.
 4. Select how to parse:
 - CSV parser: Values can contain delimiter and line break. But not support parsing “Blanks” and “Regular Expression”.
 - Text parser: Values can not contain delimiter and line break. Support parsing “Blanks” and “Regular Expression”.
 5. Select whether first line defines column names.
 6. Based on parsed data, select rows and columns to load. Data filter can be set.

Load content in system clipboard. : CSV - 1032 - d:\tmp\mybox-data-6.5.9\AppData\Temp\2022-11-16_10...

My Box CSV Texts

First line defines the columns' names
Delimiter: ,

	Table r...	Data...	Column...	Column...	Column...	Cc +
<input type="checkbox"/>	1	1	age	sex	BMI(b	
<input type="checkbox"/>	2	59		2	32.1	
<input type="checkbox"/>	3	48		1	21.6	
<input type="checkbox"/>	4	72		2	30.5	
<input type="checkbox"/>	5	24		1	25.3	
<input type="checkbox"/>	6	50		1	23	
<input type="checkbox"/>	7	23		1	22.6	
<input type="checkbox"/>	8	36		2	22	
<input type="checkbox"/>	9	66		2	26.2	
<input type="checkbox"/>	10	60		2	32.1	
<input type="checkbox"/>	11	29		1	30	
<input type="checkbox"/>	12	22		1	18.6	

Selected: 0 Rows: [1-50]50/51 Page size 50

Page <

2.16.2 Import Examples

Hover or click button “Examples” and item in popped menu.

2.16.2.1 Personal Data

Record private data.

The screenshot shows the MyBox Data Tools interface with a CSV file titled "Edit CSV File : CSV - 19 - D:\tmp\mybox-data\mybox-data-6.6.2\data\ChinaPopulation_en.csv" open. A context menu is displayed over a table row, with "My Data" selected. The table contains the following data:

		Year	Population	Area	Notes
1	4	1952	57482	29833	Notes
2	5	1953	58796	30468	Contacts
3	6	1954	60266	31242	Cash Flow
4	7	1955	61465	31809	(ten ... rural(ten t...)
5	8	1956	62828	32536	Private Property
6	9	1957	64653	33469	Eyesight
7	10	1958	65994	34195	Weight
8	11	1959	67207	34890	Height
9	12	1960	66207	34283	Menstruation
10	13	1961	65859	33880	
11	14	1962	67296	31517	
12				32778	
13				11659	
14				55636	

Selected: 0 Rows: [1-50]50/73 Page size 50 Page 1 /2

2.16.2.2 Statistic Data of China

Data from China National Bureau of Statistics.

The screenshot shows the MyBox Data Tools interface with a CSV file titled "Edit CSV File : CSV - 85 - D:\tmp\mybox-data\mybox-data-6.6.2\data\ChinaMuseums_en.csv". The main window displays a table of data with columns: Year, Type, Number, and another unnamed column. A context menu is open over the table, showing options like "My Data", "Statistic data of China", "Regression data", "Location Data", and "Close(ESC/F6 Or click anywhere outside the object)". The "Statistic data of China" option is currently selected. To the right of the table, a sidebar lists various statistical categories with their counts: Population of China (39), Census of China (66), Gross domestic product(GDP) of China (25), Consumer price index(CPI) of China (39), Food consumption of China (66), Graduates of China (25), Museums of China (selected), Health personnel of China (3), Marriage of China (3), Sport world champions of China (3), Crimes filed by China police (3), Crimes filed by China procuratorate (3), and China National Bureau of Statistics (4). The bottom of the interface shows navigation controls for pages and rows.

Year	Type	Number	
11	04	2012	5069
12	65	2013	3473
13	66	2014	3658
14	67	2015	3852
15	68	2016	4109
16	69	2017	4721
17	70	2018	4918
18	71	2019	5132
19	72	2020	5452
20	73	2021	3671

Selected: 0 Rows: [51-73]23/73 Page size 50 Page 2 /2

2.16.2.3 Data of Regression

Data can be used to analyse models of regression.

The screenshot shows the MyBox Data Tools interface with a CSV file open. The sidebar on the left contains a 'Table' section with numbered items 1 through 13, and a 'Regression data' section with several entries. The 'Regression data' section is expanded, showing a list of datasets. One dataset, 'Concrete compressive strength', is selected and highlighted in blue. The main area displays a table of data for this selected dataset.

4	4	333	143	0				
5	5	199	132	0				
6	6	266	114	0				
7	7	380	95	0				
8	8	380	95	0				
9	9	266	114	0				
10	10	475	0	0				
11	11	199	132	0				
12	12	199	132	0	192	0	978.4	826
13	13	428	48	0	228	0	932	594

Selected: 0 Rows: [1-50]50/1030 Page size 50 Page 1 /21

2.16.3 Location Data

Data can be used to generate “Location Distribution”.

The screenshot shows the MyBox Data Tools interface with a CSV file titled "EuropeanGadwalls_en.csv" open. The file contains data about European Gadwalls, including columns for Longitude, Latitude, and coordinates. A context menu is open over the data, with "Location Data" selected. Other options in the menu include "My Data", "Statistic data of China", and "Regression data". The main window displays a table with 13 rows of data, each containing a timestamp and coordinates. The bottom of the screen shows navigation and search controls.

		Longitude	Latitude	Coordinate
1				
2	<input checked="" type="checkbox"/> Pop when mouse hovering			
3	<input type="checkbox"/> Close(ESC/F6 Or click anywhere outside the window)			
4	4	2009-08-04 11:00:00	2009-08-04 11:00:00	11.73433 48.21033 WGS_84
5	5	2009-08-04 17:00:00	2009-08-04 17:00:00	11.73317 48.20967 WGS_84
6	6	2009-08-04 18:00:00	2009-08-04 18:00:00	11.733 48.20867 WGS_84
7	7	2009-08-04 23:00:00	2009-08-04 23:00:00	11.733 48.20867 WGS_84
8	8	2009-08-05 09:00:00	2009-08-05 09:00:00	11.74133 48.21067 WGS_84
9	9	2009-08-05 11:00:00	2009-08-05 11:00:00	11.73917 48.21133 WGS_84
10	10	2009-08-05 17:00:00	2009-08-05 17:00:00	11.74067 48.21117 WGS_84
11	11	2009-08-05 18:00:00	2009-08-05 18:00:00	11.74083 48.211 WGS_84
12	12	2009-08-06 11:00:00	2009-08-06 11:00:00	11.7435 48.21117 WGS_84
13	13	2009-08-06 18:00:00	2009-08-06 18:00:00	11.74333 48.21033 WGS_84

2.17 Output Data

Hover or click button “Function” to select functions under menu item “Data”.

The screenshot shows the MyBox Data Tools interface. At the top, there's a menu bar with items: Window, Document, Image, Data, File, Media, Network, Settings, Recent Accessed, Development, Help. Below the menu bar is a toolbar with various icons. A context menu is open, specifically the 'Data' submenu under the 'Function' icon. The 'Data' submenu includes options like Save, Modify, Trim, Calculation, Charts, Examples, and Export. The 'Export' option is currently selected. The main area of the interface displays a CSV file titled 'DiabetesPrediction_en.csv' with 14 columns and 442 rows of data. The bottom of the interface has navigation controls for pages, rows, and columns, along with various icons for file operations.

Index	1	2	3	4	5	6	7	8	9	10	11	12	13	14
	1	2	3	4	5	6	7	8	9	10	11	12	13	14
	59	48	72	24	50	23	36	66	60	29	22	56	53	50
	2	2	1	1	2	2	1	2	32.1	1	1	28	1	2
	26.2	30	18.6	23.7	26.2	26.2	23.7	26.2	83	85	97	92	97	97
	114	85	97	92	97	97	92	97	179	180	114	184	186	186
	255	185	57.6	109.2	105.4	105.4	109.2	105.4	119.4	93.4	57.6	144.8	62	49
	4.5	42	46	32	49	49	62	49	42	43	46	32	6	4

Selected: 0 Rows: 50/442 Page size: 50 / Page: 1 / 9

2.17.1 Export

2.17.1.1 Data Source

1. Select data rows and columns.
2. Data filter can be set.

MyBox Export - CSV - 942 - d:\tmp\mybox-data-6.5.9\data\DiabetesPrediction_en.csv

Data Row filter Target formats Target files Logs

Rows Selected Current page All pages

Columns   

<input type="checkbox"/> Table r...	<input type="checkbox"/> Data...	<input checked="" type="checkbox"/> age	<input checked="" type="checkbox"/> sex	<input checked="" type="checkbox"/> BMI(b...	<input checked="" type="checkbox"/> BP(ave...	<input type="checkbox"/> S1(blo...	<input type="checkbox"/> S2(blo...	<input type="checkbox"/> S3 +
<input type="checkbox"/> 1	1	59	2	32.1	101	157	93.2	38
<input type="checkbox"/> 2	2	48	1	21.6	87	183	103.2	70
<input checked="" type="checkbox"/> 3	3	72	2	30.5	93	156	93.6	41
<input checked="" type="checkbox"/> 4	4	24	1	25.3	84	198	131.4	40
<input checked="" type="checkbox"/> 5	5	50	1	23	101	192	125.4	52
<input checked="" type="checkbox"/> 6	6	23	1	22.6	89	139	64.8	61
<input type="checkbox"/> 7	7	36	2	22	90	160	99.6	50
<input type="checkbox"/> 8	8	66	2	26.2	114	255	185	56
<input type="checkbox"/> 9	9	60	2	32.1	83	179	119.4	42
<input checked="" type="checkbox"/> 10	10	29	1	30	85	180	93.4	43
<input checked="" type="checkbox"/> 11	11	22	1	18.6	97	114	57.6	46
<input type="checkbox"/> 12	12	56	2	28	85	184	144.8	32
<input checked="" type="checkbox"/> 13	13	53	1	23.7	92	186	109.2	62
<input type="checkbox"/> 14	14	50	2	26.2	97	186	105.4	49
<input type="checkbox"/> 15	15	61	1	24	91	202	115.4	72

Selected: 7 Rows: [1-50]50/442 Page size 50 Page 1 /9     

2.17.1.2 Formats of Targets

1. Select targets and their formats: csv, texts, excel, xml, json, html, pdf, MyBox Clipboard.
2. Set options of target files.
3. Split files in maximum lines.
4. Select whether include row numbers.
5. Select whether save date/time/era and numbers as columns' formats.

My Box Export - CSV - 942 - d:\tmp\mybox-data-6.5.9\data\DiabetesPrediction_en.csv

Data Row filter Target formats Target files Logs

Base CSV Excel Texts html json PDF

Formats  

CSV XLS TXT JSON XML HTML PDF 

Split files in maximum lines Not split

Row number

Save date/time/era and numbers as columns' formats

2.17.1.3 Target Files

1. Set target path.
2. Select whether open files after export.

My Box Export - CSV - 942 - d:\tmp\mybox-data-6.5.9\data\DiabetesPrediction_en.csv

Data Row filter Target formats Target files Logs

Target path d:\tmp\mybox-data-6.5.9\generated 

Append timestamp in file name


If files exist Replace Skip Target name append _m

Open files after export


 

2.17.2 Convert to Database Table

1. Select data rows. Data filter can be set.
2. Select columns to be copied.
3. Select whether import data.



4. Create auto-increment column, or select some columns as primary key.



2.18 Manage Data

MyBox records definition of data objects in its internal table:

	csv/excel/text files	MyBox Clipboard	Matrice	Database tables
Time to create data definition	When data file is opened for the first time	When data are copied in MyBox Clipboard	When new matrix is saved in Matrices Manager	When new table is saved in Database Table Manager
Storage location of data	Data file	Files under MyBox internal path.	Database table of MyBox	Database tables of MyBox
When delete data definition	Data file is not affected	Internal file is deleted	Data of matrix are cleared	Database table is dropped

The screenshot shows the 'Manage Data' window for a database table named 'CHINAPOPULATION_EN'. The window has a toolbar at the top with various icons for file operations like Open, Save, Print, and Export. Below the toolbar is a menu bar with options: Window, Document, Image, Data, File, Media, Network, Settings, Recent Accessed, Development, and Help.

The main area is divided into two sections. On the left, there is a list of data objects with checkboxes next to them. The objects include:

- at... 73 Matrix a
- at... 6 Matrix b
- at... 6 Excel ChinaPopulat...
- at... 6 Database Table ChinaPopulat...
- at... 1 Matrix
- at... 6 Matrix

A specific row (row 12) is selected, highlighted with a blue background. The status bar at the bottom left shows 'Rows: 50/457 Selected: 1'.

On the right, a detailed view of the selected database table '1081' is shown. The table has columns: Data row, id, year_, populatio..., and m+. The data rows show population values for years 1949 to 1954. The status bar at the bottom right shows 'Selected: 0 Rows: 50/73 Page size 50'.

Below the table view, there is a 'Query' section with options to type file types (CSV, XLS, TXT, Matrix, Database Table, MyBox Clipboard), choose a sorting order (Descending, Modify time, Name, ID, Rows number, Columns number, File), and page navigation controls.

2.19 Splice Data

1. Select or open two data.
2. Select rows and columns from the two data:
 - Rows can be: current page, selected rows, or all pages.
 - Select columns. If no column is selected, then all columns are taken.
 - Set row filter.
3. Options:
 - Direction: vertical, horizontal
 - Rows/Columns number by: Data A, Data B, longer, shorter.
4. Target can be following: new csv/excel/text file, matrix, system clipboard, MyBox clipboard, database table.

Splice Data : Database Table - 1081 - CHINAPOPULATION_EN

Window Document Image Data File Media Network Settings Recent Accessed Development Help

Tab...	ID	Type	Row...	Colu...	+
<input type="checkbox"/> 1	1105	Texts	ChinaPo...	73	6
<input type="checkbox"/> 2	1061	Texts	ChinaPo...	73	6
<input type="checkbox"/> 3	1089	MyBox Clipbo...	ChinaPo...	6	7
<input type="checkbox"/> 4	1086	MyBox Clipbo...	ChinaPo...	6	7
<input type="checkbox"/> 5	1085	MyBox Clipbo...	ChinaPo...	6	7
<input type="checkbox"/> 6	1083	MyBox Clipbo...	ChinaPo...	1	7
<input type="checkbox"/> 7	1082	MyBox Clipbo...	ChinaPo...	6	7
<input type="checkbox"/> 8	1063	MyBox Clipbo...	a	6	3
<input type="checkbox"/> 9	1065	Matrix	a	3	3
<input type="checkbox"/> 10	1064	Matrix	b	6	4
<input type="checkbox"/> 11	1062	Excel	ChinaPo...	73	6
<input checked="" type="checkbox"/> 12	1081	Database Table	ChinaPo...	73	7
<input type="checkbox"/> 13	1069	Database Table	ed	3	3
<input type="checkbox"/> 14	1068	Database Table	ChinaPo...	73	7
<input type="checkbox"/> 15	1103	CSV	ChinaPo...	73	6

Page 1 /10 Page size
50 Rows: 50/457 Selected: 1

Set as data B

Data A Data B Splice Data

Direction

Horizontal Vertical

Rows number

By Data A Data B Longer Shorter

Target

CSV XLS TXT Matrix Clipboard Database Text Image

Name

2.20 Data File

2.20.1 CSV File

1. In the file:
 - In general, the first line(header) defines column names, and each of followed lines defines a row of data.
 - Values are separated by "delimiter" which can be string.
 - If a value contains delimiter or line break, it should be surrounded by quotes.
 - If delimiter is “#”, lines started with “#” are skipped and treated as comments.
2. When the file is opened for the first time, the tool guesses its delimiter and charset.
3. When file is loaded abnormally, change options and click Refresh button.
4. Data are paginated. When pages number is larger than 1, changes should be saved before run some functions.
Options: charset, whether has first line as field names, and delimiter of data.
5. To string values, multiple lines can be edited and saved.
6. Data can be saved as different charsets and delimiters.

	Ta...	Data ...	age	sex
1	1	59	2	
2	2	48	1	
3	3	72	2	
4	4	24	1	
5	5	50	1	
6	6	23	1	
7	7	36	2	
8	8	66	2	
9	9	60	2	
10	10	29	1	
11	11	22	1	
12	12	56	2	
13	13	53	1	
14	14	50	2	

2.20.2 Text File

1. In the file:
 - In general, the first line(header) defines column names, and each of followed lines defines a row of data.
 - Values are separated by "delimiter" which can be string.
Regular expression is supported when parse the file.
 - Values should not contain delimiter.
 - If a line starts with "#", it will be skipped.
 2. When the file is opened for the first time, the tool guesses its delimiter and charset.
 3. When file is loaded abnormally, change options and click Refresh button.
 4. Data are paginated. When pages number is larger than 1, changes should be saved before run some functions.
Options: charset, whether has first line as field names, and delimiter of data.
 5. Not support multiple lines in values.
 6. Data can be saved as different charsets and delimiters.

MyBox Edit Text Data File : Texts - 69 - d:\tmp\mybox-data-6.5.9\data\ChinaCPI_en.csv

Window Document Image Data File Media Network Settings Recent Accessed Development Help

► Information

▼ Format

Charset

Determine automatically

Known

First line defines columns names

Text delimiter

String

Tab Blank Blank characters 4 blanks

8 blanks

, | # - + : ; @ & % !

" ' ? . * \ / _ = < >

If file is loaded incorrectly, change options and click button "Refresh"

► Backup

▼ Save as

Charset

First line defines columns names

Text delimiter

String

	Ta...	Data ...	year_	consumer ...	urba+
1	1	1951	112.5		
2	2	1952	102.7		
3	3	1953	105.1		
4	4	1954	101.4		
5	5	1955	100.3		
6	6	1956	99.9		
7	7	1957	102.6		
8	8	1958	98.9		
9	9	1959	100.3		
10	10	1960	102.5		
11	11	1961	116.1		
12	12	1962	103.8		
13	13	1963	94.1		
14	14	1964	96.3		
15	15	1965	98.8		

Selected: 0 Rows: 50/71 Page size 50 Page

1 /2

2.20.3 Excel File

1. Choose one worksheet to handle.
2. Worksheets can be added/renamed/deleted.
3. In general, the first line(header) defines column names, and each of followed lines defines a row of data.
4. If file is read abnormally, change options and click button "Refresh".
5. Data are paginated. When pages number is larger than 1, changes should be saved before run some functions.
6. To string values, multiple lines can be edited and saved.
7. Data can be saved with current sheet only or all worksheets.


Notice: Tool can only handle base data in Excel file.

If file includes format, style, formula, or chart, suggest to save changes as new file to avoid data loss.

Tab...	Data row	year_	college gr...	middle sc...	high : .
1	1	1949	2.1	28	6.1
2	2	1950	1.8	29.6	6.2
3	3	1951	1.9	28.4	5.9
4	4	1952	3.2	22.1	3.6
5	5	1953	4.8	45.4	5.6
6	6	1954	4.7	64.4	6.8
7	7	1955	5.5	96.9	9.9
8	8	1956	6.3	93.9	15.4
9	9	1957	5.6	129.9	18.7
10	10	1958	7.2	131.3	19.7
11	11	1959	7	179	29.9
12	12	1960	13.6	171	28.8
13	13	1961	15.1	227.1	37.9
14	14	1962	17.7	202.5	44.1
15	15	1963	19.9	195.6	43.3
16	16	1964	20.4	175.3	36.7


2.20.4 Convert/Split Data Files in Batch

1. Source files' formats can be csv, excel, and text. Options of source files can be set.
2. Target files' formats include csv, text, excel, xml, json, html, pdf. Options of target files can be set.
3. Split files as maximum lines.



2.20.5 Merge Data Files

1. Set source format.
2. Set target format.



2.21 Data in System Clipboard

1. Read contents in System Clipboard.
2. Guess delimiter and parse data.
3. User can select a delimiter to parse data.
4. Select how to parse:
 - CSV parser: Values can contain delimiter and line break. But not support parsing “Blanks” and “Regular Expression”.
 - Text parser: Values can not contain delimiter and line break. Support parsing “Blanks” and “Regular Expression”.
5. Select whether first line defines column names.

Data in System Clipboard

Window Document Image Data File Media Network Settings Recent Accessed Development Help

CSV Texts

First line defines the columns' names

Delimiter: ,

year_,population at year-end(ten thousand),male(ten thousand),female(ten thousand),urban population

Data...	year_	populatio...	male(ten t...)	female(te...)	urban(
1	1949	54167	28145	26022	5765
2	1950	55196	28669	26527	6169
3	1951	56300	29231	27069	6632
4	1952	57482	29833	27649	7163
5	1953	58796	30468	28328	7826
6	1954	60266	31242	29024	8249
7	1955	61465	31809	29656	8285
8	1956	62828	32536	30292	9185
9	1957	64653	33469	31184	9949
10	1958	65994	34195	31799	10721
11	1959	67207	34890	32317	12371
12	1960	66207	34283	31924	13073
13	1961	65859	33880	31979	12707
14	1962	67296	34517	32778	11659
15	1963	69172	35533	33639	11646
16	1964	70499	36142	34357	12950

If a value contains delimiter or line break, it should be surrounded by quotes.

Selected: 0 Rows: [1-20]20/50 Page size 20 Page 1 /3

2.22 Data in MyBox Clipboard

The screenshot shows the MyBox Data Tools application window titled "Data in MyBox Clipboard : MyBox Clipboard - 6 - b". The window has a menu bar with options: Window, Document, Image, Data, File, Media, Network, Settings, Recent Accessed, Development, and Help. Below the menu is a toolbar with various icons.

The main area displays a table with the following columns: Ta..., ID, Type, Name, Row..., Colu..., and a plus sign icon. The table contains 7 rows of data. Row 7 is selected, indicated by a checked checkbox in the first column and highlighted in grey. A context menu is open over this row, showing options: Data in MyBox Clipboa..., Current name:b, and New name: bm. Buttons for 确定 (Confirm) and 取消 (Cancel) are visible.

To the right of the table is a detailed view pane. It includes a toolbar with icons for Columns, Attributes, View, and Edit. Below this is a table titled "快乐" (Kuàilè) with columns: Tab... (checkbox), Data row, 收入 (Income), and 快乐 (Happiness). The table lists 12 rows of data. At the bottom of the right pane, there are buttons for Selected: 0, Rows: 50/238, Page size: 50, and Page navigation.

At the bottom of the application window, there are page navigation controls: Page (1/1), Page size (50), and Page navigation buttons (first, previous, next, last).

2.23 Matrix

2.23.1 Edit and Manage Matrices

1. Edit matrix.
2. Matrix can be saved and reused.


The screenshot shows the 'Manage Matrices' window in MyBox Data Tools. The left panel lists matrices with columns for ID, Type, Name, Row..., and Colu... (with a plus sign). Matrix 1065 is selected (indicated by a checked checkbox). The right panel shows the data for matrix 1065, with columns for Data row, 列1 (Column 1), 列2 (Column 2), and 列3 (Column 3). The data rows are:

Data row	列1	列2	列3
1	353.63	469.35	59.21
2	687.2	344.24	308.21
3	359.8	359.52	925.57

At the bottom, there are page navigation controls (Page 1 / 1, 50 rows) and a status message: Rows: 2/2 Selected: 1.

2.23.2 Unary Matrix Calculation

Transpose, Row Echelon Form, Reduced Row Echelon Form, Determinant By Elimination, Determinant By Complement Minor, Inverse Matrix By Elimination, Inverse Matrix By Adjoint, Matrix Rank, Adjoint Matrix, Complement Minor, Normalize, Multiply Number, Divide By Number, Power.



2.23.3 Binary Matrices Calculation

Plus, Minus, Hadamard Product, Kronecker Product, Horizontally Merge, Vertically Merge.

My Box Matrices Binary Calculation : Matrix - New data

Window Document Image Data File Media Network Settings Recent Accessed Development Help

Ta...	ID	Name	Row
<input type="checkbox"/> 1	1065	a	3
<input type="checkbox"/> 2	1064	b	6

Matrix A Matrix B Calculation Result

Vertical merge Horizontal merge Plus Minus Multiply
 Hadamard product Kronecker product

Example:
 $A = \begin{matrix} a_{11} & a_{12} \\ a_{21} & a_{21} \end{matrix}$

$B = \begin{matrix} b_{11} & b_{12} \\ b_{21} & b_{21} \end{matrix}$

Kronecker Product =
 $\begin{matrix} a_{11}*b_{11} & a_{11}*b_{12} & a_{12}*b_{11} & a_{12}*b_{12} \\ a_{11}*b_{21} & a_{11}*b_{21} & a_{12}*b_{21} & a_{12}*b_{21} \\ a_{21}*b_{11} & a_{21}*b_{12} & a_{22}*b_{11} & a_{22}*b_{12} \\ a_{21}*b_{21} & a_{21}*b_{21} & a_{22}*b_{21} & a_{22}*b_{21} \end{matrix}$

Page 1 /1 Page size 50 Rows: 2/2
Selected: 0

2.24 Database Tables

2.24.1 Manage Database Tables

1. View table definition.
2. Execute SQL.

Database Table : Database Table - 1113 - INCOMEHAPPINESS_EN

Window Document Image Data File Media Network Settings Recent Accessed Development Help

Columns Attributes View Table definition

Ta...	ID	Type	Name	Row...	Colu...
<input checked="" type="checkbox"/> 1	1113	Databas...	IncomeHappi...	477	3
<input type="checkbox"/> 2	1081	Databas...	ChinaPopulat...	73	7
<input type="checkbox"/> 3	1069	Databas...	ed	3	3
<input type="checkbox"/> 4	1068	Databas...	ChinaPopulat...	73	7
<input type="checkbox"/> 5		My Html			
<input type="checkbox"/> 6					
<input type="checkbox"/> 7					
<input type="checkbox"/> 8					

INCOMEHAPPINESS_EN

Column	Type	Length	Not null	Primary key	Auto generated	Refer to table	Refer to column
id	Long	19	Yes	Yes	Yes		
income	Double	52					
happiness	Double	52					

```
CREATE TABLE INCOMEHAPPINESS_EN (
    id BIGINT NOT NULL GENERATED BY DEFAULT AS IDENTITY (START WITH 1, INCREMENT BY 1),
    income DOUBLE,
    happiness DOUBLE,
    PRIMARY KEY ( id )
)
```


Page 1 /10

2.24.2 Limitations of SQL Identifier

1. Table name and column names should satisfy "Limitations of SQL identifier":
 - Maximum length is 128.
 - "Ordinary identifier":
 - Not surrounded by double quotation marks.
 - Must begin with a letter.
 - Contains only letters, underscore characters (_), and digits.
 - Permits Unicode letters and digits.
 - Can not be reserved words.
 - It is converted as uppercase when saved in database.
 - It is case-insensitive when referred in SQL statement.

Example, AbC is same as abc and aBC.
 - "Delimited identifier":
 - Surrounded by double quotation marks.
 - Can contain any characters.
 - It is saved as string inside the double quotations in database.
 - It should be surrounded by double quotations when referred in SQL statement, except for following: It only includes upper case letters and underscores.

Example, "AbC" is different from AbC or "ABC" while "ABC" is same as ABC and abc.
2. After database table is created:
 - Definition of Primary keys can not be changed and deleted.
 - Definition of other columns can be added and deleted but can not be changed.
3. When MyBox create name of table/column:
 - Invalid characters are converted as underscore characters.
 - If it does not start with a letter, character "a" is added in front of it.



2.24.3 Database SQL

1. Provide examples of SQL statements.
2. List names of all user tables automatically.
3. View table definitions of all user tables.
4. Display outputs of execution and results of query.
5. SQL codes can be organized as information of tree.
6. Can load or save as external files.

Database SQL: 848 - Maximum rows

Window Document Image Data File Media Network Settings Recent Accessed Development Help

Nodes Tags Time Find Select

Attributes SQL

Input statements of SQL. One statement in each line.

SELECT * FROM visit_history FETCH FIRST 300 ROWS ONLY

Examples

Results Data


Data row	RESOURC...	FILE_TYPE	OPERATIO...	RESOURC...	DATA_MO...	L/+
1	2	21	3	d:\tmp\my...	20	
2	1	21	3	d:\tmp\my...	20	
3	2	21	2	d:\tmp\my...	20	
4	1	21	2	d:\tmp\my...	20	
5	2	21	3	d:\tmp\my...	20	
6	1	21	3	d:\tmp\my...	20	
7	2	21	2	d:\tmp\my...	20	
8	1	21	2	d:\tmp\my...	20	

Selected: 0 Rows: 20/300 Page size 20 Page 1 /15

2.24.4 SQL Query

Database table has a special function menu: “Functions” - “Trim” - “Query”, which can help to input and execute SQL query:

1. Names of table and columns are listed in left.
2. Provide examples and record histories.



Database Table : Database Table - 1115 - CHINAPOPULATION_EN *

Window Document Image Data File Media Network Settings Recent Accessed Development Help

Database Table - 1115 - CHINAPOPULATION_EN

Input a statement of SQL query which can be written in multiple lines

CHINAPOPULATION_EN	Attributes
id	Options
year_	SQL*
population_at_year_end_ten_thousand_	
male_ten_thousand_	
female_ten_thousand_	
urban_ten_thousand_	
rural_ten_thousand_	

Examples

```
SELECT year_, female_ten_thousand_, urban_ten_thousand_
rural_ten_thousand_ FROM CHINAPOPULATION_EN
```

3 Script and Expression

3.1 JShell(Java interactive coding tool)

3.1.1 About JShell

JShell is one of tools in JDK:

1. JShell provides capability to interactively evaluate "snippets", as Read-Eval-Print Loop (REPL).
2. "Snippet" is a single expression, statement, or declaration of Java programming language code:
 - Semicolons should be in the end of statement while expression need not it.
 - Variables and methods can be defined and called later.
3. External Java classes should be accessible:
 - JShell picks "CLASSPATH" of system environment.
 - Other jar files or paths can be appended to "CLASSPATH".
 - Except for base classes, most of Java classes should be imported before call them.
4. JShell can be used for scientific computation and Java codes debug.

3.1.2 Run Jshell in GUI

This tool helps to run JShell in GUI:

1. Input several snippets and click button "Start" to run them.
2. Snippets are evaluated one by one.
3. Results of snippets will affect later snippets, like "an execution environment".
4. Attributes of all evaluated snippets will be shown in a table.
5. Click button "Delete" or "Clear" to drop some or all snippets from current environment.
6. Click button "Reset" to empty JShell and environment becomes blank.
7. Press "CTRL+1" to pop list of code completion suggestions.
8. If added MyBox class paths, all methods of MyBox can be referred.
9. JShell codes are organized in tree. Examples are provided.

MyBox JShell(Java interactive coding tool): 911 - Format number

Window Document Image Data File Media Network Settings Recent Accessed Development Help

Nodes Tags Time Find Select Attributes Codes Results Snippets Class paths

```

import java.math.BigDecimal;
import java.math.RoundingMode;
double scale(double v, int scale) {
    BigDecimal b = new BigDecimal(v);
    return b.setScale(scale, RoundingMode.HALF_UP).d
}

import java.text.DecimalFormat;
String formatDouble(double data, int scale) {
    try {
        String format = "#,###";
        if (scale > 0) {
            format += "." + "#".repeat(scale);
        }
        import java.math.BigDecimal;
        import java.math.RoundingMode;
        double scale(double v, int scale) {
            BigDecimal b = new BigDecimal(v);
            return b.setScale(scale, RoundingMode.HALF_UP).doubleValue();
        }
        import java.
        double circleAreaByRadius(double radius) {
            return Math.PI * radius * radius ;
        }
        formatDouble(circleAreaByRadius(273.4), 4)
    }
}

```

2022-08-31 14:08:48
double circleAreaByRadius(double radius) {
 return Math.PI * radius * radius ;
}
id: 18
Status: Valid
Type: METHOD
Name: formatDouble

2022-08-31 14:08:48
double circleAreaByRadius(double radius) {
 return Math.PI * radius * radius ;
}
id: 19
Status: Valid
Type: METHOD
Name: circleAreaByRadius

2022-08-31 14:08:48
double circleAreaByRadius(double radius) {
 return Math.PI * radius * radius ;
}
id: 20
Status: Valid
Type: VAR
Name: \$9
Value: "234,826.3854"

Loaded

3.2 JEXL(Java Expression Language)

3.2.1 About JEXL

JEXL(Java Expression Language) is a library to generate values dynamically with variables and scripts.

1. JEXL has different syntax from Java. It is more like javascript.
2. Before run expression/script, all variables in it should have values held by JexlContext.
3. Refer to Java classes by creating their instances as local variables. Full package name is required.
4. JEXL can be used for scientific computation and data manufacture.

3.2.2 Run JEXL in GUI

This tool helps to run JEXL in GUI:

1. Input JEXL expression/script.

Notice: Use single quotes instead of double quotes to surround strings.

2. Input Java codes of setting JexlContext like following:

```
jexlContext.set("name", value);
```

Example, set following to use Math.PI in expression/script:

```
jexlContext.set("Math", Math.class);
```

3. Input parameters of JEXL script if any. Separate values by comma.

4. Click button "Start" to evaluate the expression/script.

5. MyBox does following in JShell environment automatically:

- Add MyBox library paths to CLASSPATH.
- Import necessary JEXL packages.
- Execute codes of JexlContext.
- Calculate expression/script with parameters(if any).

6. If all variables and parameters have valid values, result is shown in right pane.

7. JEXL codes are organized in tree. Examples are provided.

MyBox User Guide – Data Tools v6.6.2

The screenshot shows the MyBox Data Tools interface. The left sidebar contains a tree view of JEXL codes, with the 'percentage' node selected. The main area has tabs for 'JEXL script', 'JEXL Context', and 'Jexl script paramters'. The 'JEXL script' tab displays the following code:

```
var number = 37;
var total = 518;
var scale = 2;
DoubleTools.percentage(number, total, scale);
```

A tooltip is shown over the 'percentage' node in the tree, containing the same code. The 'JEXL Context' tab shows the context setup:

```
jexlContext.set("DoubleTools", mara.mybox.tools.DoubleTools.class);
```

The right side shows a history of operations:

- 2022-08-31 14:13:54: id: 29, Status: Valid, Type: STATEMENT
- 2022-08-31 14:13:54: id: 30, Status: Valid, Type: EXPRESSION, Name: jexlScript
- 2022-08-31 14:13:54: id: 31, Status: Valid, Type: VAR, Name: \$7

3.3 Javascript

This tool helps to manage and run codes in JavaScript:


1. Edit codes in JavaScript.

The script can include any valid elements which WebEngine can parse(ECMAScript 6).

2. Run the script.

Its results are displayed in right pane. And it affects the web page in right pane too.

3. Javascript codes are organized in tree. Examples are provided.



4 Math Function

This tool helps to manage and calculate math functions:

4.1 Define Math Functions

1. List names of variables of the function, separated by English comma.

The names should satisfy rules of JavaScript:

- Can include letters, number, underline '_', and unicodes(like Chinese).
- Not start with number.

2. Define function expression as a piece of codes in JavaScript:

- The script can include any valid elements which Nashorn can parse(ECMAScript 5.1).
- It should be a number finally.
- It can refer to the given variables, but should not declare them.

3. Define domain of the function as a piece of codes in JavaScript:

- Blank means the domain is all of real numbers.
- The script can include any valid elements which Nashorn can parse(ECMAScript 5.1).
- It should be a boolean value(true or false) finally.
- It can refer to the given variables, but should not declare them.

4. Give the name of calculation result.

5. Saved in tree.

6. Examples are provided.

4.2 Calculate Math Function

1. When the tool calculates a script, 'var <variable_name>=<variable_value>;' are inserted in the head of it before the evaluation.
2. If script of domain is not blank, the given values of variables are inserted in it and check the result:
 - If true, continue to calculate the script of function expression.
 - Else this set of values is skipped.

Math Function: 217 - univariate logarithmic

Window Document Image Data File Media Network Settings Recent Accessed Development Help

Nodes Tags Time Find Select

Math Function

- Examples
- Constants
- Unary Function
- Binary Function**
 - Univariate Polynomial
 - Geometry
 - Quadric Surface
 - Trigonometry
 - Exponential Function
 - Logarithmic Function**
 - univariate logarithmic
- Numerical Analysis
- Univariate Normal probability
- Univariate Standard normal pr
- Ternary Function
- Trigonometry
- Geometry
- area of ellipsoid - half_axie
- area of ellipsoid - axie
- volumn of ellipsoid
- volumn of ellipsoid - axie

Attributes Math Function
Names of variables, separated by English comma
x, y

Expression
5 * Math.log(x * y) - 9

Function domain
x * y > 0

Result name univariate logarithmic

Calculate Data Set
x y
Decimal scale 8

```

var x=4.0;
var y=5.0;
var xMean = 1;
var xStd = 2;
var yMean = 2;
var yStd = 1;
var coefficient = 0.2;
var dx = x - xMean;
var dy = y - yMean;
var xyStd = xStd * yStd;
var dco = 1 - coefficient * coefficient;
var px = dx * dx / ( xStd * xStd );
var py = dy * dy / ( yStd * yStd );
var pxy = 2 * coefficient * dx * dy /
var expP = - (px + py - pxy) / ( 2 * coefficient );
var div = 2 * Math.PI * xyStd * Math.sqrt(1 - dco);
Math.exp(expP) / div

```

Univariate Normal probability density function

2022-09-28 14:13:12
var angle=45.0;
angle * Math.PI / 180
radian=0.78539816

4.3 Data Set

With defined range, interval, and decimal scale, data set of the function can be generated.

The screenshot shows the 'Math Function' configuration window in MyBox Data Tools. The title bar reads "My Math Function: 225 - law of sines - for edge(radian)". The menu bar includes Window, Document, Image, Data, File, Media, Network, Settings, Recent Accessed, Development, and Help. The left sidebar has tabs for Nodes, Tags, Time, and Find, with "Select" currently selected. A tree view under "Math Function" shows categories like Examples, Constants, Unary Function, Trigonometry, Geometry, Power Function, Exponential Function, Logarithmic Function, Intercept Function, Unitary Polynomial, piecewise values, Numerical Analysis, Binary Function, Ternary Function, and Trigonometry. Under Trigonometry, "law of sines - for edge(radian)" is selected and highlighted in blue. The main workspace contains several panels:

- Attributes:** Shows icons for checkmark, red X, equals, and other symbols.
- Math Function:** Displays the expression `edge_a * Math.sin(angleB_radian) / Math.sin(angleA_radian)`.
- Names of variables, separated by English comma:** Lists `angleA_radian, edge_a, angleB_radian`.
- Range:** Set from -10.0 to 10.0.
- Expression:** Shows the same expression as the Math Function panel.
- Function domain:** Shows the condition `angleA_radian > 0 && angleB_radian > 0 && edge_a > 0`.
- Result name:** Set to `edge_b`.
- Calculate:** Contains buttons for calculate, clear, and refresh.
- Data Set:** Contains dropdowns for variable names (angleA_radian, edge_a, angleB_radian), a range input (From -10.0, To 10.0), and two radio button options: "Number of split" (set to 50) and "Data interval" (set to 0.1). It also includes a "Decimal scale" dropdown set to 2.

4.4 XY Chart of Unary Function

To unary function, XY charts, including scatter chart and line chart, can be displayed.

The screenshot shows the MyBox Data Tools interface with the following details:

- Title Bar:** MyBox Math Function: 196 - sigmoid
- Menu Bar:** Window, Document, Image, Data, File, Media, Network, Settings, Recent Accessed, Development, Help
- Left Panel (Select):**
 - Math Function:**
 - Examples
 - Constants
 - Unary Function** (selected)
 - absolute
 - Trigonometry
 - Geometry
 - Power Function
 - Exponential Function
 - Logarithmic Function
 - Intercept Function
 - Unitary Polynomial
 - piecewise values** (selected)
 - direct values
 - define functions
 - Numerical Analysis
 - Binary Function
 - Univariate Polynomial
 - Geometry
 - Quadric Surface
- Middle Panel (Math Function):**
 - Attributes** tab (selected)
 - Math Function** tab
 - Names of variables, separated by English comma: x
 - Expression: $1 / (1 + \text{Math.exp}(-x))$
- Right Panel (Calculate):**
 - x
 - Range: From -20.0, To 20.0
 - Number of split: 100
 - Data interval: 0.1
 - Decimal scale: 2
- Bottom Panel (XY chart - sigmoid):**
 - Scatter chart** (selected) and **Line chart** buttons
 - Functions: sigmoid
 - Result name: sigmoid
 - Plot area: A scatter plot of the sigmoid function, showing blue dots forming a curve that approaches y=1 as x increases and y=0 as x decreases. The x-axis ranges from -2.25 to 2.25, and the y-axis ranges from 0.00 to 1.25.

4.5 XYZ Chart of Binary Function

To binary function, XYZ chart, including 3D scatter chart and surface chart, can be displayed.


mybox-data-6.5.9/generated/Univariate_Normal_probability_density_function_Scatter_chart_2022-09-28_14-2 ☆



Univariate Normal probability density function - Scatter chart

Axis X: "x" Axis Y: "y"

Axis Z: ● Univariate Normal probability density function



5 Data of Location

5.1 Data Constraints

5.1.1 Invalid Value

1. Null value of integer/long/short is the minimum value(MIN_VALUE)
2. Null value of double is the maximum value(Double.MAX_VALUE)

5.1.2 Coordinate System:

1. CGCS2000(China Geodetic Coordinate System), real locations and approximate to WGS-84(GPS).
2. GCJ-02(China encrypted coordinate), encrypted data with offsets of real locations.
3. WGS-84(GPS), real locations.
4. BD-09(Baidu encrypted coordinate), based on GCJ-02.
5. Mapbar coordinate, based on GCJ-02.
6. When coordinate is unknown or invalid, the default value is CGCS2000.

5.1.3 Coordinate Values

1. Decimal values of longitude and latitude, instead of Degrees Minutes Seconds(DMS), are used when data handled.
2. MyBox provides "Location Tools" to convert coordinate values between decimal and DMS.
3. Valid range of longitude is '-180~180', and valid range of latitude is '-90~90'.

5.1.4 Time

5.1.4.1 Date Formats

- Date and Time, like: 2014-06-11 13:51:33
- Date, like: 2014-06-11
- Year, like: 2014
- Month, like: 2014-06
- Time, like: 13:51:33
- Time with Milliseconds, like: 13:51:33.261
- Date and Time with Milliseconds, like: 2014-06-11 13:51:33.261
- Date and Time with zone, like: 2020-09-27 12:29:29 +0800
- Date and Time with Milliseconds and zone, like: 2020-09-27 12:29:29.713 +0800
- "T" can be written or omitted between date and time. "2014-06-11T13:51:33" equals to "2014-06-11 13:51:33".

5.1.4.2 Era

"0 AD" = "1 BC" = "0" = "-0" = "0000" = "-0000" = "0001-01-01 00:00:00 BC" = "公元前 1" = "公元前

0001-01-01 00:00:00"

"1 AD" = "1" = "0001" = "0001-01-01 00:00:00" = "0001-01-01 00:00:00 AD" = "公元 1" = "公元 0001-01-01 00:00:00"

"202 BC" = "-203" = "-0203" = "-0203-01-01 00:00:00" = "0202-01-01 00:00:00 BC" = "公元前 202" = "公元前 0202-01-01 00:00:00"

"202 AD" = "202" = "0202" = "0202-01-01 00:00:00" = "0202-01-01 00:00:00 AD" = "公元 202" = "公元 0202-01-01 00:00:00"

5.1.4.3 Examples

2020-07-13 11:30:59

-2020-07-13 11:30:59

-581-01-23

960

公元 960

公元前 770-12-11

公元前 1046-03-10 10:10:10

202 BC

960-01-23 AD

1046-03-10 10:10:10 BC

5.2 Data Operations

1. Add/Delete/Edit/Copy/Clear/Refresh data.
2. Query data:
 - Define and manage query conditions.
 - Current query conditions is displayed on tab "information".
 - Data satisfying current query condition are displayed in tab "Data" in pages.
 - Data rows can be displayed in different colors as values of some column.
3. Import data in csv format:
 - File encoding is UTF-8 or ASCII.
 - The first line defines data headers which are delimited by English commas.
 - Followed each line defines one data row. Data fields are delimited by English commas.
 - The order of fields is not cared.
 - Necessary fields must occupy their locations, but need not have valid values(related to data).
 - Select whether replace existed data. Predefined data or example data always replace existed values.
4. Export data:
 - Define and manage export conditions.

- Export data fields can be selected.
 - Export file format can be selected: csv, xml, json, xlsx, html, pdf.
 - Select maximum lines to split files.
 - Can export current data page.
5. Delete/Clear data:
- Define and manage delete conditions.
 - Predefined data can not be deleted.
 - Referred data(like foreign keys) can not be deleted.
6. Define, manage, and use "Conditions":
- "Conditions" are used to execute querying, deleting, or exporting.
 - Set conditions in panes:
 - Data conditions are organized as trees. Multiple nodes can be selected.
 - Multiple data fields can be selected as sorting conditions, and their orders can be changed.
 - Edit condition: Title, where, order by, fetch. They will be merged as final conditon.
 - Manage conditons: Add/delete/edit/copy.
 - Conditions ever executed are saved automatically.
 - Recently visited conditions are listed in pop window of the buttons.

5.3 Map Data

1. Kinds of data can be presented in map, including Geography Codes, Location Data, and Coordinate Querying.
2. Data in map can be:
 - All data which satisfy current query condition. "Maximum number of data" can be set to avoid performance issues.
 - Data in current page.
3. TianDiTu:
 - Accepts coordinates of CGCS2000 and display them at correct locations without offsets.
 - When display other coordinates, MyBox converts them to CGCS2000 to show correct locations.
 - Projection can be selected: EPSG:900913/3857(Web Mercator) or EPSG:4326(Geodetic).
 - Controls can selected: Zoom, Scale, Map Type, Symbols.
 - Map Types: Standard, Satellite, Mixed Satellite, Terrain, Mixed Terrain.
 - Languages in different regions.
 - Range of map levels is 1-18.
4. GaoDe Map:
 - Accepts coordinates of GCJ-02 and display them at correct locations without offsets.

- When display other coordinates, MyBox converts them to GCJ-02 to show correct locations.
 - Projection is EPSG:900913/3857(Web Mercator).
 - Map layers:
 - Can select multiples: standard, satellite, roadnet, traffic.
 - Roadnet layer and traffic layer are only supported for China.
 - Satellite layer is supported for part of foreign addresses.
 - Opacity can be set for each map layer.
 - Map language: Chinese, English, Chinese and English.
 - Range of map levels is 3-18
 - Can selected "Fit View" to adjust map level and center as best automatically while display all data.
5. Adjust map level by:
- Scroll mouse wheel.
 - Click map controls.
 - Select "Map Size"
6. Marker image:
- Selections: point(bubble), circle, or any image.
 - For Location Data, more selections: Data Set Image, Data Image. Point will be used if no valid value.
 - Size can be set(Same size for width and height)
7. Marker text:
- Selections: Label, Coordinate, Address.
 - For Location Data, more selections: Start Time, End Time, Data Value, etc.
 - Multiples selections can be picked. Each selection will be showns in a line.
 - Size can be set.
 - Can select whether text is bold.
 - Color can be set. For Location Data, "Data Color" can be chosen.
8. Pop information:
- Detailed information can be popped when mouse is upon marker.
 - Can select whether pop information.
9. Snapshot:
- DPI can be set.
 - Current map and data in map can be saved and displayed in html.
10. Keys of map can be changed in "Settings". The default keys are free and shared by all MyBox users.

5.4 Geography Code

5.4.1 Data Definition

1. Basical attributes: id, level, longitude, latitude, chinese_name, english_name, 5 codes, 5 aliases,
2. Subordinate: owner, continent, country, province, city, county, town, village, building. ("Ancestors")
3. Auxiliary attributes: altitude, precision, coordinate system, area(square meters), population, comments, isPredefined.

5.4.2 Data Constraints

1. Not null values: id, level, chinese_name or english_name.
2. Values of "level": global(only "Earth"), continent, country, province(state), city, county(district), town, village(neighborhood), building, point of interest.
3. Data is unnecessary to be subordinated level by level. Cross-over can happen. Example, a village is subordinated to Antarctica, and a city belongs to a country without province level.
4. Match data:
 - One of following can determine an address:
 - Match "id"(assigned by MyBox automatically). This is accurate matching.
 - Match "level" + ancestors + "chinese_name"/"english_name"/any one "alias". This is accurate matching.
 - Match "level" + "chinese_name"/"english_name"/any one "alias". This is fuzzy matching. Duplicated names in same level can cause false matching.
 - Matching of name or alias is case-insensitive.
 - Sometimes 5 "code" are useful to match data.

5.4.3 Edit Data

1. "subordinate" of data is set by selecting node in locations tree.
2. "level" of data should be lower than its ancestors.
3. Data must have either chinese_name or english_name.
4. Select or display coordinate in map.
5. Set as "Predefined data" or "Inputted data" against selected rows.

5.4.4 Define Condition

All geogahy codes in MyBox are organized as a Locations Tree by their subordination relationship. Multiple nodes can be selected.

5.4.5 Import Data

5.4.5.1 Predefined Data

Include continents, countries, Chinese provinces /cities /counties.

Countries have values of "area" and "population".

5.4.5.2 CSV Format

- Download address:
https://github.com/Mararsh/MyBox_data/tree/master/md/GeographyCode/en
- Necessary fields:
Level,Longitude,Latitude
And "Chinese Name" or "English Name"
- Optional fields:
Altitude,Precision,Coordinate System,Square Kilometers,Population,
Code 1,Code 2,Code 3,Code 4,Code 5,Alias 1,Alias 2,Alias 3,Alias 4,Alias 5,
Continent,Country,Province,City,County,Town,Village,Building,Comments


5.4.5.3 Data from geoname.org:

- Download address:
<http://download.geonames.org/export/zip/>
- Tab-delimited text in UTF8 encoding.
- Data fields:
countryCode postalCode placeName
adminName1 adminCode1 adminName2 adminCode2 adminName3 adminCode3
latitude longitude accuracy
- Coordinate system is WGS_84.
- Same address is written only once even when it has multiple "postal code" or coordinates.

5.4.6 Settings

1. Customize colors of data rows.
2. Provide "Default" and "Random" buttons.

MyBox User Guide – Data Tools v6.6.2




5.5 Location in Map

1. Query geography code by:

- Click map.
- Input address.
 - TianDiTu supports chinese and foreign addresses in Chinese(like "伦敦") or in English(like "Paris")
 - GaoDe map only supports addresses in China.

▪ Input longitude and latitude.

2. Query result can be saved in Geography Code table.




5.6 Location Tools

- Convert coordinate value between decimal and DMS. Valid examples of DMS:

48°51'12.28"
 -77° 3' 43.9308"
 48°51'12.28"N
 2°20'55.68"E
 S 34° 36' 13.4028"
 W 58° 22' 53.7348"
 118 度 48 分 54.152 秒
 -32 度 04 分 10.461 秒
 东经 118 度 48 分 54.152 秒
 北纬 32 度 04 分 10.461 秒
 西经 118 度 48 分 54.152 秒
 南纬 32 度 04 分 10.461 秒

- Convert coordinate values as other coordinate systems.



6 Others

6.1 Create Barcodes

1. Supported 1-d barcodes:
 - Types: Code39, Code128, Codabar, Interleaved2Of5, ITF_14, POSTNET, EAN13, EAN8, EAN_128, UPCA, UPCE, Royal_Mail_Customer_Barcode, USPS_Intelligent_Mail
 - Options about 1-d barcodes: Orientation, width/height, dpi, text location, font size, quiet-zone width, etc.
2. Supported 2-d barcodes:
 - Types: QR_Code, PDF_417, DataMatrix
 - Options about 2-d barcodes: Width/height, margin, error correction level, compact mode, etc.
 - A picture can be shown in center of QR_Code. Its size can be adjusted automatically according to error correction level.
3. Examples of parameters and suggested values.
4. Validate generated barcode at once.

6.2 Decode Barcodes

1. Supported 1-d barcodes: Code39, Code128, Interleaved2Of5, ITF_14, EAN13, EAN8, EAN_128, UPCA, UPCE
2. Supported 2-d barcodes: QR_Code, PDF_417, DataMatrix
3. Display contents of barcodes and its meta data including barcode type and error correction level if any.

6.3 Message Digest

1. Create digest for files or inputted texts.
2. Support MD2, MD5, SHA-1, SHA-224, SHA-256, SHA-384, SHA-512/224, SHA-512/256, SHA3-224, SHA3-256, SHA3-384, SHA3-512.
3. Output: Base64, Hexadecimal, Formatted hexadecimal.

6.4 Encode/Decode Base64

1. Encode file or texts as Base64.
2. Decode Base64 file or Base64 texts.
3. Set charset for texts.
4. Output as file or texts.

6.5 Extract ttf files from ttc file

<End of Document>