

## **DEFAULT OS X KEYMAP**

^ Space	Basic code completion
<b>T</b> ←	Show intention actions and quick-fixes
<b></b> #P	Parameter info (within method call
***	arguments)
^ J or Mid. button click	Quick documentation lookup
	Brief Info
<b>%</b> N, ^ <i>ω</i> , ^ N	Generate code (Getters, Setters,
vviii, ←, iii	Constructors)
^0	Override methods
^1	Implement methods
Ж∖Т	Surround with (ifelse, trycatch, for, etc.)
<b>%</b> /	Comment/uncomment with line comment
<b>%</b> ₹\/	Comment/uncomment with block commen
\t	Select successively increasing code blocks
<u>z</u> †	Decrease current selection to previous state
# \ L	Reformat code
^\TI	Auto-indent line(s)
₩D	Duplicate current line or selected block
#⊗	Delete line at caret
♣️ⓒ ^합 <b>J</b>	Smart line join (HTML and JavaScript only)
≋₊	
क्र <del>€</del>	Smart line split (HTML and JavaScript only) Start new line
บ⊷ Жชิ <b>U</b>	
	Toggle case for word at caret or selected
block	
\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\	Select till code block end/start
\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\	Delete to word end
\⊠	Delete to word start
₩+,₩-	Expand/collapse code block
<b>₩</b> W	Close active editor tab
<b>光 ① V</b>	Paste from history
Debugging	
F8	Step over
F7	Step into
<b>☆ F8</b>	Step out
<b>₹ F8</b>	Evaluate expression
ж ∵ <b>F9</b>	Resume program
<b></b>	Toggle breakpoint

View breakpoints

# û F8

Running	
^F10	Run
^F9	Debug
^	Run context configuration from editor
¥ûX	Run command line
Search/Replace	
₩F/R	Find/Replace
<b>ж G, ж</b> û <b>G</b>	Find next/previous
₩ûF/R	Find/Replace in path
Usage Search	
∵ F7/#F7	Find usages / Find usages in file
₩ û <b>F7</b>	Highlight usages in file
<b>% ₹ F7</b>	Show usages
Navigation	
₩N	Go to class
₩ûN	Go to file
N7#	Go to symbol
₩ <b>+</b> G	Go to line
^-/ <del>-</del>	Go to next/previous editor tab
5	Go to editor (from tool window)
ЖE	Recent files popup
<b>₹</b> \ → , <b>#</b> \ →	Navigate back/forward
Ж☆図	Navigate to last edit location
₹ <b>F1</b>	Select current file or symbol in any view
<b>♯Bor ♯Click</b>	Go to declaration
₩∖B	Go to implementation(s)
∑ Space, % Y	Open quick definition lookup
^ <b>û B</b>	Go to type declaration
жU	Go to super-method/super-class
^↑,^↓	Go to previous/next method
<b>#],#</b> [	Move to code block end/start
F2, û F2	Next/previous highlighted error

Edit source / View source

F5/F6	Copy/Move
₩ Delete	Safe Delete
<b>ੂੰ F6</b>	Rename
N7%	Inline Variable
<b>#</b> \tau M/V/F/C	Extract Method/Variable/Field/Constant
^ T	Refactor This (shows all available refactorings)
VCS/Local Histo	<u>-</u>
^ V	'VCS' quick popup
<b></b> ₩K	Commit project to VCS
ЖT	Update project from VCS
\ûC	View recent changes
General	
<b>企</b>	Search everywhere
<b>Ճ</b> ₩ <b>A</b>	Find Action
<b>₩0</b> ₩9	Open corresponding tool window
<b>%</b> ₹ <b>F11</b>	Toggle full screen mode
₩ û <b>F12</b>	Toggle maximizing editor
\û <b>F</b>	Add to Favorites
ロ金ブ	Inspect current file with current profile
₩,	Open Settings dialog
^_i	Switch between tabs and tool window

Live Templates / Snippets	
<b>ж</b> л	Insert Live Template
eco	'echo' statement
fore	foreach(iterable_expr as \$value) {}
forek	foreach(iterable_expr as \$key => \$value) {}
inc/inco	'include'/'include_once' statement
prif	private function
prof	protected function
pubf	public function
rqr/rqro	'require'/'require_once' statement
and more	

F2,☆F2 F4/%↓





