Game dev: Framerate

Ricard Pillosu - UPC

The past

- Computer graphics was late (1980) and initially for the business:
- Silicon Graphics
- Later they founded Pixar :)



The past

- Home computers with multimedia was way later (1985):
- Commodore Amiga
- It features graphical multitasking OS
- … in 1.4 Mb!

The past

- The PC took market advantage (1992). Still rendering was expensive!





It moves!

The past

- The revolution of the GPUs (1995):

3dfx Vodoo!

More info on history of real time graphics on video games here.

Real Time applications

- Rendering-computation fast enough, so that the series of rendered images induce the illusion of movement in the human brain of the user.
- This illusion allows for the interaction with the software doing the calculations taking into account user input.
- The unit used for measuring the frame rate in a series of images is frames per second (fps).

Lot’s of wisdom here!

Frame rate

- We exploit a limitation in the Visual Cortex called Persistence of Vision
- This optical illusion is created when images cycle of less than 60-80 ms
- This means that motion is perceived starting at 12-16 fps
- Movie industry uses the 24 fps standard for historical reasons
- Frame rate also applies to sound and input!
- Humans are better at detecting low sound framerate.

Movement is just an illusion: 30vs60.com

Movement is just an illusion: 30vs60.com

Movement is just an illusion: 30vs60.com



How do we measure time ?

- We want accurate measurement to the **microsecond**
- This is a not fully solved problem! … measuring time takes time :(
- Back in the days, using rdtsc intrinsic was standard in windows
- Microsoft discourages it since:
  - We have multiple CPUs sending tasks to each other
  - We have complex power-saving systems that could hibernate CPUs
  - We have out-of-order execution CPUs

How do we measure time ?

- Solution came from two functions (windows platform):
  - QueryPerformanceCounter: Returns a high precision timestamp. Only make sense relative to other previous measure.
  - QueryPerformanceFrequency: Returns the frequency of the counter. We can transform intervals to human readable time. It should be constant during execution.
- SDL offers platform independant versions of this functions.
- Also a simple **SDL_GetTicks()** wich is faster but less accurate (1us).

TODO 1

“Fill Start() and Read() methods they are simple, one line each!”

- We will use this class for logic, we do not need precision
- THis means that **SDL_GetTicks()** is enough

TODO 2

“Fill Constructor, Start() and Read() methods they are simple, one line each!”

- **j1PerfTimer** will be for precise measurements of code execution
- Frequency is the same across all timers, that’s why we use a **static**
- This means that we need **SDL_GetPerformanceCounter()** + **SDL_GetPerformanceFrequency()**

TODO 3

“Measure the amount of ms that takes to execute: App constructor, Awake, Start and CleanUp. LOG the results”

- Create a timer in j1App as a property
- Then use it to print in output window (LOG) the amount of ms that each method takes
- Try to guess the times before starting, which will be slowest ?

TODO 4

“Now calculate: Amount of frames since startup. Amount of time since game start (use a low resolution timer). Average FPS for the whole game life. Amount of ms took the last update. Amount of frames during the last second”

- You may need to add code in **PrepareUpdate()** method
- Create as many properties you need in **App** class
- When it works try activating / deactivating vsync

Homework

- Find out you slowest function
- Try producing lag to drop to 30 FPS under vsync