

Create prefixes for use with CDISC standards in RDF

mja@statgroup.dk

2016-03-08

Contents

Create prefixes for use with CDISC standards in RDF	1
Setup	1
Prefixes for the package	1

Create prefixes for use with CDISC standards in RDF

Setup

```
library(rrdfancillary)
library(devtools)
devtools::load_all(pkg="../..")
```

```
## Loading rrdfcdisc
```

Prefixes for the package

This script creates a list with the prefix used for the package. The prefix corresponds to the usual values.

```
## qbCDISCPrefixes<- list(
##   "rdf"= "http://www.w3.org/1999/02/22-rdf-syntax-ns#" ,
##   "skos"="http://www.w3.org/2004/02/skos/core#" ,
##   "prov"="http://www.w3.org/ns/prov#" ,
##   "rdfs"="http://www.w3.org/2000/01/rdf-schema#" ,
##   "dcat"="http://www.w3.org/ns/dcat#" ,
##   "owl"= "http://www.w3.org/2002/07/owl#" ,
##   "xsd"= "http://www.w3.org/2001/XMLSchema#" ,
##   "qb"= "http://purl.org/linked-data/cube#" ,
##   "pav"= "http://purl.org/pav" ,
##   "dct"= "http://purl.org/dc/terms/" ,
##   "mms"= "http://rdf.cdisc.org/mms#" ,
##   "cts"= "http://rdf.cdisc.org/ct/schema#",
##   "sdtn"="http://rdf.cdisc.org/sdtn-terminology#",
##   "rrdfqbcrnd0"="http://www.example.org/rrdfqbcrnd0/"
## )

qbCDISCPrefixes<- env[["qbCDISCPrefixes"]]
```

ToDo(mja): The rrdqbcrnd0 prefix should be moved to package rrdqbcrnd0

ToDo(mja): the qbCDISCprefixes is obsolete, as the env[["qbCDISCprefixes"]] in zzz.R has the same function.

```
devtools::use_data(qbCDISCprefixes,overwrite=TRUE)
```

```
## Saving qbCDISCprefixes to data/qbCDISCprefixes.rda
```