

# Using ARQ to investigate RDF data cube

*mja@statgroup.dk*

*2016-02-16*

## Contents

<b>SPARQL scripts for the demographics cube (DC-DEMO-sample.ttl)</b>	<b>1</b>
Get all member of qb:ComponentProperty . . . . .	1
<b>How to run this .Rmd file</b>	<b>4</b>

## SPARQL scripts for the demographics cube (DC-DEMO-sample.ttl)

The examples below uses `arq` from Apache Jena (<http://jena.apache.org>). To install `arq` - download and unpack the latest version of `apache-jena` from (<http://jena.apache.org/download/index.cgi>). Then you need some way of invoking `arq`; I use a not-so-clever-approach: `cd ~/bin; ln -s /opt/apache-jena-2.13.0/bin/arq`.

Given a SPARQL query and RDF data, `arq` returns the result of the query. So this is the command line way of making a SPARQL query.

The use of `arq` is described in many places, see for example (<http://www.learningsparql.com/>).

All `arq` commands below are to be run in the directory with the sample files, which is `inst/extdata/CUBE-standards-rdf` directory or `extdata/CUBE-standards-rdf` depending on the whether the development version or the installed version of the package is used.

The `cd` below in each code block is included because I could not find a quick way to get the code chunk executed in that directory. `knitr` is flexible enough to do it, I have not yet found the right way to do it. So, ignore the repeated `cd ..`

For making the SPARQL queries I used a simple trick - copy the turtle definition from the `cube.ttl`, and do a replace regexp in emacs using pattern `+\([^:]+\):+\([^\ ]+\) .*$` and replacement `\1:\2 ?\2 ;`.


### Get all member of qb:ComponentProperty

```
cd ../extdata/sample-rdf
arq --results ttl --data ../../../../rrdfqb/inst/extdata/cube-vocabulary-rdf/cube.ttl --query qb-constr
rapper -i turtle -o dot fordot.ttl > fordot.dot
dot -x -Tpng -ograph.png fordot.dot
rm -f fordot.dot
```

```
## rapper: Parsing URI file:///home/ma/projects/rrdfqbcrnd0/rrdfqbcrndex/inst/extdata/sample-rdf/fordot
## rapper: Serializing with serializer dot
## rapper: Parsing returned 29 triples
```

ToDo(MJA): location for `cube.ttl` should be generated by the program - not using a directory reference

```
knitr::include_graphics("../extdata/sample-rdf/graph.png")
```



Model:  
(Unknown)

Namespaces:

crnd-measure: <http://www.example.org/dc/measure#>  
 dccc: <http://www.example.org/dc/demo/dccc/>  
 code: <http://www.example.org/dc/code/>  
 cts: <http://rdf.cdsc.org/ct/schema#>  
 pav: <http://purl.org/pav>  
 owl: <http://www.w3.org/2002/07/owl#>  
 xsd: <http://www.w3.org/2001/XMLSchema#>  
 skos: <http://www.w3.org/2004/02/skos/core#>  
 rdfs: <http://www.w3.org/2000/01/rdf-schema#>  
 crnd-attribute: <http://www.example.org/dc/attribute#>  
 ds: <http://www.example.org/dc/demo/ds/>  
 qb: <http://purl.org/linked-data/cube#>  
 mms: <http://rdf.cdsc.org/mms#>  
 crnd-dimension: <http://www.example.org/dc/dimension#>  
 dct: <http://purl.org/dc/terms/>  
 rdf: <http://www.w3.org/1999/02/22-rdf-syntax-ns#>  
 rdfs: <http://www.w3.org/1999/02/22-rdf-syntax-ns#>  
 prov: <http://www.w3.org/ns/prov#>

The file is needed for rendering, so no clean up.

```
cd ../extdata/sample-rdf  
rm -f graph.png
```

## How to run this .Rmd file

.. add text ..