

Using ARQ to investigate RDF data cube

mja@statgroup.dk

2016-06-19

Contents

SPARQL scripts for the demographics cube (DC-DEMO-sample.ttl)	1
Get all member of qb:ComponentProperty	1
How to run this .Rmd file	4

SPARQL scripts for the demographics cube (DC-DEMO-sample.ttl)

The examples below uses `arq` from Apache Jena (<http://jena.apache.org>). To install arq - download and unpack the latest version of apache-jena from (<http://jena.apache.org/download/index.cgi>). Then you need some way of invoking `arq`; I use a not-so-clever-approach: `cd ~/bin; ln -s /opt/apache-jena-2.13.0/bin/arq`.

Given a SPARQL query and RDF data, `arq` returns the result of the query. So this is the command line way of making a SPARQL query.

The use of `arq` is described in many places, see for example (<http://www.learningsparql.com/>).

All `arq` commands below are to be run in the directory with the sample files, which is `inst/extdata/CUBE-standards-rdf` directory or `extdata/CUBE-standards-rdf` depending on the whether the development version or the installed version of the package is used.

The `cd` below in each code block is included because I could not find a quick way to get the code chunk executed in that directory. knitr is flexible enough to do it, I have not yet found the right way to do it. So, ignore the repeated `cd ..`

For making the SPARQL queries I used a simple trick - copy the turtle definition from the `cube.ttl`, and do a replace regexp in emacs using pattern `+\([^:]+\):\[^\]+\) .*$` and replacement `\1:\2 ?\2 ;`.


Get all member of qb:ComponentProperty

```
cd ../extdata/sample-rdf
arq --results ttl --data ../../../../rrdfqb/inst/extdata/cube-vocabulary-rdf/cube.ttl --query qb-constr
rapper -i turtle -o dot fordot.ttl > fordot.dot
dot -x -Tpng -ograph.png fordot.dot
rm -f fordot.dot
```

```
## rapper: Parsing URI file:///home/ma/projects/rrdfqbcrnd0/rrdfqbcrndex/inst/extdata/sample-rdf/fordot
## rapper: Serializing with serializer dot
## rapper: Parsing returned 29 triples
```

ToDo(MJA): location for `cube.ttl` should be generated by the program - not using a directory reference

```
knitr::include_graphics("../extdata/sample-rdf/graph.png")
```



Model:
(Unknown)

Namespaces:

- `dccs:` <http://www.example.org/dc/demo/dccs/>
- `code:` <http://www.example.org/dc/code/>
- `sdtms-1-3:` <http://rdf.cdisc.org/sdtm-1-3/schema#>
- `adam-2-1:` <http://rdf.cdisc.org/sdtm/adam-2-1#>
- `owl:` <http://www.w3.org/2002/07/owl#>
- `xsd:` <http://www.w3.org/2001/XMLSchema#>
- `sdtm-1-3:` <http://rdf.cdisc.org/sdtm-1-3#>
- `cdash-1-1:` <http://rdf.cdisc.org/std/cdash-1-1#>
- `skos:` <http://www.w3.org/2004/02/skos/core#>
- `rdfs:` <http://www.w3.org/2000/01/rdf-schema#>
- `adamvr-1-2:` <http://rdf.cdisc.org/std/adamvr-1-2#>
- `crmd-attribute:` <http://www.example.org/dc/attribute#>
- `sdtm-1-2:` <http://rdf.cdisc.org/std/sdtm-1-2#>
- `ds:` <http://www.example.org/dc/demo/ds/>
- `sdtmct:` <http://rdf.cdisc.org/sdtm-terminology#>
- `qb:` <http://purl.org/linked-data/cube#>
- `mms:` <http://rdf.cdisc.org/mms#>
- `crmd-dimension:` <http://www.example.org/dc/dimension#>
- `dct:` <http://purl.org/dc/terms/>
- `cdiscs:` <http://rdf.cdisc.org/std/schema#>
- `cdashct:` <http://rdf.cdisc.org/cdash-terminology#>
- `dcat:` <http://www.w3.org/ns/dcat#>
- `prov:` <http://www.w3.org/ns/prov#>
- `sdtmig-3-1-3:` <http://rdf.cdisc.org/std/sdtmig-3-1-3#>
- `crmd-measure:` <http://www.example.org/dc/measure#>
- `adamig-1-0:` <http://rdf.cdisc.org/std/adamig-1-0#>
- `cts:` <http://rdf.cdisc.org/cts/schema#>
- `pav:` <http://purl.org/pav/>
- `sdtmig-3-1-2:` <http://rdf.cdisc.org/std/sdtmig-3-1-2#>
- `sendig-3-0:` <http://rdf.cdisc.org/std/sendig-3-0#>
- `adamct:` <http://rdf.cdisc.org/adam-terminology#>
- `rdf:` <http://www.w3.org/1999/02/22-rdf-syntax-ns#>
- `sendct:` <http://rdf.cdisc.org/send-terminology#>
- `rrdfqbcnd0:` <http://www.example.org/rrdfqbcnd0/>
- `dc:` <http://purl.org/dc/elements/1.1/>

The file is needed for rendering, so no clean up.

```
cd ../extdata/sample-rdf
rm -f graph.png
```

How to run this .Rmd file

.. add text ..