

Using ARQ to make SPARQL queries

mja@statgroup.dk

2016-04-29

Contents

SPARQL scripts for the demographics cube (DC-DEMO-sample.ttl)	1
Get dimensions	1
Get attributes	2
Get observations	2
Get definition for all descriptive statistics - class <code>code:procedure</code>	5
Get the codelists	5
Get the codelist definition for all descriptive statistics - class <code>code:procedure</code>	6
Get definition for all variables used for descriptive statistics - class <code>code:factor</code>	8
Get the codelist definition for all variables used for descriptive statistics - class <code>code:factor</code>	9
Get definition for descriptive statistics median	10
Get information for selection of data	10
Get information on the underlying data in D2RQ format	11
Get underlying data for one cube observation	13
 How to run this .Rmd file	 62

SPARQL scripts for the demographics cube (DC-DEMO-sample.ttl)

The examples below uses `arq` from Apache Jena (<http://jena.apache.org>). To install `arq` - download and unpack the latest version of `apache-jena` from (<http://jena.apache.org/download/index.cgi>). Then you need some way of invoking `arq`; I use a not-so-clever-approach: `cd ~/bin; ln -s /opt/apache-jena-2.13.0/bin/arq`.

Given a SPARQL query and RDF data, `arq` returns the result of the query. So this is the command line way of making a SPARQL query.

The use of `arq` is described many places, see for example (<http://www.learningsparql.com/>).

All `arq` commands below are to be run in the directory with the sample files, which is `inst/extdata/sample-rdf` directory or `extdata/sample-rdf` depending on the whether the development version or the installed version of the package is used.

The `cd` below in each code block is included because I could not find a quick way to get the code chunk executed in that directory. `knitr` is flexible enough to do it, I have not yet found the right way to do it. So, ignore the repeated `cd ..`

Get dimensions

```
cd ../extdata/sample-rdf
arq --data DC-DEMO-sample.ttl --query DEMOdimensions.rq
```

```
## -----
## | p |
## =====
## | crnd-dimension:ethnic |
## | crnd-dimension:race |
## | crnd-dimension:procedure |
## | crnd-dimension:agegr1 |
## | crnd-dimension:factor |
## | crnd-dimension:trt01a |
## | crnd-dimension:sex |
## -----
```

Get attributes

```
cd ../extdata/sample-rdf
arq --data DC-DEMO-sample.ttl --query DEMOattributes.rq
```

```
## -----
## | p |
## =====
## | crnd-attribute:cellpartno |
## | crnd-attribute:measurefmt |
## | crnd-attribute:colno |
## | crnd-attribute:denominator |
## | crnd-attribute:unit |
## | crnd-attribute:rowno |
## -----
```

Get observations

The SPARQL script shows for each observation the dimension, attributes and measures in a row. Note: in the HTML version the output below can be scrolled using the left and right arrow.

```
cd ../extdata/sample-rdf
arq --data DC-DEMO-sample.ttl --query DEMOobservations.rq
```

```
## -----
## | s | ethnic | race | procedure |
## =====
## | ds:obs001 | code:ethnic-_ALL_ | code:race-_ALL_ | code:procedure-_ALL_ |
## | ds:obs002 | code:ethnic-_ALL_ | code:race-_ALL_ | code:procedure-_ALL_ |
## | ds:obs003 | code:ethnic-_ALL_ | code:race-_ALL_ | code:procedure-_ALL_ |
## | ds:obs004 | code:ethnic-_ALL_ | code:race-_ALL_ | code:procedure-_ALL_ |
## | ds:obs005 | code:ethnic-_ALL_ | code:race-_ALL_ | code:procedure-_ALL_ |
## | ds:obs006 | code:ethnic-_ALL_ | code:race-_ALL_ | code:procedure-_ALL_ |
```

[illegible]

[illegible]

```
## | ds:obs115 | code:ethnic-_NONMISS_ | code:race-_ALL_ | code
## | ds:obs116 | code:ethnic-_NONMISS_ | code:race-_ALL_ | code
## | ds:obs117 | code:ethnic-_NONMISS_ | code:race-_ALL_ | code
## | ds:obs118 | code:ethnic-_NONMISS_ | code:race-_ALL_ | code
## | ds:obs119 | code:ethnic-_NONMISS_ | code:race-_ALL_ | code
## | ds:obs120 | code:ethnic-_NONMISS_ | code:race-_ALL_ | code
## | ds:obs121 | code:ethnic-NOT_HISPANIC_OR_LATINO | code:race-_ALL_ | code
## | ds:obs122 | code:ethnic-NOT_HISPANIC_OR_LATINO | code:race-_ALL_ | code
## | ds:obs123 | code:ethnic-NOT_HISPANIC_OR_LATINO | code:race-_ALL_ | code
## | ds:obs124 | code:ethnic-NOT_HISPANIC_OR_LATINO | code:race-_ALL_ | code
## | ds:obs125 | code:ethnic-NOT_HISPANIC_OR_LATINO | code:race-_ALL_ | code
## | ds:obs126 | code:ethnic-NOT_HISPANIC_OR_LATINO | code:race-_ALL_ | code
## | ds:obs127 | code:ethnic-HISPANIC_OR_LATINO | code:race-_ALL_ | code
## | ds:obs128 | code:ethnic-HISPANIC_OR_LATINO | code:race-_ALL_ | code
## | ds:obs129 | code:ethnic-HISPANIC_OR_LATINO | code:race-_ALL_ | code
## | ds:obs130 | code:ethnic-HISPANIC_OR_LATINO | code:race-_ALL_ | code
## | ds:obs131 | code:ethnic-HISPANIC_OR_LATINO | code:race-_ALL_ | code
## | ds:obs132 | code:ethnic-HISPANIC_OR_LATINO | code:race-_ALL_ | code
## -----
```

Get definition for all descriptive statistics - class code:procedure

The SPARQL script shows how the R function definition for the descriptive statistics is stored in the cube.

```
cd ../extdata/sample-rdf
arq --data DC-DEMO-sample.ttl --query DEMOprocedure.rq
```

```
## -----
## | procedure | prefLabel | functiondef
## =====
## | code:procedure-max | "max" | "function (x) { max(x, na.rm = TRUE) }"
## | code:procedure-std | "std" | "function (x) { sd(x, na.rm = TRUE) }"
## | code:procedure-mean | "mean" | "function (x) { mean(x, na.rm = TRUE) }"
## | code:procedure-min | "min" | "function (x) { min(x, na.rm = TRUE) }"
## | code:procedure-percent | "percent" | "function (x) { -1 }"
## | code:procedure-count | "count" | "function (x) { length(x) }"
## | code:procedure-q3 | "q3" | "function (x) { quantile(x, probs = c(0.75), na.rm = TRUE) }"
## | code:procedure-n | "n" | "function (x) { length(x[!is.na(x)]) }"
## | code:procedure-median | "median" | "function (x) { median(x, na.rm = TRUE) }"
## | code:procedure-q1 | "q1" | "function (x) { quantile(x, probs = c(0.25), na.rm = TRUE) }"
## -----
```

Get the codelists

The SPARQL script shows the codelist.

```
cd ../extdata/sample-rdf
arq --data DC-DEMO-sample.ttl --query DEMOcodelist.rq
```

```
## -----
## | DataStructureDefinition | dimension | cprefLabel | cl
```

```

## =====
## | ds:dsd-DEMO          | crnd-dimension:agegr1 | "Codelist scheme: agegr1"@en | code:agegr1
## | ds:dsd-DEMO          | crnd-dimension:agegr1 | "Codelist scheme: agegr1"@en | code:agegr1
## | ds:dsd-DEMO          | crnd-dimension:agegr1 | "Codelist scheme: agegr1"@en | code:agegr1
## | ds:dsd-DEMO          | crnd-dimension:agegr1 | "Codelist scheme: agegr1"@en | code:agegr1
## | ds:dsd-DEMO          | crnd-dimension:agegr1 | "Codelist scheme: agegr1"@en | code:agegr1
## | ds:dsd-DEMO          | crnd-dimension:ethnic | "Codelist scheme: ethnic"@en | code:ethnic
## | ds:dsd-DEMO          | crnd-dimension:ethnic | "Codelist scheme: ethnic"@en | code:ethnic
## | ds:dsd-DEMO          | crnd-dimension:ethnic | "Codelist scheme: ethnic"@en | code:ethnic
## | ds:dsd-DEMO          | crnd-dimension:ethnic | "Codelist scheme: ethnic"@en | code:ethnic
## | ds:dsd-DEMO          | crnd-dimension:factor | "Codelist scheme: factor"@en | code:factor
## | ds:dsd-DEMO          | crnd-dimension:factor | "Codelist scheme: factor"@en | code:factor
## | ds:dsd-DEMO          | crnd-dimension:factor | "Codelist scheme: factor"@en | code:factor
## | ds:dsd-DEMO          | crnd-dimension:factor | "Codelist scheme: factor"@en | code:factor
## | ds:dsd-DEMO          | crnd-dimension:factor | "Codelist scheme: factor"@en | code:factor
## | ds:dsd-DEMO          | crnd-dimension:factor | "Codelist scheme: factor"@en | code:factor
## | ds:dsd-DEMO          | crnd-dimension:procedure | "Codelist scheme: procedure"@en | code:procedure
## | ds:dsd-DEMO          | crnd-dimension:procedure | "Codelist scheme: procedure"@en | code:procedure
## | ds:dsd-DEMO          | crnd-dimension:procedure | "Codelist scheme: procedure"@en | code:procedure
## | ds:dsd-DEMO          | crnd-dimension:procedure | "Codelist scheme: procedure"@en | code:procedure
## | ds:dsd-DEMO          | crnd-dimension:procedure | "Codelist scheme: procedure"@en | code:procedure
## | ds:dsd-DEMO          | crnd-dimension:procedure | "Codelist scheme: procedure"@en | code:procedure
## | ds:dsd-DEMO          | crnd-dimension:procedure | "Codelist scheme: procedure"@en | code:procedure
## | ds:dsd-DEMO          | crnd-dimension:procedure | "Codelist scheme: procedure"@en | code:procedure
## | ds:dsd-DEMO          | crnd-dimension:procedure | "Codelist scheme: procedure"@en | code:procedure
## | ds:dsd-DEMO          | crnd-dimension:race    | "Codelist scheme: race"@en    | code:race-Al
## | ds:dsd-DEMO          | crnd-dimension:race    | "Codelist scheme: race"@en    | code:race-As
## | ds:dsd-DEMO          | crnd-dimension:race    | "Codelist scheme: race"@en    | code:race-BI
## | ds:dsd-DEMO          | crnd-dimension:race    | "Codelist scheme: race"@en    | code:race-Na
## | ds:dsd-DEMO          | crnd-dimension:race    | "Codelist scheme: race"@en    | code:race-WI
## | ds:dsd-DEMO          | crnd-dimension:race    | "Codelist scheme: race"@en    | code:race-_
## | ds:dsd-DEMO          | crnd-dimension:race    | "Codelist scheme: race"@en    | code:race-_
## | ds:dsd-DEMO          | crnd-dimension:sex     | "Codelist scheme: sex"@en     | code:sex-F
## | ds:dsd-DEMO          | crnd-dimension:sex     | "Codelist scheme: sex"@en     | code:sex-M
## | ds:dsd-DEMO          | crnd-dimension:sex     | "Codelist scheme: sex"@en     | code:sex-U
## | ds:dsd-DEMO          | crnd-dimension:sex     | "Codelist scheme: sex"@en     | code:sex-UN
## | ds:dsd-DEMO          | crnd-dimension:sex     | "Codelist scheme: sex"@en     | code:sex-_Al
## | ds:dsd-DEMO          | crnd-dimension:sex     | "Codelist scheme: sex"@en     | code:sex-_Na
## | ds:dsd-DEMO          | crnd-dimension:trt01a  | "Codelist scheme: trt01a"@en  | code:trt01a
## | ds:dsd-DEMO          | crnd-dimension:trt01a  | "Codelist scheme: trt01a"@en  | code:trt01a
## | ds:dsd-DEMO          | crnd-dimension:trt01a  | "Codelist scheme: trt01a"@en  | code:trt01a
## | ds:dsd-DEMO          | crnd-dimension:trt01a  | "Codelist scheme: trt01a"@en  | code:trt01a
## | ds:dsd-DEMO          | crnd-dimension:trt01a  | "Codelist scheme: trt01a"@en  | code:trt01a
## -----

```

Get the codelist definition for all descriptive statistics - class `code:procedure`

The SPARQL script shows how the R function definition for the descriptive statistics is stored in the cube.

```

cd ../extdata/sample-rdf
arq --data DC-DEMO-sample.ttl --query DEMOprocedure-codelist.rq

```

```

## -----
## | s | p | o |
## =====
## | code:procedure-min | skos:topConceptOf | code:procedure
## | code:procedure-min | skos:prefLabel | "min"
## | code:procedure-min | skos:inScheme | code:procedure
## | code:procedure-min | rrdfqbcrrnd0:RdescStatDefFun | "function (x) { min(x, na.rm = TRUE)"
## | code:procedure-min | rrdfqbcrrnd0:R-selectionvalue | "min"
## | code:procedure-min | rrdfqbcrrnd0:R-selectionoperator | "=="
## | code:procedure-min | rdfs:comment | "Descriptive statistics min"@en
## | code:procedure-min | rdf:type | skos:Concept
## | code:procedure-min | rdf:type | code:Procedure
## | code:procedure-std | skos:topConceptOf | code:procedure
## | code:procedure-std | skos:prefLabel | "std"
## | code:procedure-std | skos:inScheme | code:procedure
## | code:procedure-std | rrdfqbcrrnd0:RdescStatDefFun | "function (x) { sd(x, na.rm = TRUE)"
## | code:procedure-std | rrdfqbcrrnd0:R-selectionvalue | "std"
## | code:procedure-std | rrdfqbcrrnd0:R-selectionoperator | "=="
## | code:procedure-std | rdfs:comment | "Descriptive statistics std"@en
## | code:procedure-std | rdf:type | skos:Concept
## | code:procedure-std | rdf:type | code:Procedure
## | code:procedure-q3 | skos:topConceptOf | code:procedure
## | code:procedure-q3 | skos:prefLabel | "q3"
## | code:procedure-q3 | skos:inScheme | code:procedure
## | code:procedure-q3 | rrdfqbcrrnd0:RdescStatDefFun | "function (x) { quantile(x, probs = 0.75)"
## | code:procedure-q3 | rrdfqbcrrnd0:R-selectionvalue | "q3"
## | code:procedure-q3 | rrdfqbcrrnd0:R-selectionoperator | "=="
## | code:procedure-q3 | rdfs:comment | "Descriptive statistics q3"@en
## | code:procedure-q3 | rdf:type | skos:Concept
## | code:procedure-q3 | rdf:type | code:Procedure
## | code:procedure-median | skos:topConceptOf | code:procedure
## | code:procedure-median | skos:prefLabel | "median"
## | code:procedure-median | skos:inScheme | code:procedure
## | code:procedure-median | rrdfqbcrrnd0:RdescStatDefFun | "function (x) { median(x, na.rm = TRUE)"
## | code:procedure-median | rrdfqbcrrnd0:R-selectionvalue | "median"
## | code:procedure-median | rrdfqbcrrnd0:R-selectionoperator | "=="
## | code:procedure-median | rdfs:comment | "Descriptive statistics median"@en
## | code:procedure-median | rdf:type | skos:Concept
## | code:procedure-median | rdf:type | code:Procedure
## | code:procedure-count | skos:topConceptOf | code:procedure
## | code:procedure-count | skos:prefLabel | "count"
## | code:procedure-count | skos:inScheme | code:procedure
## | code:procedure-count | rrdfqbcrrnd0:RdescStatDefFun | "function (x) { length(x) }"
## | code:procedure-count | rrdfqbcrrnd0:R-selectionvalue | "count"
## | code:procedure-count | rrdfqbcrrnd0:R-selectionoperator | "=="
## | code:procedure-count | rdfs:comment | "Descriptive statistics count"@en
## | code:procedure-count | rdf:type | skos:Concept
## | code:procedure-count | rdf:type | code:Procedure
## | code:procedure-max | skos:topConceptOf | code:procedure
## | code:procedure-max | skos:prefLabel | "max"
## | code:procedure-max | skos:inScheme | code:procedure
## | code:procedure-max | rrdfqbcrrnd0:RdescStatDefFun | "function (x) { max(x, na.rm = TRUE)"
## | code:procedure-max | rrdfqbcrrnd0:R-selectionvalue | "max"
## | code:procedure-max | rrdfqbcrrnd0:R-selectionoperator | "=="

```

```

## | code:procedure-max      | rdfs:comment      | "Descriptive statistics max"@en
## | code:procedure-max      | rdf:type          | skos:Concept
## | code:procedure-max      | rdf:type          | code:Procedure
## | code:procedure-mean     | skos:topConceptOf | code:procedure
## | code:procedure-mean     | skos:prefLabel    | "mean"
## | code:procedure-mean     | skos:inScheme     | code:procedure
## | code:procedure-mean     | rrdqbcrnd0:RdescStatDefFun | "function (x) {      mean(x, na.rm = TR
## | code:procedure-mean     | rrdqbcrnd0:R-selectionvalue | "mean"
## | code:procedure-mean     | rrdqbcrnd0:R-selectionoperator | "=="
## | code:procedure-mean     | rdfs:comment      | "Descriptive statistics mean"@en
## | code:procedure-mean     | rdf:type          | skos:Concept
## | code:procedure-mean     | rdf:type          | code:Procedure
## | code:procedure-q1       | skos:topConceptOf | code:procedure
## | code:procedure-q1       | skos:prefLabel    | "q1"
## | code:procedure-q1       | skos:inScheme     | code:procedure
## | code:procedure-q1       | rrdqbcrnd0:RdescStatDefFun | "function (x) {      quantile(x, probs =
## | code:procedure-q1       | rrdqbcrnd0:R-selectionvalue | "q1"
## | code:procedure-q1       | rrdqbcrnd0:R-selectionoperator | "=="
## | code:procedure-q1       | rdfs:comment      | "Descriptive statistics q1"@en
## | code:procedure-q1       | rdf:type          | skos:Concept
## | code:procedure-q1       | rdf:type          | code:Procedure
## | code:procedure-n        | skos:topConceptOf | code:procedure
## | code:procedure-n        | skos:prefLabel    | "n"
## | code:procedure-n        | skos:inScheme     | code:procedure
## | code:procedure-n        | rrdqbcrnd0:RdescStatDefFun | "function (x) {      length(x[!is.na(x)
## | code:procedure-n        | rrdqbcrnd0:R-selectionvalue | "n"
## | code:procedure-n        | rrdqbcrnd0:R-selectionoperator | "=="
## | code:procedure-n        | rdfs:comment      | "Descriptive statistics n"@en
## | code:procedure-n        | rdf:type          | skos:Concept
## | code:procedure-n        | rdf:type          | code:Procedure
## | code:procedure-percent | skos:topConceptOf | code:procedure
## | code:procedure-percent | skos:prefLabel    | "percent"
## | code:procedure-percent | skos:inScheme     | code:procedure
## | code:procedure-percent | rrdqbcrnd0:RdescStatDefFun | "function (x) {      -1 }"
## | code:procedure-percent | rrdqbcrnd0:R-selectionvalue | "percent"
## | code:procedure-percent | rrdqbcrnd0:R-selectionoperator | "=="
## | code:procedure-percent | rdfs:comment      | "Descriptive statistics percent"@en
## | code:procedure-percent | rdf:type          | skos:Concept
## | code:procedure-percent | rdf:type          | code:Procedure
## -----

```

Get definition for all variables used for descriptive statistics - class `code:factor`

The SPARQL script shows how the R function definition for the descriptive statistics is stored in the cube.

```

cd ../extdata/sample-rdf
arq --data DC-DEMO-sample.ttl --query DEMOfactor.rq

```

```

## -----
## | factor                | prefLabel      | DataSetRefD2RQ          | Rselectionvalue |
## |=====|
## | code:factor-_ALL_    | "_ALL_"        |                          |                  |
## | code:factor-proportion | "proportion"   |                          | "proportion"    |

```


##		code:factor-weightbl		"weightbl"		rrdfqbcrnd0:ADSL_WEIGHTBL		"weightbl"	
##		code:factor-_NONMISS_		"_NONMISS_"					
##		code:factor-quantity		"quantity"				"quantity"	
##		code:factor-age		"age"		rrdfqbcrnd0:ADSL_AGE		"age"	
##	-----								

Get the codelist definition for all variables used for descriptive statistics - class code:factor

The SPARQL script shows how the R function definition for the descriptive statistics is stored in the cube.

```
cd ../extdata/sample-rdf
arq --data DC-DEMO-sample.ttl --query DEMOfactor-codelist.rq
```

##	-----		
##	s	p	o
##	=====		
##	code:factor-weightbl	skos:topConceptOf	code:factor
##	code:factor-weightbl	skos:prefLabel	"weightbl"
##	code:factor-weightbl	skos:inScheme	code:factor
##	code:factor-weightbl	rrdfqbcrnd0:R-selectionvalue	"weightbl"
##	code:factor-weightbl	rrdfqbcrnd0:R-selectionoperator	"=="
##	code:factor-weightbl	rrdfqbcrnd0:DataSetRefD2RQ	rrdfqbcrnd0:ADSL_WEIGHTBL
##	code:factor-weightbl	rdfs:comment	"Coded values from data source. No record"
##	code:factor-weightbl	rdf:type	skos:Concept
##	code:factor-weightbl	rdf:type	code:Factor
##	code:factor-age	skos:topConceptOf	code:factor
##	code:factor-age	skos:prefLabel	"age"
##	code:factor-age	skos:inScheme	code:factor
##	code:factor-age	rrdfqbcrnd0:R-selectionvalue	"age"
##	code:factor-age	rrdfqbcrnd0:R-selectionoperator	"=="
##	code:factor-age	rrdfqbcrnd0:DataSetRefD2RQ	rrdfqbcrnd0:ADSL_AGE
##	code:factor-age	rdfs:comment	"Coded values from data source. No record"
##	code:factor-age	rdf:type	skos:Concept
##	code:factor-age	rdf:type	code:Factor
##	code:factor-_ALL_	skos:topConceptOf	code:factor
##	code:factor-_ALL_	skos:prefLabel	"_ALL_"
##	code:factor-_ALL_	skos:inScheme	code:factor
##	code:factor-_ALL_	rdfs:comment	"NON-CDISC: Represents all codelist categories"
##	code:factor-_ALL_	rdf:type	skos:Concept
##	code:factor-_ALL_	rdf:type	code:Factor
##	code:factor-quantity	skos:topConceptOf	code:factor
##	code:factor-quantity	skos:prefLabel	"quantity"
##	code:factor-quantity	skos:inScheme	code:factor
##	code:factor-quantity	rrdfqbcrnd0:R-selectionvalue	"quantity"
##	code:factor-quantity	rrdfqbcrnd0:R-selectionoperator	"=="
##	code:factor-quantity	rdfs:comment	"Coded values from data source. No record"
##	code:factor-quantity	rdf:type	skos:Concept
##	code:factor-quantity	rdf:type	code:Factor
##	code:factor-_NONMISS_	skos:topConceptOf	code:factor
##	code:factor-_NONMISS_	skos:prefLabel	"_NONMISS_"
##	code:factor-_NONMISS_	skos:inScheme	code:factor
##	code:factor-_NONMISS_	rrdfqbcrnd0:R-selectionfunction	"is.na"

```
## | code:factor-_NONMISS_ | rdfs:comment | "NON-CDISC: Represents the non-missing"
## | code:factor-_NONMISS_ | rdf:type | skos:Concept
## | code:factor-_NONMISS_ | rdf:type | code:Factor
## | code:factor-proportion | skos:topConceptOf | code:factor
## | code:factor-proportion | skos:prefLabel | "proportion"
## | code:factor-proportion | skos:inScheme | code:factor
## | code:factor-proportion | rrdqbcrnd0:R-selectionvalue | "proportion"
## | code:factor-proportion | rrdqbcrnd0:R-selectionoperator | "=="
## | code:factor-proportion | rdfs:comment | "Coded values from data source. No record"
## | code:factor-proportion | rdf:type | skos:Concept
## | code:factor-proportion | rdf:type | code:Factor
## -----
```

Get definition for descriptive statistics median

The SPARQL script shows how the function definition for the descriptive statistics is stored in the cube.

```
cd ../extdata/sample-rdf
arq --data DC-DEMO-sample.ttl --query DEMOprocedure-median.rq
```

```
## -----
## | s | p | o |
## =====
## | code:procedure-median | skos:topConceptOf | code:procedure
## | code:procedure-median | skos:prefLabel | "median"
## | code:procedure-median | skos:inScheme | code:procedure
## | code:procedure-median | rrdqbcrnd0:RdescStatDefFun | "function (x) { median(x, na.rm = T"
## | code:procedure-median | rrdqbcrnd0:R-selectionvalue | "median"
## | code:procedure-median | rrdqbcrnd0:R-selectionoperator | "=="
## | code:procedure-median | rdfs:comment | "Descriptive statistics median"@en
## | code:procedure-median | rdf:type | skos:Concept
## | code:procedure-median | rdf:type | code:Procedure
## -----
```

Get information for selection of data

The SPARQL script shows how the information for selecting data for derivation of univariate statistics is present in the cube.

```
cd ../extdata/sample-rdf
arq --data DC-DEMO-sample.ttl --query DEMOobservations-R-selection.rq
```

```
## -----
## | obs | rrdqbcrnd0Rcolumnname | Rselectionoperator | Rselectionvalue |
## =====
## | ds:obs027 | "trt01a" | "==" | "Xanomeline High Dose" |
## | ds:obs056 | "agegr1" | "==" | "65-80" |
## | ds:obs056 | "trt01a" | "==" | "Xanomeline Low Dose" |
## -----
```

Get information on the underlying data in D2RQ format

The following two SPARQL scripts are from taken from `create-ADSL-ttl.Rmd`.

First get the mapping information.

```
cd ../extdata/sample-rdf
arq --data adsl-map.ttl --query ADSL-mapping.rq
```

```
## -----
## | mapColumn                | d2rqcolumn      | d2rqdatatype |
## =====
## | <adsl-map.ttl#ADSL_COMP24FL> | "ADSL.COMP24FL" |              |
## | <adsl-map.ttl#ADSL_DCREASCD> | "ADSL.DCREASCD" |              |
## | <adsl-map.ttl#ADSL_DTHFL>    | "ADSL.DTHFL"    |              |
## | <adsl-map.ttl#ADSL_TRTSDT>   | "ADSL.TRTSDT"   | xsd:double   |
## | <adsl-map.ttl#ADSL_RFENDT>   | "ADSL.RFENDT"   | xsd:double   |
## | <adsl-map.ttl#ADSL_DCDECOD>  | "ADSL.DCDECOD"  |              |
## | <adsl-map.ttl#ADSL_RFENDTC>  | "ADSL.RFENDTC"  |              |
## | <adsl-map.ttl#ADSL_CUMDOSE>  | "ADSL.CUMDOSE"  | xsd:double   |
## | <adsl-map.ttl#ADSL_TRT01A>   | "ADSL.TRT01A"   |              |
## | <adsl-map.ttl#ADSL_AGEGR1>   | "ADSL.AGEGR1"   |              |
## | <adsl-map.ttl#ADSL_USUBJID>   | "ADSL.USUBJID"  |              |
## | <adsl-map.ttl#ADSL_TRT01PN>  | "ADSL.TRT01PN"  | xsd:double   |
## | <adsl-map.ttl#ADSL_ITTFL>    | "ADSL.ITTFL"    |              |
## | <adsl-map.ttl#ADSL_SITEGR1>  | "ADSL.SITEGR1"  |              |
## | <adsl-map.ttl#ADSL_SEX>      | "ADSL.SEX"      |              |
## | <adsl-map.ttl#ADSL_ETHNIC>   | "ADSL.ETHNIC"   |              |
## | <adsl-map.ttl#ADSL_COMP8FL>  | "ADSL.COMP8FL"  |              |
## | <adsl-map.ttl#ADSL_RFSTDTC>  | "ADSL.RFSTDTC"  |              |
## | <adsl-map.ttl#ADSL_AGE>      | "ADSL.AGE"      | xsd:double   |
## | <adsl-map.ttl#ADSL_VISNUMEN> | "ADSL.VISNUMEN" | xsd:double   |
## | <adsl-map.ttl#ADSL_EFFFL>    | "ADSL.EFFFL"    |              |
## | <adsl-map.ttl#ADSL_SAFFL>    | "ADSL.SAFFL"    |              |
## | <adsl-map.ttl#ADSL_HEIGHTBL> | "ADSL.HEIGHTBL" | xsd:double   |
## | <adsl-map.ttl#ADSL_MMSETOT>  | "ADSL.MMSETOT"  | xsd:double   |
## | <adsl-map.ttl#ADSL_STUDYID>  | "ADSL.STUDYID"  |              |
## | <adsl-map.ttl#ADSL_RACEN>    | "ADSL.RACEN"    | xsd:double   |
## | <adsl-map.ttl#ADSL_DISONSDT> | "ADSL.DISONSDT" | xsd:double   |
## | <adsl-map.ttl#ADSL_BMIBL>    | "ADSL.BMIBL"    | xsd:double   |
## | <adsl-map.ttl#ADSL_DSRAEFL>  | "ADSL.DSRAEFL"  |              |
## | <adsl-map.ttl#ADSL_AGEU>     | "ADSL.AGEU"     |              |
## | <adsl-map.ttl#ADSL_DURDIS>   | "ADSL.DURDIS"   | xsd:double   |
## | <adsl-map.ttl#ADSL_TRTDUR>   | "ADSL.TRTDUR"   | xsd:double   |
## | <adsl-map.ttl#ADSL_VISIT1DT> | "ADSL.VISIT1DT" | xsd:double   |
## | <adsl-map.ttl#ADSL_SUBJID>   | "ADSL.SUBJID"   |              |
## | <adsl-map.ttl#ADSL_AVGDD>    | "ADSL.AVGDD"    | xsd:double   |
## | <adsl-map.ttl#ADSL_WEIGHTBL> | "ADSL.WEIGHTBL" | xsd:double   |
## | <adsl-map.ttl#ADSL_EDUCLVL>  | "ADSL.EDUCLVL"  | xsd:double   |
## | <adsl-map.ttl#ADSL_SITEID>   | "ADSL.SITEID"   |              |
## | <adsl-map.ttl#ADSL_COMP16FL> | "ADSL.COMP16FL" |              |
## | <adsl-map.ttl#ADSL_RACE>     | "ADSL.RACE"     |              |
## | <adsl-map.ttl#ADSL_TRTEDT>   | "ADSL.TRTEDT"   | xsd:double   |
## | <adsl-map.ttl#ADSL_DISCONFL> | "ADSL.DISCONFL" |              |
```

```
## | <adsl-map.ttl#ADSL_ARM> | "ADSL.ARM" |
## | <adsl-map.ttl#ADSL_DURDSGR1> | "ADSL.DURDSGR1" |
## | <adsl-map.ttl#ADSL_AGEGR1N> | "ADSL.AGEGR1N" | xsd:double
## | <adsl-map.ttl#ADSL_TRT01P> | "ADSL.TRTO1P" |
## | <adsl-map.ttl#ADSL_TRT01AN> | "ADSL.TRTO1AN" | xsd:double
## | <adsl-map.ttl#ADSL_BMIBLGR1> | "ADSL.BMIBLGR1" |
## -----
```

Then dump the contents of a record in the database.

```
cd ../extdata/sample-rdf
arg --data adsl.ttl --query ADSL-record.rq
```

[illegible]

```
## | <http://www.example.org/datasets/ADSL/01-718-1254> | <http://www.example.org/datasets/vocab/ADSL_I
## | <http://www.example.org/datasets/ADSL/01-718-1254> | <http://www.example.org/datasets/vocab/ADSL_BI
## | <http://www.example.org/datasets/ADSL/01-718-1254> | <http://www.example.org/datasets/vocab/ADSL_RI
## | <http://www.example.org/datasets/ADSL/01-718-1254> | <http://www.w3.org/1999/02/22-rdf-syntax-ns#t
## | <http://www.example.org/datasets/ADSL/01-718-1254> | <http://www.example.org/datasets/vocab/ADSL_S
## | <http://www.example.org/datasets/ADSL/01-718-1254> | <http://www.example.org/datasets/vocab/ADSL_R
## | <http://www.example.org/datasets/ADSL/01-718-1254> | <http://www.example.org/datasets/vocab/ADSL_V
## | <http://www.example.org/datasets/ADSL/01-718-1254> | <http://www.example.org/datasets/vocab/ADSL_A
## | <http://www.example.org/datasets/ADSL/01-718-1254> | <http://www.example.org/datasets/vocab/ADSL_T
## | <http://www.example.org/datasets/ADSL/01-718-1254> | <http://www.example.org/datasets/vocab/ADSL_R
## | <http://www.example.org/datasets/ADSL/01-718-1254> | <http://www.example.org/datasets/vocab/ADSL_A
## | <http://www.example.org/datasets/ADSL/01-718-1254> | <http://www.example.org/datasets/vocab/ADSL_S
## | <http://www.example.org/datasets/ADSL/01-718-1254> | <http://www.example.org/datasets/vocab/ADSL_E
## -----
```

Get underlying data for one cube observation

```
cd ../extdata/sample-rdf
arq --data adsl.ttl --data DC-DEMO-sample.ttl --query DEMOobservations-R-data.rq
```

[illegible]

[illegible]

[illegible]

[illegible]

[illegible]

[illegible]

[illegible]

[illegible]

[illegible]

[illegible]

[illegible]

[illegible]

[illegible]

[illegible]

[illegible]

[illegible]

[illegible]

[illegible]

[illegible]

[illegible]

[illegible]

[illegible]

[illegible]

[illegible]

[illegible]

[illegible]

[illegible]

[illegible]

[illegible]

[illegible]

[illegible]

[illegible]

[illegible]

[illegible]

[illegible]

[illegible]

[illegible]

[illegible]

[illegible]

[illegible]

[illegible]

[illegible]

[illegible]

[illegible]

[illegible]

[illegible]

How to run this .Rmd file

62