

COMP1511 17s2

— Lecture 8 —

Pointers!

Andrew Bennett


`<andrew.bennett@unsw.edu.au>`

pointers
strings
arrays

Don't panic!

Review: Arrays

a series of boxes in memory
with a common type,
all next to each other



Review: Arrays in C

a collection of array **elements**
each element must be the same type

we refer to arrays by their **index**
valid indices for n elements are $0 \dots n - 1$

no real limit on number of elements

we **cannot** assign, scan, or print whole arrays...
but we **can** assign, scan, and print elements

Review: Arrays in C

```
// Declare an array with 10 elements  
// and initialises all elements to 0.  
int myArray[10] = {0};  
// Put some values into the array.  
myArray[0] = 3;  
myArray[5] = 17;
```

3	0	0	0	0	17	0	0	0	0
0	1	2	3	4	5	6	7	8	9

Review: Array Manipulation

scanf() can't read an entire array.
printf() can't print an entire array.
the = operator won't copy an array.

instead, you must perform an operation on each element:

```
int i = 0;
while (i < ARRAY_SIZE) {
    array2[i] = array1[i];
    i++;
}
```

Review: Array-ception

an array may have elements of any type...
including of array type!
we call these **multi-dimensional** arrays

here's an array of arrays of int:

```
int matrix[3][3] = {  
    {1, 2, 3},  
    {4, 5, 6},  
    {7, 8, 9}  
};
```

it's a two-dimensional array.

```
printf ("%d\n", matrix[1][1]); // outputs... ?
```

char-grilled

working with characters and text

long long, long, int, short, char

in *Explore Memory*
we saw a range of new types
for storing numeric data:
long long, long, int, short, char

the difference between them?
the range of data they can store,
and the amount of space they need.

char

a char behaves just like a small number
but we also have a mapping from
values to displayed characters which we call
ASCII
(the American Standard for Computer Information Interchange)

ASCII codes are just
a way of specifying numbers.

in C,
`int c = 'A';`
is the same as
`int c = 65;`

Working with char

in `<stdio.h>`, there are two useful functions:

`getchar`
read a character from “standard input”

`putchar`
prints a character to “standard output”

usually,
“standard input” and “standard output”
get connected to the terminal you’re working in.

(Autotest is an example of a program that
connects standard input and standard output
to itself to test your programs.)

the getchar pattern

```
int c = getchar ();  
while (c != EOF) {  
    // do something with `c`  
    c = getchar ();  
}
```

getchar and putchar

```
int c = getchar ();  
while (c != EOF) {  
    putchar (c);  
    c = getchar ();  
}
```

Pointers

Pointer slides continue on slide 14.

Things Stay The Same

consider this:

```
int ten = 0;  
f (ten);  
g (ten);  
printf ("%d\n", ten);
```

```
void g (int x) {  
    x = x + 6;  
}
```

```
void f (int x) {  
    x = x + 4;  
}
```

what does this print?

why?

Refresher: Memory

(in case you forgot)

an array of consecutive boxes to store data in

different types are different sizes

char = 1 byte

short = 2 bytes

etc.

everything in memory has an address;

these addresses are just numbers.

it's convenient to talk about addresses in hexadecimal

Exploring Memory

```
int num1;  
int num2;  
  
printf("Address of num1 is: %p\n", &num1);  
printf("Address of num2 is: %p\n", &num2);  
  
printf("Size of num1 is: %lu\n", sizeof(num1));  
printf("Size of num2 is: %lu\n", sizeof(num2));
```

```
Address of num1 is: 0xffffd86c  
Address of num2 is: 0xffffd868
```

```
Size of num1 is: 4  
Size of num2 is: 4
```

Exploring Memory

```
#define ARRAY_SIZE 5

int firstArray[ARRAY_SIZE];

printf ("Address of firstArray is: %p\n", &firstArray);
printf ("Looking at the addresses of firstArray:\n");

int i = 0;
while (i < ARRAY_SIZE) {
    printf ("The address of firstArray[%d] is %p\n",
           i, &firstArray[i]);
    i++;
}
```

Address of firstArray is: 0xffffd848

Looking at the addresses of firstArray:

The address of firstArray[0] is 0xffffd848

The address of firstArray[1] is 0xffffd84c

The address of firstArray[2] is 0xffffd850

The address of firstArray[3] is 0xffffd854

The address of firstArray[4] is 0xffffd858

“Address-Of”

if we declare a variable called x ,
the place where x is stored
(a “pointer” to,
the “address” of x ,
a “reference” to x)
is denoted
 $\&x$

“Dereference”

if we have
a pointer, an address, a reference
to a value x ,
and want to manipulate the value it holds,
we **dereference it**

$*x$

essentially,
 $*$ cancels out $\&$

Pass by Reference

```
int ten = 0;  
f (&ten);  
g (&ten);  
printf ("%d\n", ten);
```

```
void g (int *x) {  
    *x = *x + 6;  
}
```

```
void f (int *x) {  
    *x = *x + 4;  
}
```

what does *this* print?

(We've already seen this – scanf!)

More Arrays

passing arrays as arguments to functions
`void showArray (int arraySize, int array[]);`

More Arrays

arrays are similar to pointers.

how long is an array?

we don't know. we must always specify size.

C doesn't let you pass arrays.

instead, you get a pointer

More Arrays

modifying arrays from functions

write a function `negativeArray`,
that takes an `int` array
and make all values negative