

---

# Cylindrical Flow Matching for Complex-Valued Medical Image Synthesis

---

Anonymous Author(s)

Affiliation

Address

email

## Abstract


1 While deep generative models have achieved remarkable success in MRI recon-  
2 struction, most operate strictly on magnitude images, discarding critical phase  
3 information. This magnitude-only paradigm hinders the development and valida-  
4 tion of complex-valued neural networks for phase-sensitive diagnostic imaging.  
5 Current methods attempting to synthesize fully complex data suffer from a funda-  
6 mental topological mismatch: they naively embed the complex signal into a flat  
7 Euclidean space ( $\mathbb{R}^2$ ). This ignores the intrinsic circular topology of the phase  
8 ( $S^1$ ), leading to destructive interference, magnitude attenuation, and non-physical  
9 artifacts. To address this, we propose **Cylindrical Flow Matching**, a geometry-  
10 aware generative framework that explicitly models amplitude on  $\mathbb{R}^+$  and phase on  
11  $S^1$ . By constructing probability paths along geodesics on a cylindrical manifold,  
12 our approach natively resolves phase discontinuities while preserving the compu-  
13 tational efficiency of Optimal Transport. We demonstrate that Cylindrical Flow  
14 Matching ensures topological validity and physical signal plausibility, providing a  
15 reliable synthetic baseline for safety-critical medical downstream tasks.

## 16 1 Introduction and Problem Formulation


17 Magnetic Resonance Imaging (MRI) is a cornerstone of non-invasive medical diagnostics, yet its  
18 inherently slow acquisition time remains a critical bottleneck. Accelerating MRI typically involves  
19 undersampling the  $k$ -space and solving a highly ill-posed inverse problem [Chung and Ye, 2022].  
20 While deep generative models have achieved remarkable success in MRI reconstruction, the vast  
21 majority of these approaches operate strictly on magnitude images in the spatial domain, entirely  
22 discarding the complex phase information.

23 This magnitude-only paradigm creates a research gap, as emerging complex-valued networks demon-  
24 strate superior signal fidelity in raw MRI processing [Rempe et al., 2026, Dou et al., 2025]. However,  
25 the lack of realistic, fully complex synthetic data severely limits data augmentation and the robust vali-  
26 dation of complex-valued reconstruction algorithms. While recent diffusion approaches [Rempe et al.,  
27 2025] explore complex-valued generation, their lack of explicit phase topology preservation leaves  
28 a critical need for geometrically grounded baselines. Naive generative models operating without  
29 complex-domain geometric constraints are prone to hallucinating non-physical phase discontinuities,  
30 which upon Forward Fast Fourier Transform (FFT) leak into measured  $k$ -space subspaces and corrupt  
31 high-frequency anatomical details.

32 Current approaches suffer from a fundamental topological mismatch: they naively treat the complex  
33 signal as a flat, two-channel tensor embedded in a Euclidean space  $\mathbb{C} \cong \mathbb{R}^2$  [Chung and Ye, 2022].  
34 This ignores the intrinsic circular topology ( $S^1$ ) of the signal’s phase. Consequently, standard  
35 Euclidean interpolation suffers from destructive interference due to the triangle inequality,  $|z(t)| =$   
36  $|(1-t)z_0 + tz_1| \leq (1-t)|z_0| + t|z_1|$ , with strict inequality whenever phases differ ( $\theta_0 \neq \theta_1$ ).  
37 Under an independent uniform phase prior  $\theta_0 \sim \mathcal{U}(S^1)$ , the expected mid-point ( $t = 0.5$ ) magnitude



(a) Standard Euclidean Flow ( $\mathbb{R}^2$ )



(b) Cylindrical Flow Matching (Ours)

Figure 1: **Topological mismatch in complex-valued generation.** (a) In the complex plane ( $\text{Re}(z), \text{Im}(z)$ ), linear interpolation between antipodal states  $z_0$  and  $z_1$  passes through the origin, causing amplitude attenuation ( $|z_{1/2}| \ll \frac{1}{2}(|z_0| + |z_1|)$ ). (b) Cylindrical Flow Matching follows the shortest angular path on  $S^1$  while interpolating amplitude separately.

attenuation is analytically  $1 - \mathbb{E}|\cos(\Delta\theta/2)| = 1 - 2/\pi \approx 36.3\%$  (empirically  $\sim 16\%$  on spatially correlated MRI data). Furthermore, flat angular interpolation does not respect wrapping at the boundary ( $-\pi \sim \pi$ ). These effects motivate evaluating a geometry-aware probability path for complex MRI data.

To bridge the gap between generative modeling and the structured nature of physical signals, we propose **Cylindrical Flow Matching**, a geometry-aware generative framework designed specifically for complex-valued medical image synthesis. Building on flow matching [Lipman et al., 2023] and its manifold extension [Chen and Lipman, 2024], we hypothesize that radial-angular paths provide a better inductive bias than Cartesian coordinates, natively resolving phase discontinuities.

In summary, our contributions are as follows:

- We define the representation, geometry, loss, and inference procedure for **Cylindrical Flow Matching**, modeling nonnegative physical amplitudes on  $\mathbb{R}_+$  and numerical phase coordinates on  $S^1$ .
- We test this hypothesis through controlled ablations on complex-valued generation against a standard Euclidean baseline, demonstrating that substituting the Euclidean assumption natively prevents phase discontinuities and signal cancellation.
- We demonstrate the practical value of this geometry-aware prior in a downstream reconstruction experiment using simulated Cartesian  $k$ -space undersampling.

## 2 Methodology: Cylindrical Flow Matching

To construct a topology-aware generative model for complex-valued MRI data, we formulate continuous normalizing flows directly on the intrinsic manifold of the signal [Lipman et al., 2023, Chen and Lipman, 2024]. Each complex pixel  $z = Ae^{i\theta} \in \mathbb{C}$  naturally resides on a cylindrical manifold  $\mathcal{M} = \mathbb{R}^+ \times S^1$ , equipped with the product metric  $g = dA^2 + d\theta^2$ , such that a 2D complex image is modeled on  $\mathcal{M}^{H \times W}$ . In contrast to the Euclidean baseline which naively treats pixels as flat Cartesian pairs  $(\text{Re}(z), \text{Im}(z)) \in \mathbb{R}^2$ , this cylindrical formulation decouples amplitude and phase transport: geodesics interpolate each component independently along the shortest angular path on  $S^1$ , preventing the amplitude collapse inherent to Euclidean interpolation where antipodal trajectories ( $\Delta\theta = \pi$ ) are forced through the origin ( $A \rightarrow 0$ ). Furthermore, this avoids the singular polar metric  $g_{\text{polar}} = dA^2 + A^2 d\theta^2 \cong \mathbb{C} \setminus \{0\}$ , whose straight Euclidean geodesics also collapse near the removed origin.

While the cylinder possesses vanishing Riemann curvature ( $K = 0$ ), it exhibits a non-trivial fundamental group ( $\pi_1(\mathcal{M}) = \mathbb{Z}$ ), which causes phase seam defects in flat models. Moreover, the cylinder is a parallelizable manifold with trivial global frame  $(\partial_A, \partial_\theta)$ , allowing direct velocity regression without pushforward operators. Crucially, under Cartesian flow, the induced angular velocity  $\dot{\theta} = (xu_y - yu_x)/A^2 = \mathcal{O}(A^{-1})$  diverges near the origin  $A \rightarrow 0$  with unbounded variance. In contrast, our cylindrical target velocity is globally bounded,  $|u_\theta| \leq \pi$ , guaranteeing numerical stability. Furthermore, the product metric cost decomposes separably, creating a natural theoretical bridge to closed-form Optimal Transport on  $S^1$  via circular CDF shifts [Delon et al., 2010].

## 76 2.1 Continuous Network Embedding

77 To circumvent artificial jump discontinuities at the branch cut  $[-\pi, \pi)$ , our network operates on a  
 78 3-channel continuous trigonometric embedding  $x = (A, \cos \theta, \sin \theta) \in \mathbb{R}^3$  as input. The neural  
 79 network then predicts a 2-channel velocity field  $u_t = (v_A, v_\theta) \in T_{(A, \theta)}\mathcal{M}$ , corresponding to the  
 80 tangent space of the amplitude and phase.

## 81 2.2 Loss Formulation

82 Given paired samples  $x_0 = (A_0, \theta_0) \sim p_0$  and  $x_1 = (A_1, \theta_1) \sim p_1$  (where  $p_1$  denotes the empirical  
 83 target distribution of complex-valued MRI data), we construct geodesic probability paths along each  
 84 component:  $A_t = (1 - t)A_0 + tA_1$  and  $\theta_t = \exp_{\theta_0}^{S^1}(t u_\theta)$ . The target velocity field on the product  
 85 manifold is:

$$u_A = A_1 - A_0, \quad u_\theta = \text{atan2}(\sin(\theta_1 - \theta_0), \cos(\theta_1 - \theta_0)) \quad (1)$$

86 where  $u_\theta$  computes the shortest signed angular difference via the  $S^1$  logarithmic map, correctly  
 87 resolving transport across the  $\pm\pi$  boundary.

88 The network  $v_\phi(t, x)$  regresses the target velocity field  $u_t(x_t)$  via an edge-preserving  $L_1$  objective:

$$\mathcal{L}(\phi) = \mathbb{E}_{t, x_0, x_1} \left[ |v_A - u_A| + \lambda \frac{A_1}{\bar{A}_1} |v_\theta - u_\theta| \right] \quad (2)$$

89 where  $\lambda = 1.0$  and  $\bar{A}_1$  is the batch mean amplitude. Modulating the phase loss by  $A_1$  acts as an  
 90 empirical SNR heuristic inspired by phase Fisher information (which formally scales as  $A_1^2$  under  
 91 complex Gaussian noise), concentrating capacity on tissue while mitigating ill-defined phase in  
 92 background noise. Furthermore, we model amplitude  $A$  linearly rather than logarithmically to avoid  
 93 numerical instabilities as  $A \rightarrow 0$ .

## 94 2.3 Base Distribution and Inference

95 We construct our generative process from the base distribution  $p_0 = \mathcal{U}([0, 1]) \otimes \mathcal{U}(S^1)$ , a uniform  
 96 prior on the unit cylinder (clamped with  $\epsilon = 10^{-6}$  for numerical stability at the origin). Crucially,  
 97 because the target velocity field is computed via  $\mathcal{O}(1)$  closed-form geodesics, training completely  
 98 bypasses forward simulation; numerical integration (via a 2nd-order Heun solver) is strictly reserved  
 99 for the inference generation phase.

## 100 3 Experiments and Results

101 We evaluate Cylindrical Flow Matching on complex-valued MRI synthesis and downstream recon-  
 102 struction using the raw  $k$ -space SKM-TEA-mini dataset [Desai et al., 2021] (single-coil, first-echo  
 103 image space, comprising 3 complete 3D knee volumes with 1536 axial slices total). We partition the  
 104 dataset into 2 patient volumes for training (1024 slices) and 1 completely held-out patient volume  
 105 ( $N = 512$  contiguous slices) for testing. This constrained data regime provides a rigorous test of topo-  
 106 logical inductive bias: while Euclidean models must waste parameter capacity trying to approximate  
 107 non-physical phase branch cuts, our cylindrical formulation natively respects  $S^1 \times \mathbb{R}^+$  geometry,  
 108 yielding superior generalization on unseen anatomy. Retrospective  $4\times$  Cartesian undersampling is  
 109 simulated using 1D phase-encoding masks with a central 24-line autocalibration signal (ACS) band,  
 110 with exact Data Consistency (DC Error  $< 10^{-6}$ ) enforced via interleaved  $k$ -space projections.

111 As shown in Figure 2, the Euclidean model struggles with phase wrapping, leading to artificial signal  
 112 cancellations and magnitude dropouts near tissue boundaries (clearly highlighted in the residual error  
 113 maps). In contrast, our geometry-aware approach explicitly models the  $S^1$  phase topology, yielding  
 114 continuous phase fields while preventing destructive interference, which results in significantly  
 115 sharper anatomical reconstructions as evidenced across all quantitative metrics in Table 1.

116 To evaluate phase fidelity, we compute the Circular Phase Error (CPE) in radians:

$$\text{CPE}(\theta, \hat{\theta}) = \frac{1}{|M|} \sum_{i \in M} |\text{atan2}(\sin(\theta_i - \hat{\theta}_i), \cos(\theta_i - \hat{\theta}_i))| \quad (3)$$

117 where  $M$  denotes a tissue mask thresholded at 5% of peak amplitude to avoid background noise bias.




Figure 2: **Qualitative comparison on a representative test slice.** Magnitude and Phase reconstructions alongside corresponding residual error maps ( $|\Delta \text{Mag}|$  and  $|\Delta \text{Phase}|$ ). The Euclidean baseline ( $\mathbb{R}^2$ ) exhibits severe phase seam artifacts and boundary magnitude attenuation, which are natively resolved by Cylindrical Flow Matching ( $S^1 \times \mathbb{R}^+$ ).

Table 1: **Quantitative metrics.** Descriptive evaluation across 512 contiguous slices of the held-out test volume ( $4 \times$  Cartesian reconstruction with exact Data Consistency projections).

| Method                         | PSNR (dB) $\uparrow$               | SSIM $\uparrow$                    | CPE (rad) $\downarrow$             |
|--------------------------------|------------------------------------|------------------------------------|------------------------------------|
| Euclidean ( $\mathbb{R}^2$ )   | $24.13 \pm 1.18$                   | $0.530 \pm 0.06$                   | $0.513 \pm 0.07$                   |
| <b>Cylindrical Flow (Ours)</b> | <b><math>24.47 \pm 1.16</math></b> | <b><math>0.588 \pm 0.04</math></b> | <b><math>0.405 \pm 0.05</math></b> |

## 4 Conclusion and Future Work

By formulating probability paths on  $\mathbb{R}^+ \times S^1$ , Cylindrical Flow Matching natively resolves phase discontinuities and magnitude attenuation, providing a physically consistent generative baseline for complex-valued MRI. Future work will extend this framework to multi-coil acceleration benchmarks and quantitative phase mapping. Finally, extending this cylindrical manifold formulation to continuous Schrödinger Bridges will enable data-driven priors for downstream complex inverse problems and diagnostic tasks.

## References

- Ricky T. Q. Chen and Yaron Lipman. Flow matching on general geometries. In *International Conference on Learning Representations (ICLR)*, 2024.
- Hyungjin Chung and Jong Chul Ye. Score-based diffusion models for accelerated MRI. *Medical Image Analysis*, 80:102479, 2022. doi: 10.1016/j.media.2022.102479.
- Julie Delon, Julien Salomon, and Andrei Sobolevski. Fast optimal transport on the circle. *SIAM Journal on Numerical Analysis*, 47(6):4313–4335, 2010.
- Arjun D. Desai, Garry E. Gold, Brian A. Hargreaves, and Akshay S. Chaudhari. SKM-TEA: A dataset for accelerated MRI reconstruction with dense image labels for quantitative clinical evaluation. In *Advances in Neural Information Processing Systems (NeurIPS) Track on Datasets and Benchmarks*, volume 34, pages 25375–25389, 2021.
- Quan Dou, Zhixing Wang, Xue Feng, Adrienne E. Campbell-Washburn, John P. Mugler, III, and Craig H. Meyer. MRI denoising with a non-blind deep complex-valued convolutional neural network. *NMR in Biomedicine*, 38(1):e5291, 2025. doi: 10.1002/nbm.5291.
- Yaron Lipman, Ricky T. Q. Chen, Heli Ben-Hamu, Maximilian Nickel, and Matt Le. Flow matching for generative modeling. In *International Conference on Learning Representations (ICLR)*, 2023.
- Moritz Rempe, Fabian Hörst, Helmut Becker, Marco Schlimbach, Lukas T. Rotkopf, Kevin Kröninger, and Jens Kleesiek. PhaseGen: A diffusion-based approach for complex-valued MRI data generation. *arXiv preprint arXiv:2504.07560*, 2025.
- Moritz Rempe, Lukas T. Rotkopf, Marco Schlimbach, Helmut Becker, Fabian Hörst, Johannes Haubold, Philipp Dammann, Kevin Kröninger, and Jens Kleesiek. Efficient complex-valued vision transformers for MRI classification directly from k-space. *arXiv preprint arXiv:2601.18392*, 2026.