```
# Generated by CodeTwo - Version 2.5.0.0 - 11/4/2021 12:15:17
# MD5 hash: 6ed0f0b0ffb0ffb0ffb0ffb0ffb0ffb0

# Copyright (c) 2021 CodeTwo Sp. z o.o.
# All rights reserved.

# Module manifest for module 'exchange'
# Generated on: 11/4/2021
# Generated by: CodeTwo

@{
# Script module or binary module file associated
# RootModule = '.\exchange.psm1'
# Version number of this module.
ModuleVersion = '2.5.0.0'
# Supported PSEditions
# CompatiblePSEditions = @()
# ID used to uniquely identify this module
GUID = '6ed0f0b0-ffb0-ffb0-ffb0-ffb0ffb0ffb0'
# Author of this module
Author = 'CodeTwo'
# Company or vendor of this module
CompanyName = 'CodeTwo'
# Copyright statement for this module
Copyright = '(c) 2021 CodeTwo Sp. z o.o. All rights reserved.'
# Description of the functionality provided by this module
Description = 'CodeTwo Exchange'
# Minimum version of the Windows PowerShell engine required by this module
# PowerShellVersion = ''
# Name of the Windows PowerShell host required by this module
# PowerShellHostName = ''
# Minimum version of the Windows PowerShell host required by this module
# PowerShellHostVersion = ''
# Minimum version of Microsoft .NET Framework required by this module
# DotNetFrameworkVersion = ''
# Minimum version of the common language runtime (CLR) required by this module
# CLRVersion = ''
# Processor architecture (None, X86, Amd64) required by this module
# ProcessorArchitecture = ''
# Modules that must be imported into the global environment prior to importing this module
# RequiredModules = @()
# Assemblies that must be loaded prior to importing this module
# RequiredAssemblies = @()
# Script files (.ps1) that are run in the caller's environment prior to importing this module.
# ScriptsToProcess = @()
# Type files (.ps1xml) to be loaded when importing this module
# TypesToProcess = @()
# Format files (.ps1xml) to be loaded when importing this module
# FormatsToProcess = @()
# Modules to import as nested modules of the module specified in RootModule/ModuleToProcess
# NestedModules = @()
# Functions to export from this module, for best performance, do not use wildcards and list the functions in this manifest.
FunctionsToExport = '*'
# Cmdlets to export from this module, for best performance, do not use wildcards and list the cmdlets in this manifest.
CmdletsToExport = '*'
# Variables to export from this module
VariablesToExport = '*'
# Aliases to export from this module, for best performance, do not use wildcards and list the aliases in this manifest.
AliasesToExport = '*'
# DSC resources to export from this module
# DscResourcesToExport = @()
# List of all modules packaged with this module
# ModuleList = @()
# List of all files packaged with this module
# FileList = @()
# Private data to pass to the module specified in RootModule/ModuleToProcess. This may also contain a PSData hashtable with additional module metadata.
PrivateData = @{
# Tags applied to this module. These help with module discovery.
# Tags = @('Desktop', 'Mac', 'Windows')
# License URL for this module.
# LicenseUrl = 'http://www.codetwo.com/terms-of-use'
# Project URL for this module.
# ProjectUrl = 'http://www.codetwo.com'
# Release notes for this module.
# ReleaseNotes = ''
}
# HelpInfo URI for this module.
# HelpInfoURI = ''
# Default prefix for commands exported from this module. Override in the manifest to specify a different prefix.
# DefaultCommandPrefix = ''
}

# SIG # Begin signature block
# MIIoUAYJKoZIhvcNAQcCoIIoQTCCKD0CAQExDzANBglghkgBZQMEAgEFADCBmAYKKwYBBAGCNwIBBAqgiqQwgiqQAgEBMFEwPTAJBgcqhkjOPQIBMAoGCCqGSM49AwEHAwIEIPqqq
```