Chapter 2

Decentralization

Mastering Blockchain, 2nd Edition

Imran Bashir, Packt Publishing

Teguh Indra Bayu, Ph.D.

Fakultas Teknologi Informasi – Universitas Kristen Satya Wacana (FTI UKSW)

Learning Objectives

By the end of this lecture, students should be able to:

1. Define decentralization and explain its significance in the context of blockchain
2. Distinguish between centralized, distributed, and decentralized systems
3. Explain two methods: disintermediation and contest-driven decentralization
4. Apply the 4-question framework to evaluate decentralization needs
5. Describe the layers of a full decentralized ecosystem (storage, communication, computation)
6. Identify key decentralized organizational forms: DAO, DApp, smart contracts

Chapter Overview

Lecture roadmap — 8 key topic areas

What is Decentralization?

Core concept & historical context

Routes & Framework

4-question model for decentralizing systems

Types of Systems

Centralized vs. Distributed vs. Decentralized

Ecosystem Layers

Storage, Communication, Computation

Methods of Decentralization

Disintermediation & Contest-driven

DApps & Organizations

DAO, DAC, DAS, Smart Contracts

When to Use Blockchain?

Decision framework for practitioners

Platforms

Ethereum, MaidSafe, Lisk, Bitcoin

What is Decentralization?

Core Idea

- Distribute control away from a single central body to the periphery
- Not a new concept — used in management, government, and strategy for decades
- In blockchain: no single central authority controls the system
- Anyone can join, operate, and participate on equal footing

Benefits of Decentralization

Efficiency:	Faster decision-making at the local level
Reduced Burden:	Less pressure on top management
Motivation:	Empowers individuals and sub-units
Resilience:	No single point of failure
Trust:	Transparent, verifiable operations

Three Types of Systems

First described by Paul Baran, RAND Corporation (1964)

Centralized

One master node controls all operations. All users depend on the single central authority.

Example: Google, Amazon, Traditional Banks

Central authority has full control of all data and operations.

Distributed

Data spread across multiple nodes, but a central authority still governs the system.

Example: CDN networks, cluster computing

Often confused with decentralized — but a governing center still exists.

Decentralized

No single master node. Control is shared equally among all nodes. No governing authority.

Example: Bitcoin, Ethereum

Key blockchain property: no central authority of any kind.

Key Distinction: Distributed systems still have a central governing authority — decentralized systems do NOT.

Blockchain and Decentralization

How blockchain enables a decentralized system

No Intermediaries	Blockchain allows direct transactions without a trusted third party (bank, broker, registry)
Many Leaders via Consensus	Leadership is not fixed — any node can compete to add the next block via a consensus mechanism
Proof of Work (PoW)	Most common consensus method: nodes solve a computational puzzle to earn the right to validate transactions
Decentralized Consensus	A key innovation — users agree on the state of the ledger without any central authority or third party
Degrees of Decentralization	Ranges from semi-decentralized to fully decentralized depending on design requirements and use case

Methods of Decentralization

Two approaches to achieving decentralization

1 — Disintermediation

Complete removal of the intermediary

Example: To send money abroad, you normally use a bank. With blockchain, you send directly to the recipient's address — no bank needed.

Result: Full decentralization achieved

Limitation: Faces regulatory challenges in some sectors (e.g., banking)

2 — Contest-Driven

Multiple service providers compete for selection

Providers compete for the right to provide services. Smart contracts select based on reputation, score, or quality of service.

Result: Partial decentralization — monopoly is prevented

Advantage: Fosters a competitive ecosystem among service providers

Scale: Centralized ◀——— Competing Intermediaries ———▶ Fully Decentralized

Do You Need a Blockchain?

A practical decision framework — answer these questions before choosing blockchain

Question	Recommendation
Is high data throughput required?	**Use a traditional database**
Are updates centrally controlled?	**Use a traditional database**
Do users trust each other?	**Use a traditional database**
Are users anonymous?	**YES → Public BC / NO → Private BC**
Is consensus required within a consortium?	**YES → Private BC / NO → Public BC**

Important: Not everything needs to be decentralized. Blockchain has real trade-offs: latency, complexity, and cost.

Routes to Decentralization

Framework by Narayanan et al. — Bitcoin and Cryptocurrency Technologies, Princeton University Press

1 **What is being decentralized?**

Identify the target system (e.g., money transfer, identity, voting system)

Example: Money transfer system

2 **What level of decentralization is needed?**

Full disintermediation, or partial (competition-based)?

Example: Disintermediation

3 **What blockchain is used?**

Bitcoin, Ethereum, Hyperledger, or another suitable chain?

Example: Bitcoin

4 **What security mechanism is used?**

Atomicity, reputation-based, or cryptographic guarantees?

Example: Atomicity

Blockchain Ecosystem Decentralization

For complete decentralization, every layer of the ecosystem must also be decentralized

Identity & Wealth	Technologies: Namecoin, BitAuth, OpenID, Cryptocurrency tokens
Computation	Technologies: Ethereum (smart contracts), blockchain processing layer — business logic runs on the network
Storage	Technologies: IPFS, Filecoin, BigchainDB, Ethereum Swarm, Storj, MaidSafe
Communication	Technologies: Internet, Mesh Networks (e.g., FireChat), P2P protocols, Whisper

Key Insight — IPFS (InterPlanetary File System):

Uses Kademlia DHT + Merkle DAG. Aims to replace HTTP. Filecoin provides economic incentives for nodes to store data.

Smart Contracts & Decentralized Organizations

SC	**Smart Contract** Self-executing program on blockchain. Business logic triggered by predefined conditions. Foundation for all decentralized organizational forms.
DO	**Decentralized Organization** Software modelling a real organization on blockchain. Parties interact via code. Requires human input to execute business logic.
DAO	**Decentralized Autonomous Org.** Fully automated — AI-like governance logic. Famous case: The DAO raised $168M, was hacked (2016), triggering an Ethereum hard fork.
DAC	**Decentralized Autonomous Corp.** Subset of DAO. Can earn profit and pay dividends. Runs business logic automatically without human management.
DAS	**Decentralized Autonomous Society** Entire society on blockchain: government services (passports, records, identity) delivered via DApps and DAOs.

Decentralized Applications (DApps)

Software programs running on peer-to-peer blockchain networks

Three Types of DApps

Type I	Run on their own blockchain (e.g., Bitcoin)
Type II	Built on top of an existing blockchain (e.g., Ethereum)
Type III	Use only the protocols of an existing blockchain

DApp Requirements

- Fully open-source; no single entity controls majority tokens
- Data stored on a public, cryptographically secured blockchain
- Uses a cryptographic token for access and rewards
- Tokens generated by a standard cryptographic algorithm
- Consensus-driven via PoW or PoS

Real-World DApp Examples

KYC-Chain

Manage Know Your Customer (KYC) data via smart contracts

OpenBazaar

Decentralized P2P marketplace — an alternative to eBay, runs on Bitcoin

Lazooz

Peer-to-peer ride-sharing — decentralized Uber, earns Zooz coins via proof of movement

Platforms for Decentralization

Any blockchain network can serve as a decentralization platform

Ethereum

Token: ETH

- First Turing-complete language (Solidity)
- Supports smart contracts and DApp development
- Proposed by Vitalik Buterin, 2013
- Most prominent DApp development platform

Bitcoin

Token: BTC

- Longest-established and most resilient blockchain
- Market cap ~$145B (at time of writing)
- First choice for highest security requirements
- Limited scripting (not Turing-complete)

MaidSafe

Token: Safecoin

- SAFE network using unused community resources
- Encrypted, distributed file storage
- Automatically deduplicates files
- Incentivizes node contributions with Safecoin

Lisk

Token: LSK

- JavaScript-based DApp development (Node.js)
- DApps hosted on independent sidechains
- Delegated Proof of Stake (DPOS) consensus
- 101 elected delegate nodes secure the network

Key Terms & Definitions

Decentralization

Distribution of control away from a single central authority to many participants

Disintermediation

Complete removal of an intermediary from a process or transaction

Consensus Mechanism

Algorithm enabling participants to agree on a shared ledger without a central authority

Smart Contract

Self-executing program on a blockchain that runs business logic automatically when conditions are met

DAO

Decentralized Autonomous Organization — fully automated blockchain-based org governed by code, not people

DApp

Decentralized Application — runs on a P2P blockchain network, open-source and token-based

IPFS

InterPlanetary File System — decentralized storage using Kademlia DHT and Merkle DAG; aims to replace HTTP

Atomicity

Transaction guarantee: executes fully or not at all — ensures integrity in decentralized systems

Proof of Work

Consensus method where nodes compete by solving a computational puzzle to validate the next block

Zooko's Triangle

Naming systems can have at most 2 of 3 properties: secure, decentralized, and human-readable

Benefits vs. Limitations of Decentralization

Benefits

+ Transparency — all transactions visible on chain

+ Efficiency — faster decision-making, fewer bottlenecks

+ Cost savings — no intermediary fees

+ Trusted ecosystem — no need for a third party

+ No single point of failure — resilient architecture

+ Censorship resistance — no authority can block

+ Privacy and anonymity (on public blockchains)

Limitations & Challenges

- Security risks — lost private keys = permanent loss of funds

- Software bugs — vulnerabilities in smart contract code

- Human errors — logic mistakes can be irreversible

- Not always needed — centralized may work better

- Regulatory barriers — compliance requirements

- Latency — consensus adds processing delay

- Legal ambiguity — DAOs have no recognized legal status

Key Takeaways

1. Decentralization removes central authority — blockchain is its primary modern vehicle
2. Three system types: Centralized, Distributed (still has a center), and Decentralized (no center)
3. Two methods: Disintermediation (full removal) and Contest-driven (competitive selection)
4. Use the decision framework — not every problem requires a blockchain
5. Full ecosystem decentralization requires decentralizing storage, communication, and computation
6. New organizational forms: smart contracts, DOs, DAOs, DACs, DApps
7. Key platforms: Ethereum (Solidity, smart contracts), Bitcoin, MaidSafe, Lisk

Discussion & Q&A

Reflection Questions

1. Which industry could benefit most from decentralization, and why?
2. If a DAO has a bug causing it to malfunction, who is responsible? (Refer: The DAO hack, 2016)
3. Is today's internet truly decentralized? Was it designed to be? What changed over the years?
4. Apply the 4-question framework: choose any real-world system and evaluate how to decentralize it.

Source: Mastering Blockchain, 2nd Edition — Imran Bashir, Packt Publishing