

A Comparative Study of Audio Feature Extraction and Machine Learning Methods for Bird Species Classification[★]

Kryspin Dziarek¹, Szymon Pająk¹ and Marcin Adamski¹

¹*Faculty of Applied Mathematics, Silesian University of Technology, Kaszubska 23, 44100 Gliwice, POLAND*

Abstract

wstęp - 1 akapit, co zrobiono, jakie wyniki, minimum 180 słów

Keywords

Sound analysis, Birdsong, MFCC (Mel-Frequency Cepstral Coefficients), Random forest, Neural network

1. Introduction

Audio analysis is a process of examining and measuring sound signals to gain information, it has been a subject of research for many decades[1], and now, in the age of artificial intelligence, it has many more applications. Machine learning has become an essential tool in audio signal processing, enabling the development of systems capable of analyzing and classifying sounds. Such systems are widely used in applications including speech recognition[2], music[3] and animal identification[4], often outperforming human perception of acoustic patterns[5].

There are many techniques for feature extraction from sound, one of the most commonly used being Mel-Frequency Cepstral Coefficients (MFCC). This method converts the raw audio signal into a set of coefficients representing the spectral characteristics of sound[6]. Previous studies have established standard configurations for this algorithm, such as the number of Mel filters and cepstral coefficients. However, optimal values depend on specific dataset and application, such as detection of breathing phase[7] or respiratory diseases[8].

In addition to sound recognition, various machine learning algorithms have been applied to audio classification tasks, each providing different levels of performance. Simpler algorithms, such as k-nearest neighbors and random forests, are faster, but often less accurate solutions, while the complex ones, like neural networks, provide higher accuracy at the cost of increased computational complexity.

SSI, project 2025/2026

✉ kd315963@student.polsl.pl (K. Dziarek); sp315960@student.polsl.pl (S. Pająk); ma315929@student.polsl.pl (M. Adamski)



© 2026 Copyright for this paper by its authors. Use permitted under Creative Commons License Attribution 4.0 International (CC BY 4.0).

 CEUR Workshop Proceedings (CEUR-WS.org)

This paper presents bird species recognition with sound analysis (using MFCC) and compares different approaches for this system. The sound analysis algorithm consists of many stages, two of them are especially important, because the values they provide depend on chosen data. The number of filters used to describe the frames and number of compressed coefficients strongly affects the performance of the result. Too many features may introduce noise and redundancy, while too few may lead to information loss. The experiments conducted on a common dataset aim to identify the most effective approach for extracting the MFCC features and developing simple classification models with the best performance.

2. Methodology

This section outlines the approach used to compare different configurations of MFCC in audio feature extraction and the development of machine learning models for identifying bird species.


2.1. Audio Feature Extraction

Audio feature extraction enables the transformation of birdsong recordings into numerical representations, which are crucial for training machine learning models. A custom library called *SoundFeatures* was developed to implement the full extraction pipeline. This section describes its structure and role within the experimental setup.

Audio files were converted from MP3 to FLAC format to provide a consistent and lossless compression of the signal. Although this conversion does not restore the data lost during MP3 compression, it eliminates decoding artifacts and ensures stable input for further signal processing [9].

The audio feature extraction process consists of the following steps:

1. **Framing** - Segmenting the signal into short, overlapping frames.
2. **Windowing** - Applying a window function to each frame to minimize spectral leakage at the boundaries.
3. **Fast Fourier Transform (FFT)** - Mapping a time-domain signal into its frequency-domain representation.
4. **Power Spectrum** - Computing the energy distribution representation.
5. **Mel Filterbank Processing** - Constructing a set of triangular filters using Mel scale.
6. **Log Energy Calculation** - Mapping the linear frequency spectrum to Mel scale using Mel filterbank.
7. **Discrete Cosine Transform (DCT)** - Decorrelating the log energies to get Mel-Frequency Cepstral Coefficients



2.2. Machine Learning Algorithms

3. Experiments

3.1. Audio Feature Extraction

To analyse the MFCC efficiency based on the number of Mel filters and extracted features the experiments were conducted on dataset which was reduced to 1148 records. Both the Random Forest and the Neural Network were applied to check the F1 score for every configuration.

Figure 1: Random Forest F1 Score heatmaps for datasets with and without first coefficient




Figure 2: Neural Network F1 Score heatmaps for datasets with and without first coefficient




Figure 3: Best results

Algorithm	N Coefficients	N Filters	First Coefficient Ignored	F1 Score
Random Forest	24	178	No	0.6669
Random Forest	28	198	Yes	0.6618
Neural Network	48	150	No	0.8472
Neural Network	49	156	Yes	0.8454

While standard speech recognition systems typically employ 13 Mel coefficients and between 26 and 40 Mel filters, our results demonstrate that bird species identification requirements contain higher spectral resolution. The optimal configuration for the Neural Network was observed in the range of 45-49 Mel coefficients with at least 58 Mel filters, whereas the Random Forest achieved its best performance with 21-25 Mel coefficients and at least 146 Mel filters. These results emphasize the fact that birdsong contains faster frequency modulations and more complex harmonic structures compared to human speech, requiring denser filterbank to effectively capture significant parts of the sound, which is essential for accurate species discrimination.

The difference in the optimal spectral resolutions between the two models highlights the higher sensitivity of Random Forest to excessive feature counts, degrading its performance, while Neural Network effectively manages more complex, achieving better performance.

4. Conclusion

References

- [1] J. D. Hollabaugh, Methods for phonemic recognition in speech processing (1963).
- [2] M. Zhu, C. Wang, A systematic review of research on ai in language education: Current status and future implications (2025).
- [3] S. Serrano, M. A. B. Sahbudin, C. Chaouch, M. Scarpa, A new fingerprint definition for effective song recognition, *Pattern Recognition Letters* 160 (2022) 135–141.
- [4] C. M. Wood, A. Barceinas Cruz, S. Kahl, Pairing a user-friendly machine-learning animal sound detector with passive acoustic surveys for occupancy modeling of an endangered primate, *American Journal of Primatology* 85 (2023) 269–307.
- [5] C. Spille, B. Kollmeier, B. T. Meyer, Comparing human and automatic speech recognition in simple and complex acoustic scenes, *Computer Speech & Language* 52 (2018) 123–140.
- [6] Z. K. Abdul, A. K. Al-Talabani, Mel frequency cepstral coefficient and its applications: A review, *Ieee Access* 10 (2022) 122136–122158.
- [7] A. K. Zhantleuova, Y. K. Makashev, N. T. Duzbayev, Optimizing mfcc parameters for breathing phase detection, *Sensors* 25 (2025) 5002.
- [8] Y. Yan, S. O. Simons, L. van Bemmelen, L. G. Reinders, F. M. Franssen, V. Urovi, Optimizing mfcc parameters for the automatic detection of respiratory diseases, *Applied Acoustics* 228 (2025) 110299.
- [9] G. Shi, Data compression for audio-based smart beekeeping (2024) 50–52.