



TAKE

API Documentation

GET Get Customers

127.0.0.1:8080/take/customer

Returns list of customers.

Example Request

Get Customers

```
curl --location --request GET '127.0.0.1:8080/take/customer'
```

GET Get Customer

127.0.0.1:8080/take/customer/{{id}}

Returns the customer with the specified Id.

Example Request

Get Customer

```
curl --location -g --request GET '127.0.0.1:8080/take/customer/{{id}}'
```

POST Add Customer

127.0.0.1:8080/take/customer

Adds a new customer



Documentation Settings ▼

BODY raw

```
{
  "firstName": "XYZ",
  "lastName": "ZYX",
  "phoneNumber": "123432143"
}
```

Example Request

Add Customer

```
curl --location --request POST '127.0.0.1:8080/take/customer' \
--data-raw '{
  "firstName": "XYZ",
  "lastName": "ZYX",
  "phoneNumber": "123432143"
}'
```

PUT Edit Customer

127.0.0.1:8080/take/customer

Replaces data for specified customer with given data.

BODY raw

```
{
  "customerId": "2",
  "firstName": "ZZZ",
  "lastName": "XXX",
  "phoneNumber": "123432143"
}
```

Example Request

Edit Customer



```
curl --location --request PUT '127.0.0.1:8080/take/customer' \  
--data-raw '{  
  "customerId": "2",  
  "firstName": "ZZZ",  
  "lastName": "XXX",  
  "phoneNumber": "123432143"  
}'
```

DEL Delete Customer

```
127.0.0.1:8080/take/customer/{{id}}
```

Removes customer with a given id

HEADERS

customerId

1

Example Request

Delete Customer

```
curl --location -g --request DELETE '127.0.0.1:8080/take/customer/{{id}}'
```

GET Get Customer Orders

```
http://127.0.0.1:8080/take/customer/{{id}}/orders
```

Returns list of orders for customer with given id.

Example Request

Get Customer Orders

```
curl --location -g --request GET 'http://127.0.0.1:8080/take/customer/{{id}}/orders'
```



GET Get Ingredients

```
127.0.0.1:8080/take/ingredient
```

Returns list of ingrediends

Example Request

Get Ingredients

```
curl --location --request GET '127.0.0.1:8080/take/ingredient'
```

GET Get Ingredient

```
127.0.0.1:8080/take/ingredient/{{id}}
```

Returns ingredient with given id.

Example Request

Get Ingredient

```
curl --location -g --request GET '127.0.0.1:8080/take/ingredient/{{id}}'
```

POST Add Ingredient

```
http://127.0.0.1:8080/take/ingredient
```

Adds ingredient with a specified data.

BODY raw

```
{  
  "name": "serek"
```

}



Example Request

Add Ingredient

```
curl --location --request POST 'http://127.0.0.1:8080/take/ingredient' \  
--data-raw '{  
  "name": "serek"  
'
```

PUT Edit Ingredient

```
http://127.0.0.1:8080/take/ingredient
```

Replaces ingredient with specified id with given data.

BODY raw

```
{  
  "ingredientId" : 1,  
  "name": "maslo"  
}
```

Example Request

Edit Ingredient

```
curl --location --request PUT 'http://127.0.0.1:8080/take/ingredient' \  
--data-raw '{  
  "ingredientId" : 1,  
  "name": "maslo"  
'
```

DEL Delete Ingredient

```
http://127.0.0.1:8080/take/ingredient/{{id}}
```

Deletes the ingredient with given id.

```
curl --location -g --request DELETE 'http://127.0.0.1:8080/take/ingredient/{{id}}'
```

GET Get Meals

```
http://127.0.0.1:8080/take/meal
```

Returns list of meals

Example Request

Get Meals

```
curl --location --request GET 'http://127.0.0.1:8080/take/meal'
```

GET Get Meal

```
http://127.0.0.1:8080/take/meal/{{id}}
```

Returns meal with given id.

Example Request

Get Meal

```
curl --location -g --request GET 'http://127.0.0.1:8080/take/meal/{{id}}'
```

POST Add Meal

```
http://127.0.0.1:8080/take/meal
```

Adds meal with given data

BODY raw

Documentation Settings ▼

```
{
  "name": "boczek",
  "price": 14,
  "vegan": 0,
  "vegetarian": 0
}
```

Example Request

Add Meal

```
curl --location --request POST 'http://127.0.0.1:8080/take/meal' \
--data-raw '{
  "name": "boczek",
  "price": 14,
  "vegan": 0,
  "vegetarian": 0
}'
```

PUT Edit Meal

Replaces meal with given data.

BODY raw

```
{
  "mealId": 1,
  "name": "kaczka"
}
```

Example Request

Edit Meal

```
curl --location --request PUT 'http://127.0.0.1:8080/take/meal' \
--data-raw '{
  "mealId": 1,
  "name": "kaczka"
}'
```



DEL Delete Meal

```
http://127.0.0.1:8080/take/meal/{{id}}
```

Removes meal with specified id.

Example Request

Delete Meal

```
curl --location -g --request DELETE 'http://127.0.0.1:8080/take/meal/{{id}}'
```

GET Get Meals Quantities

```
http://127.0.0.1:8080/take/meal/{{id}}/quantities
```

Example Request

Get Meals Quantities

```
curl --location -g --request GET 'http://127.0.0.1:8080/take/meal/{{id}}/quantities'
```

GET Get Orders

```
http://127.0.0.1:8080/take/order
```

Returns list of orders.

Example Request

Get Orders

```
curl --location --request GET 'http://127.0.0.1:8080/take/order'
```




GET Get Order

```
http://127.0.0.1:8080/take/order/{{id}}
```

returns order with specified id

Example Request

Get Order

```
curl --location -g --request GET 'http://127.0.0.1:8080/take/order/{{id}}'
```

POST Add Order

```
http://127.0.0.1:8080/take/order
```

Creates a new order and connects it with customer with given id in data.

BODY raw

```
{
  "customerId": {
    "customerId": 1
  },
  "price": 30.2,
  "orderDate": "2021-10-10T00:00:00",
  "cardPayment": 1,
  "table": 5,
  "takeAway": 0
}
```

View More

Example Request

Add Order



```
curl --location --request POST 'http://127.0.0.1:8080/take/order' \  
--data-raw '{  
  "customerId": {  
    "customerId": 1  
  },  
  "price": 30.2,  
  "orderDate": "2021-10-10T00:00:00",  
  "cardPayment": 1,  
  "table": 5,  
  "takeAway": 0
```

[View More](#)

PUT Edit Order

```
http://127.0.0.1:8080/take/order
```

Replaces order with given data.

Example Request

Edit Order

```
curl --location --request PUT 'http://127.0.0.1:8080/take/order'
```

DEL Delete Order

```
http://127.0.0.1:8080/take/oder/{{id}}
```

Removes order with given id.

Example Request

Delete Order

```
curl --location -g --request DELETE 'http://127.0.0.1:8080/take/oder/{{id}}'
```

GFT Get Orders Meals



No request URL found. It will show up here once added.

Gets list of Meals for specified order.

Example Request

Get Orders Meals

```
curl --location --request GET ''
```

GET Get Quantities

http://127.0.0.1:8080/take/quantity

Returns quantities

Example Request

Get Quantities

```
curl --location --request GET 'http://127.0.0.1:8080/take/quantity'
```

GET Get Quantity

http://127.0.0.1:8080/take/quantity/{{id}}

Returns quantity with a given id.

Example Request

Get Quantity

```
curl --location -g --request GET 'http://127.0.0.1:8080/take/quantity/{{id}}'
```

POST Add Quantity

http://127.0.0.1:8080/take/quantity

Adds quantity

BODY raw

```
{
  "quantity":3,
  "unit": "ml",
  "ingredient": {
    "ingredientId": 1
  },
  "meal":{
    "id": 1
  }
}
```

View More

Example Request

Add Quantity

```
curl --location --request POST 'http://127.0.0.1:8080/take/quantity' \
--data-raw '{
  "quantity":3,
  "unit": "ml",
  "ingredient": {
    "ingredientId": 1
  },
  "meal":{
    "id": 1
  }
}
```

View More

PUT Edit Quantity

http://127.0.0.1:8080/take/quantity

Replace quantity with a given data.

Example Request

Edit Quantity

```
curl --location --request PUT 'http://127.0.0.1:8080/take/quantity'
```



DEL Delete Quantity

```
http://127.0.0.1:8080/take/quantity/{{id}}
```

Removes quantity

Example Request

Delete Quantity

```
curl --location -g --request DELETE 'http://127.0.0.1:8080/take/quantity/{{id}}'
```

GET Get Ingredients Quantities

```
http://127.0.0.1:8080/take/quantity/{{id}}/ingredient
```

Returns Quantities for a ingredient with specified id.

Example Request

Get Ingredients Quantities

```
curl --location -g --request GET 'http://127.0.0.1:8080/take/quantity/{{id}}/ingredient'
```

GET Get Meals Quantities

```
http://127.0.0.1:8080/take/quantity/{{id}}/meal
```

Returns Quantities for a meal with specified id.

Example Request

Get Meals Quantities

