

DATA 607 Wk2 Assignment 2A

Marcin K

2026-09-11

Task Description, Assignment 2A

Select six recent popular movies (or television episodes or books or songs or ...) Ask at least five people to rate each movie they have seen on a 1–5 scale. Store the collected ratings in a SQL database of your choice. Load the data from SQL into R as a dataframe.

Assignment Solution Details

Six recent movies were selected and a survey created to solicit reviews. The reviews were conducted in person and the results recorded with pen and paper. A grading scale of 1-5 was set for the movies along with a sixth option “I did not see this movie”. (a.k.a NULL)

The movies: 1. Obsession 2. The Odyssey 3. F1 4. Wicked: For Good 5. Spider Man: Brand New Day 6. Project Hail Mary

Data was added to a PostgreSQL table (movie_reviews) in a local database (DATA 607 Assignment 2A). The following is the SQL code that was used to generate the table inside the database.

The following Youtube video was very helpful in learning how to create a table in PostgreSQL: <https://www.youtube.com/watch?v=gySEbKmkvEU>

SQL Code Below

```
DROP TABLE IF EXISTS movie_reviews;
```

```
CREATE TABLE IF NOT EXISTS movie_reviews ( id SERIAL PRIMARY KEY, first_name VARCHAR(255), last_name VARCHAR(255), Obsession INT, The_Odyssey INT, F1 INT, Wicked_For_Good INT, Spider_Man_BND INT, Project_Hail_Mary INT );
```

```
INSERT INTO movie_reviews (first_name, last_name, Obsession, The_Odyssey, F1, Wicked_For_Good, Spider_Man_BND, Project_Hail_Mary) VALUES ('Michael', 'Smith', 5, 2, 3, 2, 1, NULL), ('Emily', 'Jones', NULL, 5, NULL, 3, NULL, NULL), ('Jennifer', 'Williams', NULL, 4, NULL, 5, 2, NULL), ('Ashley', 'Brown', NULL, NULL, NULL, 5, NULL, NULL), ('Adam', 'Kielkiewicz', NULL, NULL, NULL, NULL, NULL, 3, NULL);
```

```
SELECT * FROM movie_reviews;
```

```
#Two packages needed to be installed, "DBI" and "RPostgres"
```

```
library(tidyverse)
```

```
## -- Attaching core tidyverse packages ----- tidyverse 2.0.0 --  
## v dplyr      1.2.1      v readr      2.2.0
```

```
## v forcats 1.0.1      v stringr 1.6.0
## v ggplot2 4.0.3      v tibble  3.3.1
## v lubridate 1.9.5    v tidyr  1.3.2
## v purrr 1.2.2
## -- Conflicts ----- tidyverse_conflicts() --
## x dplyr::filter() masks stats::filter()
## x dplyr::lag() masks stats::lag()
## i Use the conflicted package (<http://conflicted.r-lib.org/>) to force all conflicts to become errors
```

```
library(DBI)
```

```
## Warning: package 'DBI' was built under R version 4.6.1
```

```
library(RPostgres)
```

```
## Warning: package 'RPostgres' was built under R version 4.6.1
```

```
database_connection <- dbConnect(
  RPostgres::Postgres(),
  dbname = "postgres",
  host = "localhost",
  port = 5432,
  user = "postgres",
  password = rstudioapi::askForPassword("Enter Database Password")
)
```

```
# Run a SQL query to get the results
```

```
query <- "SELECT id, first_name, last_name, Obsession,
The_Odyssey, F1, Wicked_For_Good, Spider_Man_BND, Project_Hail_Mary
FROM movie_reviews;"
```

```
R_movie_reviews <- dbGetQuery(database_connection, query)
```

```
glimpse(R_movie_reviews)
```

```
## Rows: 5
## Columns: 9
## $ id <int> 1, 2, 3, 4, 5
## $ first_name <chr> "Michael", "Emily", "Jennifer", "Ashley", "Adam"
## $ last_name <chr> "Smith", "Jones", "Williams", "Brown", "Kielkiewicz"
## $ obsession <int> 5, NA, NA, NA, NA
## $ the_odyssey <int> 2, 5, 4, NA, NA
## $ f1 <int> 3, NA, NA, NA, NA
## $ wicked_for_good <int> 2, 3, 5, 5, NA
## $ spider_man_bnd <int> 1, NA, 2, NA, 3
## $ project_hail_mary <int> NA, NA, NA, NA, NA
```