

Lecture 4: CNNs on Scientific Data
Blood Cells and Satellite Images
Finding T_c of the 2D Ising Model

Deep Learning for Scientific Discovery

Marcin Płodzień

Atomic Optics Department
Institute of Theoretical Physics
Jagiellonian University in Kraków



Doctoral School
of Exact and
Natural Sciences
Jagiellonian University

1

CNNs on Scientific Data: Blood Cells and Satellite Images



JAGIELLONIAN UNIVERSITY
IN KRAKOW

MedMNIST

MNIST

Modified National Institute of Standards and Technology database: 70 000 grey images, 28×28 pixels, of hand-written digits $0 \ldots 9$ — our "Hello world".


MedMNIST

the same idea for biomedical images: small images of a fixed size, a fixed split into training, validation and test part, one file per dataset.

- MedMNIST v2: 12 datasets of 2D images and 6 datasets of 3D images
- pathology slides, chest X-rays, skin lesions, retina scans, **blood cells**, CT, ...
- images at 28×28 pixels; larger versions at 64, 128 and 224 pixels
- one line of code to load: `pip install medmnist`

J. Yang et al., *MedMNIST v2 — A large-scale lightweight benchmark for 2D and 3D biomedical image classification*, Sci. Data **10**, 41 (2023), doi:10.1038/s41597-022-01721-8; medmnist.com

BloodMNIST: Blood Cells under the Microscope



- 17 092 microscope images of single blood cells
- colour images, 64×64 pixels
- label: one of 8 cell types, assigned by clinical pathologists

The task:
image of one cell $\rightarrow$ its type, e.g. **"neutrophil"**

A. Acevedo et al., *A dataset of microscopic peripheral blood cell images for development of automatic recognition systems*, Data in Brief **30**, 105474 (2020), doi:10.1016/j.dib.2020.105474

The Eight Cell Types

label		cell type	what it is	images
0		basophil	granulocyte with large dark granules	852
1		eosinophil	granulocyte with a two-lobed nucleus	2 181
2		erythroblast	immature red blood cell with a nucleus	1 085
3		immature granulocyte	precursor of granulocytes	2 026
4		lymphocyte	small cell with a large round nucleus	849
5		monocyte	largest white blood cell, folded nucleus	993
6		neutrophil	most common white blood cell, lobed nucleus	2 330
7		platelet	small cell fragment without a nucleus	1 643


The classes are **not balanced**: always answering "neutrophil" is right for 19.5% of the training images.

Blood Cells: the Models and Their Accuracy

	model	parameters	train	val.	test
A	dense network on the flattened image	258 245	78.3%	75.2%	75.6%
B	small CNN, sigmoid	689 221	19.5%	19.5%	**19.5%**
B2	the same small CNN, ReLU	689 221	86.0%	82.0%	81.9%
C	larger CNN	4 292 168	99.2%	95.5%	95.6%
D	C + batch norm, dropout, L2, augmentation	4 292 616	96.2%	96.4%	96.0%
E	GAP network	288 936	93.5%	94.0%	93.2%

same data, loss and optimiser; 10 epochs each

Blood Cells: Saturated Sigmoids in Model B



- Model B answers "neutrophil" for every image: 19.5%, the share of neutrophils. Its loss, 2.003, is the entropy of the class frequencies.
- the same network with ReLU: **81.9%**
- its sigmoids are saturated: the spread of their inputs grew from 0.35 to 98.60, and the gradient vanishes


Blood Cells: Layers of Models A and B2

Model A: dense network



layer	output	parameters
Flatten	12288	–
Linear	21	258 069
Linear	8	176
total		258 245


Model B2: small CNN, ReLU



layer	output	parameters
Conv2d	32 × 64 × 64	896
MaxPool2d	32 × 32 × 32	–
Flatten	32768	–
Linear	21	688 149
Linear	8	176
total		689 221

Activations (no parameters) not listed; all parameters trainable, none frozen. Model B: the layers of B2 with sigmoids, 689 221 parameters.


Blood Cells: Layers of Models C and D



layer	output	C	D
Conv2d	$32 \times 64 \times 64$	896	896
BatchNorm2d	$32 \times 64 \times 64$		64
Conv2d	$64 \times 32 \times 32$	18 496	18 496
BatchNorm2d	$64 \times 32 \times 32$		128
Conv2d	$128 \times 16 \times 16$	73 856	73 856
BatchNorm2d	$128 \times 16 \times 16$		256
Linear	512	4 194 816	4 194 816
Linear	8	4 104	4 104
total		4 292 168	4 292 616

all trainable, none frozen; layers without parameters (ReLU, max pooling, flatten, dropout in D) not listed; batch normalisation only in D


Blood Cells: Layers of the GAP Network E



layer	output	parameters
block 1 (Sequential)	$32 \times 64 \times 64$	10 272
MaxPool2d	$32 \times 32 \times 32$	–
block 2 (Sequential)	$64 \times 32 \times 32$	55 680
MaxPool2d	$64 \times 16 \times 16$	–
block 3 (Sequential)	$128 \times 16 \times 16$	221 952
Linear	8	1 032
total (all trainable)		288 936

block: two convolutions with batch normalisation and ReLU; global average pooling: a mean in `forward`, not a layer


Blood Cells: Confusion Matrices of All Models



rows: true, columns: predicted class


- A: 60% of monocytes called immature granulocytes
- B: one column, “neutrophil” for every image
- B2: 59% of basophils taken for monocytes
- C, D: almost diagonal
- E: 31% of monocytes taken for lymphocytes

CAM on Blood Cells




- top row: correctly classified test images, one per class
- bottom row: class activation map of the predicted class
- the evidence lies on the cell itself
- not on the red blood cells around it

Blood Cells: the Mistakes



- 233 of 3 421 test images are misclassified
- eight of them shown, with the map of the *predicted* class
- largest confusion: 31% of the monocytes are taken for lymphocytes
- an earlier run confused a different pair: errors are not stable from run to run

EuroSAT: Satellite Images of the Earth's Surface



- 27 000 patches from the Sentinel-2 satellites
- 64×64 pixels: $640\,\text{m} \times 640\,\text{m}$ on the ground
- label: one of 10 land-use classes

The task:
one patch $\rightarrow$ its land-use class, e.g. **"River"**


P. Helber et al., *EuroSAT: A Novel Dataset and Deep Learning Benchmark for Land Use and Land Cover Classification*, IEEE JSTARS **12**, 2217 (2019), doi:10.1109/JSTARS.2019.2918242

EuroSAT: Ten Land-Use Classes


	class	on the ground	images
0	AnnualCrop	fields sown and harvested every year: wheat, maize	3 000
1	Forest	forest	3 000
2	HerbaceousVegetation	grass and other low natural vegetation	3 000
3	Highway	motorway or major road	2 500
4	Industrial	industrial buildings	2 500
5	Pasture	grassland for grazing animals	2 000
6	PermanentCrop	orchards, vineyards	2 500
7	Residential	residential buildings	3 000
8	River	a river crossing the patch	2 500
9	SeaLake	sea or lake	3 000

EuroSAT: Results

- the GAP network of the blood cells, with 10 outputs
- augmentation: flips, shifts, rotations by 90°
- 1 000 patches per class, 10 epochs: **84.4% test accuracy**
- best: Forest (99.5%); worst: River (72.2%)
- an earlier run of the same code: 90.0%



CAM on EuroSAT



- top row: one correctly classified test patch per class
- bottom row: class activation map of the predicted class
- highway, river: the map follows the object
- forest, sea: the map covers the whole patch


2

Transfer Learning



JAGIELLONIAN UNIVERSITY
IN KRAKOW

Reusing a Trained Network




A ResNet-18 trained on ImageNet (1.28 million photographs, 1000 classes) has learned edges, textures, shapes. For a new task with few labels:

- (a) **frozen body**: keep all layers fixed (grey), remove the old output layer (red), train a new one for the 8 cell types (orange)
- (b) the same network from *random* initialisation, as a reference
- (c) **fine-tuning**: start from (a) and also train the last block, with a learning rate 10 times smaller

K. He et al., CVPR 2016, doi:10.1109/CVPR.2016.90; O. Russakovsky et al., IJCV **115**, 211 (2015), doi:10.1007/s11263-015-0816-y


Freezing and Fine-Tuning in Numbers



Freezing: `requires_grad = False`, so the optimiser never changes these weights (checked in the notebook: the frozen weights are identical before and after training).

ResNet-18 with a new output layer for 8 types	trainable	frozen
(a) frozen body	4 104	11 176 512
(c) last block (layer4) fine-tuned	8 397 832	2 782 784

Blood Cells: Transfer Does Not Help




BloodMNIST, 64×64 pixels; 10, 100, 800 labelled cells per type; 3421 test cells:

- frozen ImageNet network: 67.6, 78.0, 86.6 %
- fine-tuned last block: 62.7, 81.4, 88.6 %
- small CNN from random initialisation: **72.7, 83.2, 92.9** %

Same with our CIFAR-10 network as the source. With 10 cells per type, fine-tuning overfits (training loss 0).


Satellite Images: EuroSAT



- 27 000 patches of 64×64 pixels from the Sentinel-2 satellites (Copernicus programme), 34 European countries, 640 m $\times$ 640 m each
- RGB bands, 10 land-use classes (2000–3000 patches each): fields, forest, water, roads, houses
- textures and colours much closer to ImageNet photographs than stained blood cells

P. Helber, B. Bischke, A. Dengel, D. Borth, IEEE J-STARS **12**, 2217 (2019), doi:10.1109/JSTARS.2019.2918242; MIT licence

Satellite Images: Transfer Helps




Test accuracy (%), 2000 test patches:

labels per class	10	100	1000
ImageNet features	**77.2**	**88.4**	91.3
fine-tuned last block	73.2	87.1	**93.7**
small CNN, random	54.9	78.0	91.9
ResNet-18, random	37.3	63.5	69.8

ImageNet features: with logistic regression on top. Pretrained features: +22 points at 10 labels per class; at 1000 the small CNN catches up.

When Transfer Helps



- the source and target images must share their features: textures of landscapes resemble ImageNet photographs, stained cells under a microscope do not
- the gain is largest with few labels; with many labels a network trained on the task itself catches up
- always compare with a model trained from random initialisation on the same data


3

A Physics Example: the 2D Ising Model

JAGIELLONIAN UNIVERSITY
IN KRAKOW

The Ising Model: a Grid of Two-State Cells

- a grid of cells, each in one of **two states** (spin up or down)
- each cell **prefers the state of its neighbours**
- **temperature** is random noise: it flips cells whatever their neighbours do
- low noise: one state spreads over the whole grid; high noise: a random mosaic. In between lies a sharp threshold, the **critical temperature** T_c



a sampled configuration at T_c: patches of all sizes

Our question: can a network find T_c only by looking at snapshots of the grid, as it classified blood cells and land use?

The Same Mathematics Elsewhere

Ising-type models

- **magnets:** iron is magnetic below its Curie temperature, $1043\,\mathrm{K}$ ($770\,^{\circ}\mathrm{C}$), and not above it
- **neurons:** the joint firing patterns of retinal neurons (active or silent) are described by an Ising model fitted to recordings
- **images:** neighbouring pixels of a map or a satellite image tend to share a class; Ising-type models are used as priors to restore and segment such images


E. Schneidman, M. J. Berry, R. Segev, W. Bialek, *Weak pairwise correlations imply strongly correlated network states in a neural population*, Nature **440**, 1007 (2006), doi:10.1038/nature04701; S. Geman, D. Geman, *Stochastic Relaxation, Gibbs Distributions, and the Bayesian Restoration of Images*, IEEE TPAMI **6**, 721 (1984), doi:10.1109/TPAMI.1984.4767596

The 2D Ising Model

- a square lattice $L \times L$; on every site i a *spin* $s_i = +1$ (up) or $s_i = -1$ (down)
- a simple model of a magnet: each spin is a tiny magnetic moment
- $2^{L \cdot L}$ possible configurations $\{s_i\}$

Energy of a configuration (Hamiltonian)

$$H(\{s_i\}) = -J \sum_{\langle i,j \rangle} s_i s_j - h \sum_i s_i$$




$s_i = +1$ $\quad$ $s_i = -1$

$\langle i, j \rangle$: pairs of nearest neighbours; $J > 0$: aligned neighbours lower the energy (ferromagnet), we set $J = 1$; h: external magnetic field, we set $h = 0$.


The Couplings Decide the Lowest-Energy State

$H = -J \sum_{\langle i,j \rangle} s_i s_j - h \sum_i s_i$: the sign of J decides which neighbours are favourable. Lowest-energy configurations at $h = 0$:




$J > 0$: ferromagnetic

neighbours *aligned*
all up or all down: 2 ground states
energy $-2J$ per spin
magnetisation $M = 1$



$J < 0$: antiferromagnetic

neighbours *opposite*
checkerboard pattern: 2 ground states
energy $-2|J|$ per spin
magnetisation $M = 0$



$J = 0$: non-interacting

spins independent
all $2^{L \cdot L}$ configurations have the same energy
no order at any temperature


blue: $s_i = +1$, orange: $s_i = -1$

Ground States and the External Field


- square lattice: each spin has 4 neighbours, so 2 bonds per spin
- $h = 0$: flipping *all* spins leaves H unchanged — hence two equivalent ground states
- $h > 0$: spins prefer $+1$; $h < 0$: spins prefer -1; the field removes this symmetry and selects one state

From here on: $J = 1$ (ferromagnet), $h = 0$.

$J > 0$, $h = 0$: two ground states



$J > 0$, $h > 0$: one ground state




blue: $s_i = +1$, orange: $s_i = -1$

The Partition Function

At temperature T ($k_B = 1$) every configuration appears with the Boltzmann probability

$$p(\{s_i\}) = \frac{e^{-H(\{s_i\})/T}}{Z}, \qquad Z(T) = \sum_{\{s_i\}} e^{-H(\{s_i\})/T}$$

Z, the **partition function**, is the normalisation: a sum over all $2^{L \cdot L}$ configurations.



$2^{L \cdot L}$ terms; H_k is the energy of configuration k.

Solving the model means finding Z, or $\ln Z$, in analytical form as a function of (J, h, T); all equilibrium properties then follow by differentiation.

Observables from the Partition Function

Z gives the physical properties as functions of T $\quad (\beta = 1/T)$

mean energy	$\langle H \rangle = -\dfrac{\partial \ln Z}{\partial \beta}$	average energy of the configurations at T
specific heat	$C = \dfrac{d\langle H \rangle}{dT} = \beta^2 \dfrac{\partial^2 \ln Z}{\partial \beta^2}$	how fast the energy grows with T; proportional to the energy fluctuations
mean magnetisation	$\langle S \rangle = \dfrac{1}{\beta} \dfrac{\partial \ln Z}{\partial h}, \quad S = \sum_i s_i$	net alignment of the spins: $\neq 0$ ordered, 0 disordered
susceptibility	$\chi = \dfrac{d\langle S \rangle}{dh} = \dfrac{1}{\beta} \dfrac{\partial^2 \ln Z}{\partial h^2}$	how strongly the spins follow a small field h; proportional to the magnetisation fluctuations

Onsager's Solution of the Partition Function

Every observable is a derivative of $\ln Z$, but $Z = \sum_{\{s_i\}} e^{-\beta H(\{s_i\})}$ is a sum over 2^N ($N = L^2$ spins) configurations. **Computing $\ln Z$ exactly solves the model.**

Onsager (1944): $\ln Z$ computed exactly for the 2D square lattice, $h = 0$, $N \to \infty$

$$\frac{1}{N}\ln Z = \ln\bigl(2\cosh(2\beta J)\bigr) + \frac{1}{2\pi}\int_0^{\pi} d\phi\, \ln\Bigl[\tfrac{1}{2}\Bigl(1+\sqrt{1-\kappa^2\sin^2\phi}\Bigr)\Bigr], \qquad \kappa = \frac{2\sinh(2\beta J)}{\cosh^2(2\beta J)}$$


- **method:** write $Z = \mathrm{Tr}\, V^L$, with V the $2^L \times 2^L$ *transfer matrix* that adds one row of spins; for a large lattice $\ln Z$ is fixed by the largest eigenvalue of V, and Onsager found all eigenvalues exactly

Onsager's Solution: Critical Temperature and Exponents

- $\kappa = 1$ exactly when $\sinh(2J/T) = 1$: there $\ln Z$ is **not analytic**, so $T_c = \dfrac{2J}{\ln(1+\sqrt{2})} \approx 2.269\,J$ (located already in 1941 by Kramers and Wannier from a low/high-temperature duality)
- near T_c: $C \sim -\ln|T - T_c|$, $\langle M \rangle \sim (T_c - T)^{1/8}$, $\chi \sim |T - T_c|^{-7/4}$, $\xi \sim |T - T_c|^{-1}$: a continuous transition with exponents $\alpha = 0$, $\beta = \frac{1}{8}$, $\gamma = \frac{7}{4}$, $\nu = 1$
- $\langle M \rangle = [1 - \sinh^{-4}(2J/T)]^{1/8}$ was announced by Onsager in 1949 and derived by C. N. Yang in 1952

H. A. Kramers, G. H. Wannier, *Statistics of the Two-Dimensional Ferromagnet. Part I*, Phys. Rev. **60**, 252 (1941), doi:10.1103/PhysRev.60.252; L. Onsager, *Crystal Statistics. I. A Two-Dimensional Model with an Order-Disorder Transition*, Phys. Rev. **65**, 117 (1944), doi:10.1103/PhysRev.65.117; C. N. Yang, *The Spontaneous Magnetization of a Two-Dimensional Ising Model*, Phys. Rev. **85**, 808 (1952), doi:10.1103/PhysRev.85.808

The Phase Transition in Pictures




one sampled configuration at each temperature, 128×128 lattice ($N = 128^2$ spins); white and black: $s_i = +1$ and $s_i = -1$; $|M| = |\frac{1}{N}\sum_i s_i|$

- **below T_c:** the coupling wins over thermal noise; almost all spins point the same way: the lattice is a magnet by itself
- **above T_c:** thermal noise wins; small patches point randomly, $M = 0$
- **at T_c:** clusters of all sizes, from single spins to the whole lattice: *critical behaviour*

In an infinite lattice M drops to zero exactly at T_c: a sharp change of the whole system caused by a small change of temperature.

A Phase Transition at a Critical Temperature

- **1D** (Ising, 1925): no phase transition at any $T > 0$
- **2D**: a phase transition at $T_c \approx 2.269$
- $T < T_c$: spontaneous magnetisation, $\langle M \rangle > 0$ without any external field
- $T > T_c$: $\langle M \rangle = 0$




Monte Carlo averages for $L = 10, 20, 40$ (our data); dashed red: Onsager's solution ($L \to \infty$); dotted: T_c

M is the **order parameter**: a quantity that tells the two phases apart. Near T_c: $M \sim (T_c - T)^{1/8}$, and fluctuations of observables become large.

Sampling Spin Configurations

$2^{L \cdot L}$ configurations are too many to list: Metropolis Monte Carlo draws samples from $p(\{s_i\}) \propto e^{-H/T}$ instead.




50×50 lattice at $T = 1.2,\ 1.9,\ 2.2,\ 2.4,\ 3.2$ (black and white: the two spin values)

Low T: spins aligned. High T: a random pattern.

N. Metropolis, A. W. Rosenbluth, M. N. Rosenbluth, A. H. Teller, E. Teller, *Equation of State Calculations by Fast Computing Machines*, J. Chem. Phys. **21**, 1087 (1953), doi:10.1063/1.1699114


The Dataset



- Metropolis samples: 51 temperatures from 1.0 to 3.5, 200 configurations each, for $L = 10, 20, 40$
- each configuration is a black-and-white $L \times L$ image
- low T: almost all spins aligned; high T: random pattern
- on a small lattice $T = 2.2$ and $T = 2.4$ look alike, but lie on **opposite sides** of $T_c \approx 2.269$


Task: find T_c from the images alone, without being told about the magnetisation.

Supervised Learning Far from the Transition




- **train only where the answer is clear:** $T < 1.5$ ordered, $T > 3$ disordered; configurations in between are left out
- **data:** input X = a spin configuration (an $L \times L$ image), label y = phase
- **predict** at every temperature, also where the network has seen no data, and plot the **confidence**: the softmax probability of the predicted class

The CNN for the Ising Model



- the same building blocks as for CIFAR-10: a spin configuration is a black-and-white image
- two outputs, softmax, categorical cross-entropy, Adam optimiser
- $q_{\text{ordered}} + q_{\text{disordered}} = 1$; the **confidence** is the larger of the two


The Ising CNN: Layers



layer	output	parameters
Conv2d	$32 \times 20 \times 20$	320
MaxPool2d	$32 \times 10 \times 10$	–
Conv2d	$32 \times 10 \times 10$	9 248
MaxPool2d	$32 \times 5 \times 5$	–
Flatten	800	–
Linear	64	51 264
Linear	2	130
total (all trainable)		60 962

lattice $L = 20$ in the notebook; ReLU layers (no parameters) not listed; circular padding: the lattice is periodic

The Confidence Drops at the Critical Temperature



$L = 40$; dots: the confidence of every configuration; line: its average. Lowest average confidence at $T = 2.25$; over three trainings 2.27 ± 0.02, exact $T_c \approx 2.269$.

Near T_c the magnetisation vanishes and fluctuations are large: the two phases are hardest to tell apart.

A First Discovery with a Neural Network

What we gained

- an estimate of T_c from raw configurations, with no formula for the order parameter
- for most physical systems the order parameter is *not known*: the network signals that *something happens* near a given temperature

Limits

- finite lattice: the transition is smoothed, the dip is broadened; larger L gives a sharper estimate
- the labels and the two training windows came from us
- the network does not tell us *why* there is a transition

The network located the phase transition; the physics that explains it is still ours to find.

The Chinese Room Thought Experiment

- a person who does not understand Chinese sits inside a room
- a rulebook (an algorithm) says how to manipulate Chinese characters to answer questions written in Chinese
- to an observer outside, the room understands Chinese: the answers are coherent
- the person understands nothing; they only follow rules



Searle: manipulating symbols (syntax) is not enough for understanding (semantics).

J. R. Searle, *Minds, brains, and programs*, Behav. Brain Sci. **3**, 417 (1980), doi:10.1017/S0140525X00005756

The Chinese Room: Replies

Searle's paper lists replies to the argument and answers them.

- **systems reply:** the person does not understand, but the whole system (person, rulebook, paper) does.
  Searle: let the person memorise the rulebook; they still understand nothing.
- **robot reply:** connect the symbols to the world through cameras and motors, and they acquire meaning.
  Searle: the sensor data are just more symbols for the person in the room.
- **brain simulator reply:** simulate the neurons of a Chinese speaker instead of following a rulebook.
  Searle: simulating the formal structure of the brain still does not give its understanding.

The brain simulator reply is close to what a neural network is; the debate is still open.

J. R. Searle, *Minds, brains, and programs*, Behav. Brain Sci. **3**, 417 (1980), doi:10.1017/S0140525X00005756

The Chinese Room and Deep Learning

- **data manipulation:** a network maps inputs to outputs by learned transformations, as the person in the room follows rules
- **statistical, not semantic:** the network's knowledge is a set of correlations in the data; it does not know what the pixels, words or spins mean
- **subsymbolic:** the room uses explicit rules; a network uses weights and activations learned from data

Back to the Ising model

The CNN located T_c without an explanation: no order parameter, no mechanism of the transition. The understanding (Onsager's solution, the order parameter) remains the scientist's job.

Summary


- **blood cells and satellite images**: models with similar accuracy make different mistakes; the confusion matrix and the class activation map show which
- **transfer learning**: an ImageNet network helps on satellite images with few labels, not on blood cells
- **2D Ising model**: a CNN trained far from the transition locates T_c from spin configurations alone; explaining the transition is still our job (the Chinese room)

Next Lecture: Unsupervised Learning

Most scientific data come without labels: microscope archives, sky surveys, simulations, sequencing data.

Unsupervised learning finds structure in data without labels:

- **dimensionality reduction**: PCA, t-SNE, UMAP
- **clustering**: groups of similar samples, e.g. cell types
- **autoencoders**: compress the data to a few latent variables and reconstruct it
- **anomaly detection**: samples the model cannot reconstruct



Examples: blood-cell images grouped without labels, credit-card fraud and unseen tumour types found as anomalies.

Thank You

Questions, project ideas, feedback: marcin.plodzien@uj.edu.pl

Website · GitHub · Google Scholar



