

# Lecture 12 - Generative Adversarial Networks

Prof. André Gustavo Hochuli

[gustavo.hochuli@pucpr.br](mailto:gustavo.hochuli@pucpr.br)


[aghochuli@ppgia.pucpr.br](mailto:aghochuli@ppgia.pucpr.br)

# Topics

- Review of Lecture 11 – Image Segmentation
  - Object Segmentation (Bounding Box Level)
  - Instance / Semantic Segmentation (Pixel Level)
- Generative Adversarial Networks
  - DCGAN
  - PIX2PIX
- Practice



# Generative Adversarial Networks (GAN's)

- Generator: Noise  $\rightarrow$  Data
- Discriminator: Classification










# Generative Model

- Learns data distribution





# Generative Model



Training



# Deep Generative Model

- De-Convolutional Layers (upsampling)
- Noise to Fake Image




# Discriminator Model

- Classification: Fake or Real
  - CNN




# Adversarial Training

- Adversarial Loss (Min-Max)
  - Minimize Generator
  - Maximize Discriminator




$$\min_G \max_D V(D, G) = \mathbb{E}_{x \sim p_{data}} [\log D(x)] + \mathbb{E}_{z \sim p_z(z)} [\log(1 - D(G(z)))]$$






# Let's Code

- [LINK: Lecture\\_12-DCGAN.ipynb](#)



# Pix2Pix


- Image-Translation



# Pix2Pix

- Generative Model: Encoder-Decoder Architecture (i.e U-Net)
- Paired Annotated Dataset


## Pix2Pix (①+②)



# Let's Code

- [LINK: Lecture\\_12-pix2pix.ipynb](#)

## Pix2Pix (①+②)



# Course Final Remarks

- 12 Lectures / Topics
  - Image Processing
  - Image Classification
    - Feature Extraction
    - Shallow Classification
    - Deep Learning
      - Classification
      - Segmentation
      - GANs
- 04 assessment tasks
  - License Plate Segmentation
  - Simpsons Classification (Shallow Based Models)
  - Simpsons Classification (CNN Based)
  - Simpsons Fake (GANs based)