

The Lain Programming Language

Language Specification

Version 0.1 — Draft

May 13, 2026

Document status: Draft — normative
Language version: Lain 1.0
Date: May 13, 2026

This document is the authoritative specification of the Lain programming language. It defines the syntax, semantics, and constraints that every conforming implementation shall enforce.

Contents

Foreword	v
Introduction	vii
1 Scope	1
1.1 Compilation model	2
2 Normative references	3
3 Terms, definitions, and symbols	5
3.1 General language terms	5
3.2 Type system terms	7
3.3 Ownership and memory terms	8
3.4 Control flow and purity terms	9
3.5 Verification terms	9
3.6 Module and name resolution terms	10
4 Conformance	11
4.1 Conforming implementation	11
4.2 Conforming program	11
4.3 Diagnostic messages	12
4.4 Implementation limits	12
4.5 Safe and unsafe fragments	13
5 Lexical conventions	15
5.1 Source file encoding	15
5.2 Comments	15
5.3 Tokens	15
5.4 Whitespace	16
5.5 Keywords	16
5.6 Identifiers	17
5.7 Literals	18
5.7.1 Integer literals	18
5.7.2 Floating-point literals	18
5.7.3 Boolean literals	18
5.7.4 Character literals	18
5.7.5 String literals	19
5.7.6 Escape sequences	19
5.8 Operators and punctuators	19
5.8.1 Arithmetic operators	20
5.8.2 Comparison operators	20
5.8.3 Logical operators	20
5.8.4 Bitwise operators	20

5.8.5	Assignment operators	20
5.8.6	Other operators and punctuators	21
5.9	Token disambiguation	21
5.10	Integer arithmetic and overflow	22
6	Basic concepts	23
6.1	Declarations and definitions	23
6.2	Scopes	23
6.3	Name resolution	24
6.4	Storage duration	24
6.5	Objects and values	24
6.6	Lvalues and rvalues	24
6.7	Alignment	25
7	Types	27
7.1	Type taxonomy	27
7.2	Primitive types	27
7.2.1	Integer types	27
7.2.2	Integer rank and widening	28
7.2.3	Floating-point types	29
7.2.4	Boolean type	29
7.2.5	The void type	29
7.3	Array types	30
7.4	Slice types	30
7.5	Struct types	30
7.6	Enum types	31
7.7	Algebraic data types (ADTs)	32
7.8	Pointer types	32
7.9	Constrained types	32
7.10	Type compatibility and equivalence	33
8	Expressions	35
8.1	Operator precedence and associativity	35
8.2	Primary expressions	35
8.3	Arithmetic operators	36
8.4	Comparison operators	36
8.5	Logical operators	36
8.6	Bitwise operators	36
8.7	The <code>in</code> operator	37
8.8	Cast expression (<code>as</code>)	37
8.9	Move expression (<code>mov</code>)	38
8.10	Borrow expressions (<code>ref</code> , <code>mut</code>)	38
8.11	Field access	38
8.12	Index expression	38
8.13	Function call	38
8.14	Block expression	39
8.15	If expression	39
8.16	Match expression (<code>case</code>)	39
8.17	Constructor expression	39
8.18	Compound assignment	39
9	Statements	41

9.1	Block statement	41
9.2	Variable declaration statement	41
9.3	Assignment statement	41
9.4	Expression statement	42
9.5	If statement	42
9.6	While statement	42
9.6.1	Bounded while statement	43
9.7	Return statement	43
9.8	Defer statement	44
9.9	Unsafe block	44
9.10	Comptime if statement	44
9.11	For statement	44
10	Declarations	47
10.1	Declaration attributes	47
10.2	Struct declarations	48
10.3	Enum and ADT declarations	48
10.4	Function declarations	48
10.4.1	Parameters	48
10.4.2	Return type annotation	49
10.4.3	Purity constraints	49
10.5	Procedure declarations	49
10.6	Extern declarations	49
10.7	Comptime declarations	50
11	Ownership and linearity	51
11.1	Ownership modes	51
11.2	Linear states	51
11.3	Diagnostics	52
11.4	The read-write lock invariant	52
11.5	Non-lexical lifetimes (NLL)	53
11.6	Two-phase borrows	53
11.7	Move semantics	53
11.8	Borrowed match	53
11.9	Loop and ownership	54
11.10	Branch consistency	54
11.11	Field-level tracking	54
12	Functions and procedures	55
12.1	The func/proc distinction	55
12.2	Purity enforcement	55
12.3	Termination analysis	56
12.4	Universal Function Call Syntax (UFCS)	56
12.5	Calling conventions	57
12.6	Return values	57
12.7	The <code>panic</code> builtin	57
12.8	Function attributes	58
13	Value range constraints	59
13.1	Overview	59
13.2	Range representation	59
13.3	Range propagation rules	59

13.4	Conditional refinement	60
13.5	In-guard semantics	60
13.6	Constraint annotations	60
13.7	Interprocedural range propagation	60
13.8	Limits and known gaps	61
14	Generics and compile-time evaluation	63
14.1	Overview	63
14.2	Type parameters	63
14.3	Compile-time value parameters	63
14.4	Type as value	64
14.5	Monomorphization	64
14.6	Comptime expression blocks	64
14.7	Comptime if	64
14.8	Comptime recursion depth	65
14.9	Mode preservation in generics	65
15	Pattern matching	67
15.1	Overview	67
15.2	Syntax	67
15.3	Patterns	67
15.4	Exhaustiveness	67
15.5	Ownership and match	68
15.6	Case expression result type	68
15.7	String pattern matching	68
16	Module system	71
16.1	Overview	71
16.2	Module declarations	71
16.3	Import declarations	71
16.4	Module loading	71
16.5	Name visibility	72
16.6	Standard library module paths	72
16.7	Name mangling	73
17	C interoperability	75
17.1	Overview	75
17.2	The <code>c_include</code> declaration	75
17.3	Extern function declarations	75
17.4	Type mapping	76
17.5	ABI for function parameters	76
17.6	Pointer operations	77
17.7	String interop	77
17.8	Opaque C types	77
18	Unsafe code	79
18.1	Purpose	79
18.2	Syntax	79
18.3	What unsafe enables	79
18.4	What unsafe does NOT disable	79
18.5	Undefined behavior in unsafe	80
18.6	Borrow scope for unsafe blocks	80

18.7 Nesting	80
19 Memory model	81
19.1 Overview	81
19.2 Objects	81
19.3 Storage duration	81
19.4 Stack allocation	82
19.5 Heap allocation	82
19.6 Value semantics	83
19.7 Object representation	83
19.8 Alignment and layout	83
19.9 ADT and enum layout	84
19.10 No garbage collector	84
19.11 Memory safety in the safe fragment	85
19.12 Compiler-internal arena (informative)	85
20 Standard library	87
20.1 Overview	87
20.2 <code>std.c</code> — C standard library bindings	87
20.2.1 Purpose	87
20.2.2 Required C headers	87
20.2.3 Opaque types	87
20.2.4 Extern declarations	88
20.3 <code>std.io</code> — Console I/O	88
20.3.1 Dependencies	88
20.3.2 <code>print</code>	88
20.3.3 <code>println</code>	88
20.4 <code>std.fs</code> — File system	89
20.4.1 Dependencies	89
20.4.2 Type: <code>File</code>	89
20.4.3 <code>open_file</code>	89
20.4.4 <code>close_file</code>	89
20.4.5 <code>write_file</code>	89
20.5 <code>std.math</code> — Mathematical functions	90
20.5.1 Overview	90
20.5.2 <code>min</code>	90
20.5.3 <code>max</code>	90
20.5.4 <code>abs</code>	90
20.5.5 <code>clamp</code>	91
20.6 Generic types (informative)	91
20.6.1 <code>Option(T)</code>	91
20.6.2 <code>Result(T, E)</code>	91
Grammar summary	93
Diagnostic codes	99
Language design rationale	103
.1 The <code>func/proc</code> distinction	103
.2 Explicit <code>mov</code> at call sites	103
.3 Implicit NLL lifetimes (no annotations)	104
.4 C99 translation output	104

.5	No exception mechanism	104
.6	Explicit unsafe blocks	105
.7	Value Range Analysis instead of SMT	105
.8	Comptime generics instead of <T> syntax	105
.9	Universal Function Call Syntax (UFCS)	105
.10	Bounded while in func	106
Comparison with related languages		107
.11	Feature matrix	107
.12	Lain versus Rust	107
.13	Lain versus C	108
.14	Lain versus Zig	109
.15	Lain versus Go	109
.16	Features unique to Lain	110
Index		111

Foreword

This document specifies the Lain programming language, Version 1.0.

Lain is a statically-typed, compiled programming language for systems programming. It guarantees memory safety, type safety, and resource safety entirely at compile time with zero runtime overhead.

This specification is structured analogously to ISO/IEC 9899 (the C standard). Clauses 1 through 4 are administrative; Clauses 5 through 20 are normative. Annexes A and B are normative; Annexes C and D are informative.

Text marked **Constraint** describes a condition whose violation requires an implementation to issue a diagnostic message. Text marked *implementation-defined*¹ denotes behavior that is valid but whose exact result is determined by the implementation and shall be documented by it. Text marked **undefined behavior**² denotes a situation for which this specification imposes no requirements.

Note

Undefined behavior in Lain can arise only inside **unsafe** blocks or through direct C interoperability. All code in the safe fragment of Lain has defined behavior.

¹Implementation-defined behavior:

²Undefined behavior:

Introduction

Design philosophy

Lain is built on five foundational pillars:

- P1 — Assembly-Speed Performance** Every language feature compiles to C code that is equivalent in performance to hand-written C. There are no hidden allocations, no garbage collector, and no reference-counting overhead.
- P2 — Zero-Cost Memory Safety** Memory safety is enforced entirely at compile time through a linear type system, a borrow checker, and value range analysis. A conforming implementation that rejects all constraint violations guarantees, for safe programs, the absence of use-after-free, double-free, null dereference, and buffer overflow at runtime.
- P3 — Static Verification** The verification properties required by this specification are decidable and polynomial in program size. No SMT solver or unbounded fixpoint iteration is required.
- P4 — Determinism** Pure functions (`func`) are referentially transparent and guaranteed to terminate. The same inputs always produce the same outputs.
- P5 — Syntactic Simplicity** Lain has no implicit copies, no hidden conversions (beyond the defined integer-widening rules), and no magic methods. Ownership is always explicit.

Relationship to C

Lain compiles to C99. The C code generated by a conforming Lain implementation is the *translation output*; this specification does not prescribe the form of that output beyond the observable behavior of the resulting program.

How to read this specification

Each normative clause is structured as follows: a prose description of the syntax (with a reference to the formal grammar in Annex A), followed by the semantics, followed by **Constraint** blocks listing every condition that requires a diagnostic message. Non-normative **Note** and **Example** environments appear throughout to aid understanding.

Chapter 1

Scope

- 1 This document specifies the Lain programming language. It defines the syntax, the semantic rules, and the constraints that every conforming Lain implementation shall enforce. It serves as the single authoritative reference for language users and implementors alike.
- 2 Lain is a statically-typed, compiled programming language designed for systems programming, embedded systems, and safety-critical software. It achieves memory safety, type safety, and resource safety entirely at compile time with zero runtime overhead.
- 3 This specification covers:
 - lexical structure and grammar (§ ??);
 - type system and type inference (§ ??);
 - variable declarations, scoping, and initialization (§ ??, § ??);
 - expressions, operators, and evaluation order (§ ??);
 - statements and control flow (§ ??);
 - functions, procedures, and purity (§ ??);
 - ownership, borrowing, and the linear type system (§ ??);
 - value range constraints and static verification (§ ??);
 - compile-time evaluation and generics (§ ??);
 - pattern matching and exhaustiveness checking (§ ??);
 - module system (§ ??);
 - C interoperability (§ ??);
 - unsafe code boundaries (§ ??);
 - memory model (§ ??);
 - diagnostic messages (Annex B);
 - standard library (§ ??).
- 4 This specification does *not* cover:
 - the internal architecture of any particular compiler implementation;
 - build system integration or tooling;
 - IDE or editor support;
 - operating system interfaces beyond what the standard library provides.

1.1 Compilation model

- 1 Lain uses a source-to-C transpilation model. A Lain source file (extension `.ln`) is processed by a conforming implementation to produce C99 source code, which is subsequently compiled by a C99 compiler to produce an executable. The observable behavior of the program is defined by this specification; the form of the intermediate C99 code is *implementation-defined*¹.
- 2 A conforming implementation shall perform the following translation phases in the following order:
 1. **Lexical analysis** — source text is converted to a token stream as described in §??.
 2. **Parsing** — the token stream is reduced to an abstract syntax tree according to the grammar in Annex A.
 3. **Name resolution** — identifiers are resolved to declarations as described in §??.
 4. **Type checking** — types are inferred and verified as described in §?? through §??.
 5. **Exhaustiveness checking** — pattern matching completeness is verified as described in §??.
 6. **Use analysis (NLL)** — last-use points are computed for all variables.
 7. **Linearity and borrow checking** — ownership and borrowing rules are verified as described in §??.
 8. **Value range analysis** — bounds safety and numeric constraints are verified as described in §??.
 9. **Code emission** — well-formed programs are translated to C99.
- 3 A program that completes all phases without a diagnostic message is **well-formed** and its translation output is defined.

Note

Phases 3–8 collectively form *semantic analysis*. An implementation may interleave these phases as long as the observable behavior is equivalent to executing them in the order listed.

¹Implementation-defined behavior: the generated C99 code need not be human-readable

Chapter 2

Normative references

- ¹ The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies.

ISO/IEC 9899:2018 (C17)

Information technology — Programming languages — C.

International Organization for Standardization, Geneva, 2018.

Referenced for: C99/C17 calling conventions (§??), standard integer types and their representations (§??), and undefined behavior categories (§??).

IEC 60559:2020 (IEEE 754-2019)

Floating-point arithmetic.

International Electrotechnical Commission, Geneva, 2020.

Referenced for: semantics of `f32` and `f64` arithmetic (§??).

- ² The following documents are informative references. They are not required for conformance but provide useful background.

ISO/IEC 14882:2020 (C++20)

Programming languages — C++.

Referenced for: vocabulary and structure conventions used in this document.

The Rust Reference

The Rust Reference, <https://doc.rust-lang.org/reference/>.

Referenced for: linear type and ownership terminology.

Chapter 3

Terms, definitions, and symbols

- ¹ For the purposes of this document, the following terms and definitions apply. Terms defined here are used with these precise meanings throughout all normative clauses. Where a term is used in its ordinary English sense rather than as a defined term, it appears without emphasis.

Note

Cross-references of the form (*see §N*) point to the clause where the concept is treated normatively.

3.1 General language terms

abstract syntax tree (AST)

The in-memory tree representation of a Lain program produced by the parser and consumed by semantic analysis.

behavior

External appearance or action of a program as observed by a user or another program. See also: *defined behavior*, *implementation-defined behavior*, *unspecified behavior*, *undefined behavior*.

conforming implementation

An implementation that correctly processes all programs that satisfy the rules of this specification and issues a diagnostic message for every program that violates a **Constraint** (see §??).

conforming program

A program that uses only the syntax and semantics defined in this specification, does not rely on undefined behavior, and does not depend on implementation-defined extensions.

constraint

A requirement imposed on the source text. If a program violates a constraint, the implementation *shall* emit a diagnostic message. Constraints appear in **Constraint** environments throughout this specification.

defined behavior

Behavior that is fully and precisely specified by this document for every conforming program. Contrast with *undefined behavior* and *implementation-defined behavior*.

diagnostic message

A human-readable message issued by the implementation to report a constraint violation. Every diagnostic shall include a source location (file name, line number) and an error code of the form [EXXX] or [VRA] (see Annex B).

ill-formed program

A program that violates one or more of the syntactic or semantic rules of this specification. An ill-formed program is not a conforming program and a conforming implementation shall reject it with a diagnostic.

implementation

The system (compiler, linker, runtime) that translates a Lain source program into an executable. The reference implementation is the *lain* compiler.

implementation-defined behavior

Behavior that is valid but not fully specified by this document; the implementation shall determine the exact behavior and document it.

program

A collection of one or more Lain source files (`.ln`) that together constitute a translation unit or a set of modules.

source file

A UTF-8 encoded text file with the extension `.ln` containing Lain source text.

translation output

The C99 source code emitted by a conforming implementation for a well-formed Lain program.

undefined behavior

Behavior for which this specification imposes no requirements. A program that exhibits undefined behavior is erroneous. In the safe fragment of Lain, no operation produces undefined behavior. Undefined behavior may arise only inside `unsafe` blocks or through direct C interoperability.

unspecified behavior

Behavior for which this specification provides two or more possibilities without prescribing which shall occur. A conforming program shall not depend on unspecified behavior.

well-formed program

A program that satisfies all syntactic and semantic rules of this specification and is therefore accepted by a conforming implementation without diagnostic.

3.2 Type system terms

algebraic data type (ADT)

A composite type that is either a product type (*struct*) or a sum type (*enum*).

constrained type

A type annotated with a value range constraint of the form $T \text{ op bound}$, e.g. `int >= 0` (see §??).

integer rank

A total ordering on integer types that determines the result type of mixed-type arithmetic. The rank system is defined in §??.

integer widening

An implicit conversion from an integer type of lower rank to one of higher rank, permitted in arithmetic and assignment contexts (see §??).

linear type

A type whose values must be used exactly once. Struct types and resource types are linear. Primitive types (`int`, `bool`, etc.) are unrestricted (see §??).

nominal type

A type identified by its declared name rather than its structure.

ownership mode

An annotation on a variable or parameter that specifies the kind of access the holder has: `shared` (read-only), `var` (read-write), or `owned` (no annotation on a linear type, transferred with `mov`) (see §??).

primitive type

One of the built-in types: `int`, `u8`, `u16`, `u32`, `u64`, `usize`, `i8`, `i16`, `i32`, `i64`, `isize`, `f32`, `f64`, `bool`. Primitive types are unrestricted (non-linear).

structural type equivalence

Two types are structurally equivalent if they have the same structure. Lain uses nominal equivalence for user-defined types; the name is part of the type identity.

unrestricted type

A type whose values may be used any number of times without explicit consumption. All primitive types are unrestricted. Contrast with *linear type*.

3.3 Ownership and memory terms

active borrow

A borrow that is currently in the ACTIVE phase; its subject cannot be moved or mutated while the borrow is active (see § ??).

arena

A memory allocation strategy in which all allocations are made from a contiguous block; the entire block is freed at once. Lain’s compiler allocates all AST nodes from arenas.

borrow

A temporary access to a value without taking ownership. A shared borrow grants read-only access; a mutable borrow grants read-write access (see § ??).

borrow phase

Either RESERVED (the borrow has been registered but is not yet active, during argument evaluation) or ACTIVE (the borrow is in force) (see § ??).

consumed variable

A linear variable whose ownership has been transferred (via `mov`). Reading or transferring a consumed variable is a constraint violation.

linear state

The tracking state of a linear variable: one of *Uninit*, *Unconsumed*, or *Consumed* (see § ??).

move

The transfer of ownership of a value from one variable or storage location to another, performed by the `mov` operator. After a move, the source is in the Consumed state.

non-lexical lifetime (NLL)

A lifetime that ends at the variable’s *last use* rather than at the end of its lexical scope. Lain uses NLL to minimize the duration of borrows (see § ??).

read-write lock invariant

The aliasing invariant: at any program point, for any owned value, there exist either N shared borrows ($N \geq 0$) and no mutable borrow, or exactly one mutable borrow and no shared borrows (see § ??).

resource

A value that represents an external entity (file handle, socket, etc.) whose lifetime must be explicitly managed. Resources are modelled as linear types.

two-phase borrow

A borrow that begins in the RESERVED phase during argument evaluation and is promoted to ACTIVE after the call expression is complete (see § ??).

3.4 Control flow and purity terms

decreasing measure

An expression in a **while decreasing** statement that the implementation shall verify is non-negative when the loop condition holds and strictly decreases on every iteration (see § ??).

func

A pure, terminating function. A **func** shall not call a **proc** or contain an unbounded **while** loop (see § ??).

purity

The property of a **func**: its result depends only on its inputs and it has no observable side effects on any state outside its own stack frame.

proc

A procedure that may have side effects. A **proc** may call other **procs**, perform I/O, and contain unbounded **while** loops (see § ??).

termination

The property that a function always reaches a **return** statement in a finite number of steps. All **funcs** shall be verified to terminate by the implementation (see § ??).

3.5 Verification terms

bounds check

A runtime test that verifies an array index is within the valid range $[0, N-1]$. A conforming implementation shall eliminate bounds checks when VRA can statically prove the index is in range.

comptime

Compile-time evaluation. A **comptime** expression or function is evaluated by the compiler at compile time rather than at runtime (see § ??).

exhaustiveness

The property of a **case** expression in which every possible value of the scrutinee type is covered by at least one arm (see § ??).

in guard

A use of the **in** operator as a loop or conditional guard. An in guard of the form `idx in arr` proves to the VRA that $idx \in [0, arr.len-1]$ in the guarded body (see § ??, § ??).

interval

A pair $[\ell, u]$ representing the set of integers $\{x \mid \ell \leq x \leq u\}$. VRA represents value ranges as intervals with $-\infty$ and $+\infty$ sentinels.

monomorphization

The process by which a generic function is instantiated for each concrete set of type arguments, producing a separate, non-generic translation for each instantiation (see § ??).

return constraint

A value range constraint on the return value of a function, declared in the function signature as *T op bound* (see § ??).

value range analysis (VRA)

A static analysis that tracks integer value ranges through the program using interval arithmetic, used to eliminate bounds checks and prove constraint satisfaction (see § ??).

3.6 Module and name resolution terms

import

A directive (`import module.path`) that makes the names defined in another module available in the current module (see § ??).

module

The unit of compilation in Lain. Each source file defines one module.

qualified name

A name of the form *module.identifier* that refers to a declaration in a specific module (see § ??).

Universal Function Call Syntax (UFCS)

A syntactic sugar by which `x.f(args)` is desugared to `f(x, args)` before name resolution. UFCS allows methods to be defined as free functions (see § ??).

Chapter 4

Conformance

4.1 Conforming implementation

- ¹ A **conforming implementation** shall:
 1. accept, without diagnostic, every *conforming program*;
 2. reject, with at least one diagnostic message, every program that violates any constraint stated in this specification;
 3. translate accepted programs such that their observable behavior conforms to the semantic rules stated in this specification;
 4. implement all features described as normative in Clauses 5 through 20;
 5. document every behavior described in this specification as *implementation-defined*¹.
- ² A conforming implementation may:
 1. issue additional diagnostic messages (warnings) beyond those required by this specification, provided they do not cause a conforming program to be rejected;
 2. accept programs through implementation-defined extensions, provided those extensions are documented and do not alter the semantics of any conforming program;
 3. omit runtime bounds checks when value range analysis (§??) proves the access is within bounds.

Note

The reference implementation of Lain (*lain* compiler, version corresponding to this specification) is a conforming implementation. Where this specification marks a behavior as implementation-defined, the reference implementation's documented behavior takes precedence for programs compiled by that implementation.

4.2 Conforming program

- ¹ A **conforming program** is a program that:
 1. consists only of syntax and semantics defined in this specification;
 2. does not rely on undefined behavior;

¹Implementation-defined behavior: the exact value or behavior is implementation-defined

3. does not rely on unspecified behavior to produce a specific outcome;
 4. does not depend on any implementation-defined extension.
- 2 A **strictly conforming program** additionally:
1. does not use any behavior documented as implementation-defined, even when that behavior is deterministic on a given implementation.

4.3 Diagnostic messages

- 1 A diagnostic message issued for a constraint violation shall include:
1. the source file name;
 2. the line number of the offending construct;
 3. the diagnostic code in the form [E`XXX`] (see Annex B);
 4. a human-readable description of the violation.
- 2 A conforming implementation may issue additional diagnostic information (column number, source context, suggested fix) beyond the minimum required by § ??.

Note

The reference implementation additionally prints the source line and a caret (^) pointing to the column of the offending token.

4.4 Implementation limits

- 1 A conforming implementation shall support at least the following minimum translation limits. Programs that require more than these limits invoke *implementation-defined*².

Resource	Minimum	Clause
Identifier length (bytes)	255	§ ??
Block nesting depth	64	§ ??
Function parameters	127	§ ??
Array elements	$2^{31} - 1$	§ ??
Module import depth	32	§ ??
<code>case</code> arms per match expression	256	§ ??
Struct fields	256	§ ??
Enum variants	256	§ ??
Comptime evaluation depth	256	§ ??
Scope nesting depth	64	§ ??

²Implementation-defined behavior: the behavior when a translation limit is exceeded

4.5 Safe and unsafe fragments

- 1 The **safe fragment** of a Lain program consists of all code that does not appear inside an **unsafe** block and does not use raw pointer operations.
- 2 A conforming implementation shall guarantee, for any well-formed program in the safe fragment, that execution produces no:
 - use of a variable after its ownership has been transferred (use-after-move);
 - double transfer of ownership of the same value;
 - access to an uninitialized variable;
 - violation of the read-write lock invariant (§ ??);
 - buffer overrun that has been statically proven safe by value range analysis.
- 3 The **unsafe fragment** comprises all code inside **unsafe** blocks. Within the unsafe fragment, the programmer is responsible for upholding the memory safety invariants listed in § ??; the implementation shall not be required to verify them.

Constraint

The constraints of the ownership and linearity system (§ ??) are *not* suspended inside **unsafe** blocks. Only raw pointer operations and the bounds-check requirement are relaxed. An implementation shall continue to enforce [E001]–[E005] inside **unsafe** blocks.

Chapter 5

Lexical conventions

- 1 A Lain source file is translated in two conceptual steps: (1) the source text is decomposed into tokens as described in this clause; (2) the token stream is parsed into an abstract syntax tree according to the grammar. Implementation may combine these steps.

5.1 Source file encoding

- 1 A Lain source file shall be a sequence of bytes encoded in UTF-8 (Unicode Standard, Annex D). The byte order mark (U+FEFF) shall not appear in a source file. If it does, behavior is *implementation-defined*¹.
- 2 Multi-byte UTF-8 sequences are permitted inside string literals and comments but shall not appear in identifiers. Identifiers shall consist solely of ASCII characters (see § ??).
- 3 Line endings are normalized: a carriage return (U+000D) followed immediately by a line feed (U+000A) is treated as a single line feed. A lone carriage return is treated as a line feed.

5.2 Comments

- 1 A *line comment* begins with `//` and extends to the first following line feed character. The line feed is not part of the comment.
- 2 A *block comment* begins with `/*` and ends with the nearest following `*/`. Block comments may be nested: each opening `/*` inside a block comment opens a new nesting level requiring its own closing `*/`.
- 3 Comments are stripped during lexical analysis and have no effect on the semantics of the enclosing program.

Constraint

An unterminated block comment (one for which no matching `*/` is found before the end of the source file) is *ill-formed* ([E100]).

5.3 Tokens

- 1 The result of lexical analysis is a sequence of tokens. Whitespace and comments serve solely to separate tokens. The grammar production for *token* is given in Annex A (§ ??).
- 2 Where the token stream is ambiguous, the lexer shall apply the *maximal munch* rule: at each position, the longest sequence of characters that forms a valid token is consumed.

Example

```
1 | ..= // one token: range-inclusive, NOT '.' followed by '.='
```

¹Implementation-defined behavior: whether a leading BOM is silently skipped or causes a diagnostic

```
2 >= // one token: greater-than-or-equal, NOT '>' followed by
   ' = '

```

- 3 Keywords (§??) take priority over identifiers: the character sequence **func** at a point where an identifier is expected is always the keyword **func**.

5.4 Whitespace

- 1 The whitespace characters are: space (U+0020) and horizontal tab (U+0009). They serve only to separate adjacent tokens.
- 2 Line feeds (U+000A), after normalization (§??), are significant: they act as statement terminators in contexts where a statement may follow (see §??). Multiple consecutive line feeds are treated as a single statement boundary.

Constraint

A semicolon (;) shall not appear in a Lain source file. If one is present, the implementation shall emit [E100].

Rationale

Newlines as statement terminators eliminate the class of bugs caused by missing or accidental semicolons. They also prevent multi-statement lines, keeping statement boundaries unambiguous.

5.5 Keywords

- 1 The following identifiers are reserved as keywords. They shall not be used as user-defined identifiers. The grammar production is *keyword* (Annex A).

	Keyword	Purpose	Clause
	and	Logical AND operator	§??
	as	Type cast	§??
	case	Pattern matching	§??
	comptime	Compile-time evaluation	§??
	decreasing	Bounded-loop termination measure	§??
	defer	Deferred execution	§??
	else	Alternative branch	§??
	false	Boolean literal	§??
	for	Range-based iteration	§??
	func	Pure function declaration	§??
	if	Conditional	§??
	import	Module import	§??
	in	Range iteration / bounds guard	§??
	module	Module declaration	§??
	mov	Ownership transfer	§??
	mut	Mutable borrow expression	§??
	not	Logical NOT	§??

(continued)

	Keyword	Purpose	Clause
	or	Logical OR operator	§ ??
	panic	Abort with diagnostic message	§ ??
	proc	Procedure declaration	§ ??
	ref	Shared borrow expression	§ ??
	return	Return statement	§ ??
	struct	Struct type declaration	§ ??
	enum	Enum type declaration	§ ??
	true	Boolean literal	§ ??
	type	Type alias / type parameter	§ ??
	unsafe	Unsafe block	§ ??
	var	Mutable binding / mutable borrow	§ ??
	while	Loop statement	§ ??

- 2 The following identifiers are *reserved keywords*: they are recognized by the lexer but have no current semantics. They are reserved for future use.

Reserved keyword	Intended future purpose
end	Block terminator
extern	C interoperability declarations

Constraint

An identifier that is identical to a keyword or reserved keyword shall not be used in any context that requires an identifier. Such use is *ill-formed* ([E100]).

5.6 Identifiers

- 1 An identifier consists of ASCII letters, decimal digits, and underscores, and shall begin with a letter or underscore. The grammar production is *identifier* (Annex A).
- 2 Identifiers are case-sensitive: `foo`, `Foo`, and `F00` are three distinct identifiers.
- 3 A conforming implementation shall support identifiers of at least 255 characters. The behavior when an identifier exceeds this length is *implementation-defined*².

Constraint

An identifier shall not be identical to a keyword (§ ??).

Constraint

An identifier shall begin with a letter or underscore, not a digit. A sequence of characters that begins with a digit is an integer literal (§ ??), not an identifier.

²Implementation-defined behavior: whether oversized identifiers are truncated or cause a diagnostic

5.7 Literals

5.7.1 Integer literals

- 1 An integer literal denotes a constant integer value. Four notations are supported (grammar: *integer-literal*):

Notation	Prefix	Example
Decimal	(none)	42, 1_000_000
Hexadecimal	0x	0xFF, 0x1A_3B
Binary	0b	0b1010_0101
Octal	0o	0o755

- 2 An underscore (`_`) may appear between any two digits of an integer literal as a visual separator. It has no effect on the value.
- 3 The type of an integer literal is inferred from context (see §??). In the absence of type context, the default type is `int`.

Constraint

An integer literal whose value does not fit in the type determined by context is *ill-formed* ([E100]).

Example

```

1 var a = 255           // int, value 255
2 var b u8 = 255        // u8, value 255 -- OK
3 var c u8 = 256        // [E100]: 256 does not fit in u8
4 var d = 0xFF          // int, value 255
5 var e = 0b1111_0000    // int, value 240
6 var f = 1_000_000      // int, value 1000000

```

5.7.2 Floating-point literals

- 4 A floating-point literal consists of a decimal integer part, a decimal point, and a fractional part. An optional exponent part `eN` or `EN` may follow (grammar: *float-literal*).
- 5 The default type of a floating-point literal is `f64`.

Example

```

1 var x = 3.14          // f64
2 var y f32 = 1.0       // f32
3 var z = 2.5e3          // f64, value 2500.0

```

5.7.3 Boolean literals

- 6 The boolean literals are `true` and `false` (grammar: *bool-literal*). Both have type `bool`.

5.7.4 Character literals

- 7 A character literal is a single byte value enclosed in single quotes. It has type `u8`. Escape sequences (§??) are permitted.

Example

```

1 var a = 'A'      // u8, value 65
2 var n = '\n'     // u8, value 10
3 var z = '\0'     // u8, value 0

```

Constraint

A character literal shall contain exactly one character or one escape sequence. An empty or multi-character character literal is *ill-formed* ([E100]).

5.7.5 String literals

- 8 A string literal is a sequence of zero or more characters enclosed in double quotes. Escape sequences (§??) are permitted (grammar: *string-literal*).
- 9 The type of a string literal of N visible characters is `Fixed_u8_N+1` (an array of $N+1$ bytes, null-terminated). This type is implicitly coercible to `[u8]` (a byte slice).
- 10 The `.len` property of a string literal value equals N (excluding the null terminator).

Example

```

1 var s = "hello"   // type: Fixed_u8_6 (5 chars + null)
2                  // s.len == 5

```

- 11 String literals are stored in the read-only data segment of the translation output. Modifying a string literal through a pointer is **undefined behavior**³.

5.7.6 Escape sequences

- 12 The following escape sequences are recognized in string and character literals:

Escape	Byte value	Description
<code>\n</code>	0x0A	Line feed (newline)
<code>\t</code>	0x09	Horizontal tab
<code>\r</code>	0x0D	Carriage return
<code>\0</code>	0x00	Null byte
<code>\\</code>	0x5C	Backslash
<code>\"</code>	0x22	Double quote
<code>\'</code>	0x27	Single quote

Constraint

A backslash not followed by one of the characters in the table above is an unrecognized escape sequence and is *ill-formed* ([E100]).

5.8 Operators and punctuators

- 1 The complete set of operator and punctuator tokens is listed below. The grammar productions *operator* and *punctuator* are in Annex A.

³Undefined behavior: the result of writing through a pointer derived from a string literal

5.8.1 Arithmetic operators

	Token	Meaning
+		Addition; unary identity
-		Subtraction; unary negation
*		Multiplication
/		Division
%		Modulo (remainder)

5.8.2 Comparison operators

	Token	Meaning
==		Equal
!=		Not equal
<		Less than
>		Greater than
<=		Less than or equal
>=		Greater than or equal

5.8.3 Logical operators

	Token	Meaning
and		Logical AND (short-circuit)
or		Logical OR (short-circuit)
not		Logical NOT (prefix)
!		Logical NOT (alternate prefix form)

5.8.4 Bitwise operators

	Token	Meaning
&		Bitwise AND
		Bitwise OR
^		Bitwise XOR
«		Left shift
»		Right shift

5.8.5 Assignment operators

Token	Meaning
=	Assignment
+=	Add and assign
-=	Subtract and assign
*=	Multiply and assign
/=	Divide and assign
%=	Modulo and assign
&=	Bitwise AND and assign
=	Bitwise OR and assign
^=	Bitwise XOR and assign
<<=	Left shift and assign
>>=	Right shift and assign

5.8.6 Other operators and punctuators

Token	Meaning
.	Member access; module path separator
..	Exclusive range (half-open interval)
->	Function return type separator
(	Open parenthesis
)	Close parenthesis
{	Open brace
}	Close brace
[	Open bracket
]	Close bracket
,	List separator
:	Type annotation; match arm separator

- ² Attributes use bracket syntax **[name]** or **[name(args)]** before a declaration (§??). The brackets [and] listed above serve both as array/slice subscripts and as attribute delimiters; the context (declaration position vs. expression position) determines the role.

5.9 Token disambiguation

- ¹ Several token sequences have context-dependent meaning that is resolved by the parser, not the lexer. The lexer produces the same token regardless of context:

Symbol	Context 1	Context 2
*	Multiplication (binary)	(future: pointer dereference)
-	Subtraction (binary)	Negation (unary prefix)
.	Member access	Module path separator
&	Borrowed match prefix	Bitwise AND

5.10 Integer arithmetic and overflow

- 1 Integer arithmetic in Lain uses two's complement representation for all signed integer types. Overflow wraps modulo 2^N where N is the bit width of the type.
- 2 Unsigned integer arithmetic is modular (wrapping) by definition.
- 3 A conforming implementation that emits C99 shall compile the translation output with `-fwrapv` or equivalent, ensuring that signed integer overflow is two's complement wrapping and not undefined behavior in the C sense.

Note

This differs from ISO C, where signed integer overflow is undefined behavior. In Lain, signed overflow is defined as wrapping. Programs that rely on wrapping behavior are well-formed.

Note

Forward-looking, version 1.0. In the upcoming Paradigm B integer system (§ ??), plain arithmetic operators (+, -, *, /) on values whose static range is not provably overflow-free become ill-formed. Explicit operators are introduced for the cases where overflow is intended: `+%`, `-%`, `.*%` (wrapping) and `+|`, `-|`, `*|` (saturating). The wrapping semantics described above remain available through these explicit operators.

Chapter 6

Basic concepts

6.1 Declarations and definitions

- 1 A *declaration* introduces a name into a scope and associates it with an entity: a variable, function, procedure, type, or module. Every name shall be declared before it is used, with the exception of names that are resolved by Universal Function Call Syntax (§ ??).
- 2 A *definition* is a declaration that also allocates storage (for variables) or provides a body (for functions and procedures). In Lain, every declaration at the local level is also a definition.

Constraint

Use of an undeclared identifier is *ill-formed* ([E013]).

Example

```
1 func f() int {  
2     return x    // [E013]: x is not declared  
3 }
```

6.2 Scopes

- 1 A *scope* is a region of program text within which a declared name can be used. Lain has the following scope levels:

Module scope Names declared at the top level of a source file are in module scope. Module-scope names are accessible throughout the module and, by default, accessible from other modules that import this module.

Function/procedure scope Parameter names are in the scope of the function or procedure body.

Block scope Names declared inside a block (`{ }`) are in the scope of that block. They are not accessible outside the enclosing block.

- 2 Scopes are *lexically nested*. A name in an inner scope may *shadow* a name in an outer scope: within the inner scope, the inner name takes precedence.

Note

Shadowing is permitted but the reference implementation may issue a warning. Programs shall not rely on shadowing being silent.

- 3 A conforming implementation shall support at least 64 levels of nested block scope (§ ??).

6.3 Name resolution

- 1 Name resolution maps an identifier in source text to its declaration. The lookup algorithm is:
 1. Search the innermost block scope.
 2. If not found, search progressively wider enclosing block scopes.
 3. If not found, search the function/procedure scope (parameters).
 4. If not found, search the module scope.
 5. If not found, search imported module scopes (in import order).
 6. If not found, attempt UFCS resolution (§??).
 7. If still not found, the program is *ill-formed* ([E013]).
- 2 When the same name is visible in multiple scopes, the innermost binding takes precedence (shadowing).

6.4 Storage duration

- 1 Every object has a *storage duration* that determines the lifetime of its storage.

Automatic storage duration Variables declared inside a block or function body. Storage is allocated on entry to the block and deallocated on exit.

Static storage duration Variables declared at module scope. Storage persists for the lifetime of the program. *implementation-defined*¹.

Arena storage duration Objects allocated from an explicit **Arena**. Storage persists until the arena is freed as a whole.

6.5 Objects and values

- 1 An *object* is a region of storage interpreted according to a type. Every declared variable corresponds to an object.
- 2 Every variable has:
 - a *declared type* (§??);
 - an *ownership mode*: owned (default for linear types), **shared** (read-only reference), or **var** (mutable reference) (§??);
 - a *linear state*: Uninit, Unconsumed, or Consumed (for linear types only) (§??).

6.6 Lvalues and rvalues

- 1 An *lvalue* is an expression that designates an object with a persistent storage location: a variable identifier, a field access on an lvalue, or an array index expression on an lvalue.
- 2 An *rvalue* is an expression whose value has no persistent storage location: literals, the result of arithmetic operations, or the result of a function call.
- 3 Assignment requires the left-hand side to be an lvalue.

¹Implementation-defined behavior: whether module-scope variables are zero- initialized before **proc main** is called

Constraint

An assignment whose left-hand side is an rvalue is *ill-formed* ([E100]).

6.7 Alignment

- ¹ Every type has a required alignment. The alignment of a type is *implementation-defined*². Struct layout follows C99 struct layout rules, including padding (§??).
- ² Stack-allocated variables are aligned to their type's required alignment. The implementation shall not insert additional padding between local variables unless required by the hardware.

²Implementation-defined behavior: the same as the alignment of the corresponding C99 type

Chapter 7

Types

- 1 Lain is statically typed. Every variable, expression, and parameter has a type determined at compile time. There is no runtime type information (RTTI). The grammar productions for types are in Annex A (*type*).

7.1 Type taxonomy

- 1 The types of Lain are organized as follows:
 - *Primitive types*: integer, floating-point, boolean, void (§??);
 - *Array types*: fixed-size, compile-time-sized (§??);
 - *Slice types*: dynamically-sized views into contiguous memory (§??);
 - *Struct types*: named product types (§??);
 - *Enum types*: simple enumerations (§??);
 - *ADT types*: sum types with associated data (§??);
 - *Pointer types*: raw memory addresses, unsafe only (§??);
 - *Constrained types*: types with value range annotations (§??).
- 2 Types are classified as *linear* or *unrestricted*. Linear types must be consumed exactly once (see §??). Unrestricted types may be used any number of times.
- 3 All primitive types are unrestricted. A struct type is linear if and only if at least one of its fields is of a linear type. This property is transitive.

7.2 Primitive types

7.2.1 Integer types

- 1 The integer types are listed below. Sizes marked (*platform*) are *implementation-defined*¹.

	Type	Signedness	Bit width	Range	C99 type
	u8	unsigned	8	$[0, 2^8 - 1]$	uint8_t
	u16	unsigned	16	$[0, 2^{16} - 1]$	uint16_t
	u32	unsigned	32	$[0, 2^{32} - 1]$	uint32_t

¹Implementation-defined behavior: determined by the target platform as in the C99 standard

(continued)

	Type	Signedness	Bit width	Range	C99 type
<code>u64</code>	unsigned	64		$[0, 2^{64} - 1]$	<code>uint64_t</code>
<code>usize</code>	unsigned	(platform)		$[0, 2^N - 1]$	<code>size_t</code>
<code>i8</code>	signed	8		$[-2^7, 2^7 - 1]$	<code>int8_t</code>
<code>i16</code>	signed	16		$[-2^{15}, 2^{15} - 1]$	<code>int16_t</code>
<code>i32</code>	signed	32		$[-2^{31}, 2^{31} - 1]$	<code>int32_t</code>
<code>i64</code>	signed	64		$[-2^{63}, 2^{63} - 1]$	<code>int64_t</code>
<code>isize</code>	signed	(platform)		$[-2^{N-1}, 2^{N-1} - 1]$	<code>ptrdiff_t</code>
<code>int</code>	signed	≥ 32	(platform)		<code>int</code>

- 2 `int` is the default integer type; it corresponds to C's `int` and is at least 32 bits wide. Its exact width is *implementation-defined*².

Note

Forward-looking, version 1.0 — Q-002. In Paradigm B (the planned integer system for version 1.0), `int` becomes a *logical, unsized* type that is monomorphized at each call site. When called with an argument of concrete type `i32`, `int` resolves to `i32` in that instance; when called with `i64`, to `i64`. The default concrete type when no context binds `int` is `i32`. Generalized integer types `iN` and `uN` for any $N \in [1, 64]$ are also introduced.

- 3 `usize` and `isize` are the platform-native unsigned and signed integer types whose width equals the pointer width. Their exact width is *implementation-defined*³.

7.2.2 Hardware-aligned vs logical integer types

- 4 The `iN/uN` types fall into two semantic categories:

Hardware-aligned ($N \in \{1, 2, 4, 8, 16, 32, 64\}$, with the common subset being $\{8, 16, 32, 64\}$): these correspond to fundamental C99 `stdint` widths (`uint8_t`, `int32_t`, etc.). They are the canonical choice for C interop and for any context where exact storage size matters at the byte boundary.

Logical (other N): these are *bit-width quantities*. Their semantics are context-dependent:

- **Standalone:** storage uses the smallest hardware-aligned container fitting N bits (e.g., `u12` maps to `uint16_t`). The natural range is $[-2^{N-1}, 2^{N-1} - 1]$ signed or $[0, 2^N - 1]$ unsigned.
- **Inside a packed struct** (future feature, §??): the type occupies exactly N bits of storage with bit-exact layout.

- 5 **Distinction from refinement.** Logical `iN/uN` types differ from a refinement constraint on `int`:

- `int >= 0 and <= 7` declares an `int` with a range constraint. Storage is the `int` default (`int32_t`); bit-width is not specified.
- `u3` declares a 3-bit quantity. Standalone its range is $[0, 7]$ and its storage is `uint8_t`; in a packed struct (future) it occupies exactly 3 bits.

²Implementation-defined behavior: the width of C's `int` on the target platform

³Implementation-defined behavior: the pointer width on the target platform

The two forms are interchangeable when only the range matters; they differ when bit-exact storage layout matters.

Example

```

1 // Logical bit-width: 12-bit quantity, container = uint16_t.
2 var x u12 = 4095
3
4 // Refinement constraint on int: range [0, 4095], container =
  int32_t.
5 var y int >= 0 and <= 4095 = 4095
6
7 // Refinement type alias: a named refinement type
  (\S\, \ref{sec:types.alias-refinement}).
8 type Pressure = int >= 0 and <= 1000
9 var p Pressure = 500

```

7.2.3 Refinement type aliases

- 6 A type alias may carry a refinement constraint that narrows the underlying type's value range:

```

1 type Percent = int >= 0 and <= 100
2 type Pressure = int >= 0 and <= 1000
3 type NonZero = int != 0

```

- 7 Variables declared with a refinement type alias inherit its constraint. Assignments whose source value range violates the alias constraint are *ill-formed* ([E086]).

Example

```

1 type Percent = int >= 0 and <= 100
2
3 proc main() int {
4     var ok Percent = 75                // [E086 not raised]: 75
        fits [0,100]
5     // var bad Percent = 150          // [E086]: 150 > 100
6     return 0
7 }

```

7.2.4 Packed structs (forward-looking, version 1.1)

- 8 A future revision is expected to introduce **[packed]** struct attribute (Q-017 attribute family) for bit-exact memory layout:

```

1 [packed]
2 type GpioModer {
3     pin0 u2    // bit 0-1
4     pin1 u2    // bit 2-3
5     // ... 14 more 2-bit fields
6 }
7 // total: 32 bits = 4 bytes, bit-exact layout

```

- 9 Inside a **[packed]** struct, logical **in/uN** types occupy exactly N bits of storage. Field access generates bit-shift/mask code; the field's value still respects the natural N -bit range. This feature targets embedded use cases: hardware registers, packed network protocols, and codec implementations.

7.2.5 Integer rank and widening

- 10 The integer types are partially ordered by *rank*:

	Rank	Types	Bit width
1		<code>u8</code> , <code>i8</code>	8
2		<code>u16</code> , <code>i16</code>	16
3		<code>u32</code> , <code>i32</code> , <code>int</code>	32
4		<code>u64</code> , <code>i64</code>	64
5		<code>usize</code> , <code>isize</code>	platform

- 11 **Implicit widening:** a value of a lower-rank integer type may be used where a higher-rank integer type is expected, without an explicit cast. The result type of a binary arithmetic or bitwise operation is the higher-rank operand type.

Example

```

1 var a u8 = 42
2 var b int = a           // u8 -> int: implicit widening, OK
3 var c = a + 1000        // u8 + int -> int (wider wins)

```

Constraint

An implicit conversion from a higher-rank integer type to a lower-rank integer type (narrowing) is *ill-formed*. Narrowing requires an explicit `as` cast (§??).

Constraint

An implicit conversion between integer types and floating-point types is *ill-formed*. Such conversions require an explicit `as` cast.

Constraint

An implicit conversion between integer types and `bool` is *ill-formed*. Such conversions require an explicit `as` cast.

7.2.6 Floating-point types

- 12 `f32` and `f64` are 32-bit and 64-bit floating-point types conforming to IEC 60559 (IEEE 754). They correspond to C's `float` and `double` respectively.
- 13 The default type of a floating-point literal is `f64` (§??).
- 14 Arithmetic on `f32` and `f64` follows IEEE 754 semantics: overflow produces $\pm\infty$; the result of 0.0/0.0 and similar operations is NaN. These are defined behaviors in Lain.

7.2.7 Boolean type

- 15 `bool` has exactly two values: `true` and `false`. `bool` is stored as a single byte; its exact representation is *implementation-defined*⁴.

⁴Implementation-defined behavior: whether `true` is 1 or any non-zero value

Constraint

There are no implicit **value** conversions between **bool** and any integer type for general arithmetic or assignment.

- 16 The condition expression of **if** and **while** accepts either a value of type **bool** or any integer type. When an integer value is used in condition position, zero is treated as **false** and any non-zero value is treated as **true**. This relaxation is ergonomic only and does not extend to other contexts.

Example

```

1 var n int = read_count()
2 if n { ... }           // OK: integer in condition, non-zero is
   true
3 var b bool = n         // [E100]: not a value conversion

```

7.2.8 The void type

- 17 **void** represents the absence of a value. It is used exclusively in pointer types (***void**) for C interoperability (see §??).

Constraint

A variable declaration with type **void** is *ill-formed*.

7.3 Array types

- 1 An array type **[T; N]** denotes a contiguous sequence of N values of type **T**. N shall be a compile-time constant integer greater than zero (grammar: *array-type*).
- 2 The **.len** property of an array type yields N as a compile-time constant of type **int**.
- 3 Array elements are laid out contiguously in memory in increasing index order, with element 0 at the base address. The stride between elements is *implementation-defined*⁵.

Constraint

An array size $N \leq 0$ is *ill-formed* ([E100]).

Constraint

Every array index expression shall satisfy $0 \leq idx < arr.len$. An access for which value range analysis cannot prove this is a constraint violation ([E014]).

Example

```

1 var arr = [int; 5]{1, 2, 3, 4, 5}
2 var x = arr[2]           // OK: 2 is statically in [0, 4]
3 // var y = arr[5]       // [E014]: 5 >= arr.len

```

7.4 Slice types

- 1 A slice type **[T]** is a fat pointer to a contiguous sequence of values of type **T** whose length is determined at runtime. Its runtime representation is a pair (**ptr**: ***T**, **len**: **usize**).
- 2 **str** is a predefined alias for **[u8]**.
- 3 A slice has two properties accessible via dot notation:

⁵Implementation-defined behavior: equal to **sizeof(T)** in C99, including any intra-element padding

- `.len`: the number of elements, type `usize`;
 - `.data`: a pointer to the first element, type `*T`.
- 4 A string literal of N characters has static type `+1Fixed_u8_N` (a null-terminated fixed-size array of $N+1$ bytes) and is implicitly coercible to `[u8]`.

7.5 Struct types

- 1 A struct type groups named fields into a single named product type. The grammar production is *struct-declaration* (Annex A).
- 2 Field order is the declaration order. The memory layout of a struct is *implementation-defined*⁶.
- 3 A struct type S is linear if at least one field of S has a linear type (transitively).

Constraint

Q-008. Every field of a struct or enum variant whose declared type is linear shall be annotated `mov`. Omitting `mov` on a linear field is *ill-formed* ([E083]). This requirement makes linearity locally visible in the declaration: a reader of a struct definition does not need to inspect the field's type definition to know whether the struct is linear.

Example

```

1 type Handle {
2     mov ptr *int                // explicit 'mov' on linear field
3 }
4
5 type Session {
6     mov h Handle                // OK: Handle is linear, mov
7     name [u8]                  // unrestricted field, no mov needed
8 }
9
10 // Ill-formed: missing mov on a linear field
11 type Bad {
12     h Handle                    // [E083]
13 }
```

- 4 **Struct construction:** all fields shall be provided in declaration order. The type of each argument shall be compatible with the declared field type (§ ??).

Constraint

A struct constructor expression with a number of arguments different from the number of fields is *ill-formed* ([E100]).

Constraint

Writing to a field of a struct variable requires the variable to be declared as `var` (mutable). Writing to an immutable binding's field is *ill-formed*.

⁶Implementation-defined behavior: equal to the C99 struct layout, including compiler-inserted padding for alignment

Constraint

Using `==` or `!=` on a struct type is *ill-formed*. Field-by-field comparison must be performed explicitly.

7.6 Enum types

- 1 An enum type is a type with a finite, named set of values. Each variant carries no associated data. The grammar production is *enum-declaration* (Annex A).
- 2 The underlying representation of an enum type is *implementation-defined*⁷.
- 3 Enum values are accessed as `TypeName.VariantName`.

Constraint

Using `==` or `!=` to compare enum values is *ill-formed*. Enum values shall be compared using `case` pattern matching (§??).

Note

The constraint on `==` for enums reflects that the underlying tag representation is implementation-defined. Pattern matching is always sound.

7.7 Algebraic data types (ADTs)

- 1 An ADT is a sum type in which each variant may carry associated fields. A type declaration is classified as an ADT if at least one variant has fields. The grammar production is *enum-declaration* (Annex A, using the record-variant form).
- 2 ADTs use a niche-based representation whenever a zero-cost encoding is available; otherwise they fall back to a tagged union (a tag field of implementation-defined integer type plus a union of variant payload structs).

Note

Q-012, Z5 zero-by-construction. When the variant payload admits a *niche*—a bit pattern that cannot occur in any valid value of the payload type—that niche is used to encode a tag-less variant. Niche sources, in priority order: null pointer (`0x0`) for pointers/slices/borrows; VRA-proven unused values for constrained integers; bit patterns outside the declared variants for `bool` or small enums; niche of any recursive field.

If no niche can be derived, compilation fails with **[E120]** and a suggestion to add a value-range constraint or use the built-in `NonZero(T)` wrapper. An ADT is never silently encoded with a tag+union if a niche-based representation is achievable.

- 3 ADT values are constructed as `TypeName.VariantName(args)` for variants with fields, or `TypeName.VariantName` for unit variants.
- 4 ADT values are destructured via `case` pattern matching (§??).

7.8 Pointer types

- 1 A pointer type `*T` or `const *T` is a raw memory address. Pointer operations require an `unsafe` block (§??).
- 2 The ownership modes for pointer types are:

⁷Implementation-defined behavior: an integer type large enough to hold all variant tags; the reference implementation uses `int`

	Lain syntax	Mode	C99 type	Linear?
	<code>*T</code>	shared (read-only)	<code>const T*</code>	no
	<code>var *T</code>	mutable	<code>T*</code>	no
	<code>mov *T</code>	owned	<code>T*</code>	yes

Constraint

Dereferencing a pointer or taking the address of a variable shall occur only inside an `unsafe` block. Pointer operations in safe code are *ill-formed* ([E012]).

7.9 Constrained types

- 1 A constrained type is a type annotated with a value range constraint:

$$T \text{ op } bound$$

where $op \in \{>=, <=, >, <, ==\}$ and $bound$ is an integer literal.

- 2 Constrained types are used in function return types and parameter types to declare value range invariants that the value range analysis (§??) shall enforce.

Example

```

1 func nonzero_divisor() int >= 1 {
2     return 42 // VRA verifies: 42 >= 1 holds
3 }
```

- 3 The constraint is part of the function signature, not the type system's nominal identity. Two constrained types with the same base type are assignment-compatible.

7.10 Type compatibility and equivalence

- 1 Lain uses **nominal type equivalence**: two types are the same if and only if they have the same declared name.
- 2 Two types T_1 and T_2 are *compatible* for an expression context if:

- $T_1 = T_2$ (same nominal type), or
- T_1 is an integer type of lower rank than T_2 (implicit widening; §??).

Constraint

An expression of type T_1 used in a context requiring type T_2 , where T_1 and T_2 are not compatible, is *ill-formed*.

- 3 The operators `==` and `!=` are defined for:

- primitive numeric types;
- `bool`;
- pointer types.

They are not defined for struct types, array types, or enum types.

Chapter 8

Expressions

- 1 An expression is a syntactic construct that evaluates to a value. Every expression has a type, determined statically at compile time. The grammar production for *expression* is in Annex A.
- 2 Expressions are evaluated strictly left-to-right: for any binary operator $a \text{ op } b$ or function call $f(a, b)$, the left operand (or earlier argument) is fully evaluated before the right operand (or later argument).

8.1 Operator precedence and associativity

- 1 The following table lists all binary operators in order of decreasing precedence. All operators listed on the same row have equal precedence.

	Prec.	Operators	Assoc.	Result type
1 (high)		() [] .	left	(context-dependent)
2		unary - ! not mov ref mut	right	(operand type)
3		as	left	target type
4		* / %	left	wider operand type
5		+ -	left	wider operand type
6		<< >>	left	left operand type
7		&	left	wider operand type
8		^	left	wider operand type
9			left	wider operand type
10		< > <= >= in	left	bool
11		== !=	left	bool
12		and	left	bool
13 (low)		or	left	bool

- 2 Parentheses override precedence.

8.2 Primary expressions

- 1 A primary expression is one of: an identifier, a literal, a parenthesized expression, a block expression, an **if** expression, a **case** expression, a constructor expression, or a **comptime** expression.
- 2 **Identifier expression:** evaluates to the current value of the named variable.

Constraint

The identifier shall be declared in scope ([E013]).

Constraint

The identifier shall have been initialized before use ([E005]).

8.3 Arithmetic operators

- 1 The binary arithmetic operators are + (addition), - (subtraction), * (multiplication), / (division), and % (remainder). The result type is the wider of the two operand types (§??).
- 2 Integer division truncates toward zero. `f32/f64` division follows IEEE 754.

Constraint

Integer division or remainder where the divisor is statically provable to be zero (via value range analysis, §??) is *ill-formed* ([E015]).

Constraint

% shall not be applied to floating-point operands.

- 3 The unary - operator negates its operand. For unsigned integer types the result wraps modulo 2^N .

8.4 Comparison operators

- 1 The comparison operators ==, !=, <, >, <=, >= compare two values and yield `bool`.

Constraint

Operands of a comparison operator shall have compatible types (§??).

Constraint

== and != shall not be applied to struct types, array types, or enum types (§??).

8.5 Logical operators

- 1 `and` and `or` are short-circuit operators: the right operand is not evaluated if the result is determined by the left operand alone. `not` and ! are prefix unary negation. All yield `bool`.

Constraint

Operands of `and`, `or`, `not`, and ! shall have type `bool`.

8.6 Bitwise operators

- 1 The bitwise operators &, |, ^, <<, >> operate on integer operands. The result type is the wider operand type for &, |, ^; for shift operators, the result type is the left operand type.

Constraint

Operands of bitwise operators shall be integer types.

Constraint

The shift amount (right operand of `<<` and `>>`) shall satisfy $0 \leq \text{shift} < N$ where N is the bit width of the left operand. A shift amount outside this range is *ill-formed* ([E100]).

8.7 The `in` operator

- 1 The expression `idx in arr` evaluates to `true` if and only if $0 \leq \text{idx} < \text{arr.len}$. The operand `arr` shall be an array or slice type; `idx` shall be an integer type.
- 2 When `idx in arr` appears as the condition of a `while` or `if` statement (or as the leftmost operand of an `and`-chain condition), it establishes an **in guard**: inside the body of that statement, the implementation shall accept `arr[idx]` without requiring further bounds verification.
- 3 In-guards propagate through `and`-chains: if the left operand of `and` establishes an in-guard, that guard is active when evaluating the right operand.

Example

```

1 // In-guard: arr[i] is safe without explicit VRA
2 while i in arr {
3     var x = arr[i]    // OK: in-guarded
4     i = i + 1
5 }
6
7 // And-chain propagation:
8 while l.pos in l.src and (l.src[l.pos] as int) != ',' {
9     l.pos = l.pos + 1
10 }
```

Constraint

An in-guard of the form `idx in arr` covers only `arr[idx]` exactly. Accesses `arr[idx + k]` for any $k \neq 0$ are not covered by this guard and require separate verification or an `unsafe` block.

8.8 Cast expression (`as`)

- 1 The expression `expr as T` explicitly converts the value of `expr` to type `T`. The following casts are permitted:

		<u>From To Semantics</u>
integer	integer	Truncation (narrowing) or extension (widening)
integer	float	Nearest representable value (IEEE 754)
float	integer	Truncation toward zero
float	float	Precision change
pointer	pointer	Reinterpretation (<code>unsafe</code> required)
integer	pointer	Reinterpretation (<code>unsafe</code> required)
pointer	integer	Reinterpretation (<code>unsafe</code> required)

Constraint

Casts between pointer types, between a pointer and an integer, or between any type and a pointer shall occur only inside an **unsafe** block. Such a cast outside **unsafe** is *ill-formed* ([E012]).

Constraint

A cast between non-numeric, non-pointer types (e.g., struct to integer) is *ill-formed*.

8.9 Move expression (mov)

- 1 **mov** *expr* transfers ownership of the value produced by *expr*. The source is placed in the Consumed state; any subsequent use of the source variable is *ill-formed* ([E001]). See §??.

8.10 Borrow expressions (ref, mut)

- 1 **ref** *expr* creates a shared (read-only) borrow of *expr*. **mut** *expr* creates a mutable borrow of *expr*. Both expressions are evaluated in argument contexts to pass values without transferring ownership. See §??.

8.11 Field access

- 1 The expression *expr*.*field* accesses the named field of a struct or ADT value, or a property of an array or slice (*.len*, *.data*).

Constraint

The field name shall exist on the type of *expr*.

Constraint

Writing to a field (*expr*.*field* = *v*) requires *expr* to be a mutable lvalue.

8.12 Index expression

- 1 The expression *arr*[*idx*] accesses the element of array or slice *arr* at integer index *idx*.

Constraint

The value range analysis shall prove $0 \leq idx < arr.len$ at every index expression. An index expression for which this cannot be proved is *ill-formed* ([E014]). An **in** guard (§??) or an **unsafe** block suppresses this requirement.

8.13 Function call

- 1 A function call expression *f*(*args*) evaluates the arguments and transfers control to the callee. Arguments are evaluated left-to-right.
- 2 Argument ownership modes shall be given explicitly at the call site:

Syntax	Meaning
<i>f</i> (<i>x</i>)	shared borrow (default; parameter mode must be shared)
<i>f</i> (var <i>x</i>)	mutable borrow (parameter mode must be var)

Syntax	Meaning
--------	---------

<code>f(mov x)</code>	ownership transfer (parameter mode must be owned/ mov)
------------------------------	--

Constraint

The mode annotation at the call site shall match the declared parameter mode. A mismatch is *ill-formed*.

Constraint

The number of arguments shall equal the number of parameters (unless the callee is a variadic C function declared with `...`).

- 3 **Two-phase borrows:** during argument evaluation, borrows of the receiver of a method call are placed in the RESERVED phase and promoted to ACTIVE after all arguments are evaluated (see §??).

8.14 Block expression

- 1 A block expression `{ stmts... expr }` evaluates each statement in order, then evaluates the final expression, whose value is the value of the block. If the final expression is absent, the block has no value.

8.15 If expression

- 1 An **if** expression of the form `if cond { e1 } else { e2 }` evaluates *cond*; if true, evaluates *e*₁; otherwise, evaluates *e*₂.

Constraint

The types of *e*₁ and *e*₂ shall be compatible. If they are not, the expression is *ill-formed*.

Constraint

cond shall have type `bool`.

8.16 Match expression (case)

- 1 A **case** expression (*match-expression*) selects one of several alternatives based on pattern matching. All arms shall produce values of compatible types; the type of the **case** expression is that common type. See §?? for full exhaustiveness rules.

8.17 Constructor expression

- 1 A constructor expression builds a value of a struct or ADT type by supplying all field values. See §?? and §?? for constructor rules.

8.18 Compound assignment

- 1 Compound assignment `x op= e` is syntactic sugar for `x = x op e`. The left-hand side shall be a mutable lvalue. All compound forms of the arithmetic and bitwise operators are supported (see §??).

Chapter 9

Statements

- 1 A statement is a unit of execution. Statements are terminated by line feeds (§ ??). The grammar production for *statement* is in Annex A.

9.1 Block statement

- 1 A block statement `{ stmts... }` creates a new scope (§ ??) and executes each contained statement in order. Names declared inside a block are not accessible outside it.

9.2 Variable declaration statement

- 1 **var** `name` `[: Type]` `= expr` declares and initializes a local variable. The type may be omitted if it can be inferred from the initializer.

Constraint

A variable declaration shall include either an explicit type annotation or an initializer expression. A declaration with neither is *ill-formed* ([E100]).

Constraint

When both a type annotation and an initializer are present, the type of the initializer shall be compatible with the declared type (§ ??).

9.3 Assignment statement

- 1 An assignment statement `lvalue = expr` stores the value of *expr* into the storage designated by *lvalue*.

Constraint

The left-hand side shall be a mutable lvalue (§ ??). Assigning to an immutable binding is *ill-formed* ([E009]).

Constraint

Overwriting a linear variable whose current value has not been consumed would leak that value. Such an assignment is *ill-formed* ([E003]).

Note

Assigning to a linear variable after its previous value has been consumed (e.g., loop reassign-and-consume pattern) is permitted. The implementation resets the variable's linear state to Unconsumed after a legal overwrite.

Example

```

1 import std.fs
2
3 proc main() int {
4     var f = open_file("data.txt", "r")
5     close_file(mov f)           // f is now Consumed
6     f = open_file("data.txt", "r") // OK: overwriting Consumed
7     close_file(mov f)
8     return 0
9 }
```

9.4 Expression statement

- 1 An expression followed by a statement terminator is an expression statement. The value of the expression is discarded.

9.5 If statement

- 1 **if** *cond* { *body* } [**else if** *cond* { *body* }]... [**else** { *body* }] evaluates *cond*; if true, executes the then-body; otherwise, tests the **else if** clauses in order; if none matches, executes the **else** body (if present).

Constraint

cond shall have type **bool**.

- 2 **Range refinement**: inside the then-branch of **if** $x < N$ { }, the value range analysis (§??) knows that $x \in (-\infty, N - 1]$; inside the else-branch, $x \in [N, +\infty)$.
- 3 **In-guard**: when *cond* contains or is an **in** expression (§??), the in-guard is active inside the then-branch only.
- 4 **Branch consistency**: if one branch consumes a linear variable, all branches shall consume it. If branches disagree on the linear state of a variable from the enclosing scope, the program is *ill-formed* ([E003]).

9.6 While statement

- 1 **while** *cond* { *body* } repeatedly evaluates *cond* and, if true, executes *body*.

Constraint

An unbounded **while** loop (one without a **decreasing** measure) shall not appear inside a **func**. Such use is *ill-formed* ([E011]).

Constraint

cond shall have type **bool**.

- 2 **In-guard**: when *cond* contains or is an **in** expression, the in-guard is active inside the loop body for each iteration.

9.6.1 Bounded while statement

- 3 **while** *cond* **decreasing** *M* { *body* } is a bounded loop. In addition to the while semantics above, the implementation shall statically verify:
1. **Non-negativity** ([E080]): the implementation shall prove that $M \geq 0$ whenever *cond* is true.
 2. **Variable dependency** ([E081]): *M* shall reference at least one variable that is assigned in *body*. An *M* that references no such variable would never decrease.
 3. **Strict decrease** ([E082]): the implementation shall prove that every execution of *body* strictly decreases the value of *M*.
- 4 A bounded **while** loop is permitted inside a **func** because the implementation has statically verified termination.
- 5 The following patterns are accepted by the standard verification algorithm:

	Condition	Measure	Why
	$i < n$	$n - i$	i increases $\Rightarrow$ measure decreases
	$n > 0$	n	n decreases directly
	$a < b$	$b - a$	either a increases or b decreases
	i in <i>arr</i>	$\text{arr.len} - i$	in implies $i < \text{arr.len}$

Example

```

1 func count(n int) int {
2     var i = 0
3     while i < n decreasing n - i {
4         i = i + 1
5     }
6     return i
7 }
```

Rationale

The **decreasing** keyword bridges the gap between pure functions (which must terminate) and the common pattern of finite-input state machines (lexers, parsers) that are provably terminating. The programmer states the termination argument; the compiler verifies it.

9.7 Return statement

- 1 **return** [*expr*] terminates execution of the current function or procedure and transfers the value of *expr* (if present) to the caller.

Constraint

At the point of a **return**, all linear variables in scope shall have been consumed. A live (Unconsumed) linear variable at **return** is *ill-formed* ([E003]).

Constraint

Q-009. A return statement shall not be prefixed with `mov` or `var`. The forms `return mov x` and `return var x` are syntactically *ill-formed* ([E100]). Ownership transfer in return position is implicit from the function's declared return type.

9.8 Defer statement

- 1 `defer { body }` schedules *body* for execution immediately before the enclosing scope exits, on all exit paths (`return`, `break`, `continue`, or fall-through). Multiple `defer` statements execute in LIFO order.
- 2 **Interaction with linear types:** if a linear variable is consumed inside a `defer` body, the variable is marked as defer-consumed. It is treated as unconsumed for the purposes of the main body (it may be used before the scope exit) and as consumed at scope exit.

Constraint

A `defer` body shall not contain `return`, `break`, or `continue` statements that would transfer control out of the deferred body.

Example

```

1 import std.fs
2
3 proc process() int {
4     var f = open_file("data.txt", "r")
5     defer { close_file(mov f) } // f consumed at scope exit
6     // ... use f ...
7     return 0
8 }
```

9.9 Unsafe block

- 1 `unsafe { body }` is an unsafe block (see §??). It creates a scope in which certain static checks are relaxed.

9.10 Comptime if statement

- 1 `comptime if cond { then } [else { else }]` evaluates *cond* at compile time. Only the taken branch is type-checked and emitted; the other branch is discarded. *cond* shall be a compile-time constant expression (§??).

Note

`comptime if` is the Lain equivalent of C preprocessor `#if`: it enables platform-specific or type-specific code selection without dead-code warnings.

9.11 For statement

- 1 `for i in start..end { body }` iterates with *i* ranging from *start* (inclusive) to *end* (exclusive). The loop variable *i* is immutable; its value range is statically known to be $[start, end - 1]$ throughout the body, enabling safe array indexing without runtime bounds checks.
- 2 `for` loops are permitted in both `func` and `proc`.

Constraint

start and *end* shall have integer types.

Chapter 10

Declarations

- 1 This clause specifies top-level declarations. Local variable declarations are specified in § ?? . The grammar productions are in Annex A (*function-declaration*, *struct-declaration*, *enum-declaration*).

10.1 Declaration attributes

- 1 A declaration may be preceded by zero or more attributes. An attribute has the form `[name]` or `[name(args)]`, where *name* is a recognized attribute identifier from the closed set in Table ?? , and *args* (if present) is a comma-separated list of expressions. Multiple attributes on a single declaration are written one per line.

```
1 [fast_math]
2 func dot(a [f64], b [f64], n int) f64 { ... }
3
4 [private]
5 func internal_helper() int { ... }
6
7 [fast_math]
8 [private]
9 func hot_path() f64 { ... }
```

- 2 Recognized attribute names (closed set, version 1.0):

Table 10.1: Recognized attribute names

	Attribute	Applies to	Purpose
[fast_math]	func, proc		Enable FMA fusion (P4 opt-out, local).
[private]	any declaration		Module-private visibility.

Constraint

Q-017. An attribute name not listed in Table ?? is *ill-formed* ([E103]). An attribute that omits the identifier (e.g. [] or [(arg)]) is *ill-formed* ([E102]).

Note

Attributes are recognized at declaration position only. At expression position, [and] continue to delimit array and slice subscripts and array literals; the parser disambiguates by context.

10.2 Struct declarations

- 1 A struct declaration introduces a named product type with one or more named fields. Fields are listed in declaration order; order is significant for construction and layout.

```
1 struct Point {
2     x int
3     y int
4 }
```

- 2 A field may be annotated with `mov`, making the field (and therefore the containing struct) a linear type:

```
1 struct File {
2     mov handle *FILE
3 }
```

Constraint

A struct with zero fields is *ill-formed* ([E100]).

10.3 Enum and ADT declarations

- 1 An enum declaration introduces a type whose values are drawn from a fixed, named set of variants. If every variant has no associated fields, the type is a simple enum (§??). If at least one variant has associated fields, the type is an algebraic data type (ADT) (§??).

```
1 enum Direction { North, South, East, West } // simple enum
2
3 enum Shape {                                     // ADT
4     Circle { radius int }
5     Rectangle { width int, height int }
6     Point
7 }
```

10.4 Function declarations

- 1 A function declaration introduces a `func`: a pure, terminating, side-effect-free callable. Its grammar production is *function-declaration*.
- 2 The signature consists of: the keyword `func`, a name, an optional list of `comptime` type parameters, a parameter list, and a return type annotation.

10.4.1 Parameters

- 3 Each parameter has a name, a type, and an ownership mode. The ownership mode determines how the argument is passed:

Syntax	Mode	ABI (struct T)
name T	shared (read-only)	const T*
<code>var</code> name T	mutable	T*
<code>mov</code> name T	owned (transfer)	T (by value)

Note

For primitive types (integer, float, bool), the ABI passes the value directly regardless of ownership mode, as for primitive C arguments.

- 4 A parameter declared `comptime` name type is a compile-time type parameter; it must be bound to a concrete type at every call site.

10.4.2 Return type annotation

- 5 The return type is written after the parameter list. It may carry a value range constraint:

```
1 func abs(x int) int >= 0 { ... }
```

Constraint

All return paths of a `func` shall produce a value whose type and value range satisfy the declared return type and constraint.

10.4.3 Purity constraints**Constraint**

A `func` shall not contain an unbounded `while` loop (one without a `decreasing` measure) ([E011]).

Constraint

A `func` shall not call a `proc` or `extern proc` ([E011]).

Constraint

A `func` shall not call itself directly or indirectly (mutual recursion) ([E011]).

10.5 Procedure declarations

- 1 A procedure declaration introduces a `proc`: a callable with unrestricted side effects. Its syntax is identical to `func` except for the `proc` keyword. A `proc` may contain unbounded loops, call other `procs`, and access global mutable state.
- 2 The entry point of every Lain program shall be declared as:

```
1 proc main() int { ... }
```

Constraint

A program without a `proc main()int` definition is *ill-formed* ([E100]).

10.6 Extern declarations

- 1 An extern declaration introduces a C function into the Lain name space without providing a body. See §?? for full semantics.

```
1 extern proc printf(fmt *u8, ...) int
2 extern func strlen(s *u8) usize
```

Constraint

Variadic parameters (...) shall only appear in `extern` declarations. User-defined variadic functions are *ill-formed*.

10.7 Comptime declarations

- 1 A top-level `comptime { ... }` block is evaluated by the compiler before any runtime code is emitted. It may define compile-time constants or trigger `compileError` assertions.

Chapter 11

Ownership and linearity

- 1 This clause specifies Lain’s linear type system, ownership modes, borrow checker, and non-lexical lifetime rules. All rules in this clause are enforced at compile time with zero runtime overhead.

11.1 Ownership modes

- 1 Every parameter, return value, and struct field has one of three ownership modes:

	Mode	Param syntax	Call-site	Semantics
Shared	<code>name T</code>	<code>f(x)</code>		read-only; multiple concurrent borrows allowed
Mutable	<code>var name T</code>	<code>f(var x)</code>		exclusive read-write; no other borrow concurrent
Owned	<code>mov name T</code>	<code>f(mov x)</code>		transfers ownership; source becomes Consumed

- 2 Local variables declared with `var name = expr` have mutable storage accessible within their scope; their ownership mode in the type system is Owned (they hold linear values that must be consumed at scope exit).

11.2 Linear states

- 1 Every variable of a linear type has a *linear state* at each program point. The three states are:

Uninit The variable has been declared but no value has been assigned.

Unconsumed The variable holds a value that has not yet been transferred.

Consumed The variable’s value has been transferred via `mov` or a consuming function call.

- 2 The state machine governing transitions is:

State before	Operation	State after
Uninit	first assignment	Unconsumed
Unconsumed	<code>mov x</code> (transfer)	Consumed
Unconsumed	borrow (<code>ref/mut</code>)	Unconsumed (borrow active)
Consumed	assignment (overwrite)	Unconsumed
Consumed	read or <code>mov</code>	<i>ill-formed</i>
Uninit	read or <code>mov</code>	<i>ill-formed</i>

Note

The Consumed $\rightarrow$ Unconsumed transition via overwrite enables the loop-reassign-then-consume pattern: a linear variable declared outside a loop may be consumed and reassigned on each iteration without leaking.

11.3 Diagnostics

Constraint

Using a variable that is in the Consumed or Uninit state (reading its value or transferring it with `mov`) is *ill-formed* ([E001]).

Constraint

Transferring ownership of a variable that has already been transferred (double-move) is *ill-formed* ([E002]).

Constraint

A linear variable that is in the Unconsumed state when its scope exits (resource leak) is *ill-formed* ([E003]).

Constraint

An aliasing violation — attempting a mutable borrow when a shared borrow is active, or a shared borrow when a mutable borrow is active, or a second mutable borrow of the same variable — is *ill-formed* ([E004]).

Constraint

Attempting to move a variable that has an active borrow is *ill-formed* ([E005]).

Constraint

Moving a variable inside a loop body where the loop may execute more than once is *ill-formed* ([E006]).

Constraint

If a linear variable is consumed in one branch of an `if/else` chain but not in all branches, the program is *ill-formed* ([E007]).

11.4 The read-write lock invariant

- 1 **Invariant:** At every program point, for every variable V , exactly one of the following holds:
 1. V has $N \geq 0$ active shared borrows and zero active mutable borrows.
 2. V has exactly one active mutable borrow and zero shared borrows.
- 2 This invariant is the compile-time analogue of a reader-writer lock. A conforming implementation shall enforce it at every program point.

11.5 Non-lexical lifetimes (NLL)

- 1 A borrow's lifetime ends at the borrow's *last use*, not at the end of the variable's lexical scope. The implementation computes last-use points via a use-analysis pre-pass over the AST.

Example

```

1 var data = Data(42)
2 var r = get_ref(var data) // mutable borrow starts
3 use_ref(var r)           // last use of r: borrow ends HERE
  (NLL)
4 var y = read(data)       // OK: borrow has expired

```

11.6 Two-phase borrows

- 1 During argument evaluation for a function call, borrows of the receiver object are placed in the *RESERVED* phase. A RESERVED borrow allows concurrent shared reads of the same owner but blocks mutable writes and moves. After all arguments have been evaluated, RESERVED borrows are promoted to the *ACTIVE* phase.
- 2 This mechanism enables UFCS calls of the form `x.f(x.field)` where the first argument (the receiver) requires a mutable borrow of `x` while the second argument reads a field of `x`.

Phase	Allows on owner	Blocks on owner
RESERVED	shared reads	mutable writes, moves
ACTIVE	(nothing)	all other access

Example

```

1 proc push_n(var v Vec, n int) { v.data = v.data + n }
2
3 var v = Vec(0, 10)
4 v.push_n(v.cap) // desugars to push_n(var v, v.cap)
5                // var v enters RESERVED phase; v.cap read is
                  // allowed

```

11.7 Move semantics

- 1 The `mov` operator transfers ownership. The source variable transitions to Consumed state; any subsequent read or move of the source is *ill-formed* ([E001]).
- 2 Ownership transfer is the only way to pass a linear value to a consuming parameter. The `mov` keyword shall be present at the call site: `f(mov x)`.

11.8 Borrowed match

- 1 The `case &expr { ... }` form (see §??) performs pattern matching without consuming the scrutinee. A temporary shared borrow of the scrutinee is registered for the duration of the match body and released when the match completes.

Constraint

Inside a `case &expr` body, the scrutinee shall not be mutated or moved. Attempting to do so violates the active shared borrow ([E004]).

11.9 Loop and ownership

- 1 A linear variable declared outside a loop may be consumed inside the loop body if and only if it is also reassigned (overwritten) on every path through the loop body before the next iteration begins.

Example

```

1 import std.fs
2
3 proc main() int {
4     var f = open_file("data.txt", "r")
5     close_file(mov f)           // consumed before loop
6     var i = 0
7     while i < 3 decreasing 3 - i {
8         f = open_file("data.txt", "r") // reassign (Consumed
9         -> Unconsumed)
10        close_file(mov f)           // consume
11        i = i + 1
12    }
13    return 0
14 }
```

11.10 Branch consistency

- 1 After an `if/else` chain, the linear state of each variable from the enclosing scope is the *intersection* of its states across all branches:
 - If consumed in all branches: the variable is Consumed after the chain.
 - If consumed in no branches: the variable is Unconsumed after the chain.
 - If consumed in some but not all branches: *ill-formed* ([E007]).

11.11 Field-level tracking

- 1 The borrow checker tracks borrows at the field level. Borrowing non-overlapping fields of the same struct simultaneously is permitted:

```

1 type Pair { a int, b int }
2 var p = Pair(1, 2)
3 var ra = ref_a(ref p.a) // shared borrow of p.a
4 var rb = ref_b(ref p.b) // shared borrow of p.b -- OK:
   non-overlapping
```

Note

The reference implementation tracks field borrows at one level of depth. Nested field borrows (e.g., `p.a.x` vs `p.a.y`) are conservatively treated as overlapping.

Chapter 12

Functions and procedures

12.1 The func/proc distinction

- ¹ Lain distinguishes between pure functions (**func**) and side-effecting procedures (**proc**). This distinction is enforced statically and reflected in the type system.

Property	func	proc
Side effects	forbidden	allowed
Unbounded while	forbidden	allowed
Bounded while decreasing	allowed	allowed
for loops	allowed	allowed
Direct/indirect recursion	forbidden	allowed
Calling proc	forbidden	allowed
Calling func	allowed	allowed
Global mutable state	no access	full access
Termination guarantee	yes	no

- ² A **func** is referentially transparent: calling it with the same arguments always produces the same result. Its evaluation has no observable effect on any state outside its own stack frame.

12.2 Purity enforcement

Constraint

A **func** that calls a **proc** or **extern proc** is *ill-formed* ([E011]).

Constraint

A **func** that contains an unbounded **while** loop (one without a **decreasing** measure) is *ill-formed* ([E011]).

Constraint

A **func** that calls itself directly, or that participates in a mutual-recursion cycle, is *ill-formed* ([E011]). The implementation shall detect mutual recursion by performing a depth-first search on the call graph.

Note

Generic functions (**func** with **comptime** parameters) are excluded from mutual-recursion detection until they are monomorphized.

12.3 Termination analysis

- 1 A **func** is guaranteed to terminate because:
 1. all **while** loops carry a verified termination measure;
 2. **for** loops iterate over finite ranges;
 3. recursion is forbidden.
- 2 No termination analysis is performed for **procs**.

12.4 Universal Function Call Syntax (UFCS)

- 1 An expression of the form **x.f(args)** is desugared to **f(x, args)** before name resolution, provided **f** is not a declared field of **x**'s type. This is called Universal Function Call Syntax (UFCS).
- 2 **UFCS ownership**: the ownership mode of the first argument in the desugared call is determined by the declared mode of the first parameter of **f**:
 - If the first parameter is **var**, the receiver is automatically mutably borrowed: **x.f()** desugars to **f(var x)**.
 - If the first parameter is **mov**, the receiver is automatically moved: **x.f()** desugars to **f(mov x)**.
 - If the first parameter is shared (default), the receiver is shared: **x.f()** desugars to **f(x)**.
- 3 **UFCS resolution algorithm**:
 1. Check if **f** is a declared field of **x**'s type. If so, this is a field access, not UFCS.
 2. Search for a function named **f** whose first parameter type is compatible with the type of **x**.
 3. If found, desugar the call.
 4. If not found, emit **[E013]** (undeclared identifier).

Example

```
1 func is_empty(s [u8]) bool { return s.len == 0 }
2
3 var buf = "hello"
4 var empty = buf.is_empty()    // desugars to: is_empty(buf)
```

12.5 Calling conventions

- 1 The calling convention for Lain functions corresponds to the C99 calling convention of the target platform, as determined by the C compiler used for the translation output. The parameter passing rules are:

Lain parameter	C type	Semantics
shared struct T	const T*	pointer to read-only copy
var struct T	T*	pointer, caller's copy
mov struct T	T	by value (bitwise copy)
primitive any mode	T	by value

12.6 Return values

- 1 A return statement has the form **return** <expr>. The mode of the returned value is determined by the function's declared return type and follows the same rules as call-site argument passing.

Constraint

Q-009. A return statement shall not be prefixed with **mov** or **var**. The forms **return mov x** and **return var x** are *ill-formed* ([E100]). If a future revision introduces return-by-reference, it will require dedicated syntax.

Note

When the function's declared return type is owned (e.g. **mov T**), the expression in **return expr** is treated as a move of **expr**. No explicit **mov** keyword is permitted in return position.

12.7 The panic builtin

- 1 **panic(msg)** is a builtin expression that terminates program execution immediately. Its type is *Never* (the bottom type: a subtype of every type). Because it does not return, **panic** may appear in any expression position—including as the body of a match arm whose declared type is otherwise unrelated.
- 2 **panic** may be called from both **func** and **proc** contexts. The call is deterministic (same input yields the same termination), so it does not violate the purity of an enclosing **func**.

Constraint

Q-014, S16. When **panic** is executed, the program terminates immediately via the platform abort primitive. No **defer** block is executed. No stack unwinding occurs.

Note

The reference implementation emits, for **panic(msg)**, the equivalent of **fprintf(stderr, "panic: %.*s\n", ...) ; abort()**. The message is written to the standard error stream before abort.

Example

```

1 func head(s [u8]) u8 {
2     if s.len == 0 {
3         panic("empty slice")    // Never; satisfies the return
                                type

```

```
4     }  
5     return s[0]  
6 }
```

12.8 Function attributes

- 1 A function declaration may be prefixed with one or more attributes (§??). The attributes applicable to functions in version 1.0 are:
 - **[fast_math]** — enable fast floating-point optimizations (FMA fusion, contraction) for the body of this function. This is an opt-out from the determinism guarantee (P4) and applies only locally; functions without **[fast_math]** remain bit-deterministic within their target platform.
 - **[private]** — module-private visibility (§??).

Note

The reference implementation translates **[fast_math]** on a function f to a pair of pragmas surrounding the body of f in the emitted C source, enabling **fp-contract=fast** for f only. The default (i.e., absence of **[fast_math]**) emits **-ffp-contract=off** flags, providing deterministic floating point within a single target platform and C compiler.

Chapter 13

Value range constraints

13.1 Overview

- 1 Value Range Analysis (VRA) is a static analysis that tracks integer value ranges through a program using interval arithmetic. It is used to:
 - eliminate array bounds checks (§ ??);
 - prove division-by-zero absence (§ ??);
 - verify parameter and return constraints (§ ??);
 - prove in-guard safety (§ ??).
- 2 VRA is decidable and polynomial in program size. No SMT solver is required. All analyses performed by a conforming implementation shall terminate.

13.2 Range representation

- 1 A value range is an interval $[\ell, u]$ where $\ell \leq u$. The sentinels $-\infty$ and $+\infty$ represent the absence of a lower or upper bound, respectively. A range may additionally be *unknown* (no information available), in which case the interval is $(-\infty, +\infty)$.

13.3 Range propagation rules

- 1 The following table defines the result range for binary arithmetic operations on intervals $[a, b]$ and $[c, d]$. All arithmetic is saturating; overflow wraps to $\pm\infty$.

	Operation	Result range	Notes
	$[a, b] + [c, d]$	$[a + c, b + d]$	saturating
	$[a, b] - [c, d]$	$[a - d, b - c]$	saturating
	$[a, b] \times [c, d]$	$[\min(ac, ad, bc, bd), \max(ac, ad, bc, bd)]$	saturating
	$[a, b] \div [c, d], c > 0$	$[a \div d, b \div c]$	integer truncation
	$[a, b] \div [c, d], 0 \in [c, d]$	[E015]	division by zero
	$[a, b] \% [c, d], a \geq 0, c > 0$	$[0, d - 1]$	
	$[a, b] \% [c, d], \text{otherwise}$	unknown	conservative

13.4 Conditional refinement

- 1 After an **if** $x < N$ test, the VRA refines the range of x in the then-branch to $[\ell, N - 1]$ and in the else-branch to $[N, u]$ (where $[\ell, u]$ is the range before the test).
- 2 At the join point after an **if/else**, the range is the union of the ranges from both branches.
- 3 When conditions are chained with **and**, refinements from the left operand are active when evaluating the right operand (§??).

13.5 In-guard semantics

- 1 An in-guard **idx in arr** (§??) introduces the constraint $0 \leq idx < arr.len$ into the VRA's range environment. Inside the guarded body, **arr[idx]** is accepted without further proof.
- 2 When **idx in arr** is the condition of a **while decreasing** M loop, the VRA infers that $arr.len - idx \geq 0$ (a valid non-negativity proof for the measure $arr.len - idx$).

13.6 Constraint annotations

- 1 A constraint annotation of the form $T \text{ op } \text{bound}$ on a parameter or return type declares an invariant that the VRA shall enforce:
 - **Parameter constraint:** at every call site, the VRA shall prove that the argument satisfies the constraint.
 - **Return constraint:** at every **return** statement, the VRA shall prove that the return expression satisfies the constraint.

Constraint

A function call where the argument range cannot be proven to satisfy a parameter constraint is *ill-formed* ([E012]).

Constraint

A **return** expression whose range cannot be proven to satisfy the declared return constraint is *ill-formed* ([E012]).

13.7 Interprocedural range propagation

- 1 When a call expression appears in a context where the VRA needs a range, it uses the callee's declared return constraint (if any) as a conservative approximation.

Example

```

1 func nonzero() int >= 1 { return 42 }
2
3 func divide(a int) int {
4     return a / nonzero() // divisor range known >= 1: no
5 }                          [E015]
```

- 2 When the callee has no declared return constraint, the call expression has an unknown range.

Note

Interprocedural VRA is conservative: only declared constraints are used, not body analysis. This preserves decidability and ensures that changing a function's body cannot silently affect its callers' safety proofs.

13.8 Limits and known gaps

- ¹ The following limitations are known and accepted:
 1. VRA does not track ranges of struct fields. A struct field accessed through a pointer always has an unknown range.
 2. VRA does not track ranges across loop-carried dependences with non-linear measures.
 3. Integer overflow in VRA arithmetic uses saturating semantics; the actual `Lain` program uses wrapping arithmetic. Programs whose correctness depends on integer overflow are not analyzed correctly by VRA.
 4. Floating-point values are not tracked by VRA.

Chapter 14

Generics and compile-time evaluation

14.1 Overview

- 1 Lain implements genericity through compile-time function evaluation (CTFE). Generic types and functions accept *type parameters* (declared as `name type`) or *compile-time value parameters* (declared as `comptime name non-type`). The compiler evaluates them at compile time and monomorphizes the result. There is no type erasure and no runtime polymorphism.

14.2 Type parameters

- 1 A parameter declared `name type` is a type parameter. Types are implicitly compile-time — the `comptime` keyword shall *not* precede a type parameter. At every call site, the argument shall be a type expression known at compile time.

```
1 func identity(T type, x T) T {  
2     return x  
3 }  
4  
5 var n = identity(int, 42)           // T = int, monomorphized  
6 var s = identity(u8[:0], "hi")     // T = u8[:0], separate  
                                   monomorphization
```

- 2 Type parameters are evaluated entirely at compile time; they produce no runtime code.

Constraint

The `comptime` keyword shall not appear before a parameter whose type is `type`. `func f(comptime T type)` is ill-formed; write `func f(T type)` instead.

14.3 Compile-time value parameters

- 1 A parameter declared `comptime name non-type` is a compile-time value parameter. The argument shall be a constant expression of the declared type known at compile time.

```
1 type RingBuffer(T type, comptime N int) = type {  
2     items T[N]  
3     head  usize  
4     tail  usize  
5 }
```

14.4 Type as value

- 1 A **func** with return type **type** is a type constructor. Its body shall consist only of expressions and statements that are evaluable at compile time. The return value is a type that the caller may use in type annotations and variable declarations.

```

1 type Option(T type) = type {
2     Some { value T }
3     None
4 }
5
6 var x = Option(int).Some(42)

```

- 2 Type constructors may also be written as **func** declarations returning **type**:

```

1 func Option(T type) type {
2     return type {
3         Some { value T }
4         None
5     }
6 }

```

Constraint

A function returning type shall be declared as **func** (not **proc**).

14.5 Monomorphization

- 1 For each unique combination of comptime arguments at call sites, the implementation produces a separate instantiation of the function. The name of each instantiation in the translation output is *implementation-defined*¹.
- 2 Monomorphization is a compile-time-only operation; at runtime, each call site calls a specific, non-generic function.

14.6 Comptime expression blocks

- 1 A **comptime** { *expr* } expression evaluates *expr* at compile time. The result is a compile-time constant that may be used as a type annotation, array size, or parameter constraint value.

Constraint

A **comptime** expression shall be pure and terminating (i.e., it may only use **func** calls and the constructs permitted in **func** bodies).

14.7 Comptime if

- 1 **comptime if** *cond* { ... } **else** { ... } is a compile-time conditional. Only the taken branch is type-checked and emitted; the other branch is entirely discarded. *cond* shall evaluate to a compile-time boolean constant.

Note

comptime if enables platform-specific code selection without dead-code warnings. It is the preferred way to write code that varies based on compile-time parameters.

¹Implementation-defined behavior: determined by the implementation

14.8 Comptime recursion depth

- 1 The maximum depth of comptime function evaluation is *implementation-defined*². A comptime evaluation that exceeds this depth is *ill-formed* ([E045]).

14.9 Mode preservation in generics

- 1 When a type parameter `T` is substituted with a concrete type, the ownership mode of the parameter is preserved. If a parameter was declared `var T`, and `T` is substituted with a type that has mode `shared` in its declaration, the substituted parameter retains the `var` mode.

Note

This rule ensures that mode annotations in generic functions behave consistently regardless of the concrete type argument.

²Implementation-defined behavior: the implementation's comptime evaluation depth limit; the reference implementation enforces a limit of 256

Chapter 15

Pattern matching

15.1 Overview

- 1 The **case** expression matches a value against a sequence of patterns and evaluates the body of the first matching arm. Every **case** expression shall be exhaustive: the patterns shall collectively cover all possible values of the scrutinee type. The grammar production is *match-expression* (Annex A).

15.2 Syntax

```
1 case expr {  
2     Pattern1: body1  
3     Pattern2: body2  
4     else:      default_body  
5 }
```

- 1 Each arm consists of a pattern (or comma-separated list of patterns) and a body. The body may be a single expression or a block. The arms are tested in declaration order; the first matching arm is taken.

15.3 Patterns

- 1 The following pattern forms are supported:

Matches any value. Must be the last arm. Required for integer and character scrutinees.

Wildcard (~~Literal~~) **Literal pattern** Matches a specific integer or character value: 42:, 'a':.

Enum/ADT variant pattern Matches a specific variant. If the variant has fields, they are bound: Circle(r): ... binds the radius to r.

Range pattern Matches an inclusive range of integer or character values: 1..10: matches 1 through 10.

Multi-pattern (OR) A comma-separated list of patterns on a single arm: 1, 2, 3:

15.4 Exhaustiveness

- 1 A **case** expression is exhaustive if the set of patterns covers all values of the scrutinee type. The rules by type are:

Scrutinee type	Exhaustiveness requirement
Enum	All variants covered, or else arm present
ADT	All variants covered, or else arm present
Integer	else arm always required
u8 (char)	else arm always required
bool	true and false covered, or else

Scrutinee type	Exhaustiveness requirement
Enum	All variants covered, or else arm present
ADT	All variants covered, or else arm present
Integer	else arm always required
u8 (char)	else arm always required
bool	true and false covered, or else

Constraint

A non-exhaustive **case** expression is *ill-formed* ([E014]).

Example

```

1 enum Color { Red, Green, Blue }
2 var c = Color.Red
3
4 case c {
5     Red:    return 1
6     Green:  return 2
7     Blue:   return 3
8 } // exhaustive: all three variants covered

```

15.5 Ownership and match

- By default, **case** expr may consume the scrutinee if it is a linear type. Bindings introduced by variant patterns in consuming arms hold ownership of the bound values.
- case** &expr performs a non-consuming match: the scrutinee is not consumed but instead temporarily borrowed for the duration of the match body (see §??).

Constraint

Inside a **case** &expr body, the scrutinee shall not be mutated or moved ([E004]).

15.6 Case expression result type

- When **case** is used as an expression, all arms shall produce values of compatible types (§??). The type of the **case** expression is the common type.

Constraint

Arms of a **case** expression that produce incompatible types are *ill-formed*.

15.7 String pattern matching

- String literals may appear as patterns. A string pattern matches if the scrutinee has the same byte sequence and length as the pattern literal. The comparison is performed byte-by-byte (analogous to memcmp).

Note

String pattern matching in the translation output is implemented as a sequence of byte comparisons or `memcmp` calls, depending on the implementation. Its asymptotic cost is $O(n)$ in the pattern length.

Chapter 16

Module system

16.1 Overview

- 1 Each Lain source file defines one module. Modules are the unit of code organization and compilation. All names declared at the top level of a source file are in that module's scope and are accessible from other modules that import the module.

16.2 Module declarations

- 1 A top-level **module** `path.name` declaration declares the module name for the current source file. Module declarations are optional; if absent, the module name is *implementation-defined*¹.

16.3 Import declarations

- 1 **import module**.`path` makes the declarations of the named module available in the current source file. The grammar production is *import-declaration* (Annex A).
- 2 **Path resolution**: a module path is converted to a file system path by replacing dots with directory separators and appending `.ln`. The search is relative to the compiler's working directory. *implementation-defined*².

Module path	File path
<code>std.c</code>	<code>std/c.ln</code>
<code>std.io</code>	<code>std/io.ln</code>
<code>std.fs</code>	<code>std/fs.ln</code>
<code>std.math</code>	<code>std/math.ln</code>
<code>mylib.utils</code>	<code>mylib/utils.ln</code>

16.4 Module loading

- 1 When the compiler encounters an **import** declaration:
 1. The module path is converted to a file path.
 2. If the module has already been loaded, the import is a no-op (deduplication).

¹Implementation-defined behavior: derived from the file path by the implementation

²Implementation-defined behavior: The exact search algorithm, including support for search paths, is implementation-defined

3. Otherwise, the file is read, lexed, parsed, and recursively resolved.
4. The loaded module's declarations are merged into the importing module's declaration list.
- 2 Each module is loaded at most once. Circular imports are therefore implicitly handled: if module A imports module B which imports module A, the second import of A is a no-op because A is already loaded.

Note

The reference implementation maintains a linked list of loaded modules keyed by their dot-separated name.

16.5 Name visibility

- 1 By default, every name declared at module scope is *public*: visible to any module that imports the declaring module. This default matches the typical usage where module declarations form an API surface.
- 2 A declaration prefixed with the attribute **[private]** (§??) is *module-private*: it is visible only within the defining module and may not be referenced from any importing module.

```

1 // In module foo.bar:
2 func public_api() int { ... }    // public by default
3
4 [private]
5 func internal_helper() int { ... } // only foo.bar may
   reference this

```

Constraint

Q-018. A reference to a **[private]** declaration from a module other than the one where it is defined is *ill-formed* ([E084]). The reference may appear in any expression position—identifier lookup, member access, type instantiation, etc.

Note

Compilation under the reference implementation translates each **[private]** declaration to a C declaration with internal linkage (**static** storage class), and each public declaration to one with external linkage.

16.6 Standard library module paths

- 1 The following module paths are defined by this specification for the standard library:

Module path	Description
<code>std.c</code>	C standard library bindings
<code>std.io</code>	Console I/O
<code>std.fs</code>	File system operations
<code>std.math</code>	Mathematical functions

16.7 Name mangling

- ¹ The name of a `Lain` declaration in the translation output is *implementation-defined*³. The reference implementation uses the function name prefixed with the module path, with dots replaced by underscores. Name collisions between modules are *implementation-defined*⁴.

³Implementation-defined behavior: determined by the implementation

⁴Implementation-defined behavior: detected by the implementation; the reference implementation appends a numeric suffix to resolve conflicts

Chapter 17

C interoperability

17.1 Overview

- 1 Lain compiles to C99 and provides direct, zero-overhead interoperability with C libraries through three mechanisms:
 1. `c_include` — injects C `#include` directives;
 2. `extern` declarations — declares C functions for use in Lain;
 3. type mapping — Lain types map to their C99 counterparts.

17.2 The `c_include` declaration

- 1 `c_include "header.h"` causes the compiler to emit a `#include` directive in the generated C code. The string content is emitted verbatim.

```
1 c_include "<stdio.h>"
2 c_include "<stdlib.h>"
```

Constraint

`c_include` shall appear only at module top level.

17.3 Extern function declarations

- 1 `extern func name(params) return` declares a C function that Lain treats as pure. It may be called from both `func` and `proc` contexts.
- 2 `extern proc name(params) return` declares a C function with potential side effects. It may be called only from `proc` contexts.

Constraint

Calling an `extern proc` from a `func` is *ill-formed* ([E011]).

Note

Trust boundary — I-016. An `extern func` declaration is a *programmer assertion* that the referenced C function is pure (deterministic, no side effects, no access to mutable global state). The Lain compiler cannot verify this property and trusts the declaration. Misuse—for example, declaring `libc_rand` or `malloc` as `extern func`—is a programmer error, not a compile error, and may invalidate the guarantees that depend on purity (notably P4

determinism for any **func** that transitively calls the misdeclared extern). When in doubt, use **extern proc**.

- 3 Ownership annotations on extern parameters work identically to those on native Lain functions; the borrow checker tracks ownership of resources obtained via extern calls.

17.4 Type mapping

- 1 The following table defines the normative mapping between Lain types and their C99 equivalents. The mapping is the ABI used by the translation output.

	Lain type	C99 type	Notes
u8	<code>uint8_t</code>		
u16	<code>uint16_t</code>		
u32	<code>uint32_t</code>		
u64	<code>uint64_t</code>		
usize	<code>size_t</code>		pointer-sized
i8	<code>int8_t</code>		
i16	<code>int16_t</code>		
i32	<code>int32_t</code>		
i64	<code>int64_t</code>		
isize	<code>ptrdiff_t</code>		pointer-sized
int	<code>int</code>		at least 32-bit
f32	<code>float</code>		IEEE 754
f64	<code>double</code>		IEEE 754
bool	<code>int</code>		<i>implementation-defined</i> ¹
shared struct T	<code>const T*</code>		
var struct T	<code>T*</code>		
mov struct T	<code>T</code>		by value
[T]	<code>struct { T* data; size_t len; }</code>		fat pointer
T	<code>const T</code>		unsafe only
var *T	<code>T*</code>		unsafe only

17.5 ABI for function parameters

- 1 This table is normative and applies to all Lain function calls, including those to **extern** functions.

	Lain param	Type	C param	Direction
	name T	struct	<code>const T*</code>	in
	var name T	struct	<code>T*</code>	in/out
	mov name T	struct	<code>T</code>	in (by value)
	any mode	primitive	<code>T</code>	in

¹Implementation-defined behavior: 0 or 1

17.6 Pointer operations

- 1 Raw pointer operations (`*ptr` dereference, `&x` address-of) require an `unsafe` block (see §??).

Constraint

Pointer-to-pointer or integer-to-pointer casts shall occur only inside an `unsafe` block ([E012]).

17.7 String interop

- 1 Lain strings (`[u8]`) are byte slices, not null-terminated C strings. To pass a Lain string to a C function expecting `char*`, the `.data` pointer must be extracted explicitly:

```
1 c_include "<stdio.h>"
2 extern proc puts(s *u8) int
3
4 var s = "hello"
5 puts(s.data)    // OK: .data is *u8 = const char*
```

- 2 String literals are null-terminated (§??), so `literal.data` is a valid `const char*` for C functions that expect a C string.

17.8 Opaque C types

- 1 An opaque C type is declared with `extern type Name`. The type's layout is unknown to Lain; it may only be used behind a pointer.

```
1 extern type FILE
2 extern proc fopen(path *u8, mode *u8) mov *FILE
```

Constraint

An opaque type shall not be used as a value type (only as a pointer target). `var f FILE` is *ill-formed*.

Chapter 18

Unsafe code

18.1 Purpose

- 1 The `unsafe` block provides a controlled escape hatch for operations that a conforming implementation cannot statically verify. Unsafe blocks are explicitly delimited in the source text and are therefore auditable. Unsafe code cannot accidentally spread outside the enclosing block.

18.2 Syntax

- 1 An unsafe block is written as `unsafe { body }`. It may appear wherever a statement is valid (§??).

18.3 What unsafe enables

- 1 Inside an `unsafe` block, the following operations are permitted:
 1. **Raw pointer dereference:** `*ptr` reads the value pointed to by a raw pointer; `*ptr = v` writes through a mutable raw pointer.
 2. **Address-of:** `&x` creates a raw pointer to the storage of `x`.
 3. **Pointer and integer casts:** `p as *T`, `n as *T`, `p as usize`, etc.
 4. **Direct ADT field access:** accessing a field of an ADT variant without going through a `case` arm.
 5. **Bounds-check suppression:** array indexing inside an `unsafe` block does not require a VRA proof (the programmer asserts the access is in bounds).

18.4 What unsafe does NOT disable

- 1 The following safety features remain active inside `unsafe` blocks:

Feature	Disabled by <code>unsafe</code> ?
Pointer dereference	Yes
Pointer/integer casts	Yes
Direct ADT field access	Yes
Bounds check requirement	Yes
Ownership tracking ([E001]–[E007])	No

Feature	Disabled by <code>unsafe</code> ?
Borrow checking ([E004])	No
Move semantics	No
Type checking	No
Division-by-zero check ([E015])	No
Exhaustiveness checking ([E014])	No
Purity enforcement ([E011])	No

Constraint

Ownership and linearity rules (§ ??) are not suspended inside `unsafe` blocks. Use-after-move, double-move, and borrow conflicts are still constraint violations inside `unsafe` ([E001]–[E007]).

18.5 Undefined behavior in `unsafe`

- ¹ The following operations inside an `unsafe` block may produce **undefined behavior**¹:
 - Dereferencing a null pointer.
 - Dereferencing a pointer to freed or uninitialized memory.
 - Writing to memory through a pointer derived from a read-only (shared) source.
 - Accessing an array element with an out-of-range index.
 - Accessing a field of an ADT through a tag that does not match the active variant.
- ² A conforming implementation that generates C99 translation output inherits the undefined behavior rules of ISO/IEC 9899 (C17) for operations within `unsafe` blocks.

18.6 Borrow scope for `unsafe` blocks

- ¹ An `unsafe` block is a regular block scope for the purposes of borrow checking. Borrows registered within the block are released on block exit, and the borrow checker’s invariants hold at the block boundaries.

18.7 Nesting

- ¹ `unsafe` blocks may be nested. The inner block does not extend the permissions of the outer block beyond what is already enabled. *implementation-defined*².

¹Undefined behavior: undefined behavior if the programmer’s safety assertion is incorrect

²Implementation-defined behavior: Whether the implementation issues a diagnostic for redundant nested `unsafe` blocks is implementation-defined

Chapter 19

Memory model

19.1 Overview

- 1 Lain’s memory model is founded on three invariants:
 1. **Deterministic allocation** — every allocation is explicit and predictable; the implementation never implicitly allocates heap memory.
 2. **Zero runtime overhead** — there is no garbage collector and no reference-counting mechanism.
 3. **C99 layout compatibility** — the physical layout of all objects follows ISO/IEC 9899 (C17) rules exactly.
- 2 This clause specifies the abstract notions of *object*, *storage duration*, *object representation*, and *address*. The abstract machine described here is realised by any conforming translation output (§??).

19.2 Objects

- 1 An *object* is a contiguous region of storage that holds a value of a declared type. Every variable declaration introduces exactly one object. Fields of a struct introduce sub-objects. Elements of a fixed-size array introduce element sub-objects.
- 2 Every object has:
 - a *declared type* (§??);
 - an *ownership mode* — shared, **var**, or **mov** (§??);
 - a *linear state* — UNINIT, UNCONSUMED, or CONSUMED (§??);
 - a *storage duration* (§??);
 - an *address* — the byte address of its first storage unit, aligned as required by the target platform.

19.3 Storage duration

- 1 Three storage durations are defined:

Automatic duration Objects declared inside a function or block body (including function parameters) have automatic storage duration. Storage is allocated when the enclosing scope is entered and released when that scope exits.

Static duration Objects declared at module scope have static storage duration. Their storage persists for the entire program execution. *implementation-defined*¹.

Heap (explicit) duration Objects allocated through C interop (`malloc` or equivalent) have programmer-controlled duration. The ownership system (§??) enforces that `mov` pointers to heap memory are consumed exactly once ([E003]).

Constraint

A `return` statement shall not return a reference whose referent has automatic storage duration ([E010]).

19.4 Stack allocation

- 1 All local variables, struct values, and fixed-size arrays are allocated on the call stack. No implicit heap allocation is ever performed by the compiler.

```
1 var x int = 42           // stack: sizeof(int32_t) bytes
2 var arr int[100]         // stack: 100 * sizeof(int32_t) bytes
3 var p Point              // stack: sizeof(Point) bytes
```

- 2 Each function call produces a *stack frame* containing:
 - all local variables declared in the function;
 - all function parameters (by value or by pointer, per the calling convention of §??);
 - compiler-generated temporaries required for expression evaluation.
- 3 The stack frame is automatically reclaimed when the function returns. *implementation-defined*².

19.5 Heap allocation

- 1 Heap allocation is performed exclusively through C interop (§??). The idiomatic pattern declares the C `malloc/free` pair as `extern proc`:

```
1 c_include "<stdlib.h>"
2 extern proc malloc(size usize) mov *void
3 extern proc free(ptr mov *void)
```

- 2 Because `malloc` returns `mov *void`, the caller receives sole ownership of the allocated block. Because `free` consumes `mov *void`, calling `free` transfers that ownership to the allocator. The ownership system therefore enforces statically:

- **No use-after-free:** using the pointer after `free` is a use-after-move ([E001]).
- **No double-free:** a second call to `free` on the same pointer is a double-consume ([E002]).
- **No leak:** failing to call `free` on a `mov` pointer is an unconsumed linear value ([E003]).

¹Implementation-defined behavior: The value of a static-duration object whose declaration lacks an initializer is implementation-defined; the reference implementation zero-initializes such objects via C99 static initialization rules

²Implementation-defined behavior: The implementation's behaviour when the call stack is exhausted is implementation-defined; the reference implementation inherits the platform's stack overflow signal

19.6 Value semantics

- 1 The behaviour of assignment and function argument passing is determined by the type's linearity and the ownership mode:

Type	Assignment <code>b = a</code>	Notes
Primitives (<code>int</code> , <code>bool</code> , ...)	Bitwise copy	Always allowed
Non-linear struct	Field-by-field copy	Allowed
Linear struct (has <code>mov</code> field)	Forbidden	Requires <code>mov</code>
Non-linear array	Element-wise copy	Allowed
Linear array	Forbidden	Requires <code>mov</code>
Slice (<code>[T]</code>)	Copy <code>{data, len}</code> pair	Always allowed
Raw pointer (<code>*T</code>)	Copy address	Always allowed

Constraint

Copying a linear type without an explicit `mov` expression is *ill-formed* ([E006]).

19.7 Object representation

- 1 The *object representation* of a Lain type is its C99 equivalent as defined in § ???. Every object is a sequence of `u8` bytes whose count equals the C99 `sizeof` of the corresponding C type.
- 2 *Value equality* is defined per type:
 - Primitives: bitwise equality of the value representation.
 - Structs: field-by-field value equality.
 - Slices: equality of both the data pointer and the length.
 - Raw pointers: address equality.
 - ADTs: tag equality and, when tags match, field-by-field equality of the active variant.

19.8 Alignment and layout

- 1 Lain inherits ISO/IEC 9899 (C17) alignment and padding rules:
 - Struct fields are laid out in declaration order.
 - Each field is aligned to its natural alignment (the alignment of its C99 equivalent type).
 - The compiler inserts padding between fields as necessary.
 - The total size of a struct is rounded up to a multiple of its largest field alignment.
- 2 Lain does not provide layout control annotations. There is no `#pragma pack` equivalent, no `alignas`, and no `repr(packed)`. The layout is always the platform-default C99 layout. *implementation-defined*³.

³Implementation-defined behavior: The exact size and alignment of each type is implementation-defined, following the C99 ABI of the target platform

19.9 ADT and enum layout

- 1 An enum type is emitted as a C `enum` wrapped in a named struct so that each enum type is nominally distinct in the C translation:

```
typedef enum { Color_Red, Color_Green, Color_Blue } Color_Tag;
typedef struct { Color_Tag tag; } Color;
```

- 2 An ADT type uses a niche-based encoding whenever a zero-cost representation is derivable (Q-012, Z5 zero-by-construction). When no niche is available, the ADT falls back to a tagged union:

```
// Tagged-union fallback (only when no niche is derivable):
typedef struct {
    enum { Shape_Circle_tag, Shape_Rect_tag } tag;
    union {
        struct { float r; } Circle;
        struct { float w; float h; } Rect;
    };
} Shape;
```

- 3 *Niche encoding (zero-cost)*. When the payload of one variant contains a bit pattern that cannot occur in valid values—for instance, `0x0` for a pointer field, or a value outside a VRA-proven range for an integer field—that pattern is reserved to encode an alternative variant. No explicit tag is emitted.

```
// Niche encoding for Option(*File): size = sizeof(*File)
typedef File *Option_Ptr_File;
// Some(p)    -> non-null pointer p
// None       -> 0x0
```

- 4 If neither a niche nor a tag+union encoding can be derived—in particular, if a variant payload uses every bit pattern of its type and the user has not provided a value-range constraint—compilation fails with **[E120]**. The diagnostic suggests adding an explicit constraint or using the built-in `NonZero(T)` wrapper.

Note

Multiple-variant niches (3 or more variants) may combine pointer alignment bits (the low three bits of an aligned pointer carry up to eight tag values for free) with payload niches. The reference implementation searches niches in priority order: NULL, VRA-constrained range, bit patterns of `bool`/small enum, recursive niche of any field.

19.10 No garbage collector

- 1 Lain has no garbage collector. Consequently:
 - execution is never interrupted for memory management;
 - deallocation occurs at statically deterministic program points;
 - no reference counting or heap tracing is performed at runtime.
- 2 This makes Lain suitable for real-time, embedded, and safety-critical applications where garbage-collection pauses are unacceptable.

19.11 Memory safety in the safe fragment

- ¹ In the *safe fragment* (code outside `unsafe` blocks), the following memory safety properties hold by construction:

Property	Enforcement mechanism
No use-after-free	[E001] (use-after-move)
No double-free	[E002] (double-consume)
No leak of linear values	[E003] (unconsumed at scope exit)
No dangling references	[E010] (ref to automatic-duration object)
No out-of-bounds access	[E014] (VRA proof failure)
No null-pointer deref	No raw pointers in safe fragment
No data races	No concurrency in current version

Constraint

Inside `unsafe` blocks, pointer operations may violate the above properties if the programmer's safety assertion is incorrect (§??).

19.12 Compiler-internal arena (informative)

Note

The reference implementation uses a bump-pointer arena internally for all AST nodes, symbol table entries, and diagnostic objects. This arena is an implementation detail; it is never exposed to user code. User programs may implement arena allocators of their own through C interop.

Chapter 20

Standard library

20.1 Overview

- 1 The Lain standard library is a collection of modules under the `std` namespace (§??). All standard library modules are written in Lain, using C interop (§??) for system-level operations. They are subject to the same ownership, borrow-checking, and purity rules as user code.
- 2 This clause is normative for the modules listed in Table ?? . All other modules described in informative documentation are not part of this specification.

Table 20.1: Standard library module index

Module path	Description	Status
<code>std.c</code>	C standard library bindings	Normative
<code>std.io</code>	Console I/O	Normative
<code>std.fs</code>	File system operations	Normative
<code>std.math</code>	Pure mathematical functions	Normative

Constraint

A conforming implementation shall provide all modules listed in Table ?? at the specified module paths.

20.2 std.c — C standard library bindings

20.2.1 Purpose

- 1 `std.c` provides low-level bindings to selected C standard library functions. It is the foundation on which all other standard library modules that require system calls are built.

20.2.2 Required C headers

- 2 `std.c` emits the following C include directives into the translation output:

```
1 c_include "<stdio.h>"
2 c_include "<stdlib.h>"
```

20.2.3 Opaque types

- 3 `std.c` declares the following opaque C type:

```
1 extern type FILE
```

FILE is an opaque type representing a C standard I/O stream. It may only be used through pointers and passed to the `extern` functions declared below.

Constraint

FILE shall not be used as a value type. A declaration such as `var f FILE` is *ill-formed* (§??).

20.2.4 Extern declarations

4 The following C functions are declared in `std.c`:

Declaration	Ownership notes
<code>extern proc libc_printf(fmt *u8, ...)int</code>	Shared <code>fmt</code> ; variadic
<code>extern proc libc_puts(s *u8)int</code>	Shared <code>s</code>
<code>extern proc fopen(filename *u8, mode *u8)mov *FILE</code>	Returns owned handle
<code>extern proc fclose(stream mov *FILE)int</code>	Consumes handle
<code>extern proc fputs(s *u8, stream *FILE)int</code>	Shared args
<code>extern proc fgets(s var *u8, n int, stream *FILE)var *u8</code>	Mutable buffer

Note

`libc_printf` and `libc_puts` are renamed to avoid conflicts with user-defined functions named `printf` and `puts`.

20.3 std.io — Console I/O

20.3.1 Dependencies

1 `std.io` imports `std.c`.

20.3.2 print

print (*module std.io*)

Synopsis: `proc print(s [u8])`

Effect: Writes the byte sequence `s.data[0..s.len-1]` to standard output. No trailing newline is appended.

Parameter s: Shared borrow of a byte slice.

20.3.3 println

println (*module std.io*)

Synopsis: `proc println(s [u8])`

Effect: Writes the byte sequence `s.data[0..s.len-1]` to standard output, followed by a newline character (0x0A).

Parameter s: Shared borrow of a byte slice.

20.4 std.fs — File system

20.4.1 Dependencies

- 1 std.fs imports std.c.

20.4.2 Type: File

- 2 File is a linear struct that wraps a C FILE* handle:

```
1 type File {
2     mov handle *FILE
3 }
```

- 3 Because handle is annotated **mov**, File is a linear type. It must be consumed exactly once, typically by calling close_file.

20.4.3 open_file

open_file (module std.fs)

Synopsis: **proc** open_file(path [u8], mode [u8])**mov** File

Effect: Opens the file at path with the access mode mode (C fopen semantics). Returns an owned File value. The caller is responsible for closing the file by consuming the File.

Parameter path: Shared borrow of a null-terminated path string.

Parameter mode: Shared borrow of a mode string ("r", "w", "a", etc.).

Note

If fopen returns null, the handle field is a null pointer. Subsequent operations on such a file produce C-level undefined behavior. A future version may return Result(File, int) instead.

20.4.4 close_file

close_file (module std.fs)

Synopsis: **proc** close_file(**mov** {handle} File)

Effect: Closes the file by calling C fclose on the extracted handle pointer. Consumes the File value.

Parameter: The File value is consumed by the call; it shall not be used after this point.

20.4.5 write_file

write_file (module std.fs)

Synopsis: `proc` write_file(f File, s [u8])

Effect: Writes the byte sequence `s` to the file `f` using C `fputs`.

Parameter f: Shared borrow of the file handle.

Parameter s: Shared borrow of the string to write.

Example

```
1 import std.fs
2
3 proc main() int {
4     var f = open_file("log.txt", "w")
5     defer { close_file(mov f) }
6     write_file(f, "Hello, world!\n")
7     return 0
8 }
```

20.5 std.math — Mathematical functions

20.5.1 Overview

- 1 All functions in `std.math` are declared `func` (pure and terminating). They may be called from any context, including other `func` bodies. `std.math` has no dependencies.

20.5.2 min

min (module *std.math*)

Synopsis: `func` min(a int, b int)int

Returns: The smaller of `a` and `b`. If `a == b`, either may be returned (they are equal).

20.5.3 max

max (module *std.math*)

Synopsis: `func` max(a int, b int)int

Returns: The larger of `a` and `b`.

20.5.4 abs

abs (module *std.math*)

Synopsis: `func` abs(x int)int

Returns: The absolute value of `x`, i.e., `x` if `x >= 0`, `-x` otherwise.

Note

`abs(INT_MIN)` produces implementation-defined behaviour because `|INT_MIN|` is not representable as `int` on two's complement platforms.

20.5.5 clamp

clamp (module *std.math*)

Synopsis: `func clamp(x int, lo int, hi int) int`

Returns: `x` clamped to the inclusive range `[lo, hi]`, i.e., `max(lo, min(x, hi))`.

Constraint

Behaviour is **undefined behavior**^a if `lo > hi`.

^aUndefined behavior: undefined

20.6 Generic types (informative)

- 1 This section describes generic type constructors that are part of the standard library but are not normative in the current version of this specification.

20.6.1 Option(T)

- 2 `Option(T)` is a type constructor for optional values:

```
1 func Option(T type) type {
2     return type {
3         Some { value T }
4         None
5     }
6 }
```

- 3 Usage:

```
1 type OptionInt = Option(int)
2 var x = OptionInt.Some(42)
3 case x {
4     Some(v): libc_printf("value: %d\n", v)
5     None:    libc_printf("no value\n")
6 }
```

20.6.2 Result(T, E)

- 4 `Result(T, E)` is a type constructor for fallible computations:

```
1 func Result(T type, E type) type {
2     return type {
3         Ok { value T }
4         Err { error E }
5     }
6 }
```

- 5 Usage:

```
1 type FileResult = Result(File, int)
2
3 proc try_open(path [u8]) FileResult {
4     var f = open_file(path, "r")
5     return FileResult.Ok(mov f)
6 }
```


Grammar summary

- 6 This annex collects all grammar productions defined in this specification. It is normative. Productions are listed in the order they are introduced in the body of the specification. Each section heading identifies the originating clause.
- 7 The grammar uses an extended BNF notation. `::=` introduces a production. Quoted strings are terminals. Unquoted names are non-terminals. `{ X }` denotes zero or more repetitions. `[ X ]` denotes an optional item. `A | B` denotes alternatives.

§5 Lexical grammar

§5.5 Tokens

```
token ::=
    keyword
  | identifier
  | integer-literal
  | float-literal
  | string-literal
  | char-literal
  | bool-literal
  | operator
  | punctuator
```

§5.6 Keywords

```
keyword ::=
    "func" | "proc" | "var" | "mov" | "shared"
  | "return" | "if" | "else" | "while" | "for"
  | "in" | "case" | "import" | "module" | "struct"
  | "enum" | "unsafe" | "comptime" | "defer" | "ref"
  | "mut" | "true" | "false" | "and" | "or"
  | "not" | "as" | "decreasing" | "end"
```

§5.7 Identifiers

```
identifier      ::= identifier-start { identifier-continue }
identifier-start ::= letter | "_"
identifier-continue ::= letter | decimal-digit | "_"
letter          ::= "A" .. "Z" | "a" .. "z"
```

§5.8 Literals

```
integer-literal ::=
    decimal-literal
  | hex-literal
  | binary-literal
  | octal-literal
```

```
decimal-literal ::= nonzero-digit { decimal-digit | "_" }
                  | "0"
hex-literal     ::= "0x" hex-digit { hex-digit | "_" }
binary-literal  ::= "0b" binary-digit { binary-digit | "_" }
octal-literal   ::= "0o" octal-digit { octal-digit | "_" }

decimal-digit   ::= "0" .. "9"
nonzero-digit   ::= "1" .. "9"
hex-digit       ::= decimal-digit | "a" .. "f" | "A" .. "F"
binary-digit    ::= "0" | "1"
octal-digit     ::= "0" .. "7"

float-literal    ::= decimal-literal "." decimal-literal [ float-exponent ]
float-exponent  ::= ( "e" | "E" ) [ "+" | "-" ] decimal-literal

string-literal   ::= '"' { string-char } '"'
string-char      ::= any-source-char-except-'\"'-or-'\\' | escape-sequence
escape-sequence  ::= '\\' ( '"' | '\\' | "n" | "t" | "r" | "0" )

bool-literal     ::= "true" | "false"
```

§5.9 Operators and punctuators

```
operator         ::=
    "+" | "-" | "*" | "/" | "%"
    | "==" | "!=" | "<" | ">" | "<=" | ">="
    | "and" | "or" | "not" | "in"
    | "&" | "|" | "^" | "<<" | ">>"
    | "=" | "+=" | "-=" | "*=" | "/=" | "%="
    | "&=" | "|=" | "^=" | "<<=" | ">>="
    | "->" | "." | ".."

punctuator       ::=
    "(" | ")" | "{" | "}" | "[" | "]"
    | ":" | "," | "@"
```

§6 Program structure grammar

```
program          ::= { top-level-declaration }
top-level-declaration ::=
    module-declaration
    | import-declaration
    | struct-declaration
    | enum-declaration
    | function-declaration
    | procedure-declaration
    | comptime-declaration

module-declaration ::= "module" qualified-identifier newline
import-declaration  ::= "import" qualified-identifier newline
qualified-identifier ::= identifier { "." identifier }
```

§7 Type grammar

```
type             ::=
    primitive-type
    | array-type
```

```

| slice-type
| pointer-type
| qualified-type
| constrained-type
| user-defined-type

primitive-type ::=
    "int"   | "u8"   | "u16"  | "u32"  | "u64"  | "usize"
  | "i8"   | "i16"  | "i32"  | "i64"  | "isize"
  | "f32"  | "f64"
  | "bool" | "str"  | "void"

array-type      ::= "[" type ";" integer-literal "]"
slice-type      ::= "[" type "]"
pointer-type    ::= "*" type | "const" "*" type
qualified-type  ::= ownership-qualifier type
ownership-qualifier ::= "shared" | "var"
user-defined-type ::= qualified-identifier
constrained-type ::= type relational-op integer-literal
                    { ( "and" | "or" ) type relational-op integer-literal }
relational-op   ::= ">=" | "<=" | ">" | "<" | "=="

```

§8 Expression grammar

```

expression      ::= assignment-expression

assignment-expression ::=
    logical-or-expression
  | lvalue-expression assignment-operator assignment-expression

assignment-operator ::=
    "=" | "+=" | "-=" | "*=" | "/=" | "%="
  | "&=" | "|=" | "^=" | "<<=" | ">>="

logical-or-expression ::= logical-and-expression { "or" logical-and-expression }

logical-and-expression ::= in-expression { "and" in-expression }

in-expression      ::= equality-expression { "in" equality-expression }

equality-expression ::= relational-expression
                    { ( "==" | "!=" ) relational-expression }

relational-expression ::= shift-expression
                    { ( "<" | ">" | "<=" | ">=" ) shift-expression }

shift-expression    ::= additive-expression
                    { ( "<<" | ">>" ) additive-expression }

additive-expression ::= multiplicative-expression
                    { ( "+" | "-" ) multiplicative-expression }

multiplicative-expression ::= cast-expression
                    { ( "*" | "/" | "%" ) cast-expression }

cast-expression     ::= unary-expression { "as" type }

unary-expression    ::=

```

```

    postfix-expression
  | unary-operator unary-expression

unary-operator      ::= "-" | "not" | "!" | "mov" | "ref" | "mut"

postfix-expression  ::=
    primary-expression
  | postfix-expression "." identifier
  | postfix-expression "[" expression "]"
  | postfix-expression "(" [ argument-list ] ")"

argument-list       ::= expression { "," expression }

primary-expression  ::=
    identifier
  | literal
  | "(" expression ")"
  | block-expression
  | if-expression
  | match-expression
  | constructor-expression
  | comptime-expression

literal             ::=
    integer-literal
  | float-literal
  | string-literal
  | bool-literal

block-expression    ::= "{" { statement } expression}"

if-expression       ::=
    "if" expression block-expression
  [ "else" ( if-expression | block-expression ) ]

match-expression    ::=
    "case" [ "&" ] expression "{"
    { match-arm }
    "}"

match-arm           ::= pattern [ "if" expression ] block-expression

pattern             ::=
    "_"
  | literal
  | identifier
  | qualified-identifier "(" [ pattern-list ] ")"
  | qualified-identifier "{" [ field-pattern-list ] "}"

pattern-list        ::= pattern { "," pattern }
field-pattern-list  ::= identifier ":" pattern { "," identifier ":" pattern }

constructor-expression ::=
    qualified-identifier "{" [ field-init-list ] "}"
  | qualified-identifier "(" [ argument-list ] ")"

field-init-list     ::= identifier ":" expression { "," identifier ":" expression }

```

```
comptime-expression ::= "comptime" block-expression
```

```
lvalue-expression ::=
    identifier
  | postfix-expression "." identifier
  | postfix-expression "[" expression "]"
```

§9 Statement grammar

```
statement ::=
    block-statement
  | var-declaration
  | assignment-statement
  | expression-statement
  | if-statement
  | while-statement
  | bounded-while-statement
  | return-statement
  | defer-statement
  | unsafe-block
  | comptime-if-statement
```

```
block-statement ::= "{" { statement } "}"
```

```
var-declaration ::= "var" identifier [ ":" type ] "=" expression newline
```

```
assignment-statement ::= lvalue-expression assignment-operator expression newline
```

```
expression-statement ::= expression newline
```

```
if-statement ::=
    "if" expression block-statement
  { "else" "if" expression block-statement }
  [ "else" block-statement ]
```

```
while-statement ::= "while" expression block-statement
```

```
bounded-while-statement ::=
    "while" expression "decreasing" expression block-statement
```

```
return-statement ::= "return" [ expression ] newline
```

```
defer-statement ::= "defer" block-statement
```

```
unsafe-block ::= "unsafe" block-statement
```

```
comptime-if-statement ::=
    "comptime" "if" expression block-statement
  [ "else" block-statement ]
```

§10 Declaration grammar

```
function-declaration ::=
    "func" identifier
  [ "[" comptime-param-list "]" ]
  "(" [ param-list ] ")" return-annotation
  block-statement
```

```
procedure-declaration ::=
    "proc" identifier
    [ "[" comptime-param-list "]" ]
    "(" [ param-list ] ")" return-annotation
    block-statement

return-annotation    ::= type [ relational-op integer-literal ]
                    | ( empty )

param-list           ::= param { "," param }
param                ::= [ ownership-qualifier ] identifier type
                    | "comptime" identifier "type"

comptime-param-list  ::= comptime-param { "," comptime-param }
comptime-param       ::= identifier "type"

struct-declaration   ::= "struct" identifier "{" { field-declaration } "}"
field-declaration    ::= identifier type newline

enum-declaration     ::= "enum" identifier "{" { variant-declaration } "}"
variant-declaration  ::=
    identifier newline
    | identifier "(" type-list ")" newline
    | identifier "{" field-declaration-list "}" newline

type-list            ::= type { "," type }
field-declaration-list ::= field-declaration { field-declaration }

comptime-declaration ::= "comptime" block-statement
```

Diagnostic codes

- 8 This annex is normative. It lists every diagnostic code defined by this specification, the clause that requires the diagnostic, the category (constraint violation, warning, or informational), and a representative message text. A conforming implementation shall issue a diagnostic for every constraint violation in the table below.
- 9 Diagnostic codes are divided into the following ranges:

Range	Domain
[E001]–[E010]	Ownership and lifetime
[E011]–[E015]	Purity, safety, and verification
[E045]	Compile-time evaluation
[E080]–[E082]	Bounded while verification
[E100]	Miscellaneous
[VRA]	Value range analysis

Ownership and lifetime diagnostics ([E001]–[E010])

Code	Clause	Message and trigger
[E001]	§ ??	<i>use of moved value 'x'</i> — Issued when an expression reads or passes a variable whose linear state is CONSUMED.
[E002]	§ ??	<i>value 'x' consumed twice</i> — Issued when a second mov expression is applied to a variable already in state CONSUMED.
[E003]	§ ??	<i>linear value 'x' not consumed before end of scope</i> — Issued when a mov -mode variable exits scope in state UNCONSUMED.
[E004]	§ ??	<i>cannot borrow 'x' as mutable; it is already borrowed</i> — Issued when a mutable borrow conflicts with an existing borrow (reads or write).
[E005]	§ ??	<i>cannot borrow 'x' as shared; it is already mutably borrowed</i> — Issued when a shared borrow is requested while a mutable borrow is active.
[E006]	§ ??	<i>cannot copy linear type 'T'</i> — Issued when assignment or argument passing implicitly copies a type that has a mov -mode field.

Code	Clause	Message and trigger
[E007]	§??	<i>cannot assign through a shared reference 'x'</i> — Issued when a write is attempted through a shared (non- var) binding.
[E010]	§??	<i>cannot return reference to local variable 'x'</i> — Issued when a return statement returns a reference whose referent has automatic storage duration.

Purity, safety, and verification ([E011]–[E015])

Code	Clause	Message and trigger
[E011]	§??	<i>impure operation in pure function 'f'</i> — Issued when a func body contains a call to a proc , an unbounded while without a decreasing measure, or a direct/mutual recursion without a measure.
[E012]	§??	<i>pointer cast outside unsafe block</i> — Issued when a pointer-to-pointer or integer-to-pointer cast occurs outside an unsafe block.
[E013]	§??	<i>use of undeclared identifier 'x'</i> — Issued when an identifier is referenced before its declaration in scope.
[E014]	§??, §??	<i>index 'i' not proven in bounds of 'arr'</i> — Issued when VRA cannot prove that an array index expression is within $[0, n - 1]$. Also issued for non-exhaustive case expressions when combined with the exhaustiveness diagnostic (shared code path).
[E015]	§??	<i>division by zero</i> — Issued when VRA can prove statically that a division or modulo expression has a zero divisor.

Compile-time evaluation ([E045])

Code	Clause	Message and trigger
[E045]	§??	<i>comptime evaluation depth limit exceeded</i> — Issued when compile-time function evaluation recurses beyond the implementation's depth limit (256 in the reference implementation).

Bounded while verification ([E080]–[E082])

Code	Clause	Message and trigger
[E080]	§ ??	<i>termination measure not proven non-negative</i> — Issued when the compiler cannot prove that the decreasing expression is ≥ 0 whenever the loop condition holds.
[E081]	§ ??	<i>termination measure does not depend on a loop variable</i> — Issued when the decreasing expression consists entirely of compile-time constants and therefore cannot strictly decrease.
[E082]	§ ??	<i>termination measure not proven to decrease in loop body</i> — Issued when the compiler cannot verify that every execution of the loop body strictly decreases the measure by at least 1.

Miscellaneous ([E100])

Code	Clause	Message and trigger
[E100]	§ ??, § ??	<i>ill-formed token / semantic constraint violation</i> — A catch-all code used for lexical and syntactic errors without a dedicated code, including: missing semicolons (§ ??), using == on enum types (§ ??), and other single-token syntactic errors.

Value range analysis ([VRA])

Code	Clause	Message and trigger
[VRA]	§ ??	<i>value range proof required</i> — Issued when VRA cannot prove that an operation satisfies its required constraint and more specific code is not available. Appears as a diagnostic prefix in messages such as: “[VRA] cannot prove index in bounds” and “[VRA] return value may not satisfy constraint”.

Language design rationale

- 10 This annex is informative. It explains the reasoning behind key design decisions in the Lain language. Understanding the rationale helps readers interpret edge cases in the normative text and guides implementors when the specification is ambiguous.

.1 The `func`/`proc` distinction

- 1 **Decision.** Separate pure functions (`func`) from side-effecting procedures (`proc`) at the declaration level.
- 2 **Rationale.**
- *Termination guarantees:* a `func` is guaranteed to terminate (no unbounded `while`, no unchecked recursion). This enables the compiler to reason statically about function completion and to use `func` bodies inside `comptime` expressions.
 - *Purity propagation:* the type system propagates purity constraints — a `func` cannot call a `proc`, so pure code stays pure by construction.
 - *Optimisation:* the compiler may freely reorder, memoize, or eliminate calls to `func` because they have no observable side effects.
 - *Readability:* the declaration keyword tells the reader whether a callable has side effects without inspecting its body.
- 3 **Alternatives considered.** Single keyword with a purity annotation (`func(pure)`) was rejected as less visible. A Haskell-style IO monad was rejected as too complex for a systems language.

.2 Explicit `mov` at call sites

- 1 **Decision.** Require explicit `mov` at call sites when transferring ownership.
- 2 **Rationale.**
- *Readability:* `close_file(mov f)` makes ownership transfer visible at the call site.
 - *Intentionality:* accidental ownership transfer is a common source of bugs. Requiring `mov` forces the programmer to acknowledge the transfer.
 - *Symmetry:* the annotation appears in both declarations (`mov x T`) and at call sites (`mov x`), creating a uniform language.
- 3 **Alternatives considered.** Rust-style implicit moves were rejected because they are invisible at call sites. A library function `std::move` (C++) was rejected because ownership transfer should be a language primitive, not a library function.

.3 Implicit NLL lifetimes (no annotations)

- 1 **Decision.** Borrows have implicit lifetimes determined by non-lexical lifetime analysis. No explicit lifetime annotations are required.
- 2 **Rationale.**
 - *Simplicity:* Rust’s lifetime annotations are widely cited as its steepest learning curve. Lain targets programmers who want safety without that complexity.
 - *Sufficient expressiveness:* NLL handles the vast majority of real-world borrow patterns.
 - *Predictability:* borrows expire at last use — a single, intuitive rule.
- 3 **Trade-offs.** Some programs that Rust can verify with explicit lifetime annotations may be rejected by Lain’s more conservative analysis. Higher-order borrowing patterns are constrained.

.4 C99 translation output

- 1 **Decision.** Compile to C99 source code rather than LLVM IR, machine code, or bytecode.
- 2 **Rationale.**
 - *Portability:* C99 compilers exist for every platform, from server-class x86 to microcontrollers. Lain inherits this portability for free.
 - *Toolchain reuse:* users get GCC/Clang optimisation passes, debuggers, profilers, and sanitisers without custom tooling.
 - *Interoperability:* C interop is zero-cost because the output *is* C.
 - *Simplicity:* a C emitter is orders of magnitude simpler than an LLVM backend or a native code generator.
 - *Auditability:* the generated C code is human-readable.
- 3 **Trade-offs.** Compilation is two-phase (Lain $\rightarrow$ C $\rightarrow$ binary). Some optimisations are impossible without direct IR control. The C type system constrains what Lain can express (e.g., no guaranteed tail calls).

.5 No exception mechanism

- 1 **Decision.** Lain has no exception mechanism. All error handling uses return values.
- 2 **Rationale.**
 - *Zero overhead:* no unwinding tables, catch tables, or RTTI.
 - *Determinism:* error handling follows the same control flow as normal code; no invisible jumps.
 - *Embedded compatibility:* stack unwinding is unavailable or unreliable on many embedded platforms.
 - *Explicit error paths:* every error is visible in the function signature (via `Result` return types).
 - *Compatibility with `defer`:* the `defer` mechanism provides deterministic cleanup without exceptions.

.6 Explicit unsafe blocks

- 1 **Decision.** Pointer dereference and direct ADT field access require an explicit `unsafe` block.
- 2 **Rationale.**

- *Auditability:* safety-critical codebases can grep for `unsafe` { to enumerate all potentially dangerous operations.
- *Minimal scope:* Lain’s `unsafe` is narrow — it enables only pointer dereference, address-of, casts, direct ADT access, and bounds suppression. Unlike C (where everything is unsafe by default) or some languages (where `unsafe` enables a much larger capability set), Lain’s `unsafe` is a surgical escape hatch.
- *Social contract:* the keyword communicates to code reviewers that extra scrutiny is warranted.

.7 Value Range Analysis instead of SMT

- 1 **Decision.** Use interval-based VRA for static verification instead of an SMT solver.
- 2 **Rationale.**

- *Decidability:* VRA always terminates in polynomial time. SMT solving is NP-hard in the general case and may time out.
- *Predictability:* programmers can reason about what the compiler will accept by thinking about integer ranges. SMT solver reasoning is opaque.
- *Simplicity:* the VRA implementation is approximately 600 lines. An SMT integration would be orders of magnitude more complex and would introduce an external dependency.

- 3 **Trade-offs.** VRA is incomplete — it may reject valid programs that an SMT solver could prove correct. Non-linear constraints produce conservatively wide ranges.

.8 Comptime generics instead of <T> syntax

- 1 **Decision.** Use compile-time function evaluation with `comptime` parameters instead of traditional generic syntax.
- 2 **Rationale.**

- *Unification:* generics, type aliases, and compile-time assertions all use the same mechanism.
- *Expressiveness:* comptime functions can contain arbitrary logic, enabling type-level programming that traditional generics cannot express.
- *Simplicity:* no angle brackets, no trait bounds, no where clauses. Just functions that take types and return types.
- *Precedent:* inspired by Zig’s comptime approach, which has proven ergonomic in practice.

.9 Universal Function Call Syntax (UFCS)

- 1 **Decision.** Support UFCS: `x.f(args)` desugars to `f(x, args)`.
- 2 **Rationale.**

- *No classes needed:* UFCS provides method-like syntax without class hierarchies, virtual dispatch, or inheritance.

- *Chainability*: enables fluent APIs.
- *Discoverability*: IDE auto-completion works naturally — typing a dot after a value shows available operations.
- *Simplicity*: syntactic sugar only; no new concepts, no method tables, no implicit `this` pointer.

.10 Bounded while in func

- 1 **Decision.** Allow `while` loops in `func` bodies when a `decreasing` termination measure is supplied.
- 2 **Rationale.** Without `decreasing`, any `while` loop in a `func` would require a proof of termination that goes beyond what the compiler can verify automatically. Requiring the programmer to supply a *measure* — a non-negative integer expression that strictly decreases on every iteration — is a well-established technique from program verification (*ranking functions*). The compiler's three checks (non-negativity, variable dependency, strict decrease) are sufficient to verify termination without an external solver.
- 3 This allows algorithms such as binary search and GCD computation to be expressed as `func` without resorting to `proc`.

Comparison with related languages

- ⁴ This annex is informative. It places Lain in the context of other systems-programming languages to help readers understand its design choices. Comparisons are accurate as of the date of this specification; language features evolve and readers should verify current status.

.11 Feature matrix

Feature	Lain	Rust	C	Zig	Go
Memory safety	Compile-time	Compile-time	Manual	Runtime+OFC	OFC
Null safety	Option type	Option type	None	Optional	Nil
Exceptions	None (Result)	None (Result)	errno	Error union	panic/recover
Generics	Comptime	Trait-based	Macros	Comptime	Type params
Lifetime annots.	None (NLL)	Required	N/A	None	N/A
Purity tracking	func / proc	None	None	None	None
Pattern matching	Exhaustive	Exhaustive	switch	switch	switch
UFCS	Yes	No	No	No	No
Backend	C99	LLVM	Native	LLVM	Go compiler
GC / runtime	None	Minimal	None	Minimal	GC

.12 Lain versus Rust

Similarities

- Ownership-based memory safety with no GC.
- Move semantics with explicit transfer.
- No null pointers (Option type for optional values).
- Pattern matching with exhaustiveness checking.
- No exceptions; Result type for error propagation.
- Zero-cost abstractions.

Differences

Aspect	Lain	Rust
Lifetime annotations	Implicit (NLL only)	Explicit ('a, 'static)
Mutable borrow syntax	<code>var x</code> at call site	<code>&mut x</code>
Move syntax	Explicit <code>mov x</code>	Implicit (default)
Generics	Comptime functions	Trait-based + monomorphization
Purity	<code>func/proc</code> enforced	Convention only
Async	Not supported	<code>async/await</code>
Traits / Interfaces	Not supported	Full trait system
Macros	Not supported	<code>macro_rules!</code> + proc macros
Backend	C99	LLVM
Learning curve	Lower	Higher

- 1 **Key insight.** Lain trades Rust's expressiveness (explicit lifetime annotations, trait system, `async/await`) for simplicity. The result is a language that is easier to learn but less expressive for complex borrowing patterns.

.13 Lain versus C

Similarities

- Compiles to native code; no GC.
- Explicit memory management.
- No runtime overhead.
- Systems-level programming: raw pointers accessible in `unsafe`.

Differences

Aspect	Lain	C
Memory safety	Compile-time guarantees	Manual (error-prone)
Type safety	Strong, narrow widening	Weak, implicit conversion
Ownership	Tracked by compiler	Programmer discipline
Bounds checking	Static (VRA)	None
Division by zero	Static detection (E015)	Undefined behavior
Pattern matching	Exhaustive <code>case</code>	<code>switch</code> (fall-through)
Null safety	Option type	Null everywhere
Strings	Slices with length	Null-terminated arrays
Generics	Comptime functions	Macros / <code>void*</code>
Header files	Module system	<code>#include</code>

- ¹ **Key insight.** Lain provides C-level performance with compile-time safety guarantees. The C99 backend enables seamless interop with existing C libraries while eliminating the most common classes of C undefined behavior from the safe fragment.

.14 Lain versus Zig

Similarities

- Comptime-based generics.
- No hidden control flow; no hidden allocations.
- C interoperability as a first-class concern.
- Explicit error handling with no exceptions.

Differences

Aspect	Lain	Zig
Memory safety	Compile-time ownership	Runtime (debug)
Ownership system	Borrow checker	Manual
Backend	C99	LLVM + self-hosted
Comptime scope	Type-parameter functions	Full expression evaluation
Error handling	Result type + <code>case</code>	Error unions + <code>try</code>
Allocator model	C interop (malloc/free)	Custom allocators everywhere

- ¹ **Key insight.** Both Lain and Zig use comptime for generics. Zig’s comptime is more powerful (arbitrary expression evaluation); Lain’s ownership system provides stronger compile-time memory safety guarantees than Zig’s debug-mode runtime checks.

.15 Lain versus Go

Similarities

- Simple, readable syntax.
- Fast compilation.
- No class hierarchies.

Differences

Aspect	Lain	Go
Memory management	Ownership (no GC)	Garbage collected
Runtime	None	GC + goroutine scheduler
Generics	Comptime functions	Type parameters
Error handling	Result type	Multiple return values
Null safety	Option type	Nil (null)

Aspect	Lain	Go
Concurrency	Not supported	Goroutines + channels
Determinism	Yes (no GC pauses)	GC pauses possible

- 1 **Key insight.** Go achieves simplicity through garbage collection. Lain achieves similar simplicity goals through ownership-based safety, without a runtime — making Lain suitable for embedded and real-time applications where Go’s GC is problematic.

.16 Features unique to Lain

- 1 The following features distinguish Lain from all languages in the comparison:

Feature	Description
<code>func/proc</code> split	Compiler-enforced purity with termination guarantees. No other listed language enforces purity at the declaration level.
Caller-site ownership annotations	<code>mov</code> and <code>var</code> are visible at every call site, making ownership transfer explicit and auditable.
Interval-based VRA	Polynomial-time static verification of array bounds and arithmetic constraints, without an SMT solver.
<code>in</code> operator for index constraints	<code>idx in arr</code> establishes the bounds guard $0 \leq \text{idx} < \text{arr.len}$ in the containing scope.
Bounded <code>while</code> with <code>decreasing</code>	Allows terminating loops in pure functions via programmer-supplied ranking functions, verified by the compiler.
Non-consuming <code>match</code> (<code>case &expr</code>)	Pattern matching that does not consume the scrutinee; the scrutinee is borrowed for the duration of the match body.

Index

- ABI, 76
- abs, 90
- ADT declaration, 48
- ADT layout, 84
- algebraic data type, 7, 33
- alignment, 25, 83
- arena, 8
 - compiler-internal, 85
- arithmetic operator, 36
- array type, 31
- as operator, 37
- assignment statement, 41
- attribute, 47, 58

- basic concepts, 23
- bitfield, 29
- bitwise operator, 36
- block expression, 39
- block statement, 41
- boolean literal, 18
- boolean type, 30
- borrow, 8
 - active, 8
 - phase, 8
- borrow expression, 38
- borrowed match, 53
- bounded while
 - rationale, 106
- bounded while loop, 43
- bounds check, 9
- branch consistency, 54

- C comparison, 108
- C interoperability, 75
- C99 backend
 - rationale, 104
- c_include, 75
- calling convention, 57
- case expression, 39
- cast expression, 37
- character literal, 18

- clamp, 91
- close_file, 89
- comment, 15
- comparison operator, 36
- compilation model, 2
- compile-time evaluation, 63
- compound assignment, 39
- comptime, 9, 63
- comptime block, 64
- comptime declaration, 50
- comptime if, 44, 64
- comptime parameter, 63
- comptime recursion depth, 65
- conditional refinement, 60
- conformance, 11
- conforming implementation, 11
- conforming program, 11
- constrained type, 7, 34
- constraint annotation, 60
- constructor expression, 39

- declaration, 23, 47
- decreasing measure, 9, 43
- defer statement, 44
- definition, 23
- diagnostic codes, 99
- diagnostic message, 6
 - requirements, 12

- enum declaration, 48
- enum layout, 84
- enum type, 33
- escape sequence, 19
- exceptions
 - absence of, rationale, 104
- exhaustiveness, 9, 67
- expression, 35
- expression statement, 42
- extern declaration, 49
- extern function, 75

- field access, 38

- field-level borrow tracking, 54
- File type, 89
- floating-point literal, 18
- floating-point type, 30
- for statement, 44
- func, 9
- func purity constraints, 49
- func vs proc, 55
- func/proc distinction
 - rationale, 103
- function, 55
- function call, 38
- function declaration, 48

- garbage collector
 - absence of, 84
- generics, 63
 - rationale, 105
- Go comparison, 109
- grammar summary, 93

- heap allocation, 82

- identifier, 17
- if expression, 39
- if statement, 42
- implementation limits, 12
- implementation-defined behavior, 6
- import, 10
- import declaration, 71
- in guard, 9, 37
 - VRA semantics, 60
- in operator, 37
- index expression, 38
- integer literal, 18
- integer overflow, 22
- integer rank, 7, 30
- integer type, 27
 - hardware-aligned, 28
 - logical, 28
- integer widening, 7, 30
- interprocedural VRA, 60
- interval, 9

- keyword, 16

- language comparison, 107
- lexical conventions, 15
- lifetime annotations
 - rationale, 104
- linear state, 8, 51
- linear type, 7
- linearity, 51

- literal, 18
- logical operator, 36
- lvalue, 24

- max, 90
- memory model, 81
- memory safety, 85
- min, 90
- mode preservation, 65
- module, 10
- module declaration, 71
- module loading, 71
- module system, 71
- monomorphization, 10, 64
- mov
 - rationale, 103
- move, 8
- move expression, 38
- move semantics, 53

- name mangling, 73
- name resolution, 24
- name visibility, 72
- non-lexical lifetime, 8, 53
- normative references, 3

- object, 24, 81
- object representation, 83
- opaque type, 77
- open_file, 89
- operator, 19
- operator precedence, 35
- Option type, 91
- ownership, 51
- ownership diagnostics, 52
- ownership in loops, 54
- ownership in match, 68
- ownership mode, 7, 51

- packed struct, 29
- panic, 57
- parameter, 48
- pattern matching, 67
- pointer operations, 77
- pointer type, 33
- primary expression, 35
- primitive type, 7, 27
- print, 88
- println, 88
- proc, 9
- procedure, 55
- procedure declaration, 49
- purity, 9

- purity enforcement, 55
- qualified name, 10
- range propagation, 59
- range representation, 59
- rationale, 103
- read-write lock invariant, 8, 52
- refinement type, 29
- resource, 8
- Result type, 91
- return constraint, 10
- return statement, 43
- return type, 49
- return value, 57
- Rust comparison, 107
- rvalue, 24
- safe fragment, 13
- scope, 23
- scope (of document), 1
- slice type, 31
- source file, 6
 - encoding, 15
- stack allocation, 82
- standard library, 87
 - module paths, 72
- statement, 41
- std.c, 87
- std.fs, 89
- std.io, 88
- std.math, 90
- storage duration, 24, 81
- string interop, 77
- string literal, 19
- string pattern matching, 68
- struct declaration, 48
- struct layout, 83
- struct type, 32
- termination, 9
- termination analysis, 56
- terms and definitions, 5
- token, 15
- token disambiguation, 21
- two-phase borrow, 8, 53
- type, 27
 - taxonomy, 27
- type alias
 - refinement, 29
- type as value, 64
- type compatibility, 34
- type equivalence, 34
- type mapping, 76
- type parameter, 63
- UFCS, 10, 56
 - rationale, 105
- undefined behavior, 6
 - in unsafe, 80
- Universal Function Call Syntax, 10
- unrestricted type, 7
- unsafe
 - rationale, 105
 - what it does not disable, 79
 - what it enables, 79
- unsafe block, 44
- unsafe code, 79
- unsafe fragment, 13
- unspecified behavior, 6
- value range analysis (VRA), 10, 59
- value semantics, 83
- variable
 - consumed, 8
- variable declaration, 41
- void type, 31
- VRA, 59
 - rationale, 105
- while statement, 42
- whitespace, 16
- write_file, 89
- Zig comparison, 109