Gherking reporter

marcof

Contents

1. Features 4
   1.1. Een feature in het Nederlands 5
      1.1.1. Scenarios 5
         1.1.1.1. Scenario: Scenario 1 5
         1.1.1.2. Scenario: Scenario 2 5
   1.2. simple 6
      1.2.1. Scenarios 6
         1.2.1.1. Scenario: Scenario 1 6
         1.2.1.2. Scenario: Scenario 2 6
         1.2.1.3. Scenario: Scenario 3 with markdown 6
   1.3. feature-syntaxt-error.feature 7
      1.3.1. Errors 7
   1.4. tablestep 8
      1.4.1. Scenarios 8
         1.4.1.1. Scenario: table steps 8
         1.4.1.2. Scenario: table steps 8
   1.5. background without rules 9
      1.5.1. Background 9
      1.5.2. Scenarios 9
         1.5.2.1. Scenario: Scenario 2 9
         1.5.2.2. Scenario: Scenario 1 9
   1.6. a long name with 'None' url nameand special chars #!@#$%^&*() 10
      1.6.1. Scenarios 10
         1.6.1.1. Scenario: A scenario with None url name 10
   1.7. outline 11
      1.7.1. Scenarios 11
         1.7.1.1. Scenario: Scenario Outline name <test> 11
         1.7.1.2. Scenario: Scenario with skipped 11
         1.7.1.3. Scenario: Scenario with skipped extra new line 11
   1.8. outline 12
      1.8.1. Scenarios 12
         1.8.1.1. Scenario: Scenario Outline name <test> 12
         1.8.1.2. Scenario: Scenario with skipped 12
         1.8.1.3. Scenario: Scenario with skipped extra new line 12
   1.9. rules 13
   1.10. Rule: rule 1 13
         1.10.0.1. Scenario: Scenario 1 13
         1.10.0.2. Scenario: Scenario 2 13
   1.11. Rule: rule 2 13
         1.11.0.1. Scenario: Scenario 1 13
   1.12. Feature with tags 14
      1.12.1. Scenarios 14
         1.12.1.1. Scenario: Scenario Outline name with tags <test> 14
   1.13. outline with background 15
      1.13.1. Background 15
      1.13.2. Scenarios 15
         1.13.2.1. Scenario: Scenario Outline name <test> 15
         1.13.2.2. Scenario: Scenario with skipped 15

1.14. simple 16
1.14.1. Scenarios 16
1.14.1.1. Scenario: Scenario 1 test in subfolder 16
1.14.1.2. Scenario: Scenario added in subfolder 16
1.14.1.3. Scenario: Scenario outline 3 16
2. Tag index 17

1. Features

Feature	Outcome
Een feature in het Nederlands	
simple	
feature-syntaxt-error.feature	**failed**
tablestep	
background without rules	
a long name with 'None' url nameand special chars #!@#$%^&*()	
outline	
outline	
rules	
Feature with tags	
outline with background	
simple	

1.1. Een feature in het Nederlands

Een scenario kan meerdere stappen hebben, en een scenario kan meerdere scenario's hebben.

1.1.1. Scenarios

1.1.1.1. Scenario: Scenario 1

Stel een feit
Als iets wordt uitgevoerd
Dan het resultaat is oke

1.1.1.2. Scenario: Scenario 2

Stel een feit
En een ander feit
Als iets wordt uitgevoerd
Then the result is oke also some markdown
Als het resultaat is mislukt

1.2. simple

With a description

1.2.1. Scenarios

1.2.1.1. Scenario: Scenario 1

Given: a fact
When: something is executed
Then: the result is oke

1.2.1.2. Scenario: Scenario 2

Given: a fact
And: a other fact
When: something is executed
Then the result is oke also some markdown
Then: the result is failed

1.2.1.3. Scenario: Scenario 3 with markdown

Tag1

test header 1

test header 2
markdown test

- test 1
- test 2
  Bold text
  ~~emphasis text~~

will be rendered as header 1

will be rendered as header 2

```
fn main() {
println!("Hello, world!");
}
```

Given: a fact
Then: a Skipped line

1.3. feature-syntaxt-error.feature failed

1.3.1. Errors

Scenario	Message
Feature parse error	Could not parse feature file: features/feature-syntaxt-error.feature

1.4. tablestep

1.4.1. Scenarios

1.4.1.1. Scenario: table steps

Given: a fact

Given: some facts

fact row 1 col 1	fact row 1 col 2
fact row 2 col 1	fact row 2 col 2

1.4.1.2. Scenario: table steps

Given: a fact

Given: some facts

fact row 1 col 1	fact row 1 col 2
fact row 2 col 1	fact row 2 col 2

And: a fact

1.5. background without rules

1.5.1. Background

Given: a fact
When: something is executed
Then: the result is oke

1.5.2. Scenarios

1.5.2.1. Scenario: Scenario 2

Description test scenario

Given: a fact
And: a other fact
When: something is executed
Then: the result is failed

1.5.2.2. Scenario: Scenario 1

Given: a fact
And: a other fact
When: something is executed
Then: the result is failed

1.6. a long name with 'None' url nameand special chars #!@#$%^&*()

Tag1 Tag2

1.6.1. Scenarios

1.6.1.1. Scenario: A scenario with None url name

Given: a fact with 'Some value'

1.7. outline

1.7.1. Scenarios

1.7.1.1. Scenario: Scenario Outline name *test*

Given: a fact with '*Header1*'
Given: a fact with '*Header2*'
Examples

Header1	Header2	test
Value 1	Value 1	aaaaaaaaa1
Value 2	Value 2	2
Value 3	Value 3	3
Value 4	Value 4	4

1.7.1.2. Scenario: Scenario with skipped

Given: a skipped fact with '*Header1*'
Examples

Header1	Header2	test
Value 3	Value 3	3
Value 4	Value 4	4

1.7.1.3. Scenario: Scenario with skipped extra new line

Given: a skipped fact with '*Header1*'
Examples

Header1	Header2	test
Value 3	Value 3	3
Value 5	Value 4	4

1.8. outline

1.8.1. Scenarios

1.8.1.1. Scenario: Scenario Outline name *test*

Given: a fact with '*Header1*'
Given: a fact with '*Header2*'
Examples

Header1	Header2	test
Value 1	Value 1	1
Value 2	Value 2	2
Value 3	Value 3	3
Value 4	Value 4	4

1.8.1.2. Scenario: Scenario with skipped

Given: a skipped fact with '*Header1*'
Examples

Header1	Header2	test
Value 3	Value 3	3
Value 4	Value 4	4

1.8.1.3. Scenario: Scenario with skipped extra new line

Given: a skipped fact with '*Header1*'
Examples

Header1	Header2	test
Value 3	Value 3	3
Value 5	Value 4	4

1.9. rules

1.10. Rule: rule 1

Description of a rule

1.10.0.1. Scenario: Scenario 1

Given: a fact
When: something is executed
Then: the result is oke

1.10.0.2. Scenario: Scenario 2

Description test scenario

Given: a fact
And: a other fact
When: something is executed
Then: the result is failed

1.11. Rule: rule 2

Tag2

1. A
2. B

Markdown description of a rule

- one
  - sub item
- two

A	B
1	longer column

1.11.0.1. Scenario: Scenario 1

Given: a fact
And: a other fact
When: something is executed
Then: the result is failed

1.12. Feature with tags

Tag1 Tag2

Feature Description

1.12.1. Scenarios

1.12.1.1. Scenario: Scenario Outline name with tags *test*

Given: a fact with '*Header1*'
Given: a fact with '*Header2*'
Examples

Header1	Header2	test
Value 1	Value 1	aaaaaaaa1 asdf
Value 2	Value 2	aaa aaaaa2
Value 3	Value 3	aaaaaaaa3
Value 4	Value 4	

1.13. outline with background

1.13.1. Background

Given: a fact with 'test-background-1'
Given: a fact with 'test-background-2'

1.13.2. Scenarios

1.13.2.1. Scenario: Scenario Outline name *test*

Given: a fact with '*Header1*'
Given: a fact with '*Header2*'
Examples

Header1	Header2	test
Value 1	Value 1	aaaaaaaaaaaaaaaaaaaaaaaaaaa1
Value 2	Value 2	2
Value 3	Value 3	3
Value 4	Value 4	4

1.13.2.2. Scenario: Scenario with skipped

Given: a skipped fact with '*Header1*'
Examples

Header1	Header2	test
Value 3	Value 3	3
Value 4	Value 4	4

1.14. simple

With a description same Feature as in parent folder

1.14.1. Scenarios

1.14.1.1. Scenario: Scenario 1 test in subfolder

Given: a fact
When: something is executed
Then: the result is oke

1.14.1.2. Scenario: Scenario added in subfolder

Given: a fact
And: a other fact
When: something is executed
Then: the result is failed

1.14.1.3. Scenario: Scenario outline 3

Given: a fact
Then: a Skipped line

2. Tag index

Tag1 6, 10, 14
Tag2 10, 13, 14