

**Cloud Computing project:
The k -means Clustering Algorithm in MapReduce**

Candidati

Alice Nannini

Fabio Malloggi

Marco Parola

Stefano Poleggi

Relatore

Dr. Nicola Tonellotto

Contents

1	Introduction	1
2	Dataset	1
3	MapReduce pseudo-code	2
4	Hadoop Implementation	3
5	Spark Implementation	3
6	Tests and Results	3

1 Introduction

This project presents the implementation of the Kmeans algorithm based on a MapReduce version, using both the Hadoop framework both the Spark framework.

The two implementations of the kmeans algorithm developed must be performed with the following inputs:

- Name of the input file containing the dataset
- Number of centroids/clusters
- Output directory
- Number of total samples in the input dataset (the algorithm can be run assuming that you know this value)

The algorithm exit can occur due to two events:

- The maximum number of possible iteration has been reached
- The centroids calculated at i-th step and i+1-th step do not deviate beyond a certain threshold (Euclidean norm)

2 Dataset

The datasets for the final tests were generated with a python script, shown below and having the following format *'dataset_numPoints_kClusters_dimPoints'*.

```
import random

# inputs: n (records), k (clusters), d (dimensions)
numPoints = [1000,10000,100000]
kClusters = [7,13]
dimPoints = [3,7]

for n in numPoints:
    for k in kClusters:
        for d in dimPoints:
            # open a new file
            f = open("data/dataset_"+str(n)+"_"+str(k)+"_"+str(d)+".txt", "a")

            # compute the interval for creating the clusters
            interval = round(n/(2*k))
            count = 0
            print("dataset_"+str(n)+"_"+str(k)+"_"+str(d)+"; int: "+str(interval))

            # compute each point
            for i in range(n):
                if( (i%interval)==0 and i!=0):
                    count = count + 2

            x = ""
```

```

        for j in range(d):
            x = x + str( interval*count + random.random()*interval )
            x = x + " "
        x = x + "\n"
        # write the new point coordinates in the file
        f.write(x)

    f.close()

```

List of files generated from the previous code:

- dataset_100000_13_3.txt
- dataset_100000_13_7.txt
- dataset_100000_7_3.txt
- dataset_100000_7_7.txt
- dataset_10000_13_3.txt
- dataset_10000_13_7.txt
- dataset_10000_7_3.txt
- dataset_10000_7_7.txt
- dataset_1000_13_3.txt
- dataset_1000_13_7.txt
- dataset_1000_7_3.txt
- dataset_1000_7_7.txt

3 MapReduce pseudo-code

```

class MAPPER
    method MAP(sample_id id, sample_list l)
        for all sample s in sample_list l do
            dist = MAX_VALUE
            for all center c in cluster_centers cc do
                newDist <- computeDistance(s, c)
                if newDist < dist
                    dist <- newDist
                clusterIndex = cc.index
            EMIT(index clusterIndex, sample s)

class REDUCER
    method REDUCE(index clusterIndex, samples [s1, s2,...])
        count <- 0
        center <- cluster_centers[clusterIndex]
        for all sample s in samples [s1, s2,...] do
            count <- count + 1

```

```
    for i in [0:size(s)] do
        newCenter[i] <- newCenter[i] + s[i]
    for i in [0:size(newCenter)] do
        newCenter[i] <- newCenter[i] / count
    EMIT(index clusterIndex, sample newCenter)
```

4 Hadoop Implementation

5 Spark Implementation

6 Tests and Results