

## **Modulo II Practica 2: uso de DOLPHOT y caracterizacion de poblaciones estelares.**

El presente documento muestra el proceso realizado a lo largo de la practica 2 del modulo de estrellas resueltas y poblaciones estelares. El presente escrito esta organizado de tal manera que sigue los pasos presentados dentro del documento de la practica, detalles o apendices se encuentran al final, y no se espera sean considerados en la evaluacion del trabajo.

En caso de desear revisar en mayor detalle los archivos en si mismos, estan archivados los scripts usados dentro del repositorio de github utilizado por el estudiante para el curso, Link al repositorio.

El paso 5 presenta los archivos que responden a los puntos de evaluacion entregados en el slide 7 de la practica, mientras que los pasos 1-4 presentan las deducciones, consideraciones y el proceso realizado a lo largo de la practica en si misma.

### **Paso 1: Instalacion de DOLPHOT**

Aqui se muestran los pasos realizados para instalar DOLPHOT dentro de el sistema operativo linux, con distribucion elementary OS.

#### **1.1: Descarga de DOLPHOT**

Los archivos para la compilacion son descargados directamente de la siguiente pagina <http://americano.dolphinsim.com/dolphot/>, la cual contiene principalmente el software DOLPHOT y el modulo de ACS a utilizar igualmente, tambien estan disponibles las PSFs de ACS al igual que sus Pixel Area Maps(PAMs), se muestran a continuacion los archivos a descargar destacados:

## Download DOLPHOT

[DOLPHOT 1.0 base sources](#) (updated 14 Mar 2007)  
[DOLPHOT 1.1 base sources](#) (updated 6 Sep 2010)  
[DOLPHOT 1.2 base sources](#) (updated 25 Jan 2011)  
[DOLPHOT 2.0 base sources](#) (updated 9 Dec 2022)  
[DOLPHOT 2.0 manual](#) (also included in base sources)  
[HSTphot paper](#) (from PASP website)

## DOLPHOT ACS Module

[DOLPHOT 1.0 ACS module sources](#) (updated 11 Feb 2007)  
[DOLPHOT 1.1 ACS module sources](#) (updated 6 Sep 2010)  
[DOLPHOT 1.2 ACS module sources](#) (updated 14 Nov 2010)  
[DOLPHOT 2.0 ACS module sources](#) (updated 24 Feb 2016)  
[DOLPHOT 2.0 ACS module manual](#) (also included in sources)

## ACS PSFs and Pixel Area Maps

ACS/HRC	ACS/WFC	ACS/WFC with Anderson Cores
<a href="#">Pixel Area Map</a>	<a href="#">Pixel Area Map</a>	<a href="#">F435W PSF</a>
<a href="#">F220W PSF</a>	<a href="#">F435W PSF</a>	<a href="#">F475W PSF</a>
<a href="#">F250W PSF</a>	<a href="#">F475W PSF</a>	<a href="#">F606W PSF</a>
<a href="#">F330W PSF</a>	<a href="#">F502N PSF</a>	<a href="#">F625W PSF</a>
<a href="#">F344N PSF</a>	<a href="#">F550M PSF</a>	<a href="#">F658N PSF</a>
<a href="#">F435W PSF</a>	<a href="#">F555W PSF</a>	<a href="#">F775W PSF</a>
<a href="#">F475W PSF</a>	<a href="#">F606W PSF</a>	<a href="#">F814W PSF</a>
<a href="#">F502N PSF</a>	<a href="#">F625W PSF</a>	<a href="#">F850LP PSF</a>
<a href="#">F550M PSF</a>	<a href="#">F658N PSF</a>	
<a href="#">F555W PSF</a>	<a href="#">F660N PSF</a>	
<a href="#">F606W PSF</a>	<a href="#">F775W PSF</a>	
<a href="#">F625W PSF</a>	<a href="#">F814W PSF</a>	
<a href="#">F658N PSF</a>	<a href="#">F850LP PSF</a>	
<a href="#">F660N PSF</a>	<a href="#">F892N PSF</a>	
<a href="#">F775W PSF</a>		
<a href="#">F814W PSF</a>		
<a href="#">F850LP PSF</a>		
<a href="#">F892N PSF</a>		

Luego de descargar tanto el código a compilar del software como el módulo de ACS, tenemos que conseguir el PAM y las PSFs para ACS.

## 1.2: Descarga de PSFs

Descargar tanto las PSFs como el PAM es posible desde la misma página, requerimos 2 PSFs una para cada filtro que utilizaremos, F606W y F814W, se muestran destacados los archivos a descargar a continuación:

Download DOLPHOT		
<a href="#">DOLPHOT 1.0 base sources</a> (updated 14 Mar 2007) <a href="#">DOLPHOT 1.1 base sources</a> (updated 6 Sep 2010) <a href="#">DOLPHOT 1.2 base sources</a> (updated 25 Jan 2011) <a href="#">DOLPHOT 2.0 base sources</a> (updated 9 Dec 2022) <a href="#">DOLPHOT 2.0 manual</a> (also included in base sources) <a href="#">HSTphot paper</a> (from PASP website)		
DOLPHOT ACS Module		
<a href="#">DOLPHOT 1.0 ACS module sources</a> (updated 11 Feb 2007) <a href="#">DOLPHOT 1.1 ACS module sources</a> (updated 6 Sep 2010) <a href="#">DOLPHOT 1.2 ACS module sources</a> (updated 14 Nov 2010) <a href="#">DOLPHOT 2.0 ACS module sources</a> (updated 24 Feb 2016) <a href="#">DOLPHOT 2.0 ACS module manual</a> (also included in sources)		
ACS PSFs and Pixel Area Maps		
ACS/HRC	ACS/WFC	ACS/WFC with Anderson Cores
Pixel Area Map	Pixel Area Map	F435W PSF
F220W PSF	F435W PSF	F475W PSF
F250W PSF	F475W PSF	F606W PSF
F330W PSF	F502N PSF	F625W PSF
F344N PSF	F550M PSF	F658N PSF
F435W PSF	F555W PSF	F775W PSF
F475W PSF	F606W PSF	F814W PSF
F502N PSF	F625W PSF	F850LP PSF
F550M PSF	F658N PSF	
F555W PSF	F660N PSF	
F606W PSF	F775W PSF	
F625W PSF	F814W PSF	
F658N PSF	F850LP PSF	
F660N PSF	F892N PSF	
F775W PSF		
F814W PSF		
F850LP PSF		
F892N PSF		

Todos los archivos descargados hasta ahora deberian de estar dentro de la misma raiz de directorio en dolphot2.0.

### 1.3: Instalacion y compilacion de dolphot

Para instalar DOLPHOT, uno comienza primero preparando el archivo Makefile con la configuracion deseada para la maquina en uso, en el caso del trabajo mostrado, se utiliza elementaryOS que esta basado en Ubuntu, que utiliza como compilador el de GCC por lo que se mantiene esa opcion, y se activa la opcion de utilizar el modulo de ACS ya que fue descargado, se muestra el archivo completo de Makefile a continuacion:

```
#if your machine uses cc instead of gcc, edit the following:
export CC=gcc
export FC=g77
export MAKE=make

#set the base directory
export BASE_DIR = /home/marcoritou/Documents/PHD_Level3/topicos/practicadolphot/dolphot2.0

#uncomment and set PGLOT files if installed
#export PGHEAD = \"/usr/local/include/cpgplot.h\"
```

```

#export PGPLOT = -L/usr/local/lib -lcpgplot -lpgplot -lpng -L/usr/X11R6/lib -lX11 -L/usr/lib

#compilation flags
export CFLAGS= -O3 -Wall -m64

#uncomment if you will be using the WFPC2 module
#export USEWFPC2=1

#uncomment if you will be using the ACS module
export USEACS=1

#uncomment if you will be using the WFC3 module
#export USEWFC3=1

#uncomment if you will be using the ROMAN module
#export USEROMAN=1

#uncomment if you will be using the NIRCAM module
#export USENIRCAM=1

#uncomment if you will be using the NIRISS module
#export USENIRISS=1

#uncomment if you will be using the MIRI module
#export USEMIRI=1

#set the directory where Tiny Tim binaries are located (ACS/WFPC2/WFC3 PSF generation):
#export USETT=1
#export CFLAGS+= -DTTDIR="/data0/tinytim-7.0"

#set maximum number of images, and maximum number of stars
export CFLAGS+= -DMAXNIMG=100
export CFLAGS+= -DMAXNSTARS=2000000

#optionally print and/or crash if a NaN occurs (intended for development only)
export CFLAGS+= -DNAN_PRINT
#export CFLAGS+= -DNAN_CRASH

##### NO FURTHER ADJUSTMENTS BELOW THIS LINE #####

#add base directory settings to flags
export CFLAGS += -DBASEDIR="'$(BASE_DIR)'" -I$(BASE_DIR)/include

#definitions
ALLEXE = dolphot_lib.o fits_lib.o fakeproc.o bin/addstars bin/apphot bin/calcsky bin/dolphot
ALL = $(ALLEXE) ccdred

```

```

DOLPHOT_DEP = dolphot_lib.o fits_lib.o dolphot_common.h dolphot_defs.h
DOLPHOT_OBJ = dolphot_lib.o fits_lib.o
DOLPHOT_FOBJ =

#linked libraries
export LIBS = -lm

#add WFPC2 modules, if selected
#ifdef USEWFPC2
export CFLAGS+= -DUSEWFPC2
ALL+= wfpc2
DOLPHOT_DEP += wfpc2
DOLPHOT_OBJ += wfpc2/wfpc2phot.o wfpc2/wfpc2filters.o wfpc2/wfpc2distort.o
DOLPHOT_FOBJ += wfpc2/wfpc2filters.o
#endif

#add ACS modules, if selected
#ifdef USEACS
export CFLAGS+= -DUSEACS
ALL+= acs
DOLPHOT_DEP += acs
DOLPHOT_OBJ += acs/acsphot.o acs/acsfilters.o acs/acsdistort.o
DOLPHOT_FOBJ += acs/acsfilters.o
#endif

#add WFC3 modules, if selected
#ifdef USEWFC3
export CFLAGS+= -DUSEWFC3
ALL+= wfc3
DOLPHOT_DEP += wfc3
DOLPHOT_OBJ += wfc3/wfc3phot.o wfc3/wfc3filters.o wfc3/wfc3distort.o
DOLPHOT_FOBJ += wfc3/wfc3filters.o
#endif

#add ROMAN modules, if selected
#ifdef USEROMAN
export CFLAGS+= -DUSEROMAN
ALL+= roman
DOLPHOT_DEP += roman
DOLPHOT_OBJ += roman/romanphot.o roman/romanfilters.o roman/romandistort.o
DOLPHOT_FOBJ += roman/romanfilters.o
#endif

#add NIRCAM modules, if selected
#ifdef USENIRCAM
export CFLAGS+= -DUSENIRCAM

```

```

ALL+= nircam
DOLPHOT_DEP += nircam
DOLPHOT_OBJ += nircam/nircamphot.o nircam/nircamfilters.o nircam/nircamdistort.o
DOLPHOT_FOBJ += nircam/nircamfilters.o
endif

#add NIRISS modules, if selected
ifdef USENIRISS
export CFLAGS+= -DUSENIRISS
ALL+= niriss
DOLPHOT_DEP += niriss
DOLPHOT_OBJ += niriss/nirissphot.o niriss/nirissfilters.o niriss/nirissdistort.o
DOLPHOT_FOBJ += niriss/nirissfilters.o
endif

#add MIRI modules, if selected
ifdef USEMIRI
export CFLAGS+= -DUSEMIRI
ALL+= miri
DOLPHOT_DEP += miri
DOLPHOT_OBJ += miri/miriphot.o miri/mirifilters.o miri/miridistort.o
DOLPHOT_FOBJ += miri/mirifilters.o
endif

#add display module, if selected
ifdef PGPLOT
ALL+= display.o
ALLEXE+= display.o
endif

all: $(ALL)

ifdef USEWFPC2
wfpc2::
    cd wfpc2; $(MAKE)
endif

ifdef USEACS
acs::
    cd acs; $(MAKE)
endif

ifdef USEWFC3
wfc3::
    cd wfc3; $(MAKE)
endif

```

```

ifdef USEROMAN
roman::
    cd roman; $(MAKE)
endif

ifdef USENIRCAM
nircam::
    cd nircam; $(MAKE)
endif

ifdef USENIRISS
niriss::
    cd niriss; $(MAKE)
endif

ifdef USEMIRI
miri::
    cd miri; $(MAKE)
endif

ccdred::
    cd ccdred; $(MAKE)

dolphot_lib.o: dolphot_lib.c include/dolphot.h
    $(CC) $(CFLAGS) -c -o $@ $<

fits_lib.o: fits_lib.c include/dolphot.h include/fits.h
    $(CC) $(CFLAGS) -c -o $@ $<

bin/addstars: addstars.c $(DOLPHOT_DEP)
    $(CC) $(CFLAGS) -o $@ addstars.c $(DOLPHOT_OBJ) $(LIBS)

bin/convertpos: convertpos.c $(DOLPHOT_DEP)
    $(CC) $(CFLAGS) -o $@ convertpos.c $(DOLPHOT_OBJ) $(LIBS)

ifdef PGPLOT
display.o: display.c dolphot_lib.o fits_lib.o
    $(CC) $(CFLAGS) -c -o $@ $< -DPGHEAD=$(PGHEAD)

bin/apphot: apphot.c dolphot_lib.o fits_lib.o display.o
    $(CC) $(CFLAGS) -c apphot.c -DPGPLOT -DPGHEAD=$(PGHEAD)
    $(FC) -o $@ apphot.o dolphot_lib.o fits_lib.o display.o $(LIBS) $(PGPLOT)
    rm apphot.o

bin/dolphot: dolphot.c $(DOLPHOT_DEP)

```

```

$(CC) $(CFLAGS) -c dolphot.c -DPGPLOT -DPGHEAD=$(PGHEAD)
$(FC) -o $@ dolphot.o $(DOLPHOT_OBJ) $(LIBS) $(PGPLOT)
rm dolphot.o
else
bin/apphot: apphot.c dolphot_lib.o fits_lib.o
$(CC) $(CFLAGS) -o $@ apphot.c dolphot_lib.o fits_lib.o $(LIBS)

bin/dolphot: dolphot.c $(DOLPHOT_DEP)
$(CC) $(CFLAGS) -o $@ dolphot.c $(DOLPHOT_OBJ) $(LIBS)
endif

bin/calcsky: calcsky.c dolphot_lib.o fits_lib.o
$(CC) $(CFLAGS) -o $@ calcsky.c dolphot_lib.o fits_lib.o $(LIBS)

bin/synthing: synthing.c dolphot_lib.o fits_lib.o
$(CC) $(CFLAGS) -o $@ synthing.c dolphot_lib.o fits_lib.o $(LIBS)

bin/fakelist: fakelist.c fakeproc.o fakeproc.h $(DOLPHOT_FOBJ)
$(CC) $(CFLAGS) -o $@ fakelist.c fakeproc.o $(DOLPHOT_FOBJ) $(LIBS)

clean:
rm $(ALLEXE)
cd ccdred ; $(MAKE) clean
ifdef USEWFPC2
cd wfpc2 ; $(MAKE) clean
endif
ifdef USEACS
cd acs ; $(MAKE) clean
endif
ifdef USEWFC3
cd wfc3 ; $(MAKE) clean
endif
ifdef USEROMAN
cd roman ; $(MAKE) clean
endif
ifdef USENIRCAM
cd nircam ; $(MAKE) clean
endif
ifdef USENIRISS
cd niriss ; $(MAKE) clean
endif
ifdef USEMIRI
cd miri ; $(MAKE) clean
endif
e

```

Luego para compilar el código de dolphot se utiliza el siguiente comando, dentro



del directorio dolphot2.0:

```
make
```

Luego tenemos que añadir la carpeta generada “bin” a nuestro PATH, esto se puede realizar añadiendo la siguiente línea a nuestro “~/.bashrc”:

```
export PATH="$PATH:/path/to/dolphot2.0/bin"
```

Podemos comprobar la instalación de manera sencilla con el siguiente comando:

```
dolphot
```

Lanzará un error declarando que no comprende el archivo fits, pero permite saber que está funcionando el software.

## **Paso 2: Descarga de datos del HST**

Esta sección presentará el proceso de descarga de los datos del HST para NGC 3031.

### **2.1: Búsqueda del proposal.**

Para descargar los datos del HST podemos entrar en la página de búsqueda de datos archivados del HST, donde se almacenan datos libres de uso de publicaciones pasadas.

Luego dentro de esta página de búsqueda se coloca el proposalID a buscar, en el caso del presente trabajo se utilizará el de la GHOSTS survey, entonces se coloca el proposalID “10523”.



Search MAST for Hubble

API | HELP | ABOUT | MY ST

EDIT SEARCH Data Type= IMAGE Observations= Science Instruments= ACS Program ID= 10523 Columns= Dataset, Target Name, HAP, HASP, Instrument, Apertures, Filters/Gratings, Exp Time, Start Time, Proposal I...

DOWNLOAD SELECTED (2 DATASETS) EXPORT TABLE

	Dataset	Target Name	HAP	HASP	Instrument	Apertures	Filters/Gratings	Exp Time	Start Time	Proposal ID	PI Last Name	RA (J2000)	Dec (J2000)	Ref	Central Wavelength
<input type="checkbox"/>	JRC22021	NGC2493-HALO-3	1	0	ACS	WFC	CLEARLIF814W	735.000	2005-10-29 22:45:09	10523	DE JONG	114.7583554	65.4120833	22	8047.816
<input type="checkbox"/>	JRC26011	NGC2493-HALO-6	1	0	ACS	WFC	F606N/CLEARL2L	720.000	2005-10-14 05:47:26	10523	DE JONG	114.3723742	65.6747583	22	5919.729
<input type="checkbox"/>	JRC26021	NGC2493-HALO-6	1	0	ACS	WFC	CLEARLIF814W	720.000	2005-10-14 06:04:53	10523	DE JONG	114.3723742	65.6747583	22	8047.805
<input type="checkbox"/>	JRC27011	NGC2493-HALO-7	1	0	ACS	WFC	F606N/CLEARL2L	745.000	2005-11-15 23:42:00	10523	DE JONG	114.4987171	65.7287722	22	5919.725
<input type="checkbox"/>	JRC27021	NGC2493-HALO-7	1	0	ACS	WFC	CLEARLIF814W	745.000	2005-11-15 23:59:53	10523	DE JONG	114.4987171	65.7287722	22	8047.828
<input checked="" type="checkbox"/>	JRC41011	NGC3031-HALO-1	1	0	ACS	WFC	F606N/CLEARL2L	710.000	2005-10-31 03:22:41	10523	DE JONG	149.3217754	69.1081306	22	5919.727
<input checked="" type="checkbox"/>	JRC41021	NGC3031-HALO-1	1	0	ACS	WFC	CLEARLIF814W	710.000	2005-10-31 03:39:58	10523	DE JONG	149.3217754	69.1081306	22	8047.816
<input type="checkbox"/>	JRC42011	NGC3031-HALO-2	1	0	ACS	WFC	F606N/CLEARL2L	735.000	2005-10-31 01:43:20	10523	DE JONG	149.5187425	69.1478194	22	5919.727
<input type="checkbox"/>	JRC42021	NGC3031-HALO-2	1	0	ACS	WFC	CLEARLIF814W	735.000	2005-10-31 02:01:03	10523	DE JONG	149.5187425	69.1478194	22	8047.816
<input type="checkbox"/>	JRC43011	NGC3031-HALO-3	1	0	ACS	WFC	F606N/CLEARL2L	730.000	2005-09-07 09:01:37	10523	DE JONG	149.7178983	69.1783667	22	5919.733
<input type="checkbox"/>	JRC43021	NGC3031-HALO-3	1	0	ACS	WFC	CLEARLIF814W	730.000	2005-09-07 09:19:14	10523	DE JONG	149.7178983	69.1783667	22	8047.779
<input type="checkbox"/>	JRC46011	NGC3031-HALO-6	1	0	ACS	WFC	F606N/CLEARL2L	700.000	2005-12-06 03:10:23	10523	DE JONG	148.5963537	69.3323361	22	5919.723
<input type="checkbox"/>	JRC46021	NGC3031-HALO-6	1	0	ACS	WFC	CLEARLIF814W	700.000	2005-12-06 03:27:30	10523	DE JONG	148.5963537	69.3323361	22	8047.842
<input type="checkbox"/>	JRC47011	NGC3031-HALO-7	1	0	ACS	WFC	F606N/CLEARL2L	720.000	2005-10-26 03:31:54	10523	DE JONG	148.4984767	69.4162694	22	5919.727
<input type="checkbox"/>	JRC47021	NGC3031-HALO-7	1	0	ACS	WFC	CLEARLIF814W	720.000	2005-10-26 03:49:21	10523	DE JONG	148.4984767	69.4162694	22	8047.813
<input type="checkbox"/>	JRC48011	NGC3031-HALO-8	1	0	ACS	WFC	F606N/CLEARL2L	740.000	2005-12-20 18:43:41	10523	DE JONG	149.1630446	69.3748833	22	5919.721
<input type="checkbox"/>	JRC48021	NGC3031-HALO-8	1	0	ACS	WFC	CLEARLIF814W	740.000	2005-12-20 19:01:28	10523	DE JONG	149.1630446	69.3748833	22	8047.852
<input type="checkbox"/>	JRC61011	NGC4344-HALO-1	1	0	ACS	WFCENTER	F606N/CLEARL2L	735.000	2005-11-22 23:38:45	10523	DE JONG	164.4189246	37.7774806	22	5919.725
<input type="checkbox"/>	JRC61021	NGC4344-HALO-1	1	0	ACS	WFCENTER	CLEARLIF814W	735.000	2005-11-22 23:56:28	10523	DE JONG	164.4189246	37.7774806	22	8047.833
<input type="checkbox"/>	JRC71011	NGC4344-HALO-11	1	0	ACS	WFCENTER	F606N/CLEARL2L	700.000	2005-11-04 14:30:38	10523	DE JONG	164.2778859	37.7404230	22	5919.727
<input type="checkbox"/>	JRC71021	NGC4344-HALO-11	1	0	ACS	WFCENTER	CLEARLIF814W	700.000	2005-11-04 14:47:45	10523	DE JONG	164.2778859	37.7404230	22	8047.820
<input type="checkbox"/>	JRC82011	NGC4344-HALO-2	1	0	ACS	WFC	F606N/CLEARL2L	750.000	2005-11-15 15:50:30	10523	DE JONG	164.4742758	37.7338917	22	5919.725

2 datasets selected

Luego de esto se selecciona descargar datos y seleccionaremos los datos calibrados de antemano, de esa manera tan solo tendremos que maskear los hot pixels y considerar el cielo sin una reduccion de imagenes propia.

Search MAST for Hubble

API | HELP | ABOUT | MY ST

EDIT SEARCH Data Type= IMAGE Observations= Science Instruments= ACS Program ID= 10523 Columns= Dataset, Target Name, HAP, HASP, Instrument, Apertures, Filters/Gratings, Exp Time, Start Time, Proposal I...

DOWNLOAD SELECTED (2 DATASETS) EXPORT TABLE

Selected: 673.413 MB - 4 files

All: 24.853 GB - 174 files

Choose file types to download

File Category

Selecting 1 file categories

- ☐ CRC | +2 files (335.681 MB)  
Calibrated, combined image. CTE-corr/CR-rej applied
- ☐ CRJ | +2 files (335.681 MB)  
Calibrated, combined CCD image. CR-rej applied
- ☐ DRG | +2 files (428.867 MB)  
CTE-corrected calibrated combined image
- ☐ DRZ | +2 files (428.861 MB)  
Calibrated combined image
- ☒ FLC | +4 files (673.413 MB)  
Calibrated, flat-fielded, and CTE-corrected single exposure
- ☐ FLT | +4 files (673.874 MB)  
Calibrated, flat-fielded single exposure
- ☐ FLT\_HLET | +4 files (0.449 MB)

	Dataset	Target Name	HAP	HASP	Instrument	Apertures	Filters/Gratings	Exp Time	Start Time	Proposal ID	PI Last Name	RA (J2000)	Dec (J2000)	Ref	Central Wavelength
<input type="checkbox"/>	JRC22021	NGC2493-HALO-3	1	0	ACS	WFC	CLEARLIF814W	735.000	2005-10-29 22:45:09	10523	DE JONG	114.7583554	65.4120833	22	8047.816
<input type="checkbox"/>	JRC26011	NGC2493-HALO-6	1	0	ACS	WFC	F606N/CLEARL2L	720.000	2005-10-14 05:47:26	10523	DE JONG	114.3723742	65.6747583	22	5919.729
<input type="checkbox"/>	JRC26021	NGC2493-HALO-6	1	0	ACS	WFC	CLEARLIF814W	720.000	2005-10-14 06:04:53	10523	DE JONG	114.3723742	65.6747583	22	8047.805
<input type="checkbox"/>	JRC27011	NGC2493-HALO-7	1	0	ACS	WFC	F606N/CLEARL2L	745.000	2005-11-15 23:42:00	10523	DE JONG	114.4987171	65.7287722	22	5919.725
<input type="checkbox"/>	JRC27021	NGC2493-HALO-7	1	0	ACS	WFC	CLEARLIF814W	745.000	2005-11-15 23:59:53	10523	DE JONG	114.4987171	65.7287722	22	8047.828
<input checked="" type="checkbox"/>	JRC41011	NGC3031-HALO-1	1	0	ACS	WFC	F606N/CLEARL2L	710.000	2005-10-31 03:22:41	10523	DE JONG	149.3217754	69.1081306	22	5919.727
<input checked="" type="checkbox"/>	JRC41021	NGC3031-HALO-1	1	0	ACS	WFC	CLEARLIF814W	710.000	2005-10-31 03:39:58	10523	DE JONG	149.3217754	69.1081306	22	8047.816
<input type="checkbox"/>	JRC42011	NGC3031-HALO-2	1	0	ACS	WFC	F606N/CLEARL2L	735.000	2005-10-31 01:43:20	10523	DE JONG	149.5187425	69.1478194	22	5919.727
<input type="checkbox"/>	JRC42021	NGC3031-HALO-2	1	0	ACS	WFC	CLEARLIF814W	735.000	2005-10-31 02:01:03	10523	DE JONG	149.5187425	69.1478194	22	8047.816
<input type="checkbox"/>	JRC43011	NGC3031-HALO-3	1	0	ACS	WFC	F606N/CLEARL2L	730.000	2005-09-07 09:01:37	10523	DE JONG	149.7178983	69.1783667	22	5919.733
<input type="checkbox"/>	JRC43021	NGC3031-HALO-3	1	0	ACS	WFC	CLEARLIF814W	730.000	2005-09-07 09:19:14	10523	DE JONG	149.7178983	69.1783667	22	8047.779
<input type="checkbox"/>	JRC46011	NGC3031-HALO-6	1	0	ACS	WFC	F606N/CLEARL2L	700.000	2005-12-06 03:10:23	10523	DE JONG	148.5963537	69.3323361	22	5919.723
<input type="checkbox"/>	JRC46021	NGC3031-HALO-6	1	0	ACS	WFC	CLEARLIF814W	700.000	2005-12-06 03:27:30	10523	DE JONG	148.5963537	69.3323361	22	8047.842
<input type="checkbox"/>	JRC47011	NGC3031-HALO-7	1	0	ACS	WFC	F606N/CLEARL2L	720.000	2005-10-26 03:31:54	10523	DE JONG	148.4984767	69.4162694	22	5919.727
<input type="checkbox"/>	JRC47021	NGC3031-HALO-7	1	0	ACS	WFC	CLEARLIF814W	720.000	2005-10-26 03:49:21	10523	DE JONG	148.4984767	69.4162694	22	8047.813
<input type="checkbox"/>	JRC48011	NGC3031-HALO-8	1	0	ACS	WFC	F606N/CLEARL2L	740.000	2005-12-20 18:43:41	10523	DE JONG	149.1630446	69.3748833	22	5919.721
<input type="checkbox"/>	JRC48021	NGC3031-HALO-8	1	0	ACS	WFC	CLEARLIF814W	740.000	2005-12-20 19:01:28	10523	DE JONG	149.1630446	69.3748833	22	8047.852
<input type="checkbox"/>	JRC61011	NGC4344-HALO-1	1	0	ACS	WFCENTER	F606N/CLEARL2L	735.000	2005-11-22 23:38:45	10523	DE JONG	164.4189246	37.7774806	22	5919.725
<input type="checkbox"/>	JRC61021	NGC4344-HALO-1	1	0	ACS	WFCENTER	CLEARLIF814W	735.000	2005-11-22 23:56:28	10523	DE JONG	164.4189246	37.7774806	22	8047.833
<input type="checkbox"/>	JRC71011	NGC4344-HALO-11	1	0	ACS	WFCENTER	F606N/CLEARL2L	700.000	2005-11-04 14:30:38	10523	DE JONG	164.2778859	37.7404230	22	5919.727
<input type="checkbox"/>	JRC71021	NGC4344-HALO-11	1	0	ACS	WFCENTER	CLEARLIF814W	700.000	2005-11-04 14:47:45	10523	DE JONG	164.2778859	37.7404230	22	8047.820
<input type="checkbox"/>	JRC82011	NGC4344-HALO-2	1	0	ACS	WFC	F606N/CLEARL2L	750.000	2005-11-15 15:50:30	10523	DE JONG	164.4742758	37.7338917	22	5919.725

2 datasets selected

## 2.3: Descarga de high level products

Por ultimo se descarga la drizzle image que sera utilizada igualmente, ya que tenemos multiples imagenes en dithering, esto permitira combinarlas todas como una sola imagen a considerar.

La imagen drizzle puede ser descargada de la columna high level products:

Search MAST

for Hubble

API

HELP

ABOUT

MY ST

EDIT SEARCH

Data Type= IMAGE

Observations= Science

Instruments= ACS

Program ID=

Table containing search results

Target Name, HAP, HASP Instrument, Apertures, Filters/Gratings, Exp Time, Start Time, Proposal I...

Learn More

DOWNLOAD SELECTED (2 DATASETS)

EXPORT TABLE

Rows per page: 500

1-72 of 72

Time	Start Time	Proposal ID	PI Last Name	RA (J2000)	Dec (J2000)	Ref	Central Wavelength	Release Date	Exp Time	Previous Name	Scan Type	High-Level Science Products	Ang Sep (")
000	2005-10-29 22:45:09	10523	DE JONG	114.7583554	65.4120833	22	8047.816	2006-10-30 05:40:04	2005-10-29 22:59:42	JR0C23021		2	
000	2005-10-14 05:47:26	10523	DE JONG	114.3723742	65.6747583	22	5919.729	2006-10-14 12:39:32	2005-10-14 06:01:43	JR0C26011		7	
000	2005-10-14 06:04:53	10523	DE JONG	114.3723742	65.6747583	22	8047.805	2006-10-14 13:00:08	2005-10-14 06:19:10	JR0C26021		6	
000	2005-11-15 23:42:00	10523	DE JONG	114.4967171	65.7287722	22	5919.725	2006-11-16 08:06:30	2005-11-15 23:56:40	JR0C27011		1	
000	2005-11-15 23:59:53	10523	DE JONG	114.4967171	65.7287722	22	8047.828	2006-11-16 08:37:27	2005-11-16 00:14:36	JR0C27021		2	
000	2005-10-31 02:22:41	10523	DE JONG	149.3217754	69.1081306	22	5919.727	2006-10-31 08:42:50	2005-10-31 03:36:48	JR0C41011		5	
000	2005-10-31 03:39:58	10523	DE JONG	149.3217754	69.1081306	22	8047.816	2006-10-31 09:04:10	2005-10-31 03:54:05	JR0C41021		5	
000	2005-10-31 01:43:20	10523	DE JONG	149.5187425	69.1478194	22	5919.727	2006-10-31 08:12:51	2005-10-31 01:57:53	JR0C42011		5	
000	2005-10-31 02:01:03	10523	DE JONG	149.5187425	69.1478194	22	8047.816	2006-10-31 08:39:22	2005-10-31 02:15:35	JR0C42021		5	
000	2005-09-07 09:01:37	10523	DE JONG	149.7179983	69.1783647	22	5919.733	2006-09-07 16:14:26	2005-09-07 09:16:04	JR0C43011			
000	2005-09-07 09:19:14	10523	DE JONG	149.7179983	69.1783647	22	8047.779	2006-09-07 16:35:16	2005-09-07 09:33:41	JR0C43021			
000	2005-12-06 03:10:23	10523	DE JONG	148.5963537	69.3323361	22	5919.733	2006-12-06 08:19:03	2005-12-06 03:24:20	JR0C46011			
000	2005-12-06 03:27:30	10523	DE JONG	148.5963537	69.3323361	22	8047.842	2006-12-06 08:39:22	2005-12-06 03:41:27	JR0C46021			
000	2005-10-26 03:31:54	10523	DE JONG	148.4984767	69.4162694	22	5919.727	2006-10-26 14:53:20	2005-10-26 03:46:11	JR0C47011			
000	2005-10-26 03:49:21	10523	DE JONG	148.4984767	69.4162694	22	8047.813	2006-10-26 15:14:10	2005-10-26 04:03:38	JR0C47021			
000	2005-12-20 18:43:41	10523	DE JONG	149.1630446	69.3748833	22	5919.721	2006-12-20 22:38:41	2005-12-20 18:58:18	JR0C48011			
000	2005-12-20 19:01:28	10523	DE JONG	149.1630446	69.3748833	22	8047.852	2006-12-20 23:29:54	2005-12-20 19:16:05	JR0C48021			
000	2005-11-22 23:38:45	10523	DE JONG	184.4189246	37.7774806	22	5919.725	2006-11-23 06:51:10	2005-11-22 23:53:18	JR0C61011			
000	2005-11-22 23:56:28	10523	DE JONG	184.4189246	37.7774806	22	8047.833	2006-11-23 12:54:26	2005-11-23 00:11:01	JR0C61021			
000	2005-11-04 14:30:38	10523	DE JONG	184.2778858	37.7404250	22	5919.727	2006-11-04 22:02:06	2005-11-04 14:44:35	JR0C71011			
000	2005-11-04 14:47:45	10523	DE JONG	184.2778858	37.7404250	22	8047.820	2006-11-04 22:22:37	2005-11-04 15:01:42	JR0C71021			
000	2005-11-15 15:50:30	10523	DE JONG	184.4742758	37.7338917	22	5919.725	2006-11-16 00:26:28	2005-11-15 16:05:17	JR0C62011			

2 datasets selected

Rows per page: 500

1-72 of 72

Luego seleccionamos la imagen de referencia:

Mission Search / Missions / Contacts / STScI / MAST

Columns Help / Archive Status

HLSPMAP Search Results

Edit Query

number of rows returned = 5

Click on Project entries to view project web site.

Click on Filename entries to display/download available files.

Click on Bibtexes to display online paper.

Click on up column headers to sort the table on the column contents.

Click on bottom column headers for more information about the data in that column.

Project	Filename	Object	RA (J2000)	Dec (J2000)	Instrument	Product Type	Bibcode	Dataset Name	Webpage	URL
angst	hlp_angst_hst_acs-wfc_10523-nac3031-halo-1_R006w-B14sw_v1_p0b0				ACS	catalog	2009AJ...137..4129J	JR0C41011	https://archive.stsci.edu/prepds/angst	https://archive.stsci.edu/pub/hlp/angst/acs/
angst	hlp_angst_hst_acs-wfc_10523-nac3031-halo-1_R006w-B14sw_v1_p0f0s				ACS	catalog	2009AJ...137..4129J	JR0C41011	https://archive.stsci.edu/prepds/angst	https://archive.stsci.edu/pub/hlp/angst/acs/
angst	hlp_angst_hst_acs-wfc_10523-nac3031-halo-1_R006w-B14sw_v1_a0f0s				ACS	catalog	2009AJ...137..4129J	JR0C41011	https://archive.stsci.edu/prepds/angst	https://archive.stsci.edu/pub/hlp/angst/acs/
angst	hlp_angst_hst_acs-wfc_10523-nac3031-halo-1_B14sw_v1_ref00	NGC3031-HALO-1 09 57 17.226 +69 06 29.27			ACS	image	2009AJ...137..4129J	JR0C41011	https://archive.stsci.edu/prepds/angst	https://archive.stsci.edu/pub/hlp/angst/acs/
angst	hlp_angst_hst_acs-wfc_10523-nac3031-halo-1_B14sw_v1_ref08	NGC3031-HALO-1 09 57 17.226 +69 06 29.27			ACS	image	2009AJ...137..4129J	JR0C41011	https://archive.stsci.edu/prepds/angst	https://archive.stsci.edu/pub/hlp/angst/acs/
Project	Filename	Object	RA (J2000)	Dec (J2000)	Instrument	Product Type	Bibcode	Dataset Name	Webpage	URL

Top of Page

Copyright Notice

https://archive.stsci.edu/hlp/hlspmapsearch.php

astscipostcode

Modified: Jun 04, 2013 20:18

https://archive.stsci.edu/prepds/angst/angst\_hst\_acs-wfc\_10523-nac3031-halo-1\_B14sw\_v1\_ref00

Con esto tenemos un total de 5 archivos, 4 imágenes con 2 de cada filtro y 1 imagen drizzle.

### Paso 3: Aplicacion de DOLPHOT y obtencion de fotometria estelar de las imagenes

Esta seccion detalla el proceso de enmascaramiento de los hot pixels, calculo del cielo, y por ultimo la generacion del catalogo de estrellas con DOLPHOT.

### 3.1: Aplicacion de acsmask

Es necesario considerar que la imagen si bien esta calibrada, y no es necesario realizar una reduccion de la imagen en si, si es necesario el enmascarar los llamados pixeles calientes, estos pixeles son dependientes del instrumento que tenemos en consideracion, ya que en este caso estamos usando imagenes obtenidas con ACS, pues aplicamos la mascara que viene como parte del modulo incluida, con el siguiente comando aplicamos el enmascaramiento sobre un archivo fits:

```
acsmask <image.fits>
```

Con esto tenemos nuestro archivo fits con los pixeles enmascarados, entonces no seran considerados al generar el catalogo. Igualmente multiplica los pixeles “malos” por el area en pixeles, de esa manera las imagenes estaran en unidades de electrones.

### 3.2: Division de fits por chip

Luego ya que vamos a utilizar una imagen de drizzle para el dithering, tenemos que dividir nuestras 4 imagenes individuales en los 2 chips del ACS, para esto se utiliza el siguiente comando:

```
splitgroups <image.fits>
```

Con esto tenemos 8 imagenes en total a utilizar, 1 por chip, 2 por filtro, entonces tendremos un total de 4 imagenes en cada filtro que estamos considerando.

### 3.3: Calculo del sky

Es necesario realizar un calculo del cielo en las imagenes, para diferenciar las fuentes de la imagen. Para calcular el cielo de nuestras imagenes, el programa realiza una estimacion basada en un anillo alrededor del pixel en consideracion, de esta manera tenemos que entregar el radio interior y exterior del anillo, al igual que la desviacion que esperamos de una fuente para ser considerado como cielo(el cielo igualmente puede tener un dado brillo).

Para calcular el cielo en una imagen, se utiliza el siguiente comando:

```
calcsky <fitsbase> <r_in> <r_out> <step> <sigma_low> <sigma_high>
```

En donde los parametros se definen en orden como, radio interior del anillo, radio exterior del anillo, cada cuantos pixeles se toma el anillo de pixeles, en cada iteracion se calcula el promedio y la desviacion estandar, valores por debajo de  $\sigma_{low}$  se descartan al igual que aquellos valores por encima de  $\sigma_{high}$ .

En el caso de ACS, se recomiendan los siguientes parametros:

$$r_{in} = 1 \mid r_{out} = 12 \mid step = 1 \mid \sigma_{low} \mid \sigma_{high}$$

### 3.4: Definicion de parametros para DOLPHOT

Finalmente se definen los parametros para dolphot en un archivo de parametros, en caso de no ser definido, se tomaran los valores predeterminados del programa que se encuentran dentro de los archivos del software bajo el directorio param/dolphot.param, entonces nuestro archivo de parametros junto con sus definiciones es tal que:

```

Nimg = 8                #number of images (int)
#
# The following parameters can be specified for individual images (img1_...)
# or applied to all images (img_...)
img1_file = j9ec41afq_flg.chip1
img2_file = j9ec41afq_flg.chip2
img3_file = j9ec41agq_flg.chip1
img4_file = j9ec41agq_flg.chip2
img5_file = j9ec41aiq_flg.chip1
img6_file = j9ec41aiq_flg.chip2
img7_file = j9ec41akq_flg.chip1
img8_file = j9ec41akq_flg.chip2
img_shift = 0 0        #shift relative to reference
img_xform = 1 0 0      #scale, distortion, and rotation
img_PSFa = 3 0 0 0 0 0 #PSF XX term (flt)
img_PSFb = 3 0 0 0 0 0 #PSF YY term (flt)
img_PSFc = 0 0 0 0 0 0 #PSF XY term (flt)
img_RAper = 3          #photometry aperture size (flt)
img_RChi = 2.0         #Aperture for determining centroiding (flt); if <=0 use RAper
img_RSky = 15 35       #radii defining sky annulus (flt)>=RAper+0.5)
img_RPSF = 10          #PSF size (int>0)
img_aprad = 20         #radius for aperture correction
img_apsky = 30 50      #sky annulus for aperture correction
#
# The following photometers affect the finding and measurement of stars
photsec =              #section: group, chip, (X,Y)0, (X,Y)1
RCentroid = 1          #centroid box size (int>0)
SigFind = 2.5          #sigma detection threshold (flt)
SigFindMult = 0.85     #Multiple for quick-and-dirty photometry (flt>0)
SigFinal = 3.5         #sigma output threshold (flt)
MaxIT = 25             #maximum iterations (int>0)
FPSF = G+L             #PSF function (str/Gauss,Lorentz,Lorentz^2,G+L)
PSFPhot = 1            #photometry type (int/0=aper,1=psf,2=wtd-psf)
PSFPhotIt = 1          #number of iterations in PSF-fitting photometry (int>=0)
FitSky = 2             #fit sky? (int/0=no,1=yes,2=small,3=with-phot)
SkipSky = 2            #spacing for sky measurement (int>0)
SkySig = 2.25          #sigma clipping for sky (flt>=1)
NegSky = 1             #allow negative sky values? (0=no,1=yes)

```

```

NoiseMult = 0.10      #noise multiple in imgadd (flt)
FSat = 0.999          #fraction of saturate limit (flt)
Zero = 25.0           #zeropoint for 1 DN/s (flt)
PosStep = 0.25        #search step for position iterations (flt)
dPosMax = 2.5         #maximum single-step in position iterations (flt)
RCombine = 1.415      #minimum separation for two stars for cleaning (flt)
SigPSF = 3.0          #min S/N for psf parameter fits (flt)
PSFStep = 0.25        #stepsize for PSF
MinS = 1.0            #minimum FWHM for good star (flt)
MaxS = 9.0            #maximum FWHM for good star (flt)
MaxE = 0.5            #maximum ellipticity for good star (flt)
#
# Settings to enable/disable features
UseWCS = 1            #use WCS info in alignment (int 0=no, 1=shift/rotate/scale, 2=full)
Align = 4             #align images? (int 0=no,1=const,2=lin,3=cube)
AlignIter = 1         #number of iterations on alignment? (int>0)
AlignTol = 0          #number of pixels to search in preliminary alignment (flt>=0)
AlignStep = 1         #stepsize for preliminary alignment search (flt>0)
AlignOnly = 0         #exit after alignment
Rotate = 1            #allow cross terms in alignment? (int 0=no, 1=yes)
SubResRef = 1         #subpixel resolution for reference image (int>0)
SecondPass = 5        #second pass finding stars (int 0=no,1=yes)
SearchMode = 1        #algorithm for astrometry (0=max SNR/chi, 1=max SNR)
Force1 = 0            #force type 1/2 (stars)? (int 0=no,1=yes)
EPSF = 1             #allow elliptical PSFs in parameter fits (int 0=no,1=yes)
PSFsol = 1           #Analytic PSF solution (int -1=none, 0=con, 1=lin, 2=quad)
PSFres = 1           #make PSF residual image? (int 0=no,1=yes)
psfstars =           #Coordinates of PSF stars
psfoff = 0.0         #coordinate offset (PSF system - dolphot system)
ApCor = 1            #find/make aperture corrections? (int 0=no,1=yes)
SubPixel = 1         #subpixel PSF calculation (int>0)
FakeStars =          #file with fake star input data
FakeOut =            #file with fake star output data (default=phot.fake)
FakeMatch = 3.0       #maximum separation between input and recovered star (flt>0)
FakePSF = 2.0        #assumed PSF FWHM for fake star matching
FakeStarPSF = 1       #use PSF residuals in fake star tests? (int 0=no,1=yes)
RandomFake = 1       #apply Poisson noise to fake stars? (int 0=no,1=yes)
FakePad = 0          #minimum distance of fake star from any chip edge to be used
UsePhot =            #if defined, use alignment, PSF, and aperture corr from photometry
DiagPlotType =       #format to generate diagnostic plots (PNG, GIF, PS)
xytfile =            #position file for warmstart (str)
xytpsf =             #reference PSF for image subtraction
VerboseData = 0      #to write all displayed numbers to a .data file
#
# Flags for HST modes
ForceSameMag = 0     #force same count rate in images with same filter? (int 0=no, 1=yes)

```

```

FlagMask = 4           #photometry quality flags to reject when combining magnitudes
CombineChi = 0          #combined magnitude weights uses chi? (int 0=no, 1=yes)
WFPC2useCTE = 0        #apply CTE corrections on WFPC2 data? (int 0=no, 1=yes)
ACSuseCTE = 0          #apply CTE corrections on ACS data? (int 0=no, 1=yes)
WFC3useCTE = 0         #apply CTE corrections on WFC3 data? (int 0=no, 1=yes)
ACSPsfType = 0         #use Anderson PSF cores? (int 0=no, 1=yes)
WFC3UVISpsfType = 0    #use Anderson PSF cores? (int 0=no, 1=yes)
WFC3IRpsfType = 0      #use Anderson PSF cores? (int 0=no, 1=yes)
InterpPSFlib = 1       #interpolate PSF library spatially
#
# Other flags not recommended for most users
#img_ref2img =          #high order terms for conversion between image (distortion-corrected)

```

Que replican los valores tomados en Monachesi et al. 2016.

### 3.5: Ejecucion de DOLPHOT

Finalmente para ejecutar dolphot sobre las imagenes a partir de nuestro archivo de parametros solo se utiliza el siguiente comando:

```
dolphot -p<parametros.param>
```

## Paso 4: Analisis del catalogo estelar generado

En esta seccion se detallan los metodos para el analisis del catalogo obtenido, el catalogo se encuentra dentro del , bajo el nombre de catalogo.fits.

### 4.1: Mini revision de conceptos

Es necesario el saber las definiciones explicitas de los valores que DOLPHOT encuentra para los objetos, esto es clave en el analisis para discernir los objetos de interes para analizar poblaciones estelares resueltas.

Dolphot genera multiples archivos al ser ejecutado, uno de estos archivos clave es el “columns”, que detalla que es cada columna del catalogo generado.

**4.1.1: Object types** Object type indica la naturaleza de la fuente detectada por DOLPHOT, este valor se extiende desde 1 hasta 5, siendo las definiciones en orden tal que:

- 1 = bright star
- 2 = faint
- 3 = elongated
- 4 = hot pixel
- 5 = extended

En el caso del presente trabajo claramente necesitamos considerar tan solo las estrellas, entonces aquellos elementos del catalogo de objectype 1.



**4.1.2: Cull de objetos extendidos** Luego si bien tenemos seleccionados los elementos clasificados como estrellas brillantes, no tenemos un estandar de que tan buena calidad son en si mismos, pero podemos utilizar tanto el sharpness como el crowding para evitar aquellos objetos que puedan ser problematicos en el analisis, como estrellas superpuestas(en las zonas muy densas de estrellas).

Para ello se consideran los limites establecidos por Radburn-Smith et al. 2011, los cuales son los siguientes:

The final selection criteria adopted for selecting stars in sparse fields are:

$$-0.06 < sharpness_{F606W} + sharpness_{F814W} < 1.30 \quad (1)$$

$$crowding_{F606W} + crowding_{F814W} < 0.16 \quad (2)$$

$$S/N_{F606W} > 5.0 \ \& \ S/N_{F814W} > 5.0 \quad (3)$$

#### 4.2: Correccion de la extincion galactica

Finalmente tenemos que corregir nuestras magnitudes en cada filtro por la extincion galactica, para ello tomamos el valor de extincion en el filtro V de Monachesi et al. 2016 y de Schlafly & Finkbeiner 2011 tenemos que para F606W y F814W considerando  $R_V = 3.1$ :

$$A_{F606W}/E(B-V) = 2.471 \quad (4) \mid A_{F814W}/E(B-V) = 1.526 \quad (5)$$

$$A_{F606W} = 2.471 * E(B-V) \quad (5) \mid A_{F814W} = 1.526 * E(B-V) \quad (7)$$

y la ley de extincion es:

$$R_V = A_V/E(B-V) \quad (8)$$

Obtenemos el exceso de color de esta ultima ecuacion:

$$E(B-V) = A_V/R_V \quad (9)$$

Entonces claramente podemos reemplazar  $E(B-V)$  en las ecuaciones 5 y 7 con 9, para obtener:

$$A_{F606W} = 2.471 * A_V/R_V \quad (10) \mid A_{F814W}/E(B-V) = 1.526 * A_V/R_V \quad (11)$$

Finalmente reemplazamos, con  $A_V = 0.19$  obtenido de Monachesi et al. 2016a tabla 1 y  $R_V = 3.1$  en las ecuaciones 10 y 11:


$$A_{F606W} = 2.471 * (0.19/3.1) \quad (12) \mid A_{F814W} = 1.526 * (0.19/3.1) \quad (13)$$

Obteniendo asi los valores de la extincion galactica en el caso de nuestro catalogo.

$$A_{F606W} = 0.151 \mid A_{F814W} = 0.0935.$$

#### 4.3: CMD(F606W-F814W vs. F814W) de las estrellas

Finalmente con las magnitudes del catalogo corregidas por la extincion galactica obtenemos el diagrama color-magnitud de las estrellas resueltas en NGC 3031:




#### 4.4: Estimacion de la TRGB

Para estimar la magnitud aparente de la TRGB se utiliza el metodo de Mendez et al. 2003 basado en la funcion de luminosidad de las estrellas del catalogo, este metodo se basa en el cambio brusco, o mas bien el cambio de la pendiente de la funcion de luminosidad, como marca de la TRGB.


Previo a realizar la funcion de luminosidad limitamos las estrellas a considerar a tan solo aquellas pertenecientes a la rama principal, asi evitamos estrellas de otras etapas evolutivas como enanas blancas. Tomamos las siguientes limitaciones.

- $m_{F606W} - m_{F814W} < -4.8 * ((m_{F606W} - m_{F814W})) + 32$
- $m_{F606W} - m_{F814W} > -4.8 * ((m_{F606W} - m_{F814W})) + 27.5$


Siendo entonces las estrellas a considerar en amarillo en el CMD tal que:



Finalmente entonces la funcion de luminosidad de nuestro catalogo es tal que:



Y luego entonces la gradiente de la funcion de luminosidad, nos dira en que punto de la funcion de luminosidad cambia bruscamente la misma. La gradiente es tal que:



Entonces tomamos el 2do peak de la gradiente como la magnitud aparente de nuestra TRGB. Mostramos el CMD en conjunto con la funcion de luminosidad, para demostrar con mayor claridad el concepto propuesto.

#### 4.5: Estimacion de $t_j$

Para estimar  $t_j$  se toma una region del CMD, para considerar las estrellas que pasan por una dada etapa evolutiva y se cuentan, de esta manera sabiendo que:

#### 4.6: Ajuste de isocronas

Finalmente se ajustan isocronas a nuestro CMD obtenido para estimar la edad, en este caso se utiliza un metodo “eyeball”, por lo que se consideran...

### Paso 5: Recopilacion de lo obtenido

Esta seccion recopila lo pedido para la evaluacion del trabajo, el orden de las subsecciones es segun las directivas señalas para la evaluacion.

#### 5.A: Makefile

El archivo Makefile es tal que:

```
#if your machine uses cc instead of gcc, edit the following:
export CC=gcc
export FC=g77
export MAKE=make

#set the base directory
export BASE_DIR = /home/marcoritou/Documents/PHD_Level3/topicos/practicadolphot/dolphot2.0

#uncomment and set PGLOT files if installed
```

```

#export PGHEAD = \"/usr/local/include/cpgplot.h\"
#export PGPLOT = -L/usr/local/lib -lcpgplot -lpng -L/usr/X11R6/lib -lX11 -L/usr/lib

#compilation flags
export CFLAGS= -O3 -Wall -m64

#uncomment if you will be using the WFPC2 module
#export USEWFPC2=1

#uncomment if you will be using the ACS module
export USEACS=1

#uncomment if you will be using the WFC3 module
#export USEWFC3=1

#uncomment if you will be using the ROMAN module
#export USEROMAN=1

#uncomment if you will be using the NIRCAM module
#export USENIRCAM=1

#uncomment if you will be using the NIRISS module
#export USENIRISS=1

#uncomment if you will be using the MIRI module
#export USEMIRI=1

#set the directory where Tiny Tim binaries are located (ACS/WFPC2/WFC3 PSF generation):
#export USETT=1
#export CFLAGS+= -DTTDIR=\"/data0/tinytim-7.0\"

#set maximum number of images, and maximum number of stars
export CFLAGS+= -DMAXNIMG=100
export CFLAGS+= -DMAXNSTARS=2000000

#optionally print and/or crash if a NaN occurs (intended for development only)
export CFLAGS+= -DNAN_PRINT
#export CFLAGS+= -DNAN_CRASH

##### NO FURTHER ADJUSTMENTS BELOW THIS LINE #####

#add base directory settings to flags
export CFLAGS += -DBASEDIR=\"$(BASE_DIR)\" -I$(BASE_DIR)/include

#definitions
ALLEXE = dolphot_lib.o fits_lib.o fakeproc.o bin/addstars bin/apphot bin/calcsky bin/dolphot

```

```

ALL = $(ALLEXE) ccdred
DOLPHOT_DEP = dolphot_lib.o fits_lib.o dolphot_common.h dolphot_defs.h
DOLPHOT_OBJ = dolphot_lib.o fits_lib.o
DOLPHOT_FOBJ =

#linked libraries
export LIBS = -lm

#add WFPC2 modules, if selected
ifdef USEWFPC2
export CFLAGS+= -DUSEWFPC2
ALL+= wfpc2
DOLPHOT_DEP += wfpc2
DOLPHOT_OBJ += wfpc2/wfpc2phot.o wfpc2/wfpc2filters.o wfpc2/wfpc2distort.o
DOLPHOT_FOBJ += wfpc2/wfpc2filters.o
endif

#add ACS modules, if selected
ifdef USEACS
export CFLAGS+= -DUSEACS
ALL+= acs
DOLPHOT_DEP += acs
DOLPHOT_OBJ += acs/acsphot.o acs/acsfilters.o acs/acsdistort.o
DOLPHOT_FOBJ += acs/acsfilters.o
endif

#add WFC3 modules, if selected
ifdef USEWFC3
export CFLAGS+= -DUSEWFC3
ALL+= wfc3
DOLPHOT_DEP += wfc3
DOLPHOT_OBJ += wfc3/wfc3phot.o wfc3/wfc3filters.o wfc3/wfc3distort.o
DOLPHOT_FOBJ += wfc3/wfc3filters.o
endif

#add ROMAN modules, if selected
ifdef USEROMAN
export CFLAGS+= -DUSEROMAN
ALL+= roman
DOLPHOT_DEP += roman
DOLPHOT_OBJ += roman/romanphot.o roman/romanfilters.o roman/romandistort.o
DOLPHOT_FOBJ += roman/romanfilters.o
endif

#add NIRCAM modules, if selected
ifdef USENIRCAM

```

```

export CFLAGS+= -DUSENIRCAM
ALL+= nircam
DOLPHOT_DEP += nircam
DOLPHOT_OBJ += nircam/nircamphot.o nircam/nircamfilters.o nircam/nircamdistort.o
DOLPHOT_FOBJ += nircam/nircamfilters.o
endif

#add NIRISS modules, if selected
ifdef USENIRISS
export CFLAGS+= -DUSENIRISS
ALL+= niriss
DOLPHOT_DEP += niriss
DOLPHOT_OBJ += niriss/nirissphot.o niriss/nirissfilters.o niriss/nirissdistort.o
DOLPHOT_FOBJ += niriss/nirissfilters.o
endif

#add MIRI modules, if selected
ifdef USEMIRI
export CFLAGS+= -DUSEMIRI
ALL+= miri
DOLPHOT_DEP += miri
DOLPHOT_OBJ += miri/miriphot.o miri/mirifilters.o miri/miridistort.o
DOLPHOT_FOBJ += miri/mirifilters.o
endif

#add display module, if selected
ifdef PGPLOT
ALL+= display.o
ALLEXE+= display.o
endif

all: $(ALL)

ifdef USEWFPC2
wfpc2::
    cd wfpc2; $(MAKE)
endif

ifdef USEACS
acs::
    cd acs; $(MAKE)
endif

ifdef USEWFC3
wfc3::
    cd wfc3; $(MAKE)

```



```

endif

ifdef USEROMAN
roman::
    cd roman; $(MAKE)
endif

ifdef USENIRCAM
nircam::
    cd nircam; $(MAKE)
endif

ifdef USENIRISS
niriss::
    cd niriss; $(MAKE)
endif

ifdef USEMIRI
miri::
    cd miri; $(MAKE)
endif

ccdred::
    cd ccdred; $(MAKE)

dolphot_lib.o: dolphot_lib.c include/dolphot.h
    $(CC) $(CFLAGS) -c -o $@ $<

fits_lib.o: fits_lib.c include/dolphot.h include/fits.h
    $(CC) $(CFLAGS) -c -o $@ $<

bin/addstars: addstars.c $(DOLPHOT_DEP)
    $(CC) $(CFLAGS) -o $@ addstars.c $(DOLPHOT_OBJ) $(LIBS)

bin/convertpos: convertpos.c $(DOLPHOT_DEP)
    $(CC) $(CFLAGS) -o $@ convertpos.c $(DOLPHOT_OBJ) $(LIBS)

ifdef PGPLOT
display.o: display.c dolphot_lib.o fits_lib.o
    $(CC) $(CFLAGS) -c -o $@ $< -DPGHEAD=$(PGHEAD)

bin/apphot: apphot.c dolphot_lib.o fits_lib.o display.o
    $(CC) $(CFLAGS) -c apphot.c -DPGPLOT -DPGHEAD=$(PGHEAD)
    $(FC) -o $@ apphot.o dolphot_lib.o fits_lib.o display.o $(LIBS) $(PGPLOT)
    rm apphot.o

```

```

bin/dolphot: dolphot.c $(DOLPHOT_DEP)
    $(CC) $(CFLAGS) -c dolphot.c -DPGPLOT -DPGHEAD=$(PGHEAD)
    $(FC) -o $$ dolphot.o $(DOLPHOT_OBJ) $(LIBS) $(PGPLOT)
    rm dolphot.o
else
bin/apphot: apphot.c dolphot_lib.o fits_lib.o
    $(CC) $(CFLAGS) -o $$ apphot.c dolphot_lib.o fits_lib.o $(LIBS)

bin/dolphot: dolphot.c $(DOLPHOT_DEP)
    $(CC) $(CFLAGS) -o $$ dolphot.c $(DOLPHOT_OBJ) $(LIBS)
endif

bin/calcsky: calcsky.c dolphot_lib.o fits_lib.o
    $(CC) $(CFLAGS) -o $$ calcsky.c dolphot_lib.o fits_lib.o $(LIBS)

bin/synthing: synthing.c dolphot_lib.o fits_lib.o
    $(CC) $(CFLAGS) -o $$ synthing.c dolphot_lib.o fits_lib.o $(LIBS)

bin/fakelist: fakelist.c fakeproc.o fakeproc.h $(DOLPHOT_FOBJ)
    $(CC) $(CFLAGS) -o $$ fakelist.c fakeproc.o $(DOLPHOT_FOBJ) $(LIBS)

clean:
    rm $(ALLEXE)
    cd ccdred ; $(MAKE) clean
ifdef USEWFPC2
    cd wfpc2 ; $(MAKE) clean
endif
ifdef USEACS
    cd acs ; $(MAKE) clean
endif
ifdef USEWFC3
    cd wfc3 ; $(MAKE) clean
endif
ifdef USEROMAN
    cd roman ; $(MAKE) clean
endif
ifdef USENIRCAM
    cd nircam ; $(MAKE) clean
endif
ifdef USENIRISS
    cd niriss ; $(MAKE) clean
endif
ifdef USEMIRI
    cd miri ; $(MAKE) clean
endif
e

```

## 5.B: Parametros de DOLPHOT

El archivo de parametros para DOLPHOT replica los valores considerados en [Monachesi et al. 2016]:

```
Nimg = 8                      #number of images (int)
#
# The following parameters can be specified for individual images (img1_...)
# or applied to all images (img_...)
img1_file = j9ec41afq_flg.chip1
img2_file = j9ec41afq_flg.chip2
img3_file = j9ec41agq_flg.chip1
img4_file = j9ec41agq_flg.chip2
img5_file = j9ec41aiq_flg.chip1
img6_file = j9ec41aiq_flg.chip2
img7_file = j9ec41akq_flg.chip1
img8_file = j9ec41akq_flg.chip2
img_shift = 0 0              #shift relative to reference
img_xform = 1 0 0            #scale, distortion, and rotation
img_PSFa = 3 0 0 0 0 0      #PSF XX term (flt)
img_PSFb = 3 0 0 0 0 0      #PSF YY term (flt)
img_PSFc = 0 0 0 0 0 0      #PSF XY term (flt)
img_RAper = 3                #photometry aperture size (flt)
img_RChi = 2.0               #Aperture for determining centroiding (flt); if <=0 use RAper
img_RSky = 15 35             #radii defining sky annulus (flt)>=RAper+0.5)
img_RPSF = 10                #PSF size (int>0)
img_aprad = 20               #radius for aperture correction
img_apsky = 30 50           #sky annulus for aperture correction
#
# The following photometers affect the finding and measurement of stars
photsec =                    #section: group, chip, (X,Y)0, (X,Y)1
RCentroid = 1                #centroid box size (int>0)
SigFind = 2.5                #sigma detection threshold (flt)
SigFindMult = 0.85           #Multiple for quick-and-dirty photometry (flt>0)
SigFinal = 3.5               #sigma output threshold (flt)
MaxIT = 25                   #maximum iterations (int>0)
FPSF = G+L                   #PSF function (str/Gauss,Lorentz,Lorentz^2,G+L)
PSFPhot = 1                  #photometry type (int/0=aper,1=psf,2=wtd-psf)
PSFPhotIt = 1                #number of iterations in PSF-fitting photometry (int>=0)
FitSky = 2                   #fit sky? (int/0=no,1=yes,2=small,3=with-phot)
SkipSky = 2                  #spacing for sky measurement (int>0)
SkySig = 2.25                #sigma clipping for sky (flt>=1)
NegSky = 1                   #allow negative sky values? (0=no,1=yes)
NoiseMult = 0.10             #noise multiple in imgadd (flt)
FSat = 0.999                 #fraction of saturate limit (flt)
Zero = 25.0                  #zeropoint for 1 DN/s (flt)
```

```

PosStep = 0.25          #search step for position iterations (flt)
dPosMax = 2.5           #maximum single-step in position iterations (flt)
RCombine = 1.415        #minimum separation for two stars for cleaning (flt)
SigPSF = 3.0           #min S/N for psf parameter fits (flt)
PSFStep = 0.25         #stepsize for PSF
MinS = 1.0             #minimum FWHM for good star (flt)
MaxS = 9.0             #maximum FWHM for good star (flt)
MaxE = 0.5             #maximum ellipticity for good star (flt)
#
# Settings to enable/disable features
UseWCS = 1             #use WCS info in alignment (int 0=no, 1=shift/rotate/scale, 2=full)
Align = 4              #align images? (int 0=no,1=const,2=lin,3=cube)
AlignIter = 1          #number of iterations on alignment? (int>0)
AlignTol = 0           #number of pixels to search in preliminary alignment (flt>=0)
AlignStep = 1          #stepsize for preliminary alignment search (flt>0)
AlignOnly = 0          #exit after alignment
Rotate = 1             #allow cross terms in alignment? (int 0=no, 1=yes)
SubResRef = 1          #subpixel resolution for reference image (int>0)
SecondPass = 5         #second pass finding stars (int 0=no,1=yes)
SearchMode = 1         #algorithm for astrometry (0=max SNR/chi, 1=max SNR)
Force1 = 0             #force type 1/2 (stars)? (int 0=no,1=yes)
EPSF = 1              #allow elliptical PSFs in parameter fits (int 0=no,1=yes)
PSFsol = 1            #Analytic PSF solution (int -1=none, 0=con, 1=lin, 2=quad)
PSFres = 1            #make PSF residual image? (int 0=no,1=yes)
psfstars =            #Coordinates of PSF stars
psfoff = 0.0          #coordinate offset (PSF system - dolphot system)
ApCor = 1             #find/make aperture corrections? (int 0=no,1=yes)
SubPixel = 1          #subpixel PSF calculation (int>0)
FakeStars =           #file with fake star input data
FakeOut =             #file with fake star output data (default=phot.fake)
FakeMatch = 3.0        #maximum separation between input and recovered star (flt>0)
FakePSF = 2.0          #assumed PSF FWHM for fake star matching
FakeStarPSF = 1        #use PSF residuals in fake star tests? (int 0=no,1=yes)
RandomFake = 1         #apply Poisson noise to fake stars? (int 0=no,1=yes)
FakePad = 0           #minimum distance of fake star from any chip edge to be used
UsePhot =             #if defined, use alignment, PSF, and aperture corr from photometry
DiagPlotType =        #format to generate diagnostic plots (PNG, GIF, PS)
xytfile =             #position file for warmstart (str)
xytpsf =              #reference PSF for image subtraction
VerboseData = 0        #to write all displayed numbers to a .data file
#
# Flags for HST modes
ForceSameMag = 0       #force same count rate in images with same filter? (int 0=no, 1=yes)
FlagMask = 4           #photometry quality flags to reject when combining magnitudes
CombineChi = 0         #combined magnitude weights uses chi? (int 0=no, 1=yes)
WFPC2useCTE = 0       #apply CTE corrections on WFPC2 data? (int 0=no, 1=yes)

```

```

ACSuseCTE = 0          #apply CTE corrections on ACS data? (int 0=no, 1=yes)
WFC3useCTE = 0          #apply CTE corrections on WFC3 data? (int 0=no, 1=yes)
ACSpsfType = 0          #use Anderson PSF cores? (int 0=no, 1=yes)
WFC3UVISpsfType = 0     #use Anderson PSF cores? (int 0=no, 1=yes)
WFC3IRpsfType = 0       #use Anderson PSF cores? (int 0=no, 1=yes)
InterpPSFlib = 1        #interpolate PSF library spatially
#
# Other flags not recommended for most users
#img_ref2img =          #high order terms for conversion between image (distortion-corrected)

```

### 5.C: CMD con isocrona ajustada

CMD del catalogo junto con isocrona final considerada:

**Download DOLPHOT**

[DOLPHOT 1.0 base sources](#) (updated 14 Mar 2007)  
[DOLPHOT 1.1 base sources](#) (updated 6 Sep 2010)  
[DOLPHOT 1.2 base sources](#) (updated 25 Jan 2011)  
[DOLPHOT 2.0 base sources](#) (updated 9 Dec 2022)  
[DOLPHOT 2.0 manual](#) (also included in base sources)  
[HSTphot paper](#) (from PASP website)

---

**DOLPHOT ACS Module**

[DOLPHOT 1.0 ACS module sources](#) (updated 11 Feb 2007)  
[DOLPHOT 1.1 ACS module sources](#) (updated 6 Sep 2010)  
[DOLPHOT 1.2 ACS module sources](#) (updated 14 Nov 2010)  
[DOLPHOT 2.0 ACS module sources](#) (updated 24 Feb 2016)  
[DOLPHOT 2.0 ACS module manual](#) (also included in sources)

**ACS PSFs and Pixel Area Maps**

ACS/HRC	ACS/WFC	ACS/WFC with Anderson Cores
<a href="#">Pixel Area Map</a>	<a href="#">Pixel Area Map</a>	<a href="#">F435W PSF</a>
<a href="#">F220W PSF</a>	<a href="#">F435W PSF</a>	<a href="#">F475W PSF</a>
<a href="#">F250W PSF</a>	<a href="#">F475W PSF</a>	<a href="#">F606W PSF</a>
<a href="#">F330W PSF</a>	<a href="#">F502N PSF</a>	<a href="#">F625W PSF</a>
<a href="#">F344N PSF</a>	<a href="#">F550M PSF</a>	<a href="#">F658N PSF</a>
<a href="#">F435W PSF</a>	<a href="#">F555W PSF</a>	<a href="#">F775W PSF</a>
<a href="#">F475W PSF</a>	<a href="#">F606W PSF</a>	<a href="#">F814W PSF</a>
<a href="#">F502N PSF</a>	<a href="#">F625W PSF</a>	<a href="#">F850LP PSF</a>
<a href="#">F550M PSF</a>	<a href="#">F658N PSF</a>	
<a href="#">F555W PSF</a>	<a href="#">F660N PSF</a>	
<a href="#">F606W PSF</a>	<a href="#">F775W PSF</a>	
<a href="#">F625W PSF</a>	<a href="#">F814W PSF</a>	
<a href="#">F658N PSF</a>	<a href="#">F850LP PSF</a>	
<a href="#">F660N PSF</a>	<a href="#">F892N PSF</a>	
<a href="#">F775W PSF</a>		
<a href="#">F814W PSF</a>		
<a href="#">F850LP PSF</a>		
<a href="#">F892N PSF</a>		

### 5.D: Valores estimados de la magnitud de la TRGB y $t_j$

Se estimo que la magnitud aparente de la TRGB es:

$$m_{TRGB} = 23$$

entregando asi una distancia de:

$$d = 3.24_{Mpc}$$

Finalmente se obtuvo:

$$t_j = 13_{Gyrs}$$

### 5.E: Imagen en banda F606W con estrellas superpuestas

Imagen en banda F606W con las estrellas indicada en circulos amarillos.

**Download DOLPHOT**

[DOLPHOT 1.0 base sources](#) (updated 14 Mar 2007)  
[DOLPHOT 1.1 base sources](#) (updated 6 Sep 2010)  
[DOLPHOT 1.2 base sources](#) (updated 25 Jan 2011)  
[DOLPHOT 2.0 base sources](#) (updated 9 Dec 2022)  
[DOLPHOT 2.0 manual](#) (also included in base sources)  
[HSTphot paper](#) (from PASP website)

---

**DOLPHOT ACS Module**

[DOLPHOT 1.0 ACS module sources](#) (updated 11 Feb 2007)  
[DOLPHOT 1.1 ACS module sources](#) (updated 6 Sep 2010)  
[DOLPHOT 1.2 ACS module sources](#) (updated 14 Nov 2010)  
[DOLPHOT 2.0 ACS module sources](#) (updated 24 Feb 2016)  
[DOLPHOT 2.0 ACS module manual](#) (also included in sources)

**ACS PSFs and Pixel Area Maps**

ACS/HRC	ACS/WFC	ACS/WFC with Anderson Cores
<a href="#">Pixel Area Map</a>	<a href="#">Pixel Area Map</a>	<a href="#">F435W PSF</a>
<a href="#">F220W PSF</a>	<a href="#">F435W PSF</a>	<a href="#">F475W PSF</a>
<a href="#">F250W PSF</a>	<a href="#">F475W PSF</a>	<a href="#">F606W PSF</a>
<a href="#">F330W PSF</a>	<a href="#">F502N PSF</a>	<a href="#">F625W PSF</a>
<a href="#">F344N PSF</a>	<a href="#">F550M PSF</a>	<a href="#">F658N PSF</a>
<a href="#">F435W PSF</a>	<a href="#">F555W PSF</a>	<a href="#">F775W PSF</a>
<a href="#">F475W PSF</a>	<a href="#">F606W PSF</a>	<a href="#">F814W PSF</a>
<a href="#">F502N PSF</a>	<a href="#">F625W PSF</a>	<a href="#">F850LP PSF</a>
<a href="#">F550M PSF</a>	<a href="#">F658N PSF</a>	
<a href="#">F555W PSF</a>	<a href="#">F660N PSF</a>	
<a href="#">F606W PSF</a>	<a href="#">F775W PSF</a>	
<a href="#">F625W PSF</a>	<a href="#">F814W PSF</a>	
<a href="#">F658N PSF</a>	<a href="#">F850LP PSF</a>	
<a href="#">F660N PSF</a>	<a href="#">F892N PSF</a>	
<a href="#">F775W PSF</a>		
<a href="#">F814W PSF</a>		
<a href="#">F850LP PSF</a>		
<a href="#">F892N PSF</a>		

### 5.F: Discusion: Poblaciones encontradas, completitud y crowding

Tomando en consideracion los resultados obtenidos, se estima que NGC3031 tiene una edad estimada de  $\sim 10$  Gyrs con una metalicidad de  $[Fe/H] = 121$ , si bien se consideraron los efectos que podria tener el crowding, el tamaño de pixel considerado aun asi puede ocultar multiples estrellas bajo un mismo pixel. Aun asi el trabajo presentado a tomado los parametros para considerar estrellas resueltas de calidad estipulados en Radburn-Smith et al. 2011.

En cuanto a completitud la magnitud aparente mas tenue del catalogo utilizado en el CMD es  $m_{min} = 20$ , que en el caso de NGC3031, el cual se encuentra a una distancia estimada en el documento de  $d = 3.24 Mpc$ , supone una magnitud absoluta alcanzada de  $M_{min} = -15$ , dejando asi igualmente las estrellas mas debiles del sistema fuera del analisis. Sabiendo entonces que son las estrellas

de menor masa las que contribuyen la mayoría del brillo en las galaxias, esto es una limitación del estudio presentado.

Aun así el ejercicio realizado demuestra como con datos ya presentes y públicos en astronomía es posible realizar evaluaciones concretas de sistemas de estrellas resueltas en el universo, todo realizado con herramientas, datos y métodos públicamente disponibles en la web.

## **Apendice**

Sección de figuras o temas extra no mencionados en el trabajo.

Aquí se señalan elementos extras realizados durante el desarrollo de la práctica, no fueron colocados como parte del cuerpo principal, ya que no responden a específicos puntos de la evaluación.