

Contents

1	Template	2
2	Search	3
2.1	Ternary Search	3
3	Data Structures	3
3.1	Segment Tree	3
3.2	Monotonic Queue	4
4	Sequences	4
4.1	Max/Min subsegment	4
4.1.1	Max/Min submatrix	5
5	Algebra	5
5.1	All divisors	5
5.2	Primality test	6
5.3	Binary exponentiation	6
5.4	Greatest common divisor	6
5.4.1	Least common multiple	7
5.4.2	Extended Euclides Algorithm	7
5.5	Linear Diophantine Equations	7
5.5.1	Any solution	7
5.6	Integer Factorization	7
5.6.1	Pollard's Rho	7
5.7	Fast Fourier Transform	9
5.7.1	Polynomial Multiplication	9
6	Graphs	10
6.1	DFS	10
6.2	BFS	11
6.2.1	Shortest path on unweighted graph	11
6.3	Flood Fill	12
6.4	Topological Sort (Directed Acyclic Graph)	12
6.4.1	DFS Variation	12
6.4.2	Kahn's Algorithm	13
6.5	Bipartite Graph Check (Undirected Graph)	13
6.6	Cycle Check (Directed Graph)	14
6.7	Dijkstra	15
7	Dynamic Programming	15
7.1	Coin Change	15
7.1.1	Canonicity check	16
7.2	Knapsack	17
7.3	LIS	18
7.4	Travelling Salesman Problem	19

8	Math Formulas	20
8.1	Sum of an arithmetic progression	20
8.2	Permutation with repeated elements	20
8.3	Check if is geometric progression	20
8.4	Bitwise equations	20
8.5	Cube of Binomial	20
8.5.1	Sum of Cubes	20
8.5.2	Difference of Cubes	21
8.6	Binomial expansion	21
9	Facts	21
9.1	XOR	21
9.1.1	Self-inverse property	21
9.1.2	Identity element	21
9.1.3	Commutative	21
9.1.4	Associative	21

1 Template

```

1 #include <bits/stdc++.h>
2 using namespace std;
3
4 #define dedinhos cin.tie(0)->sync_with_stdio(0)
5 using ll = long long;
6 #define vll vector<ll>
7 #define vvll vector<vll>
8 #define pll pair<ll, ll>
9 #define vpll vector<pll>
10 #define vvpll vector<vpll>
11 #define endl '\n'
12 #define all(xs) xs.begin(), xs.end()
13 #define found(x, xs) (xs.find(x) != xs.end())
14 #define rep(i, a, b) for(ll i = (a); i < (ll)(b); ++i)
15 #define per(i, a, b) for(ll i = (a); i >= (ll)(b); --i)
16 #define eb emplace_back
17
18 signed main() {
19
20
21     return 0;
22 }

```

2 Search

2.1 Ternary Search

$O(\log n)$

Function $f(x)$ is unimodal on an interval $[l, r]$. Unimodal means: the function strictly increases first, reaches a maximum, and then strictly decreases OR the function strictly decreases first, reaches a minimum and then strictly increases

```
1 double ternary_search(double l, double r) {
2     double eps = 1e-9; // error limit
3     while(r - l > eps) {
4         double m1 = l + (r-l) / 3;
5         double m2 = r - (r-l) / 3;
6
7         double f1 = f(m1);
8         double f2 = f(m2);
9
10        if(f1 < f2)
11            l = m1;
12        else
13            r = m2;
14    }
15
16    return f(l);
17 }
```

3 Data Structures

3.1 Segment Tree

$O(n \log n)$

Maximum value variation.

```
1 /**
2  * Author: Lucian Bicsi
3  * Date: 2017-10-31
4  * License: CC0
5  * Source: folklore
6  * Description: Zero-indexed max-tree. Bounds are inclusive
7  *              to the left and exclusive to the right.
8  * Can be changed by modifying T, f and unit.
9  * Status: stress-tested
10 */
11 struct Tree {
12     typedef int T;
13     static constexpr T unit = INT_MIN;
```

```

14 T f(const T &a, const T &b) { return max(a, b); } // (any
    associative fn)
15 vector<T> s; int n;
16 Tree(int n = 0, T def = unit) : s(2*n, def), n(n) {}
17 void update(int pos, T val) {
18     for (s[pos += n] = val; pos /= 2;)
19         s[pos] = f(s[pos * 2], s[pos * 2 + 1]);
20 }
21 T query(int b, int e) { // query [b, e)
22     T ra = unit, rb = unit;
23     for (b += n, e += n; b < e; b /= 2, e /= 2) {
24         if (b % 2) ra = f(ra, s[b++]);
25         if (e % 2) rb = f(s[--e], rb);
26     }
27     return f(ra, rb);
28 }
29 };

```

3.2 Monotonic Queue

$O(n)$

Can be used to find the nearest max/min element to the left/right

Can be used to find the max/min element to the left/right

Can be used to find the sum of the max/min element of all intervals. Formula:

$$L_i = p(i), R_i = n(i)$$

If R_i is the new smallest/biggest, $R_i = n$. If L_i is the new smallest/biggest,

$$L_i = -1.$$

$$ans += a[i](i - L_i)(R_i - i)$$

4 Sequences

4.1 Max/Min subsegment

$O(n)$

```

1 ll kadane(const vll &a) {
2     ll n = a.size();
3     ll ans = a[0], ans_l = 0, ans_r = 0;
4     ll sum = 0, minus_pos = -1;
5
6     for (ll r = 0; r < n; ++r) {
7         sum += a[r];
8         if (sum > ans) {
9             ans = sum;
10             ans_l = minus_pos + 1;
11         }
12     }
13 }

```

```

12         ans_r = r;
13     }
14     if (sum < 0) {
15         sum = 0;
16         minus_pos = r;
17     }
18 }
19
20 return ans;
21 }

```

4.1.1 Max/Min submatrix

$O(nm^2)$

```

1 ll MSR(ll n, ll m, const vll &a) {
2     ll ans = -LLONG_MAX;
3
4     for(ll i=0; i<m; i++) {
5         vll r(n+1, 0);
6
7         for(ll j=i; j<m; j++) {
8             for(ll k=0; k<n; k++)
9                 r[k] += a[k][j];
10
11             ans = max(ans, kadane(n, r));
12         }
13     }
14
15     return ans;
16 }

```

5 Algebra

5.1 All divisors

$O(\sqrt{n})$

```

1 vll divisors(ll n) {
2     vll divs;
3     for (ll i = 1; 1LL * i * i <= n; i++) {
4         if (n % i == 0) {
5             divs.push_back(i);
6             if (i != n / i) {
7                 divs.push_back(n / i);
8             }
9         }
10    }

```

```

11     return divs;
12 }
13

```

5.2 Primality test

$O(\sqrt{n})$

```

1 bool isPrime(ll n)
2 {
3     if(n!=2 && n % 2==0)
4         return false;
5
6     for(ll d=3; d*d <= n; d+=2)
7     {
8         if(n % d==0)
9             return false;
10    }
11
12    return n >= 2;
13 }

```

5.3 Binary exponentiation

$O(\log n)$

```

1 ll bincpow(ll a, ll b) {
2     ll res = 1;
3     while (b > 0) {
4         if (b & 1)
5             res = res * a;
6         a = a * a;
7         b >>= 1;
8     }
9     return res;
10 }

```

5.4 Greatest common divisor

$O(\log \min(a, b))$

```

1 ll gcd (ll a, ll b) {
2     while (b) {
3         a %= b;
4         swap(a, b);
5     }
6     return a;
7 }

```

5.4.1 Least common multiple

```
1 ll lcm(ll a, ll b) {  
2     return a / gcd(a, b) * b;  
3 }
```

5.4.2 Extended Euclides Algorithm

```
1 ll gcd(ll a, ll b, ll& x, ll& y) {  
2     if (b == 0) {  
3         x = 1;  
4         y = 0;  
5         return a;  
6     }  
7     ll x1, y1;  
8     ll d = gcd(b, a % b, x1, y1);  
9     x = y1;  
10    y = x1 - y1 * (a / b);  
11    return d;  
12 }
```

5.5 Linear Diophantine Equations

$O(\log \min(a, b))$

5.5.1 Any solution

```
1 bool find_any_solution(ll a, ll b, ll c, ll &x0, ll &y0, ll  
2     &g) {  
3     g = gcd(abs(a), abs(b), x0, y0);  
4     if (c % g) {  
5         return false;  
6     }  
7     x0 *= c / g;  
8     y0 *= c / g;  
9     if (a < 0) x0 = -x0;  
10    if (b < 0) y0 = -y0;  
11    return true;  
12 }
```

5.6 Integer Factorization

5.6.1 Pollard's Rho

$O(\sqrt[4]{n} \log n)$

```

1  /**
2  *  @param a first multiplier
3  *  @param b second multiplier
4  *  @param mod
5  *  @return a * b mod n (without overflow)
6  *  @brief Multiplies two numbers  $\geq 10^{18}$ 
7  *  Time Complexity:  $O(\log b)$ 
8  */
9  ll mult(ll a, ll b, ll mod) {
10     ll result = 0;
11     while (b) {
12         if (b & 1)
13             result = (result + a) % mod;
14         a = (a + a) % mod;
15         b >>= 1;
16     }
17     return result;
18 }
19
20 /**
21 *  @param x first multiplier
22 *  @param c second multiplier
23 *  @param mod
24 *  @return  $f(x) = x^2 + c \text{ mod } (\text{mod})$ 
25 *  @brief Polynomial function chosen for pollard's rho
26 *  Time Complexity:  $O(1)$ 
27 */
28 ll f(ll x, ll c, ll mod) {
29     return (mult(x, x, mod) + c) % mod;
30 }
31
32 /**
33 *  @param n number that we want to find a factor p
34 *  @param x0 number where we will start
35 *  @param c constant in polynomial function
36 *  @return fac
37 *  @brief Pollard's Rho algorithm (works only for composite
38         numbers)
39 *  if(g==n) try other starting values
40 *  Time Complexity:  $O(n^{1/4} \log n)$ 
41 */
42 ll rho(ll n, ll x0=2, ll c=1) {
43     ll x = x0;
44     ll y = x0;
45     ll g = 1;
46     while (g == 1) {
47         x = f(x, c, n);
48         y = f(y, c, n);
49         y = f(y, c, n);
50         g = __gcd(x - y, n);
51     }
52     return g;
53 }

```



```

49     g = gcd(abs(x - y), n);
50 }
51 return g;
52 }

```

5.7 Fast Fourier Transform

$O(n \log n)$

```

1  using cd = complex<double>;
2  const double PI = acos(-1);
3
4  /**
5   * @param a vector that we want to transform
6   * @param invert inverse fft or not
7   * @brief apply fft or inverse fft to a vector
8   * Time Complexity:  $O(n \log n)$ 
9   */
10 void fft(vector<cd> &a, bool invert) {
11     ll n = a.size();
12     if (n == 1)
13         return;
14
15     vector<cd> a0(n / 2), a1(n / 2);
16     for (ll i = 0; 2 * i < n; i++) {
17         a0[i] = a[2*i];
18         a1[i] = a[2*i+1];
19     }
20     fft(a0, invert);
21     fft(a1, invert);
22
23     double ang = 2 * PI / n * (invert ? -1 : 1);
24     cd w(1), wn(cos(ang), sin(ang));
25     for (ll i = 0; 2 * i < n; i++) {
26         a[i] = a0[i] + w * a1[i];
27         a[i + n/2] = a0[i] - w * a1[i];
28         if (invert) {
29             a[i] /= 2;
30             a[i + n/2] /= 2;
31         }
32         w *= wn;
33     }
34 }

```

5.7.1 Polynomial Multiplication

```

1  /**
2   * @param a first polynomial coefficients

```

```

3  * @param b second polynomial coefficients
4  * @return product of two polynomials
5  * @brief Multiplies two polynomials
6  * Time Complexity: O(n log n)
7  */
8  vll multiply(vll const& a, vll const& b) {
9      vector<cd> fa(a.begin(), a.end()), fb(b.begin(), b.end()
10         );
11      ll n = 1;
12      while (n < a.size() + b.size())
13          n <<= 1;
14      fa.resize(n);
15      fb.resize(n);
16
17      fft(fa, false);
18      fft(fb, false);
19      for (ll i = 0; i < n; i++)
20          fa[i] *= fb[i];
21      fft(fa, true);
22
23      vll result(n, 0);
24      for (ll i = 0; i < n; i++) {
25          result[i] += round(fa[i].real());
26          if(result[i] >= 10) {
27              result[i+1] += result[i] / 10;
28              result[i] %= 10;
29          }
30      }
31      return result;
32 }

```

6 Graphs

6.1 DFS

$O(n + m)$

```

1  void dfs(ll at, ll n ,vll adj[], bool visited[]) {
2      if(visited[at])
3          return;
4
5      visited[at] = true;
6
7      vll neighbours = adj[at];
8      for(auto nex: neighbours)
9          dfs(nex.first, n, adj, visited);
10 }

```

6.2 BFS

$O(n + m)$

```
1 void bfs(ll s, ll n, vll adj[]) {
2     bool visited[n] = {0};
3     visited[s] = true;
4
5     queue<ll> q;
6     q.push(s);
7     while (!q.empty())
8     {
9         vll neighbours = adj[q.front()];
10        for(auto nex: neighbours) {
11            if(!visited[nex]) {
12                visited[nex]=true;
13                q.push(nex);
14            }
15        }
16        cout << q.front() << '\n';
17        q.pop();
18    }
19 }
```

6.2.1 Shortest path on unweighted graph

$O(n + m)$

```
1 vll solve(ll s, ll n, vll adj[]) {
2     bool visited[n] = {0};
3     visited[s] = true;
4
5     queue<ll> q;
6     q.push(s);
7     vll prev(n, -1);
8     while (!q.empty())
9     {
10        vll neighbours = adj[q.front()];
11        for(auto nex: neighbours) {
12            if(!visited[nex]) {
13                visited[nex]=true;
14                q.push(nex);
15                prev[nex] = q.front();
16            }
17        }
18        q.pop();
19    }
20
21    return prev;
22 }
```

```

23
24 vll reconstructPath(ll s, ll e, vll prev) {
25     vll path;
26     for(ll i=e; i!=-1; i=prev[i])
27         path.push_back(i);
28
29     reverse(path.begin(), path.end());
30
31     if(path[0]==s)
32         return path;
33     else {
34         vll place;
35         return place;
36     }
37 }
38
39 vll bfs(ll s, ll e, ll n, vll adj[]) {
40     vll prev = solve(s, n, adj);
41
42     return reconstructPath(s, e, prev);
43 }

```

6.3 Flood Fill

$O(n + m)$

```

1 int dir_y[] = {};
2 int dir_x[] = {};
3
4 int ff(int i, int j, char c1, char c2) {
5     if ((i < 0) || (i >= n)) return 0;
6     if ((j < 0) || (j >= m)) return 0;
7     if (grid[i][j] != c1) return 0;
8
9     int ans = 1;
10    grid[i][j] = c2;
11
12    for (int d = 0; d < 8; ++d)
13        ans += floodfill(i+dir_y[d], j+dir_x[d], c1, c2);
14
15    return ans;
16 }

```

;

6.4 Topological Sort (Directed Acyclic Graph)

6.4.1 DFS Variation

$O(n + m)$

```

1 void dfs(ll at, ll n ,vll adj[], bool visited[], vll &ts) {
2     if(visited[at])
3         return;
4
5     visited[at] = true;
6
7     vll neighbours = adj[at];
8     for(auto nex: neighbours)
9         dfs(nex.first, n, adj, visited);
10    ts.push_back(at);           // Only change
11 }

```

6.4.2 Kahn's Algorithm

```

1 priority_queue<ll, vll, greater<ll>> pq;
2 for(ll at=0; at<n; at++)           // Push all sources of
3     connected components in graph
4     if(in_degree[at] == 0)
5         pq.push(at);
6
7 while(!pq.empty()) {
8     ll at = pq.top(); pq.pop();
9     vll neighbors = adj[at];
10    for(auto nex: neighbors) {
11        in_degree[nex]--;
12        if(in_degree[nex]>0) continue;
13        pq.push(nex);
14    }
15 }

```

6.5 Bipartite Graph Check (Undirected Graph)

$O(n + m)$

```

1 bool isBipartite(ll s, ll n, vll adj[]) {
2     queue<ll> q;
3     q.push(s);
4     vll color(n, -1); color[s]=0;
5     bool flag = true;
6     while (!q.empty())
7     {
8         vll neighbours = adj[q.front()];
9         for(auto nex: neighbours) {
10            if(color[nex] == -1) {
11                color[nex] = 1-(color[q.front()]);
12                q.push(nex);
13            }
14        }
15    }
16 }

```

```

14         else if(color[nex] == color[q.front()]) {
15             flag = false;
16             break;
17         }
18     }
19     q.pop();
20 }
21
22 return flag;
23 }

```

6.6 Cycle Check (Directed Graph)

$O(n + m)$

```

1  enum { UNVISITED = -1, VISITED = -2,  EXPLORED=-3};
2
3  void cycleCheck(ll at, ll n ,vll adj[], int visited[], ll
4      dfs_parent[]) {
5      visited[at] = EXPLORED;
6
7      vll neighbours = adj[at];
8      for(auto nex: neighbours) {
9          if(visited[nex] == UNVISITED) {
10             // Tree edges (part of the DFS spanning tree)
11             dfs_parent[nex] = at;
12             cycleCheck(nex, n, adj, visited);
13         }
14         else if(visited[nex] == EXPLORED) {
15             if(nex == dfs_parent[at]) {
16                 // Trivial cycle
17                 // Do something
18             }
19             else {
20                 // Non trivial cycle - Back Edge ((u, v)
21                 // such that v is the ancestor of node u but
22                 // is not part of the DFS tree)
23                 // Do something
24             }
25         }
26         else if(visited[nex] == VISITED) {
27             // Forward/Cross edge ((u, v) such that v is a
28             // descendant but not part of the DFS tree)
29             // Do something
30         }
31     }
32 }

```

```

31     visited[at] = VISITED;
32 }

```

6.7 Dijkstra

$O(n \log n + m \log n)$

```

1  void dijkstra(ll s, vll & d, vll & p) {
2      d.assign(n, LLONG_MAX);
3      p.assign(n, -1);
4
5      d[s] = 0;
6      priority_queue<pll, vpll, greater<pll>> q;
7      q.push({0, s});
8      while (!q.empty()) {
9          ll v = q.top().second;
10         ll d_v = q.top().first;
11         q.pop();
12         if (d_v != d[v])
13             continue;
14
15         for (auto edge : adj[v]) {
16             ll to = edge.first;
17             ll len = edge.second;
18
19             if (d[v] + len < d[to]) {
20                 d[to] = d[v] + len;
21                 p[to] = v;
22                 q.push({d[to], to});
23             }
24         }
25     }
26 }

```

7 Dynamic Programming

7.1 Coin Change

$O(nm)$

```

1  /**
2   * @brief Calculates the minimum number of coins required to
3   *        make a target amount using dynamic programming (
4   *        memoization).
5   * @param m The target amount of money to reach.
6   * @param cs Coins
7   * @return The minimum number of coins needed to sum up to '
8   *         m'

```

```

6  */
7  ll coin_change(ll m, const vll &cs)
8  {
9      if (m == 0)
10         return 0;
11
12     if (st[m] != -1)
13         return st[m];
14
15     auto res = oo;
16     for (auto c : cs)
17         if (c <= m)
18             res = min(res, coin_change(m - c, cs) + 1);
19     return st[m] = res;
20 }

```

7.1.1 Canonicity check

$O(n^3)$

```

1  /**
2   * @brief Makes change for a given amount using a greedy
3   * approach.
4   * Assumes the coin denominations 'xs' are sorted in
5   * descending order.
6   */
7  vll greedy(ll x, ll N, const vll &xs)
8  {
9      vll res(N, 0);
10     for(ll i=0; i<N; i++)
11     {
12         auto q = x / xs[i];
13         x -= q*xs[i];
14         res[i] = q;
15     }
16
17     return res;
18 }
19
20 /**
21 * @brief Calculates the total monetary value of a given
22 * combination of coins.
23 */
24 ll value(const vll &M, ll N, const vll &xs)
25 {
26     ll res=0;
27     for(ll i=0; i<N; i++)
28         res += M[i]*xs[i];
29     return res;
30 }

```



```

27 }
28
29 /**
30  * @brief Finds the smallest amount of money for which the
      greedy algorithm fails
31  * to produce an optimal solution (i.e., the minimum number
      of coins).
32  * This is based on a known algorithm for testing if a coin
      system is "canonical".
33  */
34 ll min_counterexample(ll N, const vll &xs)
35 {
36     if(N <= 2)
37         return -1;
38
39     ll ans=oo;
40
41     for(ll i=N-2; i>=0; --i) {
42         auto g = greedy(xs[i]-1, N, xs);
43
44         vll M(N, 0);
45
46         for(ll j=0; j<N; ++j)
47         {
48             M[j] = g[j] + 1;
49             auto w = value(M, N, xs);
50             auto G = greedy(w, N, xs);
51
52             auto x = accumulate(M.begin(), M.end(), 0);
53             auto y = accumulate(G.begin(), G.end(), 0);
54
55             if(x < y)
56                 ans = min(ans, w);
57
58             M[j]--;
59         }
60     }
61
62     return ans == oo ? -1 : ans;
63 }

```

7.2 Knapsack

$O(nm)$

```

1 /**
2  * @brief Finds the maximum sum possible of the knapsack
3  * Can solve subset sum problem (change max to logic OR)
4  */

```

```

5 pair<ll, vll> knapsack(ll M, const vpll &cs)
6 {
7     ll N = cs.size() - 1; // Elements start at 1
8
9     for(ll i=0; i<=N; i++)
10         st[i][0] = 0;
11
12     for(ll m=0; m<=M; m++)
13         st[0][m] = 0;
14
15     for(ll i=1; i<=N; i++)
16     {
17         for(ll m = 1; m <= M; m++)
18         {
19             st[i][m] = st[i-1][m];
20             ps[i][m] = 0;
21             auto [w, v] = cs[i];
22
23             if(w <= M && st[i-1][m-w] + v > st[i][m])
24             {
25                 st[i][m] = st[i-1][m-w] + v;
26                 ps[i][m] = 1;
27             }
28         }
29     }
30
31     // Elements recuperation
32     ll m = M;
33     vll is;
34
35     for(ll i=N; i>=1; --i)
36     {
37         if(ps[i][m])
38         {
39             is.push_back(i);
40             m -= cs[i].first;
41         }
42     }
43
44     reverse(is.begin(), is.end());
45
46     return {st[N][M], is};
47 }

```

7.3 LIS

$O(n \log n)$

```
1 /**
```

```

2  * @param xs      Target Vector.
3  * @param values  True if want values, indexes otherwise.
4  * @return       Longest increasing subsequence as values
                    or indexes.
5  * https://judge.yosupo.jp/problem/
6  * source: Yogi Nam
7  * Time complexity:  $O(N \log(N))$ 
8  */
9  vll lis(const vll& xs, bool values) {
10     assert(!xs.empty());
11     vll ss, idx, pre(xs.size()), ys;
12     for(ll i=0; i<xs.size(); i++) {
13         // change to upper_bound if want not decreasing
14         ll j = lower_bound(all(ss), xs[i]) - ss.begin();
15         if (j == ss.size()) ss.eb(), idx.eb();
16         if (j == 0) pre[i] = -1;
17         else pre[i] = idx[j - 1];
18         ss[j] = xs[i], idx[j] = i;
19     }
20     ll i = idx.back();
21     while (i != -1)
22         ys.eb((values ? xs[i] : i)), i = pre[i];
23     reverse(all(ys));
24     return ys;
25 }

```

7.4 Travelling Salesman Problem

$O(N^2 2^N)$

```

1  /**
2  * @brief Returns the min cost hamiltonian cycles
3  * @param i Current city
4  * @param mask Visited cities
5  * Can be modified to return the max cost
6  * Can include only a set qnt of cities
7  * Can modify the dist graph to a non-complete graph:
8  * Set dist[i][j] = INT_MAX
9  */
10
11 int tsp(int i, int mask) {
12     if(mask == (1 << n) - 1)
13         return dist[i][0];
14
15     if(st[i][mask] == -1)
16         return st[i][mask];
17
18     int res = INT_MAX;

```

```

19     for(int j=0; j<n; j++) {
20         if(mask & (1 << j))
21             continue;
22         res = min(res, tsp(j, mask | (1 << j), n) + dist[i][
                j]);
23     }
24
25     return (st[i][mask] = res);
26 }

```

8 Math Formulas

8.1 Sum of an arithmetic progression

$$S_n = \frac{n}{2}(a_1 + a_n)$$

8.2 Permutation with repeated elements

$$P_n = \frac{n!}{n_1!n_2!\dots n_k!}$$

8.3 Check if is geometric progression

$$a_i^2 = a_{i-1}a_{i+1}$$

8.4 Bitwise equations

$$a|b = a \oplus b + a \& b$$

$$a \oplus (a \& b) = (a|b) \oplus b$$

$$(a \& b) \oplus (a|b) = a \oplus b$$

$$a + b = a|b + a \& b$$

$$a + b = a \oplus b + 2(a \& b)$$

$$a - b = (a \oplus (a \& b)) - ((a|b) \oplus a)$$

$$a - b = ((a|b) \oplus b) - ((a|b) \oplus a)$$

$$a - b = (a \oplus (a \& b)) - (b \oplus (a \& b))$$

$$a - b = ((a|b) \oplus b) - (b \oplus (a \& b))$$

8.5 Cube of Binomial

$$(a + b)^3 = a^3 + 3a^2b + 3ab^2 + b^3$$

$$(a - b)^3 = a^3 - 3a^2b + 3ab^2 - b^3$$

8.5.1 Sum of Cubes

$$a^3 + b^3 = (a + b)(a^2 - ab + b^2)$$

8.5.2 Difference of Cubes

$$a^3 - b^3 = (a - b)(a^2 + ab + b^2)$$

8.6 Binomial expansion

$$\binom{n}{k} = \frac{n!}{k!(n-k)!}$$
$$(a + b)^n = \sum_{k=0}^n \binom{n}{k} a^k b^{n-k}$$

9 Facts

9.1 XOR

9.1.1 Self-inverse property

To cancel a XOR, you can XOR again the same value because $a \oplus a = 0$, so $(value \oplus a) \oplus a = value$

9.1.2 Identity element

$$a \oplus 0 = a$$

9.1.3 Commutative

$$a \oplus b = b \oplus a$$

9.1.4 Associative

$$(a \oplus b) \oplus c = a \oplus (b \oplus c)$$