

# Package ‘bifactor’

November 13, 2021

**Type** Package

**Title** Exploratory Factor, Bi-factor, Two-tier and Multiple-tier Modeling

**Version** 0.1.0

**Date** 2021-07-20

**Description** Fit exploratory factor, bi-factor, two-tier and multiple-tier models with correlated factors.

**License** GPL-3

**LazyData** TRUE

**Depends** R (>= 4.0)

**Imports** Rcpp, Rcsdp

**URL** <https://github.com/Marcosjnez/bifactor>

**BugReports** <https://github.com/Marcosjnez/bifactor/issues>

**Encoding** UTF-8

**RoxygenNote** 7.1.2

**LinkingTo** Rcpp, RcppArmadillo

**NeedsCompilation** yes

**Author** Marcos Jimenez [aut, cre, cph],  
Francisco J. Abad [aut, cph],  
Eduardo Garcia-Garzon [aut, cph],  
Luis E. Garrido [aut, cph]

**Maintainer** Marcos Jimenez <marcosjnezhquez@gmail.com>

## R topics documented:

asympt_cov	2
bifactor	3
cv_eigen	5
efast	6
get_target	8
parallel	9
random_oblq	10

random_orth . . . . .	11
random_poblq . . . . .	11
retr_oblq . . . . .	12
retr_orth . . . . .	13
retr_poblq . . . . .	13
rotate . . . . .	14
se . . . . .	16
sim_factor . . . . .	17
sl . . . . .	18
<b>Index</b>	<b>20</b>

---

asyp_cov	<i>Asymptotic standard errors for correlation matrices.</i>
----------	---

---

**Description**

Get the asymptotic standard errors of correlation matrices of normal or arbitrary random deviates.

**Usage**

```
asyp_cov(R, X = NULL, eta = 1, type = "normal")
```

**Arguments**

- R Correlation matrix.
- X Optional raw data matrix.
- eta Skewness parameter for elliptical data distributions.
- type Type of random deviates: "normal", "elliptical" or "general".

**Details**

If type = "normal", the calculation assumes that the raw data follows a multivariate normal distribution. If type = "elliptical", the calculation assumes that the raw data follows an elliptical distribution with skewness parameter eta. If type = "general", no assumption is made but need to provide the raw data via the X argument.

**Value**

The asymptotic covariance matrix of R.

**References**

M.W. Browne and A. Shapiro (1986). The asymptotic covariance matrix of sample correlation coefficients under general conditions. *Linear Algebra and its Applications*, 82, 169-176. [https://doi.org/10.1016/0024-3795\(86\)90150-3](https://doi.org/10.1016/0024-3795(86)90150-3)

bifactor

*Fit an exploratory bi-factor or generalized bi-factor model.***Description**

Fit an exploratory bi-factor or generalized bi-factor model with correlated factors.

**Usage**

```
bifactor(R, n_generals, n_groups, bifactor_method = "GSLiD", projection = "oblq",
  PhiTarget = NULL, PhiWeight = NULL, blocks = NULL, oblq_blocks = NULL,
  init_Target = NULL, method = "minres", maxit = 20L,
  cutoff = 0, w = 1, random_starts = 1L, cores = 1L, init = NULL,
  efa_control = NULL, rot_control = NULL,
  SL_first_efa = NULL, SL_second_efa = NULL, verbose = TRUE)
```

**Arguments**

R	Correlation matrix.
n_generals	Number of general factors to extract.
n_groups	Number of group factors to extract.
bifactor_method	"GSLiD" and "SL" (Schmid-Leiman) Defaults to "GSLiD".
projection	Projection method. Available projections: "orth" (orthogonal), "oblq" (oblique) and "poblq" (partially oblique). Defaults to "oblq".
PhiTarget	Target matrix for the factor correlations. Defaults to NULL.
PhiWeight	Weight matrix for the factor correlations. Defaults to NULL.
blocks	Vector with the number of factors for which separately applying the rotation criterion. Defaults to NULL.
oblq_blocks	Vector with the number of factors for each oblique block. E.g.: c(2, 4) means that there are two blocks of oblique factors: one block with 2 factors and another block with 4 factors. Everything else is orthogonal. Defaults to NULL.
init_Target	Initial target matrix for the loadings. Defaults to NULL.
method	EFA fitting method: "ml" (maximum likelihood for multivariate normal variable), "minres" (minimum residuals), "pa" (principal axis) or "minrank" (minimum rank). Defaults to "minres".
maxit	Maximum number of iterations for the GSLiD algorithm. Defaults to 20L.
cutoff	Cut-off used to update the target matrix upon each iteration. Defaults to 0.
w	w parameter for the extended target criterion ("xtarget"). Defaults to 1L.
random_starts	Number of rotations with different random starting values. The rotation with the smallest cost function value is returned. Defaults to 1L.
cores	Number of cores for parallel execution of multiple rotations. Defaults to 1L.

<code>init</code>	Initial uniquenesses values for exploratory factor analysis estimation. Defaults to NULL.
<code>efa_control</code>	List of control parameters for efa fitting. Defaults to NULL.
<code>rot_control</code>	List of control parameters for the rotation algorithm. Defaults to NULL.
<code>SL_first_efa</code>	List of arguments to pass to efast to perform the first-order solution for the Schmid-Leiman method. Defaults to NULL.
<code>SL_second_efa</code>	List of arguments to pass to efast to perform the second-order solution for the Schmid-Leiman method. Defaults to NULL.
<code>verbose</code>	Print the convergence progress information. Defaults to TRUE.

### Details

If `efa.control = NULL`, then `list(maxit = 1e4)` is passed to `efa.control`. If `rot_control = NULL`, then `list(maxit = 1000, eps = 1e-05)` is passed to `rot_control`, where `eps` is the absolute tolerance. When the objective function does not make a larger improvement than `eps`, the algorithm is assumed to converge.

If `Target` is provided but not `Weight`, then `Weight = 1 - Target` by default, which means a partially specified target rotation is performed. The same applies for `PhiTarget` and `PhiWeight`.

If `init = NULL`, then the squared multiple correlations of each item with the remaining ones are used as initial values (These are known to be upper bounds).

If `init_Target` is provided, then an initial target by means of the Schmid-Leiman transformation is not necessary.

If `cutoff` is not 0, loadings smaller than such a cut-off are fixed to 0. When `cutoff = 0`, an empirical cut-off is used for each column of the loading matrix. They are the mean of the one-lagged differences of the sorted squared normalized loadings. Then, the target is determined by fixing to 0 the squared normalized loadings smaller than such cut-offs.

### Value

List of class `bifactor`.

`efa` List containing objects related to the exploratory factor analysis estimation. See `efast`.

`bifactor` List with the following components:

- `loadings` - Rotated loading matrix.
- `Phi` - Factor correlation matrix.
- `T` - Transformation matrix.
- `f` - Objective value at the minimum.
- `iterations` - Number of iterations performed by the rotation algorithm.
- `convergence` - Convergence of the rotation algorithm.
- `uniquenesses` - Vector of uniquenesses.
- `Rhat` - Correlation matrix predicted by the model.
- `Target` - Updated target matrix.

- Weight - Weight matrix. It is the complement of the updated target.
- GSLiD\_iterations - Number of iterations performed by the GSLiD algorithm.
- GSLiD\_convergence - Convergence of the GSLiD algorithm.
- min\_congruences - Vector containing, for each iteration, the minimum Tucker's congruence between the current loading matrix and the previous loading matrix.
- max\_abs\_diffs - Vector containing, for each iteration, the maximum absolute difference between the current loading matrix and the previous loading matrix.

elapsed                      Total amount of time spent for execution (in nanoseconds).

## References

Jiménez, M., Abad, F.J., Garcia-Garzon, E., Garrido, L.E. (2021, June 24). Generalized exploratory bi-factor Modeling. Under review. Retrieved from [https://osf.io/7aszj/?view\\_only=8f7bd98025104347a96f60a6736f5a64](https://osf.io/7aszj/?view_only=8f7bd98025104347a96f60a6736f5a64)

## Examples

```
## Not run: # Simulate data:
sim <- sim_factor(n_generals = 3, groups_per_general = 5, items_per_group = 6,
  generals_rho = 0.3)
scores <- MASS::mvrnorm(1e4, rep(0, nrow(sim$R)), Sigma = sim$R)
s <- cor(scores)

# Fit an Generalized exploratory bi-factor model with GSLiD:
GSLiD <- bifactor(s, n_generals = 3, n_groups = 15, method = "minres",
  projection = "poblq", bifactor_method = "GSLiD", oblq_blocks = 3,
  random_starts = 10, cores = 8, w = 1, maxit = 20, verbose = TRUE)

## End(Not run)
```

---

cv\_eigen

*Cross-validated eigenvalues.*

---

## Description

Estimate cross-validated eigenvalues and the dimensionality using the Kaiser's rule.

## Usage

```
cv_eigen(X, N = 100L, hierarchical = FALSE, efa = NULL, cores = 1L)
```

**Arguments**

X	Raw data matrix.
N	Number of cross-validated samples.
hierarchical	Logical indicating whether a second cross-validated eigenvalues estimation should be performed from the factor scores obtained after a first factor analysis analysis.
efa	A list of arguments to pass to efast when hierarchical = TRUE.
cores	Number of cores to perform parallel computations.

**Details**

None yet.

**Value**

A list with the cross-validated eigenvalues and the estimated dimensionality.

**References**

Chen F., Roch S., Rohe K., Yu S (2021). Estimating Graph Dimension with Cross-validated Eigenvalues, arXiv. <https://arxiv.org/abs/2108.03336>

---

efast	<i>Fast exploratory factor analysis.</i>
-------	--

---

**Description**

Fast exploratory factor analysis.

**Usage**

```
efast(R, n_factors, method = "minres", rotation = "oblimin", projection = "oblq",
      Target = NULL, Weight = NULL, PhiTarget = NULL, PhiWeight = NULL,
      blocks = NULL, oblq_blocks = NULL, normalize = FALSE, gamma = 0, epsilon = 1e-02, k = 0, w = 1,
      random_starts = 1L, cores = 1L, init = NULL, efa_control = NULL, rot_control = NULL)
```

**Arguments**

R	Correlation matrix.
n_factors	Number of common factors to extract.
method	EFA fitting method: "ml" (maximum likelihood for multivariate normal variables), "minres" (minimum residuals), "pa" (principal axis) and "minrank" (minimum rank). Defaults to "minres".
rotation	Rotation criterion. Available rotations: "varimax", "cf" (Crawford-Ferguson), "oblimin", "geomin", "target", "xtarget" (extended target) and "none". Defaults to "oblimin".



- loadings - Unrotated loadings.
- uniquenesses - Vector of uniquenesses.
- Rhat - Correlation matrix predicted by the model.
- residuals - Residual correlation matrix.
- f - Objective value at the minimum.
- Heywood - TRUE if any Heywood case is encountered and FALSE otherwise.
- iterations - Number of iterations for the L-BFGS-B algorithm to converge.
- convergence - TRUE if the L-BFGS-B algorithm converged and FALSE otherwise.
- method - Method used to fit the exploratory factor analysis.

rotation      List of class rotation. Only if the argument rotation is not "none". See rotate for the components.

elapsed      Total amount spent for execution (in nanoseconds).

## References

Jiménez, M., Abad, F.J., Garcia-Garzon, E., Garrido, L.E. (2021, June 24). Generalized exploratory bi-factor Modeling. Under review. Retrieved from [https://osf.io/7aszj/?view\\_only=8f7bd98025104347a96f60a6736f5a64](https://osf.io/7aszj/?view_only=8f7bd98025104347a96f60a6736f5a64)

## Examples

```
## Not run:
# Simulate data:
sim <- sim_factor(n_generals = 2, groups_per_general = 5, items_per_group = 6)
scores <- MASS::mvrnorm(1e3, rep(0, nrow(sim$R)), Sigma = sim$R)
s <- cor(scores)

# Fit efa:
efa <- efast(s, n_factors = 12, method = "minres", rotation = "oblimin",
projection = "oblq", gamma = 0, random_starts = 10L, cores = 1L)

## End(Not run)
```

---

get\_target

*Get a target from a loading matrix.*

---

## Description

Get a target for the loading matrix using a custom or empirical cut-off.

## Usage

```
get_target(loadings, Phi = NULL, cutoff = 0)
```



**Arguments**

loadings	A matrix of loadings.
Phi	A correlation matrix among the factors. Defaults to NULL.
cutoff	The cut-off used to create the target matrix. Defaults to 0.

**Details**

If cutoff is not 0, loadings smaller than such a cut-off are fixed to 0. When cutoff = 0, an empirical cut-off is used for each column of the loading matrix. They are the mean of the one-lagged differences of the sorted squared normalized loadings. Then, the target is determined by fixing to 0 the squared normalized loadings smaller than such cut-offs.

**Value**

A target matrix.

**References**

Garcia-Garzon, E., Abad, F. J., & Garrido, L. E. (2019). Improving bi-factor exploratory modeling: Empirical target rotation based on loading differences. *Methodology: European Journal of Research Methods for the Behavioral and Social Sciences*, 15(2), 45–55. <https://doi.org/10.1027/1614-2241/a000163>

Jiménez, M., Abad, F.J., Garcia-Garzon, E., Garrido, L.E. (2021, June 24). Generalized exploratory bi-factor Modeling. Under review. Retrieved from [https://osf.io/7aszj/?view\\_only=8f7bd98025104347a96f60a6736f5a64](https://osf.io/7aszj/?view_only=8f7bd98025104347a96f60a6736f5a64)

---

parallel	<i>Parallel analysis using principal components.</i>
----------	--

---

**Description**

Perform parallel analysis to detect dimensionality using principal components.

**Usage**

```
parallel(X, n_boot = 100L, quant = .95, replace = FALSE,
         hierarchical = FALSE, efa = NULL, cores = 1L)
```

**Arguments**

X	Raw data matrix.
n_boot	Number of bootstrap samples.
quant	Quantile of the distribution of bootstrap eigenvalues to which the compare the sample eigenvalues.
replace	Logical indicating whether the columns of X should be permuted with replacement.

hierarchical	Logical indicating whether a second parallel analysis should be performed from the factor scores obtained after a first factor analysis analysis.
efa	A list of arguments to pass to efast when secon_PA = TRUE.
cores	Number of cores to perform the parallel bootstrapping.

### Details

Not yet.

### Value

A list with the bootstrapped eigenvalues and the estimated dimensionality.

### References

Horn, J. L. (1965). A Rationale and Test For the Number of Factors in Factor Analysis, *Psychometrika*, 30, 179-85. <https://doi.org/10.1007/BF02289447>

---

random_oblq	<i>Generate random oblique matrices.</i>
-------------	--

---

### Description

Generate random oblique matrices from a standard normal distribution.

### Usage

```
random_oblq(p, q)
```

### Arguments

p	Number of rows.
q	Number of columns. Should not be greater than p.

### Value

An oblique matrix with normally distributed data.

### References

Jiménez, M., Abad, F.J., Garcia-Garzon, E., Garrido, L.E. (2021, June 24). Generalized exploratory bi-factor Modeling. Under review. Retrieved from [https://osf.io/7aszj/?view\\_only=8f7bd98025104347a96f60a6736f5a64](https://osf.io/7aszj/?view_only=8f7bd98025104347a96f60a6736f5a64)

---

random_orth	<i>Generate random orthogonal matrices.</i>
-------------	---

---

**Description**

Generate random orthogonal matrices from a standard normal distribution. First, a matrix of random standard normal variables is simulated and then, the Q factor from the QR decomposition is returned.

**Usage**

```
random_orth(p, q)
```

**Arguments**

p	Number of rows.
q	Number of columns. Should not be greater than p.

**Value**

An orthogonal matrix with normally distributed data.

**References**

Jiménez, M., Abad, F.J., Garcia-Garzon, E., Garrido, L.E. (2021, June 24). Generalized exploratory bi-factor Modeling. Under review. Retrieved from [https://osf.io/7aszj/?view\\_only=8f7bd98025104347a96f60a6736f5a64](https://osf.io/7aszj/?view_only=8f7bd98025104347a96f60a6736f5a64)

---

random_poblq	<i>Generate a random partially oblique matrix.</i>
--------------	--

---

**Description**

First, a matrix is simulated from a standard normal distribution. Second, the matrix is normalized and the Gram-Schmidt process is performed between the oblique blocks. Finally, the orthogonal blocks correspond to those columns of the Q matrix from the QR decomposition.

**Usage**

```
random_poblq(p, q, oblq_blocks)
```

**Arguments**

p	Number of rows.
q	Number of columns. Should not be greater than p.
oblq_blocks	A vector with the number of factors for each oblique block. E.g.: c(2, 4) means that there are two blocks of oblique factors: one with 2 factors and another with 4 factors. Everything else is orthogonal.

**Value**

A partially oblique matrix.

**References**

Jiménez, M., Abad, F.J., Garcia-Garzon, E., Garrido, L.E. (2021, June 24). Generalized exploratory bi-factor Modeling. Under review. Retrieved from [https://osf.io/7aszj/?view\\_only=8f7bd98025104347a96f60a6736f5a64](https://osf.io/7aszj/?view_only=8f7bd98025104347a96f60a6736f5a64)

**Examples**

```
random_poblq(p = 7, q = 7, oblq_blocks = c(3, 2))
```

---

retr\_oblq

*Retraction of a matrix onto the oblique manifold.*


---

**Description**

Transform a matrix into an oblique matrix.

**Usage**

```
retr_oblq(X)
```

**Arguments**

X                      A matrix.

**Value**

An oblique matrix.

**References**

Jiménez, M., Abad, F.J., Garcia-Garzon, E., Garrido, L.E. (2021, June 24). Generalized exploratory bi-factor Modeling. Under review. Retrieved from [https://osf.io/7aszj/?view\\_only=8f7bd98025104347a96f60a6736f5a64](https://osf.io/7aszj/?view_only=8f7bd98025104347a96f60a6736f5a64)

retr\_orth

*Retraction of a matrix onto the orthogonal manifold.***Description**

Transform a matrix into an orthogonal matrix.

**Usage**

```
retr_orth(X)
```

**Arguments**

X                      A matrix.

**Value**

An orthogonal matrix.

**References**

Jiménez, M., Abad, F.J., Garcia-Garzon, E., Garrido, L.E. (2021, June 24). Generalized exploratory bi-factor Modeling. Under review. Retrieved from [https://osf.io/7aszj/?view\\_only=8f7bd98025104347a96f60a6736f5a64](https://osf.io/7aszj/?view_only=8f7bd98025104347a96f60a6736f5a64)

retr\_poblq

*Retraction of a matrix onto the partially oblique manifold.***Description**

Transform a matrix into a partially oblique matrix.

**Usage**

```
retr_poblq(X, oblq_blocks)
```

**Arguments**

X                      A matrix.

oblq\_blocks          A vector with the number of factors for each oblique block. E.g.: c(2, 4) means that there are two blocks of oblique factors: one with 2 factors and another with 4 factors. Everything else is orthogonal.

**Value**

A partially oblique matrix.

References

Jiménez, M., Abad, F.J., Garcia-Garzon, E., Garrido, L.E. (2021, June 24). Generalized exploratory bi-factor Modeling. Under review. Retrieved from [https://osf.io/7aszj/?view\\_only=8f7bd98025104347a96f60a6736f5a64](https://osf.io/7aszj/?view_only=8f7bd98025104347a96f60a6736f5a64)

Examples

```
X <- replicate(8, rnorm(8))
retr_poblq(X, c(2, 3, 3))
```

---

rotate	<i>Fast rotation algorithm for factor analysis.</i>
--------	---

---

Description

Riemannian Newton Trust-Region algorithm to quickly perform (parallel) rotations with different random starting values.

Usage

```
rotate(loadings, rotation = "oblimin", projection = "oblq",
Target = NULL, Weight = NULL, PhiTarget = NULL, PhiWeight = NULL,
blocks = NULL, oblq_blocks = NULL, gamma = 0, epsilon = 0.01, k = 0, w = 1,
random_starts = 1L, cores = 1L, rot_control = NULL)
```

Arguments

loadings	Unrotated loading matrix.
rotation	Rotation criterion. Available rotations: "varimax", "cf" (Crawford-Ferguson), "oblimin", "geomim", "target", "xtarget" (extended target) and "none". Defaults to "oblimin".
projection	Projection method. Available projections: "orth" (orthogonal), "oblq" (oblique), "poblq" (partially oblique). Defaults to "oblq".
Target	Target matrix for the loadings. Defaults to NULL.
Weight	Weight matrix for the loadings. Defaults to NULL.
PhiTarget	Target matrix for the factor correlations. Defaults to NULL.
PhiWeight	Weight matrix for the factor correlations. Defaults to NULL.
blocks	Vector with the number of factors for which seperately applying the roation criterion. Defaults to NULL.
oblq_blocks	Vector with the number of factors for each oblique block. E.g.: c(2, 4) means that there are two blocks of oblique factors: one block with 2 factors and another block with 4 factors. Everything else is orthogonal. Defaults to NULL.
gamma	$\gamma$ parameter for the oblimin criterion. Defaults to 0 (quartimin).

epsilon	$\epsilon$ parameter for the geomin criterion. Defaults to 0.01.
k	$k$ parameter for the Crawford-Ferguson family of rotation criteria. Defaults to 0.
w	$w$ parameter for the extended target criterion ("xtarget"). Defaults to 1.
random_starts	Number of rotations with different random starting values. The rotation with the smallest cost function value is returned. Defaults to 1L.
cores	Number of cores for parallel execution of random starts. Defaults to 1L.
rot_control	List of control parameters for the rotation algorithm. Defaults to NULL.

### Details

If `rot_control = NULL`, then `list(maxit = 1000, eps = 1e-05)` is passed to `rot_control`, where `eps` is the absolute tolerance. When the objective function does not make a larger improvement than `eps`, the algorithm is assumed to converge. If `Target` is provided but not `Weight`, then `Weight = 1 - Target` by default, which means a partially specified target rotation is performed. The same applies for `PhiTarget` and `PhiWeight`.

### Value

List of class rotation with the following components:

loadings	Rotated loading matrix.
Phi	Correlation matrix among the factors.
T	Rotation matrix.
f	Objective value at the minimum.
iterations	Number of iterations for the rotation algorithm to converge.
convergence	TRUE if the algorithm converged and FALSE otherwise.
elapsed	Total amount of time spent for execution (in nanoseconds).

### References

- Jiménez, M., Abad, F.J., Garcia-Garzon, E., Garrido, L.E. (2021, June 24). Generalized exploratory bi-factor Modeling. Under review. Retrieved from [https://osf.io/7aszj/?view\\_only=8f7bd98025104347a96f60a6736f5a64](https://osf.io/7aszj/?view_only=8f7bd98025104347a96f60a6736f5a64)
- Zhang, G., Hattori, M., Trichtinger, L. A., & Wang, X. (2019). Target rotation with both factor loadings and factor correlations. *Psychological Methods*, 24(3), 390–402. <https://doi.org/10.1037/met0000198>

---

se	<i>Standard errors for rotated factor loadings, factor correlations and uniquenesses.</i>
----	---

---

## Description

Compute the sandwich standard errors of factor loadings, factor correlations and uniquenesses.

## Usage

```
se(n, fit = NULL, R = NULL, Lambda = NULL, Phi = NULL, X = NULL,
  method = "minres", projection = "oblq", rotation = "oblimin",
  Target = NULL, Weight = NULL, PhiTarget = NULL, PhiWeight = NULL,
  gamma = 0, k = 0, epsilon = 0.01, w = 1, type = "normal", eta = 1)
```

## Arguments

n	Sample size.
fit	Optional efast model.
R	Correlation matrix.
Lambda	Estimated factor loadings.
Phi	Estimated factor correlations.
X	Raw data matrix.
method	Method used to estimate the factor model: "minres", "pa", "ml", or "minres".
projection	Projection used to rotate the factor loadings: "orth", "oblq" or "poblq".
rotation	Rotation criterion. Available rotations: "varimax", "cf" (Crawford-Ferguson), "oblimin", "geomin", "target", "xtarget" (extended target) and "none". Defaults to "oblimin".
Target	Target matrix for the loadings. Defaults to NULL.
Weight	Weight matrix for the loadings. Defaults to NULL.
PhiTarget	Target matrix for the factor correlations. Defaults to NULL.
PhiWeight	Weight matrix for the factor correlations. Defaults to NULL.
gamma	$\gamma$ parameter for the oblimin criterion. Defaults to 0 (quartimin).
k	$k$ parameter for the Crawford-Ferguson family of rotation criteria. Defaults to 0.
epsilon	$\epsilon$ parameter for the geomin criterion. Defaults to 0.01.
w	$w$ parameter for the extended target criterion ("xtarget"). Defaults to 1L.
type	Type of random deviates: "normal", "elliptical" or "general".
eta	Skewness parameter for elliptical data distributions.



## Details

Currently, only available for method = minres.

## Value

A list with the standard errors of the rotated factor loadings, factor correlations and uniquenesses.

## References

Zhang G, Preacher KJ, Hattori M, Jiang G, Trichtinger LA (2019). A sandwich standard error estimator for exploratory factor analysis with nonnormal data and imperfect models. *Applied Psychological Measurement*, 43, 360–373. <https://doi.org/10.1177/0146621618798669>

---

sim_factor	<i>Simulate a bi-factor or generalized bifactor population structure.</i>
------------	---

---

## Description

Simulate a bi-factor or generalized bifactor population structure with cross-loading, pure items and correlated factors.

## Usage

```
sim_factor(n_generals, groups_per_general, items_per_group,
loadings_g = "medium", loadings_s = "medium",
crossloadings = 0, pure = FALSE,
generals_rho = 0, groups_rho = 0,
method = "minres", fit = "rmsr", misfit = 0.025)
```

## Arguments

n_generals	Number of general factors.
groups_per_general	Number of group factors per general factor.
items_per_group	Number of items per group factor.
loadings_g	Loadings' magnitude on the general factors: "low", "medium" or "high". Defaults to "medium".
loadings_s	Loadings' magnitude on the group factors: "low", "medium" or "high". Defaults to "medium".
crossloadings	Magnitude of the cross-loadings among the group factors. Defaults to 0.
pure	Fix a pure item on each general factor. Defaults to FALSE.
generals_rho	Correlation among the general factors. Defaults to 0.
groups_rho	Correlation among the group factors. Defaults to 0.
method	Method used to generate population error: "minres" or "ml".
fit	Fit index to control the population error.
misfit	Misfit value to generate population error.

## Details

`sim_factor` generates bi-factor and generalized bifactor patterns with cross-loadings, pure items and correlations among the general and group factors. When `crossloading` is different than 0, one cross-loading is introduced for an item pertaining to each group factor. When `pure` is TRUE, one item loading of each group factor is removed so that the item loads entirely on the general factor. To maintain the item communalities constant upon these modifications, the item loading on the other factors may shrunk (if adding cross-loadings) or increase (if setting pure items).

Loading magnitudes may range between 0.3-0.5 ("low"), 0.4-0.6 ("medium") and 0.5-0.7 ("high").

## Value

List with the following objects:

<code>lambda</code>	Population loading matrix.
<code>Phi</code>	Population factor correlation matrix.
<code>R</code>	Population correlation matrix.
<code>R_error</code>	Population correlation matrix with error.
<code>uniquenesses</code>	Vector of population uniquenesses.
<code>delta</code>	Minimum of the objective function that correspond to the misfit value.

## References

Jiménez, M., Abad, F.J., Garcia-Garzon, E., Garrido, L.E. (2021, June 24). Exploratory generalized bifactor Modeling. Under review. Retrieved from [https://osf.io/7aszj/?view\\_only=8f7bd98025104347a96f60a6736f5a64](https://osf.io/7aszj/?view_only=8f7bd98025104347a96f60a6736f5a64)

---

sl	<i>Schmid-Leiman Transformation.</i>
----	--------------------------------------

---

## Description

Schmid-Leiman transformation into a bi-factor or generalized bi-factor pattern.

## Usage

```
sl(R, n_generals, n_groups, first_efa = NULL, second_efa = NULL)
```

## Arguments

<code>R</code>	Correlation matrix.
<code>n_generals</code>	Number of general factors.
<code>n_groups</code>	Number of group factors.
<code>first_efa</code>	Arguments to pass to <code>efast</code> in the first-order factor extraction. See <code>efast</code> for the default arguments.
<code>second_efa</code>	Arguments to pass to <code>efast</code> in the second-order factor extraction. See <code>efast</code> for the default arguments.

## Details

First, a hierarchical factor model is fitted using a second-order factor analysis on the factor correlation obtained from a first-order factor analysis. Then, the item loadings on the general factors are assumed to be the direct effects of the general factors according to such hierarchical model. On the other hand, the item loadings on the group factors become the originally first-order loadings post-multiplied by the diagonal matrix containing the root of the item uniquenesses.

Obviously, the first-order factor analysis should be oblique to perform a second exploratory factor analysis.

If the second-order solution does not use an orthogonal projection, then the correlation matrix among the general factors for the Schmid-Leiman solution is simply that obtained from such second-order solution.

## Value

loadings	Loading matrix of the Schmid-Leiman solution.
first_order_solution	Object of class efast with the first-order solution.
second_order_solution	Object of class efast with the second-order solution.
uniquenesses	Vector of uniquenesses.
Rhat	Correlation matrix predicted by the (hierarchical) model.

## References

Jiménez, M., Abad, F.J., Garcia-Garzon, E., Garrido, L.E. (2021, June 24). Generalized exploratory bi-factor Modeling. Under review. Retrieved from [https://osf.io/7aszj/?view\\_only=8f7bd98025104347a96f60a6736f5a64](https://osf.io/7aszj/?view_only=8f7bd98025104347a96f60a6736f5a64)

## Examples

```
## Not run:
# Simulate data:
sim <- sim_factor(n_generals = 2, groups_per_general = 3, items_per_group = 5)
lambda <- sim$lambda
Target <- ifelse(lambda > 0, 1, 0)

# Target rotation for the first-order efa and oblimin for the second-order efa:
first <- list(rotation = "target", projection = "oblq", Target = Target)
second <- list(rotation = "oblimin", projection = "oblq", gamma = 0)

SL <- sl(sim$R, n_generals = 2, n_groups = 6, first, second)

## End(Not run)
```

# Index

`asypm_cov`, [2](#)

`bifactor`, [3](#)

`cv_eigen`, [5](#)

`efast`, [6](#)

`get_target`, [8](#)

`parallel`, [9](#)

`random_oblq`, [10](#)

`random_orth`, [11](#)

`random_poblq`, [11](#)

`retr_oblq`, [12](#)

`retr_orth`, [13](#)

`retr_poblq`, [13](#)

`rotate`, [14](#)

`se`, [16](#)

`sim_factor`, [17](#)

`sl`, [18](#)