



It's Hard To Stop A Trane.®

RESIDENTIAL PRODUCTS




AIR CONDITIONERS



FURNACES



PACKAGED SYSTEMS



HEAT PUMPS



AIR HANDLERS



INDOOR AIR QUALITY



SMART THERMOSTATS



TRADITIONAL THERMOSTATS



COILS



Lower Global Warming Potential

Includes all new equipment that contains or is compatible with R-454B refrigerant.



TRANE
TECHNOLOGIES

TRANE RESIDENTIAL PRODUCTS

62-1014-R-39

AIR CONDITIONERS

VARIABLE SPEED

PREMIER



20 TruComfort™ Variable Speed Air Conditioner with WeatherGuard™

5TTV0

Up to 23.6 SEER2/14.0 EER2†

COMMON FEATURES:



- 2, 3, 4 and 5 ton
- Woven Spine Fin™ coil
- Variable-speed fan motor
- Swept fan blade
- Compressor sound insulator



18 TruComfort™ Variable Speed Air Conditioner

5TTV8

Up to 18.1 SEER2/11.5 EER2†

- Climatuff® Variable Speed inverter compressor
- Trane Link Connectivity
- Standard 4 wire connection, 2 wire optional

MULTI-SPEED

PRIORITY



17 Multi-Speed Air Conditioner with WeatherGuard™

5TTX7

Up to 18.0 SEER2†

COMMON FEATURES:



17 Multi-Speed Air Conditioner

5TTR7

Up to 17.1 SEER2†

- 2, 3, 4 and 5 ton
- Spine Fin™ coil
- Swept fan blade
- Climatuff® inverter compressor

SINGLE STAGE

CHOICE



15 Single-Stage Air Conditioner with WeatherGuard™

5TTX5

Up to 17.0 SEER2†



15 Single-Stage Air Conditioner

5TTR5

Up to 17.0 SEER2†

COMMON FEATURES:

- 1.5 – 5 ton
- Spine Fin™ coil



14 Single-Stage Air Conditioner

5TTR4

Up to 14.3 SEER2

- Swept fan blade
- Climatuff® compressor



13 Single-Stage Air Conditioner

5TTR3

13.4 SEER2

3 PHASE

CHOICE



14 Single-Stage Air Conditioner (3-Phase)

5TTA4

Up to 16.0 SEER2

COMMON FEATURES:

- 3, 3.5, 4 & 5 ton
- Spine Fin™ coil

13 Single-Stage Air Conditioner (3-Phase)

5TTA3

13.4 SEER2



- ① Compressor
- ② Coil
- ③ Functional Parts

Registered Limited Warranty terms are available when you register within 60 days of installation. You can register online at Trane.com or by phone at 855-260-2975, otherwise Trane's Base Limited Warranty terms will apply. Base Limited Warranty information on specific products can be found on ComfortSite.com. Product Registration and Registration Transfer exclusions vary in the US from state to state and in Canada from province to province. To determine if there are specific exclusions for your state or province check your local laws.

QUESTIONS ABOUT WARRANTY? CONTACT YOUR LOCAL TRANE REPRESENTATIVE.

HEAT PUMPS

TRUCOMFORT™ VARIABLE SPEED

PREMIER



20 TruComfort™ Variable Speed Heat Pump with WeatherGuard™

5TWV0

Up to 22.4 SEER2/13.0 EER2/
10.5 HSPF2†

COMMON FEATURES:



- 2, 3, 4 and 5 ton
- Woven Spine Fin™ coil
- Variable-speed fan motor
- Swept fan blade
- Compressor sound insulator
- Climatuff® Variable Speed inverter compressor
- Trane Link Connectivity
- Standard 4 wire connection, 2 wire optional



18 TruComfort™ Variable Speed Heat Pump

5TWV8

Up to 18.1 SEER2/11.5 EER2/8.5 HSPF2†



17 Multi-Speed Heat Pump with WeatherGuard™

5TWX7

Up to 18.0 SEER2/
11.0 HSPF2†

COMMON FEATURES:



17 Multi-Speed Heat Pump

5TWX7

Up to 17.1 SEER2/
11.0 HSPF2†

- 2, 3, 4 and 5 ton
- Spine Fin™ coil
- Climatuff® inverter compressor



16 Multi-Speed Low Profile Heat Pump

5HPL5

Up to 16.0 SEER2/
8.1 HSPF2†

- Side discharge
- 2, 3, 4 and 5 ton
- Copper tube aluminum fin coil

SINGLE STAGE

CHOICE



15 Single-Stage Heat Pump with WeatherGuard™

5TWX5

Up to 17.0 SEER2/8.5 HSPF2†

COMMON FEATURES:

- 1.5 – 5 ton
- Spine Fin™ coil



15 Single-Stage Heat Pump

5TWR5

Up to 17.0 SEER2/8.5 HSPF2†

- Climatuff® compressor
- Compressor sound insulator (select models)



14 Single-Stage Heat Pump

5TWR4

14.3 SEER2/7.5 HSPF2



14 Single-Stage Heat Pump (3 Phase)

5TWA4

Up to 16.0 SEER2/8.1 HSPF2

- 3, 3.5, 4 and 5 ton
- Spine Fin™ coil

† This product meets ENERGY STAR requirements when appropriate coil components are used. Ask your dealer for details.

90%+ AFUE CONDENSING

PREMIER



96 Modulating Variable Speed

Formerly XC95m

TUHM / TDHM COMMUNICATING

Up to 97.3% AFUE

- 60 – 120 MBU input
- ComfortLink™ II capability
- Fully modulating gas valve
- Three-wire connections
- Variable-speed communicating ECM blower motor
- Continuous Comfort-R™ mode
- Single or two pipe vent options
- Digital user interface for easy set up and diagnostics
- Silicon nitride igniter
- Variable-speed draft inducer
- Certified to 2% air leakage
- ENERGY STAR® qualified



97 Two-Stage Variable Speed

Formerly S9V2-VS

97% AFUE

- Variable-speed ECM blower motor
- Comfort-R™ mode
- Compatible with 1-stage, 2-stage, and variable speed* OD equipment
- Variable speed draft inducer



96 Two-Stage Variable Speed

Formerly S9V2

96% AFUE

- Variable-speed ECM blower motor
- Comfort-R™ mode
- Compatible with 1-stage, 2-stage, and variable speed* OD equipment
- Two-speed draft inducer



96 Two-Stage

Formerly S9X2

Up to 96% AFUE

- Compatible with 1 and 2 stage OD equipment
- High efficiency 9 tap Constant Torque ECM blower
- Two-speed draft inducer



COMMON 2-STAGE S-SERIES FEATURES INCLUDED:

- 40 – 120 MBU input
- Two-stage heat
- Single or two pipe vent options
- Fully insulated/gasketed
- Dry contact Humidifier and EAC terminals
- Silicon nitride igniter
- Standard 34" height
- Certified to 1% air leakage
- IFC board with digital configuration, status, and fault codes
- ENERGY STAR® qualified

CHOICE



96 Single-Stage

Formerly S9X1

Up to 96% AFUE

- 40 – 120 MBU input
- Single-stage heat
- High efficiency 9 tap Constant Torque ECM motor
- Single-speed draft inducer
- Silicon nitride igniter
- Fully insulated/gasketed
- Single or two pipe vent options
- IFC board with digital configuration, status, and fault codes
- ENERGY STAR® qualified
- Certified to 1% air leakage



95 Single-Stage Ultra-Low NOx†

Formerly L9X1

95% AFUE

- 50, 70, & 100 MBU input
- Single-stage heat
- High efficiency 9 tap Constant Torque ECM blower
- Ultra-Low NOx Certified
- Silicon nitride igniter
- Fully insulated cabinet

† California Only



92 Single-Stage Builder-Grade

Formerly S9B1

92.1% AFUE

- 40 – 120 MBU input
- Single-stage heat
- 9 tap Constant Torque ECM blower motor
- Single-speed draft inducer
- Silicon nitride igniter
- Single or two pipe vent options
- Stainless steel heat exchanger



80% AFUE NON-CONDENSING

PREMIER



80 Two-Stage Variable Speed

Formerly S8V2-C

- 40 – 120 MBU input
- Trane Link Communicating Capability
- Can be connected in communicating or 24V non-communicating modes
- Two-stage heat
- High efficiency, variable speed constant airflow blower motor
- Two-speed draft inducer
- Silicon nitride igniter
- Fully insulated**/gasketed
- Aluminized steel heat exchanger
- Compatible with Trane CleanEffects™



80 Two-Stage

Formerly S8X2

- 40 – 120 MBU input
- Two-stage heat
- High efficiency 9 tap Constant Torque ECM blower
- Two-speed draft inducer
- Silicon nitride igniter
- Fully insulated**/gasketed
- Aluminized steel heat exchanger
- Compatible with Trane CleanEffects™



PRIORITY



80 Single-Stage Variable Speed Ultra-Low NOx†

Formerly L8V

- 40 – 100 MBU input
- Single-stage heat
- Variable-speed blower motor
- Variable-speed draft inducer
- Ultra-Low NOx Certified
- Certified to 1% air leakage

† California Only



80 Single-Stage

Formerly S8X1

- 40 – 120 MBU input
- Single-stage heat
- High efficiency 9 tap Constant Torque ECM blower
- Single-speed draft inducer
- Silicon nitride igniter
- Fully insulated**/gasketed
- Humidifier & EAC terminals
- Certified to 1% air leakage



80 Single-Stage Builder-Grade

Formerly S8B1

- 40 – 120 MBU input
- Single-stage heat
- 9 tap Constant Torque ECM blower
- Single-speed draft inducer
- Silicon nitride igniter
- Certified to 1.4% air leakage



L8V1†

- 55-100 MBU input
- Single-stage heat
- 5 tap Constant Torque ECM blower
- Ultra-Low NOx Certified
- 14 ng/J operation
- Silicon nitride igniter
- Fully insulated cabinet

† California Only



*Relay panel required when matched with variable speed outdoor units
**14.5" models do not contain blower compartment insulation



- ① Heat Exchanger
- ② Functional Parts

Registered Limited Warranty terms are available when you register within 60 days of installation. You can register online at Trane.com or by phone at 855-260-2975, otherwise Trane's Base Limited Warranty terms will apply. Base Limited Warranty information on specific products can be found on ComfortSite.com. Product Registration and Registration Transfer exclusions vary in the US from state to state and in Canada from province to province. To determine if there are specific exclusions for your state or province check your local laws.

QUESTIONS ABOUT WARRANTY? CONTACT YOUR LOCAL TRANE REPRESENTATIVE.

COILS

CASED MULTI-POSITION



5TXC

- Single, 2-stage and variable speed equipment
- TXV (heat pump capable)
- Enhanced fin design for efficiency and humidity control
- Double-sloped high temp drain pan
- All-aluminum to prevent formicary corrosion
- Factory installed Refrigerant Detection System



5MXC

- Single stage equipment only
- Fixed orifice
- TXV kit available for expanded ratings and applications (heat pump capable)
- All-aluminum to prevent formicary corrosion
- Shipped with Refrigerant Detection System



5PXC-U/5PXC-D

U = Upflow/Downflow*
D = Downflow only**
(Optimized for downflow efficiency and ratings)

- Single, 2-stage and variable speed equipment
- TXV (heat pump capable)
- Double-sloped high temp drain pan
- Enhanced fin design for efficiency and humidity control
- All-aluminum to prevent formicary corrosion
- Factory installed Refrigerant Detection System



UNCASED



5AXA

- TXV (heat pump capable)
- Single sloped non-corrosive drain pan
- Enhanced fin design for efficiency and humidity control
- All-aluminum to prevent formicary corrosion
- Single and 2-stage equipment only
- Shorter depth ideal for plenum placement
- Shipped with Refrigerant Detection System



CASED



5PXFH

- Single, 2-stage and variable speed equipment
- TXV (heat pump capable)
- High temp drain pan
- All-aluminum to prevent formicary corrosion
- Factory installed Refrigerant Detection System



*Convertible to horizontal left or right with kit.
**Convertible to horizontal right with kit.

AIR HANDLERS

HYPERION™

PREMIER



Hyperion™ Variable Speed Air Handler

5TAMX

- Trane Link compatible or 24V operation
- Trane Link mobile app capability
- 2 – 5 ton
- Continuous Comfort-R™ mode
- Composite Vortica™ blower housing
- All-aluminum epoxy coated coil
- Double wall modular cabinet
- Multi-position installation
- Side return option
- Electronic expansion valve
- Variable-speed ECM blower motor
- Meets 2% air leakage requirements



PRIORITY



Hyperion™ Air Handler

5TAM5

- 1.5 – 5 ton
- High efficiency four-speed ECM blower motor
- Composite Vortica™ blower housing
- All-aluminum epoxy coated coil
- Double wall modular cabinet
- Multi-position installation
- Side return option
- R-454B TXV
- Meets 2% air leakage requirements



METAL-STYLE

PREMIER



TruComfort™ Variable Speed Air Handler

5TEM6

- Trane Link compatible or 24V operation
- ComfortLink™ II



COMMON FEATURES:

- 2 – 5 ton
- 24V operation
- Variable-speed ECM blower motor
- All-aluminum coil
- Multi-position installation
- Metal Vortica™ blower
- Galvanized steel metal cabinet
- Meets 2% air leakage requirements
- R-454B TXV

PRIORITY

Variable Speed Air Handler

5TEM6



CHOICE

Air Handler

5TEM4

- 2 – 5 ton
- ECM blower motor
- Metal Vortica™ blower
- All-aluminum coil
- Galvanized steel metal cabinet
- R-454B TXV
- Multi-position installation
- Meets 2% air leakage requirements



UPFLOW

CHOICE



Compact Plus Air Handler

5TMM5

- 2 – 3 ton
- Upflow design with front and bottom return options
- ECM blower motor
- R-454B TXV
- Galvanized steel metal cabinet
- Meets 2% air leakage requirements
- All-aluminum coil



MODULAR AIR HANDLER

PRIORITY



120V Modular Variable Speed Air Handler

POVO

- 34" cabinet height
- High efficiency, variable speed blower motor
- Fully insulated cabinet
- 4-way multi-poise
- Entirely electric operation
- 24V operation



Functional Parts



① Coil
② Functional Parts

① Coil
② Functional Parts

Registered Limited Warranty terms are available when you register within 60 days of installation. You can register online at Trane.com or by phone at 855-260-2975, otherwise Trane's Base Limited Warranty terms will apply. Base Limited Warranty information on specific products can be found on ComfortSite.com. Product Registration and Registration Transfer exclusions vary in the US from state to state and in Canada from province to province. To determine if there are specific exclusions for your state or province check your local laws.

QUESTIONS ABOUT WARRANTY? CONTACT YOUR LOCAL TRANE REPRESENTATIVE.

TRANE CLEANEFFECTS™



EFD

10

- Up to 100 times more effective than a standard 1" throwaway filter
- Power door provides easy access to internal components and features a filter status display as well as safety interlocks that automatically shut down the power when the door is opened for maintenance or cleaning
- Removes particles down to 0.3 micron in size
- Removes more than 99% of a surrogate for the virus that causes Covid-19 within 30 minutes
- ComfortLink II™ communicating or 24 volt capability
- Zero ozone emissions. Cleaner air without harmful ozone byproducts so you can breathe easier
- Allergy and Asthma Friendly® Certified
- Quiet operation



QUIKBOX™



EQBFM

- MERV 11 and MERV 13 filter options
- Quick shirt box type design
- Stores flat, installs in seconds
- 7 sizes to match most cabinet widths
- Backward compatible for all Perfect Fit (TFM) filter boxes
- New smaller cabinet to meet competitive brands
- Low pressure drop; up to 6 mos. lifecycle

SLIMFIT FILTER



BAYSF

1165, 1185, 1235, 1255

- 1" Pleated Filter, MERV 4 rated, lasts up to 90 days
- Made-to-fit cabinet sizes for TEM Air Handlers and S9V and S9X furnace side return cabinets
- 2" depth low profile painted steel cabinet with hinged door for easy filter replacement

EVAPORATIVE HUMIDIFIERS



EHUMD500

10

FAN POWERED

- Capacity: 18 gallons per day
- Sq. Ft. Capacity: Up to 4,200
- Unit Type: Power humidifier/automatic control



EHUMD300

10

LARGE BYPASS

- Capacity: 16.8 gallons per day
- Sq. Ft. Capacity: Up to 4,000
- Unit Type: Large bypass humidifier/automatic control

EHUMD200

10

SMALL BYPASS

- Capacity: 12 gallons per day
- Sq. Ft. Capacity: Up to 3,000
- Unit Type: Small bypass humidifier/manual control



EHUMD800

10

- Capacity: 11 – 34.6 gallons per day
- Sq. Ft. Capacity: Up to 5,000

EHUMD800LC

10

- For 120V applications only
- For low conductivity water applications
- Up to 11 gal. per day output
- Replaceable LC canister available

DEHUMIDIFIERS



EHUMD500

5

WATER REMOVAL:
70 Pints/Day
8.75 Gallons/Day



EDHUM98

5

WATER REMOVAL:
98 Pints/Day
12.25 Gallons/Day



EDHUM120

5

WATER REMOVAL:
120 Pints/Day
15.125 Gallons/Day

COMMON FEATURES:

- Features a horizontal configuration with optional vertical discharge
- Designed for quiet operation
- Engineered for low temperature operation providing comfort year round

- Optional digital controller for outdoor air ventilation and humidity control
- Superior MERV-13 filtration to improve indoor air quality

- Ducting options for fresh outdoor air ventilation to meet ASHRAE 62.2 ventilation requirements
- Push button reset for transformer protection

VENTILATION



Premium Energy Recovery Ventilation (ERV)

10

EERVE125, EEVER225, EERVE280

- Efficient heat and humidity transfer recaptures up to 70-80% of the energy exhausted from the airstream
- Dial-A-Flow adjustment for simple air flow balancing
- 2 high-efficiency variable speed EC motors, meet California energy codes
- Multi position mounting
- Compact design and reduced weight for easier installation vs alternatives
- MERV 8 standard, MERV 13 filter options available
- High-efficiency core operates dry in all conditions, no condensate pans needed
- Energy-efficient operation decreases HVAC load, cutting down on energy use and costs

Energy Recovery Ventilation (ERV)

10

EERVR100, EERVR200, EERVR300

- Static plate energy transfer core for efficient transfer of heat and moisture
- MERV 8 replaceable filter included
- Multi position mounting
- Pull-down door latches for quick service access



EVENQF130V

5

- 62.2 Compliant Ventilation
- Full ECM Motor with Intelligent Logic Controller
- Adjustable airflow from 40 to 130 cfm to meet ventilation codes for all size homes
- 24V functionality from a smart thermostat, or use the on-board controller for "set-it and forget it" installation
- MERV 8 filter included for improved IAQ

Functional Parts

10

Registered Limited Warranty terms are available when you register within 60 days of installation. You can register online at Trane.com or by phone at 855-260-2975, otherwise Trane's Base Limited Warranty terms will apply. Base Limited Warranty information on specific products can be found on ComfortSite.com. Product Registration and Registration Transfer exclusions vary in the US from state to state and in Canada from province to province. To determine if there are specific exclusions for your state or province check your local laws.

QUESTIONS ABOUT WARRANTY? CONTACT YOUR LOCAL TRANE REPRESENTATIVE.

SMART THERMOSTATS

CONNECTED CONTROLS



LINK360

UX360, SC360

Smart Thermostat & System Controller

- TruComfort™ Variable Speed
- Trane Link Zoning Systems
- Remote wired temperature sensor available through the hub
- Remote wireless indoor temperature and humidity sensor (optional): ZSENS930AW00MA
- Remote Climate Access with Trane Home app
- Trane Diagnostics ready
- Trane Technician app compatibility allows for easy technician commissioning and servicing
- Compatible with 24V Indoor Equipment
 - 5 heat / 2 cool
 - 3 dry auxiliary contacts***
 - Remote ID, OD sensor connections
- WiFi connectivity
- Control from a smartphone, tablet, or computer
- Customizable home screen
- Runtime history
- 7" diagonal color touchscreen
- 1-Touch Presets - Home, Away, Sleep
- 7 Day programmable with up to four schedules per day
- Smart Continuous Fan
- Adjustable Continuous Airflow (35-100%)
- Five day weather forecast
- Indoor relative humidity display
- Test modes and alert diagnostics
- Over-the-air Software Upgrades
- Color: Designer White



XL1050

TZON1050

- ComfortLink™ II communications
- ComfortLink™ II zoning
- Compatible with 24 volt systems*
 - 5 heat / 2 cool
 - Remote ID, OD sensor connections
- Remote Climate Access with Trane Home app
- Built in Bridge for Z-Wave devices
- Trane Diagnostics ready
- WiFi connectivity
- Control from a smartphone, tablet, or computer
- 7" diagonal color HD display
- 1-touch presets - Home, Away, Sleep
- 7-day programmable with up to four schedules per day
- Integrated Dehumidification Solution
- Customizable home screen
- Runtime history
- Allergy and quick clean air cycles
- Smart continuous fan
- Adjustable continuous airflow
- Ventilation control*
- Service, filter, humidifier, UV light, air cleaner reminders
- 5-day weather forecast, weather radar, and alerts
- Indoor relative humidity display
- Test modes and alert diagnostics
- Over the air or local software upgrade
- BK Terminal for humidity control
- Over-the-air Software Upgrades
- Color: Designer Silver



XL1040

TZON1040

- For use with ComfortLink™ II Zoning Systems (XL1050 required)
- 3-Wire Communicating Zone Sensor
- 4.3" diagonal color touchscreen
- Zone Mode - Auto only
- Fan Mode - Auto/On
- Displays Zone Temperature & Relative Humidity
- Average multiple zone temp sensors
- Displays Outdoor Temperature (Trane Home™ registration or wired ODT required)
- Clean Screen Function
- 3 Levels of Restricted Access
- Fahrenheit or Celsius
- Adjust zone Setpoint at 1040, 1050, and from the Trane Home™ app
- Schedule 1040, 1050 from the Trane Home app
- Zone Schedule Override - Permanent Hold
- Enter zone name at 1040 and 1050
- Local software upgrades
- Screen color with backlit options
- Screen saver options
- Color: Designer Silver



XL850

TCONT850

- Remote Climate Access with Trane Home app**
- Built in Bridge for Z-Wave devices
- ComfortLink™ II communications
- WiFi connectivity
- Trane Diagnostics ready
- Compatible with 24 volt systems*
- 5 heat / 2 cool
- 7-day programmable with up to 4 periods/day
- 4.3" color display
- Dual Fuel Capable
- Filter change reminders
- 5-day weather forecast, local radar & alerts
- Integrated Dehumidification Solution
- Allergy and quick clean cycles
- Ventilation control*
- Maintenance reminders
- Customizable home screen
- Over-the-air Software Upgrades
- Color: Designer Silver



XL824

TCONT824

- ENERGY STAR® certified
- Remote Climate Access with Trane Home app**
- WiFi connectivity
- Built in Bridge for Z-Wave devices
- Trane Diagnostics ready
- Used with conventional 24 volt systems
- 5 heat / 2 cool
- 7-day programmable
- 4.3" color display
- 2 aux dry contacts***
- Humidity sensor
- Humidifier, ventilation, and dehumidifier control
- Filter change reminders
- 5-day weather forecast, local radar & alerts
- Dual Fuel capable
- Integrated Dehumidification Solution
- Allergy and quick clean cycles
- Maintenance reminders
- Customizable home screen
- Smart continuous fan
- Over-the-air Software Upgrades
- Color: Designer Silver



XR724

CONT724

- Remote Climate Access with Trane Home app**
- WiFi connectivity
- 4 heat/2 cool
- Trane Diagnostics ready
- 4.3" diagonal LCD touchscreen
- Screen lock out and guest lock out
- Built-in humidity sensor
- Dehumidification setting
- Dual Fuel capable
- Filter, maintenance and humidifier service reminder alerts
- Over-the-air Software Upgrades
- Color: Silver

SENSORS



ZZSENSAL0400

Wired Outdoor Temperature Sensor

- Compatible with Trane Link Zone Panel (ZZON2PNL)
- Indoor sensor for use with:
 - TZON1050
 - TCONT624
 - TCONT824
 - TCONT850



BAYSENS01

Wired Outdoor Temperature Sensor

- Outdoor sensor for use with:
 - TZONE950
 - TZON1050
 - TCONT624
 - TCONT824
 - TCONT850



ZSENS930

Indoor Wireless Temperature and Humidity Sensor

- Z-Wave device
- LINK360 compatible
- Monitor through Trane Home mobile app
- Integrates with built-in bridge of
 - TZON1050
 - TCONT824
 - TCONT850



*BAY24VRPAC52DC Relay Panel required.

**Complimentary service for up to 8 professionally installed smart thermostats. Complimentary service includes up to 1 lighting or appliance module per control (maximum 8) installed. Unlimited Trane® Home Wi-Fi cameras (live streaming only) is included with complimentary Trane® Home remote climate access. Cameras and lighting controls are optional purchase.

***Auxiliary dry contacts may be configured to control 1) whole house humidifier; 2) dehumidifier; 3) ventilation system.

****Requires Z-Wave Bridge, purchase separately to connect to Trane Home Mobile App.

7-DAY OR 5/1/1 PROGRAMMABLE



XR303

TCONT303

- 4 heat/2 cool
- Humidity sensor
- Dual fuel capable



XR302

TCONT302

- 4 heat/2 cool
- Dual fuel capable



XR203

TCONT203

- 4 heat/2 cool
- Dual fuel capable



XR202

TCONT202

- 1 heat/1 cool



COMMON FEATURES

- 5" Interactive touch screen
- Auto changeover
- Real-time clock
- Large back lit display
- Armchair programming
- Air filter reminder

COMMON FEATURES

- 3.5" Diagonal backlit display
- Simple programming
- Standard wiring terminal block
- Simultaneous display
- Soft key controls

NON-PROGRAMMABLE



XR103

TCONT103

- 2 heat/1 cool HP only
- Configurable Switchover Valve
- Emergency Heat
- Common required



XR102

TCONT102

- Up to 1 heat/1 cool
- No Common Terminal
- Battery Powered Only



COMMON FEATURES

- Push button, non-programmable
- 1.9" Diagonal display
- Fahrenheit or Celsius

SENSORS



ZZSENSAL0300

Wired Indoor Temperature Sensor

- Indoor sensor for use with:
TCONT303
TCONT302

BAYSEN30ATEMPA

Wired Indoor Temperature Sensor

- Outdoor sensor for use with:
TCONT303
TCONT302

Functional
Parts



Functional
Parts



Registered Limited Warranty terms are available when you register within 60 days of installation. You can register online at Trane.com or by phone at 855-260-2975, otherwise Trane's Base Limited Warranty terms will apply. Base Limited Warranty information on specific products can be found on ComfortSite.com. Product Registration and Registration Transfer exclusions vary in the US from state to state and in Canada from province to province. To determine if there are specific exclusions for your state or province check your local laws.

QUESTIONS ABOUT WARRANTY? CONTACT YOUR LOCAL TRANE REPRESENTATIVE.

PACKAGED

HEAT PUMPS



3-Phase



1-Phase

PRIORITY

15 3-Phase Two-Stage Heat Pump Packaged



5WCZ5

Up to 15.2 SEER2/8.1 HSPF

- 3, 4 and 5 ton
- 3-Phase only (208v/230v & 460v)
- 2-stage Climatuff® compressor
- Variable-speed indoor blower motor
- Comfort-R™ mode
- Composite Vortica™ blower
- Tough corrosion and UV resistant paint
- Demand defrost
- Ultra quiet
- CleanEffects™ compatible (horizontal only)

15 Two-Stage Heat Pump Packaged



5WCZ5

Up to 15.2 SEER2/8.1 HSPF

- 2, 2.5, 3, 3.5, 4 and 5 ton
- 1-Phase only (208v/230v)
- 2-stage Climatuff® compressor
- Variable-speed indoor blower motor
- Comfort-R™ mode
- Composite Vortica™ blower
- Tough corrosion and UV resistant paint
- Demand defrost
- Ultra quiet
- CleanEffects™ compatible (horizontal only)

CHOICE

14 3-Phase Single-Stage Heat Pump Packaged



5WCC4

Up to 13.6 SEER2/7 HSPF

- 3, 4 and 5 ton
- 3-Phase only (208v/230v & 460v)
- Climatuff® compressor
- Variable-speed indoor blower motor
- Composite Vortica™ blower
- Tough corrosion and UV resistant paint
- Demand defrost
- CleanEffects™ compatible (horizontal only)

14 Single-Stage Heat Pump Packaged



5WCC4

Up to 13.6 SEER2/7 HSPF

- 2, 2.5, 3, 3.5, 4 and 5 ton
- 1-Phase only (208v/230v)
- Climatuff® compressor
- Spine Fin™ condenser
- Tough corrosion and UV resistant paint
- Composite Vortica™ blower
- Demand defrost
- CleanEffects™ compatible (horizontal only)

GAS/ELECTRIC



3-Phase



1-Phase

PRIORITY

15 3-Phase Two-Stage Gas Furnace/Air Conditioner Packaged



5YCZ5

Up to 15.2 SEER2/81% AFUE

- 3, 4 and 5 ton
- 3-Phase only (208v/230v & 460v)
- 2-stage Climatuff® compressor
- 2-stage gas heat
- Variable-speed indoor blower motor
- Composite Vortica™ blower
- Comfort-R™ mode
- Spine Fin™ condenser
- Tough corrosion and UV resistant paint
- All stainless steel heating system
- Ultra quiet
- CleanEffects™ compatible (horizontal only)

15 Two-Stage Gas Furnace/Air Conditioner Packaged



5YCZ5

15.2 SEER2/81% AFUE

- 2, 2.5, 3, 3.5 and 5 ton
- 1-Phase only (208v/230v)
- 2-stage Climatuff® compressor
- 2-stage gas heat
- Variable-speed indoor blower motor
- Composite Vortica™ blower
- Comfort-R™ mode
- Spine Fin™ condenser
- Ultra quiet
- Tough corrosion and UV resistant paint
- All stainless steel heating system
- CleanEffects™ compatible (horizontal only)

CHOICE

14 3-Phase Single-Stage Gas Furnace/Air Conditioner Packaged



5YCC4

Up to 14.3 SEER2/81% AFUE

- 3, 4 and 5 ton
- 3-Phase only (208v/230v & 460v)
- Climatuff® compressor
- Spine Fin™ condenser
- Composite Vortica™ blower
- All stainless steel heating system
- Tough corrosion and UV resistant paint
- CleanEffects™ compatible (horizontal only)

14 Single-Stage Gas Furnace/Air Conditioner Packaged



5YCC4

Up to 14.3 SEER2/81% AFUE

- 2, 2.5, 3, 3.5, 4 and 5 ton
- 1-Phase only (208v/230v)
- Climatuff® compressor
- Spine Fin™ condenser
- Composite Vortica™ blower
- All stainless steel heating system
- Tough corrosion and UV resistant paint
- CleanEffects™ compatible (horizontal only)

EARTHWISE™ HYBRID DUAL FUEL



PRIORITY

15 Two-Stage Hybrid Gas Furnace/Heat Pump Packaged



5DCZ5

Up to 15.2 SEER2/8.1 HSPF

- 2, 2.5, 3, 3.5, 4 and 5 ton
- 1-Phase only (208v/230v)
- 2-stage Climatuff® compressor
- Variable-speed indoor blower motor
- Spine Fin™ condenser
- Comfort-R™ mode
- Composite Vortica™ blower
- Heat pump and/or 2-stage gas heat operation
- All stainless steel heating system
- Ultra quiet
- CleanEffects™ compatible (horizontal only)

COOLING



CHOICE

14 Single-Stage Air Conditioner Packaged



5TCC4

Up to 14.3 SEER2

- 2, 2.5, 3, 3.5, 4 and 5 ton
- 1-Phase only (208v/230v)
- Climatuff® compressor
- Spine Fin™ condenser
- Composite Vortica™ blower
- CleanEffects™ compatible (horizontal only)

8



- ① Compressor
- ② Coil
- ③ Functional Parts



- ① Heat Exchanger
- ② Compressor
- ③ Coil
- ④ Functional Parts

All Trane Packaged systems have a Base Limited Warranty of 5 years on the compressor, coil, and functional parts. Gas/Electric and Earthwise Hybrid Dual Fuel systems have a Base Limited Warranty of 20 years on the heat exchanger. Limited Warranty Term for Trane Products Installed in Commercial Applications: Coil, Parts – 1 year Limited Warranty; Compressor – 5 years Limited Warranty; Packaged Unit Heat Exchanger – 5 years Product Registration and Registration Transfer exclusions vary in the US from state to state and in Canada from province to province. To determine if there are specific exclusions for your state or province check your local laws.

QUESTIONS ABOUT WARRANTY? CONTACT YOUR LOCAL TRANE REPRESENTATIVE.



Lower Global Warming Potential

To minimize environmental impacts, the HVAC industry is transitioning to Lower Global Warming Potential (GWP) refrigerants. Trane's newest lineup of equipment designs are tagged with our two-tone green icon for easy identification.



It's Hard To Stop A Trane.®

All trademarks referenced are the trademarks of their respective owners.

About Trane

Trane – by Trane Technologies (NYSE: TT), a global climate innovator – creates comfortable, energy efficient indoor environments for commercial and residential applications. For more information, visit Trane.com or TraneTechnologies.com

© 2025 TRANE. ALL RIGHTS RESERVED. 62-1014-R-39 02/25