DAY-16

PAGE NO.:
DATE:

(i) A set is an unordered, mutable collection that stores unique values only.

→ Created using {}.

ie: {"apple", "banana", "mango"}

(ii) Why:

- Remove duplicates from data
- Improve cleaning speed
- Useful in merging & intersecting tables
- extract unique values from column.

eg: fruits = {"Apple", "Banana", "Apple", "mango"}
print(fruits).

(iii) Add items:

fruits.add("orange")
print(fruits)

(iv) Remove:

fruits.discard("Banana")
print(fruits)

Scanned with OKEN Scanner

PAGE NO.:
DATE:

Set operation :-

```
a = {1,2,3}
b = {3,4,5}
print("Union", a|b)        |: Union
print(a-b)                 -: Difference
print(a&b)  → op → {1,2}   &: Intersection
print(a^b)                 ^: symmetric Difference
            → o/p → {1,2,4,5}
```

Remove duplicates :-

```
Cities = ["Mumbai", "pune", "Delhi", "mumbai"]
Unique = set(cities)
print("Unique": Unique)
```

Common skill :-

```
deptA = {"SQL", "Excel", "python"}
deptB = {"Excel", "python", "powerBI"}
print("common skills": deptA & deptB)
                    → o/p → {'python', 'Excel'}
```

Missing value :-

```
list1 = {"SQL", "Excel", "powerBI"}
list2 = {"SQL", "powerBI"}
missing = list1 - list2
print(missing).  → o/p → {"Excel"}
```

Scanned with OKEN Scanner