DAY-3

GROUP BY :-

is used to group rows that have the same values into summary rows.

ie: ~~SELE~~ -- Calculate total employee in each city?

```
SELECT city, COUNT(emp-id) FROM
    employees
GROUP BY city;
```

```
SELECT DISTINCT city FROM
    employees;
```

HAVING :-

is used to filter groups based on the result of "aggregate function columns".

ie: -- All the city where employes count is greater than 2.?

classmate

Date
Page

```
SELECT city, COUNT(emp-id) FROM
                        employee
GROUP BY city
HAVENG COUNT(emp-id) > 2;
```

✡ **ORDER BY:-**

is used to sort the result based on one or more columns.

ie:-

```
SELECT * FROM employee
ORDER BY salary DESC/ASC;
```

✡ **LIMIT:-**

is used to restrict the number of Rows returned in the output.

ie:

```
SELECT * FROM employee
LIMIT 10;
```

Que: -- TOP 2 highest earner?

```
SELECT * FROM employees
ORDER BY DESC, LIMIT 2;
```

Scanned with OKEN Scanner

Ques :- --10th place highest salary earners?

```
SELECT DISTINCT salary FROM
employees
ORDER BY DESC
LIMIT 1 OFFSET 9;
```

Scanned with OKEN Scanner