sign_language_cnn_100_percent

May 5, 2020

```
In [2]: import matplotlib.pyplot as plt
        import numpy as np
        import tensorflow as tf
        import pandas as pd
       from tensorflow import keras
       from tensorflow.keras.layers import Conv2D, Flatten, MaxPooling2D, AveragePooling2D, Den
        from keras.preprocessing.image import ImageDataGenerator
        import string
       from libitmal import kernelfuns as itmalkernelfuns
        itmalkernelfuns.EnableGPU()
       %matplotlib inline
       def get_mnist_dataset():
           test_pd = pd.read_csv("./SignLanguageData/sign_mnist_test.csv",
           train_pd = pd.read_csv("./SignLanguageData/sign_mnist_train.csv",
               skiprows=1)
           return train_pd, test_pd
       train_pd, test_pd = get_mnist_dataset()
       X_train, X_test = train_pd.values[:,1:], test_pd.values[:,1:]
       y_train, y_test = train_pd.values[:,0], test_pd.values[:,0]
       class_names = list(string.ascii_lowercase)
       train_pd.head()
Out[2]:
           3 107
                   118
                        127 134 139
                                      143
                                            146 150
                                                     153
                                                           . . .
                                                                207.4 207.5 207.6 \
       0
           6 155
                   157
                        156 156
                                  156
                                       157
                                            156
                                                 158
                                                      158
                                                                   69
                                                                         149
                                                                                128
       1
           2 187
                   188
                        188 187
                                  187
                                       186
                                            187 188
                                                      187
                                                                  202
                                                                         201
                                                                                200
           2 211
                   211
                        212 212 211
                                       210
                                            211 210
                                                      210
                                                                  235
                                                                         234
                                                                                233
       3
          13 164
                   167
                        170 172 176
                                       179
                                            180
                                                 184
                                                      185
                                                                   92
                                                                         105
                                                                                105
          16 161 168
                        172 173 178
                                       184
                                            189 193 196
                                                                   76
                                                                          74
                                                                                 68
```

```
207.7 206.4
                         206.5 206.6 204.6 203.8
                                                     202.13
        0
              87
                     94
                           163
                                         103
                                                135
                                                         149
                                  175
        1
             199
                           199
                                  198
                                                194
                                                         195
                    198
                                         195
        2
             231
                    230
                           226
                                  225
                                         222
                                                229
                                                         163
        3
                                  157
                                                         179
             108
                    133
                           163
                                         163
                                                164
        4
              62
                     53
                            55
                                   48
                                         238
                                                255
                                                         255
        [5 rows x 785 columns]
In [3]: X_train = X_train / 255
        X_{test} = X_{test} / 255
        X_train = X_train.reshape(*X_train.shape[:1], 28, 28)
        X_test = X_test.reshape(*X_test.shape[:1], 28, 28)
        X_train = X_train.reshape(X_train.shape[0], 28, 28, 1)
        X_test = X_test.reshape(X_test.shape[0], 28, 28, 1)
        batch_size, height, width, channel = X_train.shape
        print(X_train.shape)
(27454, 28, 28, 1)
In [185]: # Datageneration form https://www.kaggle.com/madz2000/cnn-using-keras-99-7-accuracy
          datagen = ImageDataGenerator(
                  featurewise_center=False, # set input mean to 0 over the dataset
                  samplewise_center=False, # set each sample mean to 0
                  featurewise_std_normalization=False, # divide inputs by std of the dataset
                  samplewise_std_normalization=False, # divide each input by its std
                  zca_whitening=False, # apply ZCA whitening
                  rotation_range=10, # randomly rotate images in the range (degrees, 0 to 180)
                  zoom_range = 0.1, # Randomly zoom image
                  width_shift_range=0.1, # randomly shift images horizontally (fraction of total
                  height_shift_range=0.1, # randomly shift images vertically (fraction of total
                  horizontal_flip=False, # randomly flip images
                  vertical_flip=False # randomly flip images
          )
          datagen.fit(X_train)
In [6]: def create_le_net():
            model = keras.models.Sequential([
                ZeroPadding2D(input_shape=X_train.shape[1:], padding=(3, 3)),
                Conv2D(filters=6, kernel_size=(5, 5), strides=1, activation="tanh"),
                AveragePooling2D(pool_size=6, strides=2, padding="same"),
```

```
AveragePooling2D(pool_size=6, strides=2, padding="same"),
                Conv2D(filters=120, kernel_size=(5, 5), strides=1, activation="tanh"),
                Flatten(),
                Dense(84, activation="tanh"),
                Dense(len(class_names), activation="softmax")
            ])
            return model
        def create_model():
            model = keras.models.Sequential([
                ZeroPadding2D(input_shape=X_train.shape[1:], padding=(3, 3)),
                Conv2D(filters=16, kernel_size=(3, 3), activation="relu"),
                AveragePooling2D(),
                Conv2D(filters=32, kernel_size=(3, 3), activation="relu"),
                AveragePooling2D(),
                Flatten(),
                Dense(256, activation="relu"),
                Dense(512, activation="relu"),
                Dense(128, activation="relu"),
                Dense(64, activation="relu"),
                Dense(len(class_names), activation="softmax")
            1)
            return model
In [201]: X_test.shape
Out[201]: (7171, 28, 28, 1)
In [187]: # LeNet
          model = create_model()
In [188]: #keras.utils.plot_model(model, "my_mnist_model.png", show_shapes=True)
In [189]: model.compile(loss="sparse_categorical_crossentropy",
                        optimizer="adam",
                        metrics=["accuracy"])
In [190]: from keras.callbacks import EarlyStopping, ModelCheckpoint
          early_stopping = EarlyStopping(monitor='loss',
                                        patience=30,
                                        verbose=0,
                                        mode='min')
          mcp_save = ModelCheckpoint('cnn_model_checkpoint.h5',
                                     save_best_only=True,
```

Conv2D(filters=16, kernel_size=(5, 5), strides=1, activation="tanh"),

```
batch_size = 128,
        validation_split=0.2),
      epochs=500,
      validation_split=0.2,
      callbacks=[early_stopping, mcp_save])
Epoch 1/500
Epoch 2/500
Epoch 3/500
Epoch 4/500
Epoch 5/500
Epoch 6/500
Epoch 7/500
Epoch 8/500
Epoch 9/500
Epoch 10/500
Epoch 11/500
Epoch 12/500
Epoch 13/500
Epoch 14/500
Epoch 15/500
Epoch 16/500
Epoch 17/500
Epoch 18/500
Epoch 19/500
```

monitor='val_loss',

y_train,

mode='min')

history = model.fit(datagen.flow(X_train,


```
Epoch 20/500
Epoch 21/500
Epoch 22/500
Epoch 23/500
Epoch 24/500
Epoch 25/500
Epoch 26/500
Epoch 27/500
Epoch 28/500
Epoch 29/500
Epoch 30/500
Epoch 31/500
Epoch 32/500
Epoch 33/500
Epoch 34/500
Epoch 35/500
Epoch 36/500
Epoch 37/500
Epoch 38/500
Epoch 39/500
Epoch 40/500
Epoch 41/500
Epoch 42/500
Epoch 43/500
```

```
Epoch 44/500
Epoch 45/500
Epoch 46/500
Epoch 47/500
Epoch 48/500
Epoch 49/500
Epoch 50/500
Epoch 51/500
Epoch 52/500
Epoch 53/500
Epoch 54/500
Epoch 55/500
Epoch 56/500
Epoch 57/500
Epoch 58/500
Epoch 59/500
Epoch 60/500
Epoch 61/500
Epoch 62/500
Epoch 63/500
Epoch 64/500
Epoch 65/500
Epoch 66/500
Epoch 67/500
```

```
Epoch 68/500
Epoch 69/500
Epoch 70/500
Epoch 71/500
Epoch 72/500
Epoch 73/500
Epoch 74/500
Epoch 75/500
Epoch 76/500
Epoch 77/500
Epoch 78/500
Epoch 79/500
Epoch 80/500
Epoch 81/500
Epoch 82/500
Epoch 83/500
Epoch 84/500
Epoch 85/500
Epoch 86/500
Epoch 87/500
Epoch 88/500
Epoch 89/500
Epoch 90/500
Epoch 91/500
```


```
Epoch 92/500
Epoch 93/500
Epoch 94/500
Epoch 95/500
Epoch 96/500
Epoch 97/500
Epoch 98/500
Epoch 99/500
Epoch 100/500
Epoch 101/500
Epoch 102/500
Epoch 103/500
Epoch 104/500
Epoch 105/500
Epoch 106/500
Epoch 107/500
Epoch 108/500
Epoch 109/500
Epoch 110/500
Epoch 111/500
Epoch 112/500
Epoch 113/500
Epoch 114/500
Epoch 115/500
```

```
Epoch 116/500
Epoch 117/500
Epoch 118/500
Epoch 119/500
Epoch 120/500
In [191]: import pandas as pd
    evaluation = model.evaluate(X_test, y_test)
    print(f'Model evaluation: {evaluation}')
    pd.DataFrame(history.history).plot(figsize=(14, 10))
    plt.grid(True)
    plt.gca().set_ylim(-0.1, 1.1)
    plt.xlabel("Epoch [N]")
    plt.ylabel("Percentage [%]")
    plt.title("Loss and Accuracy as a function of epochs")
    plt.show()
7171/7171 [=========] - 1s 71us/step
Model evaluation: [0.0008896882954271737, 1.0]
```



```
In [192]: import math
          num\_rows = 3
         num\_cols = 3
         X_new = X_test[:num_rows*num_cols]
          y_pred = model.predict_classes(X_new)
          fig, ax = plt.subplots(num_rows, num_cols, figsize=(18, 16))
          for index, image in enumerate(X_new):
              ax[math.floor(index/num_rows), index%num_rows].imshow(image.reshape((28,28)))
              ax[math.floor(index/num_rows), index%num_rows].set_title(
                  f"Actual: {class_names[y_test[index]]}\nPredicted: {class_names[y_pred[index]]
                  fontsize=16)
              ax[int(index/num_rows), index%num_rows].axis('off')
          fig.tight_layout()
          fig.suptitle(f'First Predictions', fontsize=20)
          fig.subplots_adjust(top=0.88)
          fig.show()
```

First Predictions




```
In [193]: y_pred = model.predict_classes(X_test)

confusion_indices = np.where(y_pred != y_test)
X_confusion = X_test[confusion_indices]
y_pred_confusion = y_pred[confusion_indices]
y_test_confusion = y_test[confusion_indices]

fig, ax = plt.subplots(num_rows, num_cols, figsize=(18, 16))
for index, image in enumerate(X_confusion[:num_rows*num_cols]):
    ax[math.floor(index/num_rows), index%num_rows].imshow(image.reshape((28,28)), intex[math.floor(index/num_rows), index%num_rows].set_title(
    f"Actual: {class_names[y_test_confusion[index]]}\nPredicted: {class_names[y_predicted: {class_names[y_predicted
```

```
fig.tight_layout()
fig.suptitle('Incorrect Predictions', fontsize=20)
fig.subplots_adjust(top=0.88)
fig.show()
```

Incorrect Predictions



In [194]: import sklearn.metrics as metrics

```
confusion_matrix = metrics.confusion_matrix(y_test, y_pred)
row_sum = confusion_matrix.sum(axis=1, keepdims=True)
norm_confusion_matrix = confusion_matrix / row_sum

# Because j and z aren't possible we cant include them in confusion matrix
class_names_clean = class_names.copy()
class_names_clean.remove('j')
class_names_clean.remove('z')
```

```
np.fill_diagonal(norm_confusion_matrix, 0)

fig, ax = plt.subplots(figsize=(18, 16))

mat_ax = ax.matshow(norm_confusion_matrix, interpolation='nearest', cmap=plt.cm.gray)
fig.colorbar(mat_ax)
ax.set_title('Confusion matrix for characters', fontsize=20)
ax.set_xlabel('Actual Class', fontsize=12)
ax.set_ylabel('Predicted Class', fontsize=12)
ax.set_xticks(ticks=np.arange(0, len(class_names_clean)))
ax.set_xticklabels(class_names_clean)
ax.set_yticks(ticks=np.arange(0, len(class_names_clean)))
ax.set_yticklabels(class_names_clean)
fig.show()
```

Confusion matrix for characters

