

Package ‘mlmr’

May 5, 2026

Title Mixed-Effects and Multilevel Models in R

Version 0.1.0

Author Marcus Harris [aut, cre]

Maintainer Marcus Harris <marcus.harris.uconn@gmail.com>

Description

A Shiny interface and R toolkit for fitting, understanding, and reporting mixed-effects and multi-level models with lme4. The package supports centering decisions, nested and flexible random-effects structures, equations, APA-style tables, diagnostics, and reproducible code.

License MIT + file LICENSE

URL <https://marcusharrisphd.com/mlmr/>, <https://github.com/MarcusHarrisUConn/mlmr>

BugReports <https://github.com/MarcusHarrisUConn/mlmr/issues>

Encoding UTF-8

Roxygen list(markdown = TRUE)

RoxygenNote 7.3.2

Imports shiny,
bslib,
lme4,
ggplot2

Suggests haven,
knitr,
readxl,
rmarkdown

VignetteBuilder knitr

Contents

mlmr-package	2
run_mlmr	2
Index	4

mlmr-package

Mixed-Effects and Multilevel Models in R

Description

mlmr provides a guided Shiny interface and supporting R toolkit for fitting, understanding, and reporting mixed-effects and multilevel models with **lme4**.

Details

The package is designed for users who want an HLM-style graphical workflow while preserving transparent and reproducible R code. The app supports level-based predictor selection, centering decisions, fixed effects, random intercepts, random slopes, interactions, model diagnostics, APA-style tables, level-by-level equations, combined equations, Tau variance-covariance displays, and reproducible exports.

Launch the app with `run_mlmr()`.

Author(s)

Marcus Harris

See Also

`run_mlmr`

run_mlmr

Launch the mlmr Shiny App

Description

Launches the **mlmr** Shiny interface for mixed-effects and multilevel modeling with **lme4**.

Usage

```
run_mlmr(launch.browser = TRUE, port = getOption("shiny.port", NULL))
```

Arguments

`launch.browser` Logical; whether to open the app in the default browser.
`port` Optional port passed to shiny::runApp.

Details

The app opens with a built-in HSB-style example dataset and a preset model so users can test the complete workflow before uploading their own data. Uploaded data can be provided as CSV, TSV/TXT, Excel, SPSS, SAS, or Stata files when the optional import packages are installed.

Value

Runs the Shiny application. This function is called for its side effect and does not return a modeling object.

Examples

```
if (interactive()) {  
  run_mlmr()  
}
```

Index

* **package**

mlmr-package, [2](#)

mlmr (mlmr-package), [2](#)

mlmr-package, [2](#)

run_mlmr, [2](#), [2](#)