

DM549/DS(K)820/MM537/DM547

Lecture 1: Propositional Logic

Kevin Schewior

Email: [kevs@sdu.dk](mailto:kevs@sdu.dk)

University of Southern Denmark

September 2, 2024

## Definition (Definition 1.1.1)

A *proposition* (et udsagn) is a declarative statement (that is, a statement that declares a fact) that is true (sand) or false (falsk) but not both.

## Definition (Definition 1.1.1)

A *proposition* (et udsagn) is a declarative statement (that is, a statement that declares a fact) that is true (sand) or false (falsk) but not both.

### Remarks:

- We denote a true proposition as **T** and a false one as **F**.

## Definition (Definition 1.1.1)

A *proposition* (et udsagn) is a declarative statement (that is, a statement that declares a fact) that is true (sand) or false (falsk) but not both.

### Remarks:

- We denote a true proposition as **T** and a false one as **F**.
- Alternatively, one can also think of bits, where 1 corresponds to **T** and 0 corresponds to **F**.

# Logical Operators

Using *operators* (operatorer), we can build *compound propositions* (sammensatte udsagn) from other (possibly compound) propositions.

# Logical Operators

Using *operators* (operatorer), we can build *compound propositions* (sammensatte udsagn) from other (possibly compound) propositions.

Here,  $p$ ,  $q$ , and  $r$  will be variables representing propositions.

# Logical Operators

Using *operators* (operatorer), we can build *compound propositions* (sammensatte udsagn) from other (possibly compound) propositions.

Here,  $p$ ,  $q$ , and  $r$  will be variables representing propositions.

Today, we will get to know the following operators:

- the negation  $\neg$ ,
- the conjunction  $\wedge$ ,
- the disjunction  $\vee$ ,
- the implication  $\Rightarrow$ ,
- the bi-implication  $\Leftrightarrow$ ,
- the exclusive or  $\oplus$ .

# The Logical Negation

We can define an operator through a so-called *truth table* (sandhedstabel):

$p$	$\neg p$
T	F
F	T

For every value of the operand  $p$ , the value of the compound proposition is given.



# The Logical Negation

We can define an operator through a so-called *truth table* (sandhedstabel):

$p$	$\neg p$
T	F
F	T

For every value of the operand  $p$ , the value of the compound proposition is given.

## Remarks:

- Read: “not (ikke)  $p$ ” or “ $p$ ’s negation (negation)”

# The Logical Negation

We can define an operator through a so-called *truth table* (sandhedstabel):

$p$	$\neg p$
T	F
F	T

For every value of the operand  $p$ , the value of the compound proposition is given.

## Remarks:

- Read: “not (ikke)  $p$ ” or “ $p$ ’s negation (negation)”
- In words:  $\neg$  “flips” the truth value of  $p$ .

# The Logical Negation

We can define an operator through a so-called *truth table* (sandhedstabel):

$p$	$\neg p$
T	F
F	T

For every value of the operand  $p$ , the value of the compound proposition is given.

## Remarks:

- Read: “not (ikke)  $p$ ” or “ $p$ ’s negation (negation)”
- In words:  $\neg$  “flips” the truth value of  $p$ .
- Alternative notation:  $\bar{p}$ ,  $!p$ .

# The Logical And and the Logical Or

We can also define binary (as opposed to unary) operators through truth tables:

$p$	$q$	$p \wedge q$
T	T	T
T	F	F
F	T	F
F	F	F

$p$	$q$	$p \vee q$
T	T	T
T	F	T
F	T	T
F	F	F

For every combination of values of the operands  $p$  and  $q$ , the value of the compound proposition is given.

# The Logical And and the Logical Or

We can also define binary (as opposed to unary) operators through truth tables:

$p$	$q$	$p \wedge q$	$p$	$q$	$p \vee q$
T	T	T	T	T	T
T	F	F	T	F	T
F	T	F	F	T	T
F	F	F	F	F	F

For every combination of values of the operands  $p$  and  $q$ , the value of the compound proposition is given.

## Remarks:

### ■ Read:

- ▶  $p \wedge q$ : “ $p$  and  $q$ ” (“ $p$  og  $q$ ”)
- ▶  $p \vee q$ : “ $p$  or  $q$ ” (“ $p$  eller  $q$ ”)

# The Logical And and the Logical Or

We can also define binary (as opposed to unary) operators through truth tables:

$p$	$q$	$p \wedge q$	$p$	$q$	$p \vee q$
T	T	T	T	T	T
T	F	F	T	F	T
F	T	F	F	T	T
F	F	F	F	F	F

For every combination of values of the operands  $p$  and  $q$ , the value of the compound proposition is given.

## Remarks:

### ■ Read:

- ▶  $p \wedge q$ : “ $p$  and  $q$ ” (“ $p$  og  $q$ ”)
- ▶  $p \vee q$ : “ $p$  or  $q$ ” (“ $p$  eller  $q$ ”)

### ■ In words:

- ▶ For  $p \wedge q$  to be T, both  $p$  and  $q$  must be T.
- ▶ For  $p \vee q$  to be T, at least one of  $p$  and  $q$  must be T.

# The Logical And and the Logical Or

We can also define binary (as opposed to unary) operators through truth tables:

$p$	$q$	$p \wedge q$	$p$	$q$	$p \vee q$
T	T	T	T	T	T
T	F	F	T	F	T
F	T	F	F	T	T
F	F	F	F	F	F

For every combination of values of the operands  $p$  and  $q$ , the value of the compound proposition is given.

## Remarks:

### ■ Read:

- ▶  $p \wedge q$ : “ $p$  and  $q$ ” (“ $p$  og  $q$ ”)
- ▶  $p \vee q$ : “ $p$  or  $q$ ” (“ $p$  eller  $q$ ”)

### ■ In words:

- ▶ For  $p \wedge q$  to be T, both  $p$  and  $q$  must be T.
- ▶ For  $p \vee q$  to be T, at least one of  $p$  and  $q$  must be T.

### ■ How to memorize? Perhaps “a∧d” helps.

# A Quiz

Go to [pollev.com/kevs](https://pollev.com/kevs)





# The Logical Implication

Another operator:

$p$	$q$	$p \Rightarrow q$
T	T	T
T	F	F
F	T	T
F	F	T

# The Logical Implication

Another operator:

$p$	$q$	$p \Rightarrow q$
T	T	T
T	F	F
F	T	T
F	F	T

## Remarks:

- Read:

- ▶ “ $p$  implies  $q$ ” (“ $p$  medfører  $q$ ”)

# The Logical Implication

Another operator:

$p$	$q$	$p \Rightarrow q$
T	T	T
T	F	F
F	T	T
F	F	T

## Remarks:

- Read:

- ▶ “ $p$  implies  $q$ ” (“ $p$  medfører  $q$ ”)
- ▶ “if  $p$ , then  $q$ ” (“hvis  $p$ , så  $q$ ”)

# The Logical Implication

Another operator:

$p$	$q$	$p \Rightarrow q$
T	T	T
T	F	F
F	T	T
F	F	T

## Remarks:

### ■ Read:

- ▶ “ $p$  implies  $q$ ” (“ $p$  medfører  $q$ ”)
- ▶ “if  $p$ , then  $q$ ” (“hvis  $p$ , så  $q$ ”)
- ▶ “ $q$  if  $p$ ” (“ $q$  hvis  $p$ ”)

# The Logical Implication

Another operator:

$p$	$q$	$p \Rightarrow q$
T	T	T
T	F	F
F	T	T
F	F	T

## Remarks:

### ■ Read:

- ▶ “ $p$  implies  $q$ ” (“ $p$  medfører  $q$ ”)
- ▶ “if  $p$ , then  $q$ ” (“hvis  $p$ , så  $q$ ”)
- ▶ “ $q$  if  $p$ ” (“ $q$  hvis  $p$ ”)
- ▶ “ $p$  only if  $q$ ” (“ $p$  kun hvis  $q$ ”)

# The Logical Implication

Another operator:

$p$	$q$	$p \Rightarrow q$
T	T	T
T	F	F
F	T	T
F	F	T

## Remarks:

### ■ Read:

- ▶ “ $p$  implies  $q$ ” (“ $p$  medfører  $q$ ”)
- ▶ “if  $p$ , then  $q$ ” (“hvis  $p$ , så  $q$ ”)
- ▶ “ $q$  if  $p$ ” (“ $q$  hvis  $p$ ”)
- ▶ “ $p$  only if  $q$ ” (“ $p$  kun hvis  $q$ ”)
- ▶ “ $p$  is a sufficient condition for  $q$ ” (“ $p$  er en tilstrækkelig betingelse for  $q$ ”)

# The Logical Implication

Another operator:

$p$	$q$	$p \Rightarrow q$
T	T	T
T	F	F
F	T	T
F	F	T

## Remarks:

### ■ Read:

- ▶ “ $p$  implies  $q$ ” (“ $p$  medfører  $q$ ”)
- ▶ “if  $p$ , then  $q$ ” (“hvis  $p$ , så  $q$ ”)
- ▶ “ $q$  if  $p$ ” (“ $q$  hvis  $p$ ”)
- ▶ “ $p$  only if  $q$ ” (“ $p$  kun hvis  $q$ ”)
- ▶ “ $p$  is a sufficient condition for  $q$ ” (“ $p$  er en tilstrækkelig betingelse for  $q$ ”)
- ▶ “ $q$  is a necessary condition for  $p$ ” (“ $q$  er en nødvendig betingelse for  $p$ ”)

# The Logical Implication

Another operator:

$p$	$q$	$p \Rightarrow q$
T	T	T
T	F	F
F	T	T
F	F	T

## Remarks:

### ■ Read:

- ▶ “ $p$  implies  $q$ ” (“ $p$  medfører  $q$ ”)
- ▶ “if  $p$ , then  $q$ ” (“hvis  $p$ , så  $q$ ”)
- ▶ “ $q$  if  $p$ ” (“ $q$  hvis  $p$ ”)
- ▶ “ $p$  only if  $q$ ” (“ $p$  kun hvis  $q$ ”)
- ▶ “ $p$  is a sufficient condition for  $q$ ” (“ $p$  er en tilstrækkelig betingelse for  $q$ ”)
- ▶ “ $q$  is a necessary condition for  $p$ ” (“ $q$  er en nødvendig betingelse for  $p$ ”)

- $p$  is called the assumption (antagelse),  $q$  the consequence (konsekvens)



# The Logical Implication

Another operator:

$p$	$q$	$p \Rightarrow q$
T	T	T
T	F	F
F	T	T
F	F	T

## Remarks:

### ■ Read:

- ▶ “ $p$  implies  $q$ ” (“ $p$  medfører  $q$ ”)
- ▶ “if  $p$ , then  $q$ ” (“hvis  $p$ , så  $q$ ”)
- ▶ “ $q$  if  $p$ ” (“ $q$  hvis  $p$ ”)
- ▶ “ $p$  only if  $q$ ” (“ $p$  kun hvis  $q$ ”)
- ▶ “ $p$  is a sufficient condition for  $q$ ” (“ $p$  er en tilstrækkelig betingelse for  $q$ ”)
- ▶ “ $q$  is a necessary condition for  $p$ ” (“ $q$  er en nødvendig betingelse for  $p$ ”)

■  $p$  is called the assumption (antagelse),  $q$  the consequence (konsekvens)

■ In words: for  $p \Rightarrow q$  to be T,  $q$  may not be F if  $p$  is T

# The Logical Implication

Another operator:

$p$	$q$	$p \Rightarrow q$
T	T	T
T	F	F
F	T	T
F	F	T

## Remarks:

### ■ Read:

- ▶ “ $p$  implies  $q$ ” (“ $p$  medfører  $q$ ”)
- ▶ “if  $p$ , then  $q$ ” (“hvis  $p$ , så  $q$ ”)
- ▶ “ $q$  if  $p$ ” (“ $q$  hvis  $p$ ”)
- ▶ “ $p$  only if  $q$ ” (“ $p$  kun hvis  $q$ ”)
- ▶ “ $p$  is a sufficient condition for  $q$ ” (“ $p$  er en tilstrækkelig betingelse for  $q$ ”)
- ▶ “ $q$  is a necessary condition for  $p$ ” (“ $q$  er en nødvendig betingelse for  $p$ ”)

■  $p$  is called the assumption (antagelse),  $q$  the consequence (konsekvens)

■ In words: for  $p \Rightarrow q$  to be T,  $q$  may not be F if  $p$  is T

■ Alternative notation:  $\rightarrow$  (book!)

# The Logical Bi-implication

A similarly looking operator:

$p$	$q$	$p \Leftrightarrow q$
T	T	T
T	F	F
F	T	F
F	F	T

# The Logical Bi-implication

A similarly looking operator:

$p$	$q$	$p \Leftrightarrow q$
T	T	T
T	F	F
F	T	F
F	F	T

## Remarks:

- Read:

- ▶ “ $p$  if and only if  $q$ ” (“ $p$  hvis og kun hvis  $q$ ”)

# The Logical Bi-implication

A similarly looking operator:

$p$	$q$	$p \Leftrightarrow q$
T	T	T
T	F	F
F	T	F
F	F	T

## Remarks:

### ■ Read:

- ▶ “ $p$  if and only if  $q$ ” (“ $p$  hvis og kun hvis  $q$ ”)
- ▶ “ $p$  iff  $q$ ” (“ $p$  hviss  $q$ ”)

# The Logical Bi-implication

A similarly looking operator:

$p$	$q$	$p \Leftrightarrow q$
T	T	T
T	F	F
F	T	F
F	F	T

## Remarks:

### ■ Read:

- ▶ “ $p$  if and only if  $q$ ” (“ $p$  hvis og kun hvis  $q$ ”)
- ▶ “ $p$  iff  $q$ ” (“ $p$  hviss  $q$ ”)
- ▶ “ $p$  is a necessary and sufficient condition for  $q$ ” (“ $p$  er en nødvendig og tilstrækkelig betingelse for  $q$ ”)

# The Logical Bi-implication

A similarly looking operator:

$p$	$q$	$p \Leftrightarrow q$
T	T	T
T	F	F
F	T	F
F	F	T

## Remarks:

### ■ Read:

- ▶ “ $p$  if and only if  $q$ ” (“ $p$  hvis og kun hvis  $q$ ”)
- ▶ “ $p$  iff  $q$ ” (“ $p$  hviss  $q$ ”)
- ▶ “ $p$  is a necessary and sufficient condition for  $q$ ” (“ $p$  er en nødvendig og tilstrækkelig betingelse for  $q$ ”)

- In words: for  $p \Leftrightarrow q$  to be T,  $p$  and  $q$  must have the same truth value.

# The Logical Bi-implication

A similarly looking operator:

$p$	$q$	$p \Leftrightarrow q$
T	T	T
T	F	F
F	T	F
F	F	T

## Remarks:

### ■ Read:

- ▶ “ $p$  if and only if  $q$ ” (“ $p$  hvis og kun hvis  $q$ ”)
- ▶ “ $p$  iff  $q$ ” (“ $p$  hviss  $q$ ”)
- ▶ “ $p$  is a necessary and sufficient condition for  $q$ ” (“ $p$  er en nødvendig og tilstrækkelig betingelse for  $q$ ”)

■ In words: for  $p \Leftrightarrow q$  to be T,  $p$  and  $q$  must have the same truth value.

■ Alternative notation:  $\leftrightarrow$  (book!)



# The Exclusive Or

The last operator:

$p$	$q$	$p \oplus q$
T	T	F
T	F	T
F	T	T
F	F	F

# The Exclusive Or

The last operator:

$p$	$q$	$p \oplus q$
T	T	F
T	F	T
F	T	T
F	F	F

## Remarks:

■ Read:

► “either  $p$  or  $q$ ” (“enten  $p$  eller  $q$ ”)

# The Exclusive Or

The last operator:

$p$	$q$	$p \oplus q$
T	T	F
T	F	T
F	T	T
F	F	F

## Remarks:

■ Read:

- ▶ “either  $p$  or  $q$ ” (“enten  $p$  eller  $q$ ”)
- ▶ “ $p$  xor  $q$ ”

# The Exclusive Or

The last operator:

$p$	$q$	$p \oplus q$
T	T	F
T	F	T
F	T	T
F	F	F

## Remarks:

- Read:

- ▶ “either  $p$  or  $q$ ” (“enten  $p$  eller  $q$ ”)
- ▶ “ $p$  xor  $q$ ”

- In words: for  $p \oplus q$  to be T,  $p$  and  $q$  must have different truth values.

# The Exclusive Or

The last operator:

$p$	$q$	$p \oplus q$
T	T	F
T	F	T
F	T	T
F	F	F

## Remarks:

- Read:

- ▶ “either  $p$  or  $q$ ” (“enten  $p$  eller  $q$ ”)
- ▶ “ $p$  xor  $q$ ”

- In words: for  $p \oplus q$  to be T,  $p$  and  $q$  must have different truth values.

- **Caution:** The book uses

- ▶ “either  $p$  or  $q$ ” to say  $p \vee q$  and
- ▶ “either  $p$  or  $q$  but not both” to say  $p \oplus q$ .

# A Quiz

Go to `pollev.com/kevs`



# The Precedence Hierarchy of Logical Operators

**Precedence order** (“order of evaluation”) **of operators:**

■  $\neg, \wedge, \vee, \Rightarrow, \Leftrightarrow$

# The Precedence Hierarchy of Logical Operators

**Precedence order** (“order of evaluation”) **of operators:**

- $\neg, \wedge, \vee, \Rightarrow, \Leftrightarrow$
- There is no consensus on the position of  $\oplus$ .



# The Precedence Hierarchy of Logical Operators

## **Precedence order (“order of evaluation”) of operators:**

- $\neg, \wedge, \vee, \Rightarrow, \Leftrightarrow$
- There is no consensus on the position of  $\oplus$ .

## **Note:**

- I (and I believe I speak for a larger group of Mathematicians) would not assume that the reader knows the precedence order among  $\wedge$  and  $\vee$ ; neither among  $\Rightarrow$  and  $\Leftrightarrow$ . In these cases, I am putting parentheses.

# The Precedence Hierarchy of Logical Operators

## **Precedence order (“order of evaluation”) of operators:**

- $\neg, \wedge, \vee, \Rightarrow, \Leftrightarrow$
- There is no consensus on the position of  $\oplus$ .

## **Note:**

- I (and I believe I speak for a larger group of Mathematicians) would not assume that the reader knows the precedence order among  $\wedge$  and  $\vee$ ; neither among  $\Rightarrow$  and  $\Leftrightarrow$ . In these cases, I am putting parentheses.
- Similarly, if you are not sure about the precedence, just put parentheses.