

Nexora Cloud Customer Support

Enterprise Knowledge Base & Standard Operating Procedures

SECTION 1: IDENTITY & ACCESS MANAGEMENT (IAM)

KB-1001: Comprehensive Account Authentication & Access Control Guide

1. Overview

This document establishes the definitive enterprise standard for user authentication, access control pathways, and session management on the Nexora Cloud platform. To maintain a zero-trust architecture, all inbound authentication requests must pass a multi-layered verification perimeter, matching valid cryptographic credentials against active, non-restricted tenant records in the Nexora Directory Service (NDS).

2. System Prerequisites & State Validation

Before an authentication lifecycle can be initiated, the system must programmatically validate that the requesting entity meets the following state requirements:

- **Active Directory Record:** The account must exist within the primary NDS database and cannot be marked with a `DELETED`, `ARCHIVED`, or `DEPROVISIONED` flag.
- **Cryptographic Email Verification:** The primary communication endpoint (email address) must possess a verified status (`is_verified=true`) stemming from a successful handshake protocol (see KB-1006).
- **Active & Valid Subscription Ledger:** The tenant associated with the user account must hold an active, non-delinquent ledger balance or a valid enterprise subscription tier (`subscription_status` IN ('ACTIVE', 'TRIAL', 'GRACE_PERIOD')). Accounts flagged with `SUSPENDED_BILLING` are restricted from standard user-space access.
- **Endpoint Security Compliance:** The requesting browser or API client must support TLS 1.3 encryption protocols and successfully pass the automated Web Application Firewall (WAF) risk-scoring mechanism.

3. Step-by-Step Interactive Login Procedure

```
[ User Input ] ---> [ WAF / IP Threat Check ] ---> [ Credential Matching ]
                                                    |
                                                    (If MFA Enabled)
                                                    |
[ Session Established ] <--- [ Token Issuance ] <--- [ MFA Challenge ]
```

1. **Ingress Navigation:** The user navigates to the official, secure ingress point at `https://console.nexoracloud.com/login`. Agents must instruct users to verify the browser address bar for the valid EV-SSL certificate to mitigate phishing vectors.
2. **Identity Assertion Entry:** The user enters their fully qualified primary email address and associated cryptographic password string into the designated inputs.
3. **Submission & Security Interception:** The user selects the **Sign In** button. This action triggers an asynchronous POST request, transmitting the payload over an encrypted TLS channel to the `/api/v2/auth/`

identity-assert endpoint. The platform's WAF evaluates the request against known botnets, credential-stuffing signatures, and anomalous IP reputations.

4. **Multi-Factor Authentication (MFA) Interception:** If the NDS returns an MFA_REQUIRED status code, the UI transitions to the secondary verification screen. The user must input the time-based or push-based token generated by their registered authenticator device.

5. **Token Issuance & Session Hydration:** Upon successful verification of all layers, the authentication server issues a cryptographically signed JSON Web Token (JWT) alongside a secure, HttpOnly, SameSite=Strict cookie. The client application is hydrated with user profile metadata, and access to the cloud dashboard is granted.

4. Diagnostic Troubleshooting & Remediation Workflows

ERROR SYMPTOM / MESSAGE	ROOT CAUSE ANALYSIS	REMEDIATION PROTOCOL
Error 401: Invalid Credentials	Mismatch between the submitted identity string/password and the hashed record in NDS.	• Step 1: Verify Caps Lock state. • Step 2: Clear localized browser cache/cookies. • Step 3: Utilize password reset pipeline (KB-1002).
Error 423: Account Temporarily Locked	Triggering of the brute-force mitigation threshold (5 consecutive failed attempts).	• Step 1: Enforce a strict 15-minute cool-down window. • Step 2: Advise customer against testing passwords during lock. • Step 3: Tier 1 agents may bypass via Admin Console if identity is out-of-band verified.
Error 403: MFA Token Mismatch	Desynchronization between the host server time and the client-side authenticator device clock.	• Step 1: Navigate to device settings. • Step 2: Enable Network Time Protocol (NTP) synchronization. • Step 3: Issue a manual time sync within the Google Authenticator/Duo app.

5. Enterprise Escalation Matrix

Agents must immediately escalate the ticket to the **Tier 2 Security Operations Center (SOC)** via the internal route SEC-IAM-ESCALATE under the following conditions:

- The user claims total credential correctness, but repeated account lockouts occur without user interaction (indicative of a sustained, targeted brute-force or credential-stuffing attack).
- The account displays an UNAUTHORIZED_GEOGRAPHY flag, indicating the user is attempting access from a restricted or high-risk territory not aligned with their enterprise profile.
- The user suspects active account compromise (e.g., unauthorized configuration modifications, unfamiliar API keys generated, or unexpected resource allocation alerts).

KB-1002: Enterprise Self-Service & Manual Password Reset Protocols

1. Overview

This standard operating procedure dictates the secure lifecycle of password remediation. Password management serves as a primary vector for social engineering; therefore, strict adherence to automated pathways and validation requirements is mandatory.

2. Standard Operational Procedure

```
[ Click Forgot Password ] ---> [ Send Tokenized Link ] ---> [ Validate 30-Min Window ] ---> [ Apply Complexity Filter ]
```

- 1. Initiation:** On the primary login portal, the end-user clicks the **Forgot Password** link, diverting the client routing to `https://console.nexoracloud.com/recovery/password`.
- 2. Identity Declaration:** The user enters their registered primary email address and fulfills a cryptographic CAPTCHA challenge designed to deter automated denial-of-service (DoS) attempts on the mail delivery queues.
- 3. Tokenized Transmission:** The backend verifies existence of the email. If found, an automated transaction is pushed to the mail subsystem, delivering a unique, high-entropy, one-time tokenized URI string to the customer:
`https://console.nexoracloud.com/recovery/reset?token=nx_tok_[alpha_numeric_string]`.
Security Note: To prevent username enumeration attacks, the system frontend will display a generic success message ("If the account exists, a recovery link has been sent") regardless of whether the email is present in the database.
- 4. Credential Modification:** Upon clicking the URI, the client verifies token validity. The user is presented with a secure input form to construct and confirm their new cryptographic password string.
- 5. Invalidation & Re-Authentication:** Upon submission, the token is permanently invalidated, all active web sessions across all devices are forcefully terminated (`revocation_scope=ALL`), and the user is redirected to the standard login pipeline.

3. Cryptographic Complexity Requirements

The Nexora Cloud Identity Service enforces strict complexity filters at the schema validation layer. Passwords failing any of the following criteria will be rejected with a `422 Unprocessable Entity` response:

- **Absolute Length:** Must contain a minimum of **12 characters**, up to a maximum of **128 characters**.
- **Character Diversity:** Must include at least **one uppercase letter** (A-Z), **one lowercase letter** (a-z), **one numerical digit** (0-9), and **one special symbol/character** (e.g., !, @, #, \$, %, ^, *, &, ±).
- **Entropy & Dictionary Filtering:** Passwords cannot contain predictable sequences (e.g., `123456`, `qwerty`), cannot match known leaked credentials in the HaveIBeenPwned database, and cannot contain the user's own username, first name, last name, or the string `Nexora`.

4. Lifecycle & Security Hardening

- **Temporal Decay:** All generated reset links possess an absolute expiration lifetime of **30 minutes** from the exact timestamp of generation. Once expired, the token string is purged from the active memory cache, and any utilization attempt will yield a `TOKEN_EXPIRED` exception.

- **Single-Use Constraint:** A token is valid for exactly one state change. Once consumed, it cannot be reused under any circumstances.
 - **Rate Limiting:** A maximum of **3 password reset requests per rolling 1-hour window** is permitted per email address or IP address to prevent email-bombing vectors.
-

KB-1003: Multi-Factor Authentication (MFA) Initialization & Enrollment

1. Overview

Multi-Factor Authentication (MFA) is a non-optional enforcement posture for administrative accounts and a highly encouraged security posture for standard users. This document details the procedures for binding an account to a secondary cryptographic Time-Based One-Time Password (TOTP) generator application.

2. End-to-End Setup Procedure

1. **Authentication and Navigation:** The authenticated user navigates to their profile infrastructure, specifically selecting the **Security Settings** tab located at `https://console.nexoracloud.com/account/security`.
2. **Activation Trigger:** The user scrolls to the Multi-Factor Authentication pane and clicks **Enable MFA**. The system will prompt the user to re-enter their current password to verify active ownership of the session.
3. **Cryptographic Seed Generation:** The Nexora security engine generates a random 256-bit seed key unique to that user. This seed is represented visually as a **QR Code** using standard alphanumeric translation, alongside a plain text string wrapper for manual entry.
4. **Device Syncing:** The user opens a validated authenticator application (e.g., Google Authenticator, Microsoft Authenticator, Duo Mobile, or 1Password) on their mobile device or hardware security key and scans the displayed QR code. This securely transmits the shared secret seed to the device.
5. **Handshake Verification:** To ensure the pairing was successful and that the device's clock is properly synchronized, the user must read the shifting 6-digit numeric token generated by their app, enter it into the Nexora confirmation field, and click **Verify and Save**.
6. **Confirmation and State Mutation:** The backend checks the token against its own calculations using the standard TOTP algorithm. If it matches, the account status changes to `mfa_enabled=true`, and a payload of **10 alphanumeric Emergency Recovery Backup Codes** is displayed.

3. Operational Best Practices

- **Backup Code Safeguarding:** Agents must instruct users to download or physically print the provided recovery codes. These codes must be stored in an offline, physically secure container, or within an encrypted enterprise password vault. They must never be saved in plain text files on local hard drives.
 - **Isolation of Factors:** Authenticator applications should ideally reside on an independent physical device (e.g., a separate mobile smartphone or dedicated hardware token) rather than the same machine used to access the Nexora Cloud environment.
-

KB-1004: Multi-Factor Authentication (MFA) Emergency Recovery & De-Enrollment

1. Overview

When a user loses access to their primary multi-factor authentication mechanism (due to hardware failure, device loss, or data corruption), they enter an unauthenticated state. This document governs the verification processes required to restore access while preventing unauthorized account takeover via social engineering.

2. Self-Service Recovery Process

1. **Initiation:** On the secondary MFA prompt during the login flow, the user selects the link titled **Use Backup Recovery Code**.
2. **Token Submission:** The user enters one of the 10 unique, high-entropy 8-character backup codes generated during their initial MFA setup.
3. **Validation & Invalidation:** The Nexora authentication engine checks the database array of unused recovery codes for that specific account. If a match occurs, the login is permitted, and that specific backup code is permanently flagged as `CONSUMED` and cannot be re-used.
4. **Immediate Remediation:** Once logged in via a backup code, the user must immediately navigate to their security panel, disable the lost MFA device, and re-enroll their new device using the protocol outlined in KB-1003.

3. Administrative Manual De-Enrollment Workflow

If the user has lost both their MFA device *and* their backup recovery codes, manual intervention is required. This process is strictly managed due to high security risks.

```
[ Inbound Support Request ] ---> [ Tier 1 Gathers Info ] ---> [ Route to SEC-IAM-RECOVERY ] ---> [ Out-of-Band ID Verification ] ---> [ Manual Flag Reset via Admin Console ]
```

1. **Inbound Sorting:** The customer contacts Nexora support via an unauthenticated channel (e.g., guest chat or direct corporate email). Tier 1 agents must **never** disable MFA under any circumstance.
2. **Ticket Routing:** The agent creates a ticket and immediately routes it to the specialized security group `SEC-IAM-RECOVERY` with a priority status of **P2**.
3. **Out-of-Band Identity Verification:** A dedicated Security Engineer will execute an out-of-band identity validation protocol. This includes:
 - Verifying corporate email control via specialized challenge tokens.
 - Confirming historical billing attributes (e.g., last 4 digits of the card on file, exact amount of the last invoice transaction, or corporate tax ID validation).
 - Requiring a live video verification or an authorized confirmation from the designated corporate Account Owner or security liaison.
4. **Manual Database Modification:** Once identity is proven beyond reasonable doubt, the security engineer utilizes the secure administrative console to clear the MFA configuration flag (`mfa_enabled=false`). An automated notification is sent to all registered email addresses and phone numbers associated with the account, alerting them to the security configuration change.

KB-1005: Automated Account Lockout & Security Mitigation Policies

1. Overview

To defend the platform against distributed brute-force attacks, credential stuffing, and automated dictionary guessing vectors, Nexora Cloud employs an aggressive automated account lockout mechanism.

2. Triggering Parameters

The system tracks failed authentication attempts globally and granularly using an sliding time-window cache. The specific parameters required to trigger an automated lockout include:

- **Threshold:** Exactly **5 consecutive failed login attempts** targeting a single account identifier within a rolling **15-minute window**.
- **Scope of Lockout:** The lockout applies to the unique account email across all IP addresses, alongside a localized IP block if the source address is generating high failure rates across multiple user accounts simultaneously.

3. Resolution Pathways

When an account hits the lockout threshold, its state transitions to `LOCKED` and all subsequent authentication requests are dropped with an immediate `423 Locked` error code. Resolution can be achieved via two distinct methodologies:

- **Temporal Cool-Down (Passive Resolution):** The customer must cease all authentication attempts for a continuous duration of **15 minutes**. At the expiration of this window, the account state automatically resets to `ACTIVE``, granting the user another set of authentication attempts.

Warning: Any authentication attempt made *during* the 15-minute lock period will fail automatically and reset the internal 15-minute timer back to zero.

- **Password Reset (Active Bypass):** If the user cannot wait or suspects their password was forgotten, executing a successful password reset workflow via KB-1002 will clear the failed attempts counter and immediately unlock the account state.
- **Customer Support Override:** If the issue persists due to automated scripts running in the user's environment (e.g., misconfigured API tools or continuous integrations), the customer must submit a support request. Tier 1 agents can manually flush the failed attempts cache via the Admin Interface under `User Management -> Actions -> Flush Login Attempts Cache`.

KB-1006: Asynchronous Email Verification Protocols

1. Overview

Email verification is a foundation of tenant security, ensuring that identity communications are routed to authentic endpoints controlled by the actual account registrant. This document explains the lifecycle of verification sequences.

2. Detailed Technical Procedure

1. **Account Event Trigger:** Upon new user registration, or when an existing user updates their primary email address within the profile manager, the platform halts the account setup flow and puts the user state into `PENDING_VERIFICATION`.
2. **Token Generation & Queuing:** The platform engine compiles a cryptographic payload containing the user ID, timestamp, and a random cryptographic salt. It signs this payload using SHA-256 to form a secure token. This token is queued within the notification delivery subsystem.
3. **The Communication Handshake:** The user receives a message titled "Action Required: Verify Your Nexora Cloud Account". Within this message is an embedded hyperlink pointing directly to the validation engine: `https://console.nexoracloud.com/verify-email?id=usr_...&token=vx_...`.
4. **Link Interaction:** The customer clicks the embedded link. The incoming request is processed by the verification router, which decrypts the token, confirms its signature against the database, and ensures the target account matches.
5. **State Mutation & Redirection:** If the token passes validation, the database mutates the account record to `is_verified=true` and unlocks all restricted cloud provisioning dashboards. The user is redirected to a success screen and prompted to sign in.

3. Common Failure Anomalies & Resolution Steps

- **Spam Filter and Mail Gateway Interception:** Corporate spam firewalls (e.g., Mimecast, Proofpoint) may intercept, flag, or quarantine the automated transaction emails.
Remediation: Advise the customer to check all Junk, Spam, and Promotional folders. For enterprise clients, provide the Nexora outbound IP whitelist blocks so their IT administrators can permit the delivery traffic.
- **Token Expiration / Temporal Decay:** Verification links possess a hard-coded lifetime of **24 hours**. If clicked after this timeframe, the page will render a `LINK_EXPIRED` warning.
Remediation: The user must navigate to the login console, input their credentials, and click the **Resend Verification Email** button to trigger a fresh token lifecycle.


SECTION 2: USER PROFILE & SUBSCRIPTION MANAGEMENT

KB-1007: User Profile Management & Identity Mutation Policies

1. Overview

The Profile Management framework allows users to update their personal identity records, linguistic preferences, and environmental contexts. Because updating identity attributes can be used in account takeover vectors, certain data changes require step-up authentication.

2. Permitted User Modification Fields



Users can adjust the following attributes within their account profile view at <https://console.nexoracloud.com/account/profile> :

- **Legal Name Strings:** Modification of First Name and Last Name fields (limited to alphanumeric characters and standard punctuation symbols; scripts or HTML injection attempts are scrubbed by input sanitization filters).
- **Contact Number Validation:** Updating mobile or office phone records.
- **Temporal Context (Timezone Selector):** Altering the user's operational timezone (e.g., UTC, EST, CET). This setting dictates the temporal presentation of monitoring graphs, log entries, and billing cycles throughout the console interface.
- **Linguistic Localization:** Setting preferred interface display languages (e.g., English, Spanish, German, Japanese).

3. Security Re-Authentication Perimeter

To prevent session-hijacking actors from changing profile fields to establish long-term access, modifying sensitive elements (such as telephone records used for SMS fallbacks or changing primary account emails) triggers a **Step-Up Authentication Challenge**.

Before the change payload is committed to the database, the UI displays a modal window requiring the user to re-enter their current password and their active MFA token. If this step-up check fails, the transaction is dropped, a security alert is logged in the user's audit trail, and the profile remains unchanged.

KB-1008: Notification Engine & Alert Subscription Architecture

1. Overview

The Nexora Cloud Notification Engine handles all outbound customer messaging. Users can fine-tune their messaging preferences to receive actionable alerts without cluttering their inbox.

2. Notification Classifications

NOTIFICATION CATEGORY	SYSTEM FUNCTIONALITY & CONTENT	DEFAULT INGRESS CHANNEL	USER DISABLING PERMITTED?
Billing Alerts	Invoices, failed payment retries, credit card expiration warnings, quota thresholds.	Email / In-Platform	No (Mandatory Contractual Alerting)
Security Alerts	Password changes, MFA de-enrollments, new IP address logins, API key creations.	Email / SMS / In-Platform	No (Mandatory Platform Hardening)
Product Updates	Feature releases, deprecation schedules, API version shifts, newsletters.	Email / Optional Webhook	Yes
Incident Notifications	Infrastructure service outages, region down times, scheduled maintenance windows.	Email / Webhook / PagerDuty	Yes (Configurable per cloud region)

3. Subscription Management Procedure

To customize alert delivery vectors, the user navigates to `Settings -> Notifications`. From this dashboard, agents can guide users to toggle switches for individual channels (Email, SMS, Webhook integrations). For infrastructure health status alerts, users can filter down to specific regions (e.g., `us-east-1`, `eu-central-1`) to avoid receiving updates for regions where they do not host active workloads.

SECTION 3: SUPPORT OPERATIONS & INCIDENT MANAGEMENT

KB-1009: Standardized Support Ticket Creation Protocols

1. Overview

Support tickets are the primary communication link between our customers and Nexora's engineering staff. To ensure fast resolution times and eliminate back-and-forth troubleshooting cycles, tickets must contain a structured set of diagnostic information upon creation.

2. Information Requirements Matrix

When gathering details from a customer via chat, email, or telephone to create a support ticket, agents must ensure the following fields are accurately filled out within the internal ticketing system:

- **Unique Account/Tenant ID:** The global identifier string for the affected cloud account (format: ACC-XXXX-XXXX).
- **Granular Resource Identifiers:** The exact IDs of the compromised or malfunctioning infrastructure components (e.g., Virtual Machine IDs: vm-83921 , Database Clusters: db-cluster-prod-01).
- **Comprehensive Issue Description:** A clear explanation detailing what occurred, what was expected to occur, and the exact steps required to reliably reproduce the error state.
- **Diagnostic Evidence Capture:** High-resolution screenshots of error dialogues, raw text outputs of terminal execution blocks, and relevant stack traces or log files.
- **Systemic Impact Classification:** A clear assessment of how the issue affects the customer's operational status (e.g., single-user inconvenience vs. total production outage).

3. Automated Routing System

Once submitted, the ticket is parsed by Nexora’s automated routing engine. The system analyzes the text using natural language processing to look for key terms (e.g., "Kubernetes ingress", "Billing charge", "Slow database query") and matches them against account priority tiers. The ticket is then routed directly to the appropriate specialized engineering group (e.g., ENG-NETWORKING , FIN-BILLING , ENG-COMPUTE), minimizing internal transfer times.


KB-1010: Support Ticket Escalation Standard Operating Procedure

1. Overview

Ticket escalation moves a customer issue to a more experienced technical team or a higher management layer. Escalations must follow strict criteria to ensure our specialized senior engineers can prioritize high-impact issues.

2. Quantitative Escalation Criteria

A ticket must be escalated immediately if it satisfies any of the following operational conditions:



Support

- **SLA Breaching Risk:** The ticket's age approaches within 15 minutes of its maximum allowable initial response or resolution time target as outlined in the SLA policy (KB-1012).
- **Technical Limit Reached:** A Tier 1 or Tier 2 agent has executed all troubleshooting steps outlined in the documentation, but the system continues to return anomalous behavior that suggests a backend bug or platform infrastructure defect.
- **Elevated Security Vector:** The customer identifies a security vulnerability, reports an active data leak, or exposes a flaw that could compromise multi-tenant isolation barriers. This requires immediate escalation to the Tier 3 Security Operations Center.
- **Severe Business Impact Escalation:** A customer's production workload is offline, halting their business operations, and the initial troubleshooting steps have not resolved the issue within 30 minutes.

3. Mandatory Pre-Escalation Documentation

Before an agent changes the ownership assignment or escalates a ticket, they must fill out the internal escalation template within the ticket's internal notes. Tickets escalated without this completed summary will be rejected by senior engineering teams:

```
=====
MANDATORY ESCALATION SUMMARY
=====
1. VERIFIED TENANT ID: [e.g., ACC-9921-0021]
2. ISOLATED COMPONENT: [e.g., Core Storage / Block Storage Volume vol-021]
3. TROUBLESHOOTING ACTIONS EXECUTED: [Detail every KB article followed,
    commands run, and results observed]
4. CURRENT SYSTEM STATE/ERROR OBSERVATION: [Insert raw logs/API responses]
5. REASON FOR ESCALATION: [e.g., Tier 1 lacks database write access to modify customer
    metadata]
=====
```

KB-1011: Ticket Priority Classification Framework

1. Overview

To ensure resources are allocated efficiently across our global support organization, incoming issues are sorted into four distinct priority levels based on business impact and urgency.

2. Matrix Definition of Priority Levels

[BUSINESS IMPACT MATRIX]

High / Total

Partial / Degraded

Urgent	P1: CRITICAL	P2: HIGH
Urgency		
Standard	P3: MEDIUM	P4: LOW

- **P1 - Critical Business Impact:**
Operational State: Core systems are completely down; the cloud management console is unreachable globally; a primary region experiences an outage; production databases are corrupted or offline. No workaround is available.
- **P2 - High Operational Impact:**
Operational State: Customer production workloads are running but experience severe performance degradation or high latency; secondary system tools (e.g., logging exports or automated backup schedules) are failing; a significant business group cannot access key features. A manual workaround is temporary or complex.
- **P3 - Medium Operational Impact:**
Operational State: Non-production environments (such as staging, development, or testing environments) are impaired; a system feature is malfunctioning but has an available workaround; minor bugs occur in GUI elements.
- **P4 - Low Informational/Operational Impact:**
Operational State: General architectural inquiries; documentation typos; enhancement requests; billing invoice inquiries that do not threaten service continuity.



KB-1012: Service Level Agreement (SLA) & Contractual Commitments

1. Overview

The Service Level Agreement (SLA) defines Nexora Cloud's legal and operational commitments to its customers regarding support responsiveness. Adherence to these response windows is audited monthly by leadership teams.

2. Target Response Timelines per Priority Tier

The response SLA measures the elapsed time between a user submitting a ticket and a qualified Nexora support representative posting a meaningful, non-automated initial assessment response.

P1 (Critical)	: 15 Minutes	[=====]
P2 (High)	: 1 Hour	[=====]
P3 (Medium)	: 4 Hours	[=====]

P4 (Low) : 24 Hours

[=====>]

- **Priority 1 (Critical):** Initial Response Window is **15 minutes** absolute. Status updates must be provided every 15 minutes until resolution or stabilization. Operating availability: 24/7/365.
- **Priority 2 (High):** Initial Response Window is **1 hour** absolute. Status updates must be provided every 2 hours. Operating availability: 24/7/365.
- **Priority 3 (Medium):** Initial Response Window is **4 business hours**. Status updates must be provided every 24 hours. Operating availability: Standard Regional Business Hours.
- **Priority 4 (Low):** Initial Response Window is **24 business hours**. Status updates provided on milestone achievements. Operating availability: Standard Regional Business Hours.

3. SLA Exclusions & Stop-Clock Criteria

Calculations determining SLA compliance exclude periods of time under the following specific operational contexts:

- **Planned Maintenance Windows:** Announced infrastructure down-times communicated at least 7 days prior to execution.
- **Customer Pend State:** The clock pauses whenever a ticket's status is changed to `PENDING_CUSTOMER_ACTION`. The clock resumes immediately once the customer updates the ticket string.
- **Force Majeure Events:** Global telecommunication network outages outside of Nexora's autonomous network systems.

SECTION 4: COMMUNICATIONS & CUSTOMER RELATIONSHIP MANAGEMENT

KB-1013: Professional Customer Communication Guidelines

1. Overview

Every written or verbal interaction by Nexora support staff influences our brand reputation. This document establishes communication standards designed to ensure clear, precise, and supportive customer interactions.

2. Core Communication Principles

- **Absolute Accuracy:** Never guess or provide speculative technical information. If the answer to a question is unknown, state that you are actively investigating the issue with internal engineering teams.
- **Concise Clarity:** Avoid overly dense blocks of text. Use bulleted lists, numbered step sequences, and code snippet blocks to present troubleshooting pathways clearly.

- **Eliminate Assumptions:** Do not assume the customer possesses advanced systems engineering knowledge unless their profile indicates an enterprise administrator status. Avoid using obscure internal jargon.
- **Proactive Cadence:** Provide updates to customers before they contact us to ask for status checks, especially during long-running root cause investigations.

3. Communication Log Documentation Requirements

All verbal or out-of-band communication (such as telephone support calls, screen-share diagnostics, or Slack connect spaces) must be documented in the ticket record within **15 minutes** of concluding the interaction. The record must include:

- A clear summary of the discussion topics.
- The troubleshooting steps mutually attempted.
- Any configuration changes authorized by the customer.
- Clearly defined next actions and who is responsible for them.

KB-1014: Formal Complaint Resolution Process

1. Overview

When a customer expresses frustration regarding service delivery, feature defects, or support response times, the issue transitions into a formal complaint workflow to ensure structured resolution and prevent customer churn.

2. Five-Step Resolution Methodology

1. **Immediate Acknowledgment:** Validate the customer's concerns promptly. Avoid defensive language and acknowledge the impact the issue has on their business operations.
2. **Comprehensive Context Gathering:** Review the customer's entire account history, including open tickets, past infrastructure issues, and communication logs, to understand the full scope of their frustration.
3. **Root-Cause Investigation:** Collaborate with internal system leads or account managers to identify the technical breakdown or communication bottleneck that caused the issue.
4. **Actionable Resolution Delivery:** Present the customer with a clear explanation of what occurred, the steps taken to resolve the issue, and the preventive measures implemented to prevent recurrence. Where applicable, coordinate with account management to apply appropriate SLA service credits.
5. **Formal Documentation and Close-Out:** Log the complaint within the internal quality assurance database (`QA-COMPLAINTS-DB`). Archive the resolutions to help optimize internal agent training programs.

KB-1015: Live Chat Operational Engagement Procedures

1. Overview

Live chat provides real-time assistance. It demands rapid assessment and concise technical guidance from support agents.

2. Key Performance Indicators & Performance Standards

- **Speed to Response (First Response Time):** Agents must accept and post an initial greeting within **30 seconds** of a chat request joining their assigned queue.
- **Identity Verification Perimeter:** Before discussing account-specific attributes, changing billing parameters, or providing details about active cloud resources, agents must verify the user's identity. This requires sending an in-app verification prompt or validating a security PIN code generated within the customer's authenticated console profile.
- **Interaction Summary Protocol:** Upon resolving the customer's immediate questions, the agent must write out a brief text summary detailing the actions taken during the chat session and paste it directly into the chat thread before closing the window.
- **Professional Off-Boarding:** Conclude the interaction with a standard corporate closing sequence, ensuring the customer has no further questions before ending the chat session.

KB-1016: Technical Case Handoff & Transition Standard Operating Procedure

1. Overview

When tickets move between international regional centers (such as during "follow-the-sun" shifts) or transition between Tier 1 and Tier 2 engineering teams, a formal handoff protocol is required to ensure continuity of care.

2. Structural Requirements for Case Transitions

The transitioning agent must compile a structured handoff note within the ticket interface, ensuring it includes the following detailed attributes:

- **Current Operational State:** A clear statement of the issue status at the moment of shift change.
- **Comprehensive Troubleshooting Summary:** A bulleted chronological log of all diagnostic commands executed, tests performed, and results collected so far.
- **Isolated Root Cause Vector:** A clear identification of components or code paths that have been ruled out, alongside the current suspected cause.
- **Explicit Next Steps:** Clear instructions detailing exactly what action needs to be taken next (e.g., "Review database synchronization logs at 14:00 UTC", "Await user confirmation regarding replica node connectivity").

3. Primary Goal

The primary objective of this handoff standard is to provide the incoming engineer with complete context, ensuring the customer never has to repeat information or perform previously completed troubleshooting steps.

SECTION 5: FREQUENTLY ASKED QUESTIONS (ENTERPRISE FAQ)

FAQ-2001: Comprehensive Troubleshooting: Why am I unable to access my Nexora Cloud Platform?

1. Root Cause Analysis Summary

Authentication failures generally stem from configuration issues across four distinct vectors: input credential mismatches, account security protections, multi-factor device desynchronization, or local browser anomalies.


2. Diagnostics and Actionable Resolutions

- **Input Password Accuracy Verification:** Ensure that your Caps Lock indicator is disabled. If you utilize an automated password manager vault, verify that the entry corresponds to the specific email address registered with Nexora Cloud.
- **Mitigating Account Lockout Restraints:** If you have repeatedly input incorrect passwords, the platform's security controls will apply a 15-minute lock on your account profile (see KB-1005). To resolve this quickly, avoid attempting logins for 15 minutes, or initiate a password reset sequence to bypass the lock.
- **Resolving Multi-Factor Authentication Failures:** If the system continually rejects your 6-digit TOTP token, the issue is typically caused by a time offset error on your mobile device. Access your phone's clock configuration settings, toggle the option to automatically adjust time settings via your network carrier, and restart your authenticator application.
- **Addressing Localized Browser Complications:** Cached browser data or conflicting security extensions can occasionally disrupt active token exchange flows. Attempt to open a private/incognito browsing window to bypass local storage issues, or clear your browser's application cache.

FAQ-2002: Understanding Account Suspension: Why is my account flagged as suspended?

1. Primary Reasons for System-Initiated Suspensions

Nexora Cloud restricts account access under three conditions to protect platform infrastructure integrity and enforce operational compliance:



- **Billing Delinquency:** Suspensions occur when a primary payment method fails repeatedly across several billing cycles, and the account passes its grace period without payment or communication with billing support.
- **Acceptable Use Policy (AUP) Violations:** Accounts will face suspension if monitoring tools detect activities that violate our terms of service. This includes utilizing compute infrastructure to run unauthorized cryptocurrency miners, hosting malicious content, or operating open Tor relays.
- **Security Incident Containment:** If a tenant account leaks its root API keys or a virtual machine instance is compromised, the platform may temporarily suspend the account. This action isolates the environment and stops outgoing malicious traffic or unauthorized resource use.

2. Resolution Steps

To resolve an account suspension, check the primary email inbox associated with your account for an official notification from `security@nexoracloud.com` or `billing@nexoracloud.com`. This message will detail the specific reason for suspension. You can then submit a support ticket via our guest portal to coordinate remediation with our compliance and financial teams.

FAQ-2003: Step-by-Step Guide: How do I upgrade my infrastructure subscription plan?

1. Detailed Upgrade Sequence Instructions

To upgrade your infrastructure plan and access higher compute tiers, larger storage allocations, and lower latency networking options, follow these instructions:

1. **Access the Billing Control Panel:** Navigate to the console interface, locate the left sidebar navigation menu, select the **Billing & Invoices** control tab, and click the **Plan Details** option.

- 2. **Initiate the Upgrade Flow:** Review your current resource consumption metrics and click the **Upgrade Plan Tier** button.
- 3. **Select the Target Infrastructure Tier:** Review the available options (e.g., Developer, Professional, Enterprise Core) and select the subscription level that matches your technical requirements.
- 4. **Confirm Payment Details:** Review the adjusted pricing summary, select your preferred payment method, and click **Confirm Subscription Modification**.

2. Core Billing Conditions

- **Immediate Resource Scaling:** Tier upgrades are processed in real-time. Higher resource quotas and performance tiers are available immediately upon completing the transaction.
- **Prorated Billing Calculations:** Plan pricing adjustments are calculated using a prorated billing model. Your next monthly billing statement will reflect a credit for the unused portion of your previous plan, combined with a charge for the remaining days of your new upgrade tier.

FAQ-2004: Customer Engagement Matrix: How can I contact Nexora Support?

1. Available Communication Channels

Nexora Cloud offers three primary support channels tailored to different contract tiers and technical needs:

CHANNEL	TARGET AUDIENCE	AVAILABILITY
Support Portal	All Account Tiers	24/7/365 (SLA varies by plan)
Live Chat Interface	Professional & Enterprise	Standard Regional Business Hours
Dedicated Email	Enterprise Core Only	24/7/365 Priority Ingress

2. Information to Include for Faster Resolution

To help our engineering staff diagnose and resolve your issues quickly, ensure your support requests contain the following core information:

- Your unique Customer Account Identifier (ACC-XXXX-XXXX).
- A clear, concise summary of the issues encountered, alongside relevant log outputs or stack traces.
- High-resolution screenshots illustrating the behavior or error screens in the console interface.

- A clear statement detailing the operational impact of the issue on your business continuity.