SUR 2025/2026 Project

Marek Hric (xhricma00) · Jakub Komanický (xkomanj00)

2026-05-04

1. Data and Augmentation

The supplied splits are session-disjoint for the target (train holds *m431* sessions 01–02, dev holds session 03) and speaker-disjoint for the impostors (13 speakers in train, 6 distinct speakers in dev), which pre-stresses generalisation to unseen identities and an unseen recording session of the target. The remainder of this report traces each per-modality system from the syllabus baseline to its production form by changing one design choice per step, so individual metric deltas are attributable to specific decisions.

Augmentation is performed once, offline (`scripts/augment_dataset.py`), producing `dataset/*_aug` directories that the trainer enumerates as ordinary samples. Audio augmentation applies time stretch (0.9–1.1×), gain (±6 dB), polarity flip ($p=0.5$), peaking equalisation (±3 dB at 200–4000 Hz) and additive white Gaussian noise (SNR 15–30 dB). Image augmentation applies horizontal flip ($p=0.5$), rotation (±10°), translation (±5 %), brightness and contrast scaling (0.85–1.15×) and per-pixel WGN ($\sigma\in[0,0.04]$). Vertical flip and hue rotation are excluded because faces are not vertically symmetric and skin tone is identity-relevant. The augmentation count is 15× per target sample and 5× per non-target — an explicit asymmetry, since the target class has only 30 base utterances total. Class imbalance is handled at the loss level via `class_weight='balanced'` [@pedregosa2011scikit], so the trained classifier intercept satisfies $P(\text{target}\mid x)=0.5$ at logit zero regardless of the empirical training ratio.

2. Image System

Image features are 9-bin Histograms of Oriented Gradients [@dalal2005hog] over 8×8-pixel cells with 2×2-cell L2-Hys normalised blocks on 80×80 grayscale crops, yielding 2916-d vectors. A balanced logistic regression with L2 regularisation ($C=0.1$) classifies them. Hard decisions threshold $\mathrm{decision_function}$ at zero. The progression from the syllabus baseline isolates three design changes:

Step	Description	AUC	EER
1	Baseline: pixels → PCA(D=21) → Gaussian LDA + 2 IRLS	0.943	20.00 %
2	HOG → PCA(D=21) → Gaussian LDA + 2 IRLS	0.977	9.17 %
3	HOG (full 2916-d) → balanced LogReg, $C=0.1$, no augmentation	0.903	21.67 %
4	+ offline augmentation (production)	1.000	0.00 %

Step 1→2 isolates the HOG vs. raw-pixel feature gain at fixed dimensionality. Step 2→3 is a *regression*: dropping PCA in favour of full-dimensional HOG with L2 leaves the threshold-zero hard rule mis-calibrated at only 10 target training images. Step 3→4 shows that augmentation is what makes the high-dimensional architecture viable — full-dimensional + L2 in isolation is worse than the PCA-bridged baseline classifier of step 2.

3. Audio System

Both audio systems share the same frontend: an energy + zero-crossing-rate voice activity detector (VAD), 13 mel-frequency cepstral coefficients [@davis1980mfcc] at 25 ms / 10 ms framing via `librosa` [@mcfee2015librosa] with per-utterance cepstral mean–variance normalisation, and probabilistic-YIN F$_0$ estimation [@mauch2014pyin] over voiced frames in 60–400 Hz. From the F$_0$ track and frame energies we compute five prosodic statistics ($\log F_0$ mean and standard deviation, jitter, shimmer, voicing ratio).

Path A — aggregated features and logistic regression. The 5 prosodic statistics and the 13 MFCC means form an 18-d utterance-level vector classified by balanced LogReg ($C=1.0$). This is shipped as `audio_logreg.txt`.

Path B — Gaussian Mixture Model with universal background, MAP-free. Following [@reynolds2000gmmubm] we fit a 16-mixture diagonal-covariance universal background model (UBM) on non-target frames and a 4-mixture diagonal-covariance target GMM on *m431* frames, *independently* by EM. We chose MAP-free over MAP adaptation

because ~32 k augmented target frames are plentiful at the per-component level ($\alpha_k\to 1$ regardless of relevance factor), and a relevance-factor sweep over $\tau\in{5, 10, 20, 100, 500, 2000, 10000}$ produced an AUC plateau of 0.98 with the threshold-zero hard rule miscalibrated (EER threshold drifted to $+0.25$). The per-utterance score is the frame-averaged log-likelihood ratio. We did not attempt i-vector front-end factor analysis [@dehak2011ivector] — the standard upgrade over GMM-UBM — because it requires hundreds of background speakers for the total-variability matrix to be estimable, whereas our pool has 19 distinct non-target speakers.

The VAD-empty pathology. Auditing eval revealed 79 of 1346 samples (5.9 %) producing identical audio score $ \approx +1.535$. These extract to all-zero feature vectors: under heavy gain attenuation or short voiced segments, the energy-relative VAD trims every frame, leaving prosodic and MFCC statistics at their zero-fallback. The trained classifier maps this zero input to a bias-driven default that happened to be positive, mislabelling all 79 as target. Spectral-flatness and voiced-fraction analysis confirmed all 79 are real speech, not white noise (median voiced fraction 0.60); the sentinel default was discarding genuine information. The same pathology contaminates training: 121 of 1112 augmented training utterances also extract to zero vectors, with the target class disproportionately affected (81 zero-frame target augmentations vs. 40 non-target), so the model also *learned* a small "zero $\Rightarrow$ target" correlation as a class-asymmetric augmentation artefact.

Hybrid VAD-on / VAD-off fallback. The fix is a routing scheme (`scripts/audio_gmm_hybrid.py`): an auxiliary 16+4 GMM-UBM is trained on the same MFCC frames *without* applying VAD; at scoring time the production VAD-on model is consulted first, and the no-VAD model takes over only when VAD has trimmed every frame. The hybrid is shipped as `audio_gmm_hybrid.txt` and short-circuits both the eval-time sentinel defaults and the train-time spurious correlation at scoring.

The audio progression covers both clean and stress development splits:

Step	Description	Clean AUC	Stress AUC
1	Baseline: course MFCC + 2 GMMs M=30 (no VAD, no CMVN)	0.978	0.799
2	+ frame-energy VAD + per-utt CMVN, same 2 GMMs M=30	1.000	0.730
3	Production GMM-UBM (MAP-free, sentinel for VAD-empty)	0.997	0.463
4	Hybrid VAD-on/off (production)	0.997	**0.870**

VAD and CMVN saturate clean dev (steps 1 → 2) but degrade the stress split because they introduce the failure mode that step 4 must repair. The hybrid recovers the baseline's stress robustness without sacrificing clean-dev performance.

4. Multimodal Fusion

Fusion is performed at the score level. For each per-modality system, dev-set scores are z-normalised; a balanced logistic regression is fitted on the concatenated z-scores and the ground-truth labels; the classifier is then applied to z-normalised eval scores. Score-level was preferred to feature-level because the audio (18-d) and image (2916-d) spaces are extremely imbalanced: stacking them with ~1100 training samples invites the curse of dimensionality, whereas a 2- or 3-feature fusion logreg has too few parameters to overfit the 70-sample dev split. We submit three variants: `fusion_logreg.txt` over $(z(\text{audio_logreg}), z(\text{image}))$; `fusion_hybrid_image.txt` over $ (z(\text{audio_gmm_hybrid}), z(\text{image}))$; and `fusion_3way.txt` over $(z(\text{audio_logreg}), z(\text{audio_gmm_hybrid}), z(\text{image}))$. The three-way variant tests whether the two audio paths capture complementary signal, since aggregated 18-d features and frame-level GMM likelihoods are structurally different objects.

5. Validation Strategy

The clean `*_dev` split (n=70) is the primary diagnostic. To probe generalisation under input degradation we built a *stress* dev: the same dev samples re-augmented with a *disjoint* envelope (gain -15 to -8 dB, SNR 3–13 dB, peaking EQ -7 to -4 dB at 4500–7500 Hz, time-stretch 0.78–0.88, image brightness 0.45–0.70, per-pixel noise $ \sigma\in[0,0.10]$), yielding 50 target / 120 non-target stress samples. Disjointness converts each stress sample from interpolation to extrapolation under the trained model.

We also ran a 2-fold leave-one-target-session-out session-grouped cross-validation (`scripts/cv_session_check.py`) on the training pool. Image AUC stays at 0.982 across folds; audio AUC drops to 0.789 — confirming image features are session-invariant and audio is session-sensitive, which motivates using *both* available target sessions (01 and 02) for production training.

The 50/50-prior decision rule is enforced in two places: every classifier sets `class_weight='balanced'` (equalising effective per-class loss mass during training, so the trained intercept satisfies $P(\text{target}\mid x)=0.5$ at logit zero); and every config sets `output.hard_threshold_logit = 0.0`, so the hard decision is $\mathrm{score}\geq 0$. This implements the symmetric-cost detection-cost operating point [@martin1997det].

6. Results

The submission ships one image system, two audio systems and three fusion variants — 6 result files in total.

Clean dev (n = 70: 10 target / 60 non-target):

System	AUC	EER	TP	FP	FN	TN
image_logreg	1.000	0.00 %	10	1	0	59
audio_logreg	0.983	3.33 %	7	0	3	60
audio_gmm_hybrid	0.997	1.67 %	9	0	1	60
fusion_logreg	1.000	0.00 %	10	0	0	60
fusion_hybrid_image	1.000	0.00 %	10	0	0	60
fusion_3way	1.000	0.00 %	10	0	0	60

Stress dev (n = 170: 50 target / 120 non-target):

System	AUC	EER	TP	FP	FN	TN
image_logreg	0.607	40.00 %	35	60	15	60
audio_logreg	0.521	47.08 %	50	113	0	7
audio_gmm_hybrid	0.870	24.08 %	47	69	3	51
fusion_logreg	0.625	39.17 %	50	111	0	9
fusion_hybrid_image	0.875	20.42 %	50	107	0	13
fusion_3way	0.860	21.83 %	35	15	15	105

On the unlabelled eval set (n = 1346), predicted-target counts under the threshold-zero rule are 127 (image_logreg), 153 (audio_logreg), 139 (audio_gmm_hybrid), 142 (fusion_logreg), 178 (fusion_hybrid_image) and 139 (fusion_3way). DET curves [@martin1997det] are saved at `artifacts/curves*.png`; we prefer DET over ROC because its log-deviate axes spread the high-performance region that AUC saturation collapses into the corner of the ROC.

All three fusion variants saturate clean dev. Stress dev separates them clearly: `fusion_hybrid_image` maximises AUC (0.875); `fusion_3way` is the only system whose stress confusion matrix is balanced (precision 0.70 versus 0.31 for the alternatives), trading a small AUC decrement for substantial precision gain. Under an operating point that penalises false positives more strongly than the assignment's symmetric costs, `fusion_3way` would be the strongest single submission.

7. Discussion

The most surprising finding is the *clean–stress inversion* in the audio progression: the simple syllabus baseline (no VAD, no CMVN) handles the stress split substantially better than the production preprocessed pipeline does. The mechanism is that the production VAD trims every frame on heavily attenuated audio (161 of 170 stress samples and 79 of 1346 eval samples produce all-zero feature vectors); without VAD, the attenuated signal is still scored on its remaining content. The hybrid fallback recovers the baseline's stress robustness on the GMM-UBM path while preserving clean-dev saturation. We did not attempt to remove or retune the VAD on the LogReg path because disabling it costs ~35 AUC points on clean dev, and a routing fix restricted to the small known-degenerate slice is a smaller

intervention than a full pipeline retune. A from-scratch convolutional network was ruled out for reasons analogous to i-vectors: a small CNN (~50 k parameters) needs an order of magnitude more target examples than the 320 augmented samples we have.

8. Reproduction

```
uv run scripts/augment_dataset.py --config configs/augment_audio.toml
uv run scripts/augment_dataset.py --config configs/augment_image.toml
uv run scripts/train.py    --config configs/audio_baseline.toml
uv run scripts/train.py    --config configs/image_baseline.toml
uv run scripts/train.py    --config configs/fusion_baseline.toml
uv run scripts/evaluate.py --config configs/audio_baseline.toml  --split eval
uv run scripts/evaluate.py --config configs/image_baseline.toml  --split eval
uv run scripts/evaluate.py --config configs/fusion_baseline.toml --split eval
uv run scripts/audio_gmm_pipeline.py --mode map_free
uv run scripts/audio_gmm_hybrid.py
uv run scripts/fix_vad_empty.py
uv run scripts/fusion_hybrid_image.py
uv run scripts/fusion_3way.py
```

All randomness is seeded; reproduction is deterministic from a fixed seed.

References


```
@article{davis1980mfcc,
  author={Davis, S. and Mermelstein, P.},
  title={Comparison of Parametric Representations for Monosyllabic Word Recognition in Continuously Spoke
  journal={IEEE Transactions on Acoustics, Speech and Signal Processing},
  volume={28}, number={4}, pages={357--366}, year={1980},
  doi={10.1109/TASSP.1980.1163420}
}
@inproceedings{martin1997det,
  author={Martin, A. and Doddington, G. and Kamm, T. and Ordowski, M. and Przybocki, M.},
  title={The {DET} Curve in Assessment of Detection Task Performance},
  booktitle={Proc. 5th European Conference on Speech Communication and Technology},
  pages={1895--1898}, year={1997},
  doi={10.21437/Eurospeech.1997-504}
}
@article{reynolds2000gmmubm,
  author={Reynolds, D. A. and Quatieri, T. F. and Dunn, R. B.},
  title={Speaker Verification Using Adapted {G}aussian Mixture Models},
  journal={Digital Signal Processing},
  volume={10}, number={1--3}, pages={19--41}, year={2000},
  doi={10.1006/dspr.1999.0361}
}
@inproceedings{dalal2005hog,
  author={Dalal, N. and Triggs, B.},
  title={Histograms of Oriented Gradients for Human Detection},
  booktitle={Proc. IEEE Conf.\ Computer Vision and Pattern Recognition (CVPR)},
  pages={886--893}, year={2005},
  doi={10.1109/CVPR.2005.177}
}
@article{pedregosa2011scikit,
  author={Pedregosa, F. and others},
  title={Scikit-learn: Machine Learning in {P}ython},
  journal={Journal of Machine Learning Research},
  volume={12}, pages={2825--2830}, year={2011}
}
@article{dehak2011ivector,
  author={Dehak, N. and Kenny, P. J. and Dehak, R. and Dumouchel, P. and Ouellet, P.},
  title={Front-End Factor Analysis for Speaker Verification},
  journal={IEEE Transactions on Audio, Speech, and Language Processing},
```

```
  volume={19}, number={4}, pages={788--798}, year={2011},
  doi={10.1109/TASL.2010.2064307}
}
@inproceedings{mauch2014pyin,
  author={Mauch, M. and Dixon, S.},
  title={{pYIN}: A Fundamental Frequency Estimator Using Probabilistic Threshold Distributions},
  booktitle={Proc. IEEE Int.\ Conf.\ Acoustics, Speech and Signal Processing (ICASSP)},
  pages={659--663}, year={2014},
  doi={10.1109/ICASSP.2014.6853678}
}
@inproceedings{mcfee2015librosa,
  author={McFee, B. and Raffel, C. and Liang, D. and Ellis, D. P. W. and McVicar, M. and Battenberg, E. a
  title={{librosa}: Audio and Music Signal Analysis in {Python}},
  booktitle={Proc. 14th Python in Science Conference (SciPy)},
  pages={18--24}, year={2015},
  doi={10.25080/Majora-7b98e3ed-003}
}
```