

## HANDLING FILE INPUT / OUTPUT OPERATIONS IN C

The C/C++ programming language does not have any built-in instructions to perform the Input / Output operations. They are provided by library functions.

### Standard „formatted” input/output file library    **< stdio.h >**

I / O operations performed by **streams**

Streams are represented by specific “file variables” of the type **FILE**. Such a variable/structure is created automatically when you open the stream (it contains information about the file name, opening mode, etc.). All further operations on the stream, require a pointer to this structure.

Standard streams for input and output (opened automatically)

**stdin**    – standard input stream (console - keyboard)  
**stdout**    – standard output stream (console - monitor)  
**stderr**    – standard error messages stream (console)  
**stdprn**    – standard printer stream

User defined streams:

```
FILE *file, *result_data_file ;           // definition of „file variables”
```

1. Accessing functions:    **fopen** (returns a pointer to FILE) and **fclose**

```
FILE * fopen( char *file_name, char *open_mode )
```

The type of open\_mode is defined by characters:

<b>r</b>	–	open for reading (read only)
<b>w</b>	–	open for writing (create new file)
<b>a</b>	–	open for appending at the end
<b>+</b>	–	with the possibility to update (overwrite)
<b>b</b>	–	open as <b>binary</b> stream
<b>t</b>	–	open as <b>text</b> stream

```
int fclose( FILE *stream )           // function that closes the pointed file stream
```

```
FILE *file;           // Example creation of a new binary file, with the ability to update
file = fopen( "a:\\results.dat", "w+b" );
if( file == NULL )           // controlling the I/O errors
{
    printf( "Error while opening output file" );
    return -1;
}
...
fclose( file );           // closing (releasing) the FILE, before exiting the program
```

## 2. List of functions for WRITING the data to file stream

Writing data to a TEXT file (data encoded in ASCII codes, spaces, NL, ...)

```
int fputc ( int character, FILE *stream )           // writing a single character  
int fprintf ( FILE *stream, char *format, . . . )   // writing words / numbers  
                                                // high level formatted output, with the same arguments as printf()  
int fputs ( char *text, FILE *stream )           // writing text lines (C-strings)
```

Writing data to a BINARY file (data encoded in rough bytes)

```
int fwrite ( void* memory_buffer,  
             size_t block_size, size_t block_count,  
             FILE * stream)  
            // function that copies (block_count*block_size) bytes  
            // from the specified memory area (buffer) to the stream (file)
```

### Example

```
#include <stdio.h>  
struct TStudent  
{  
    char surname[31];  
    char name[16];  
    int age;  
};  
  
int main( void ) {  
    FILE *file;  
    TStudent student_array[10];  
    if ( (file = fopen( "test.bin" , "wb" ) ) != NULL )  
    { // Record the entire content of the student database to a binary file  
      fwrite( student_array, sizeof(TStudent), 10 , file );  
      fclose( file );  
    }  
  
    if ( (file = fopen( "test.txt" , "wt" ) ) != NULL )  
    { // Record the entire content of the student database to a text file  
      for( int i = 0; i < 10; i++ )  
        fprintf( file, "%s %s %d \n", student_array[i].surname,  
                  student_array[i].name, student_array[i].age );  
      fclose( file );  
    }  
    return 0;  
}
```

If we use predefined **stdout** (standard output stream) as a stream identifier, then the output will be made on the console / screen monitor.

eg. **fprintf**( **stdout**, "format" , ..... )  $\equiv$  **printf**( "format" , ..... )

### 3. List of functions for READING the data from a file stream

Reading the data from a **TEXT** file (data encoded in ASCII codes, spaces, NL, ...)

int **fgetc** ( FILE \***stream** ) *// reading the single character*

int **fscanf** ( FILE \***stream**, char \***format**, . . . ) *// reading words/numbers  
// high level formatted input, with the same arguments as scanf()*

char\* **fgets** ( char \***text**, int **max\_length**, FILE \***stream** ) *// reading "lines"  
// Loading a C-string (char array) consisting of at most (max\_length-1) characters*

Reading the data from a **BINARY** file (data encoded in rough bytes)

int **fread** ( void\* **memory\_buffer**,  
size\_t **block\_size**, size\_t **block\_count**,  
FILE \* **stream**)  
*// function that copies (block\_count\*block\_size) bytes  
// from the file stream to the specified memory area (buffer)*

#### Example

```
#include <stdio.h>
struct TStudent
{
    char surname[31];
    char name[16];
    int age;
};

void main( void ) {
    FILE *file;
    TStudent student_array [10];
    int count;
    if ( (file = fopen( "test.bin" , "rb" ) ) != NULL )
    { // Read the content of the student database from a binary file
        count = 0;
        while( fread( &student_array[count],sizeof(TStudent),1,file)==1)
            count++;
        fclose( file );
    }

    if ( (file = fopen( "test.txt" , "rt" ) ) != NULL )
    { // Import the content of the student database from a text file
        for( int i = 0; ( ! feof(file) ) && (i < 10); i++ )
            fscanf( file, "%s %s %d" , student_array[ i ].surname,
                student_array[ i ].name, &(student_array[ i ].age) );
        fclose( file );
    }

    return 0;
}
```

#### 4. Auxiliary file-positioning functions:

```
int fEOF ( FILE *stream )           // tests reaching the end of the given file

int fseek ( FILE *stream, long offset, int origin)
    // Move the file indicator position
    // relatively to specified origin:
        SEEK_SET - the beginning of the file
        SEEK_CUR - the current position
        SEEK_END - the end of the file

long ftell ( FILE *stream )         // returns current position of file indicator

int fflush ( FILE *stream )        // „sweeps” the buffer of a given stream
```

#### Example task on final test:

```
// Function that determines the position of the maximum value in a binary file
#include <stdio.h>

long Maximum( char *file_name )
{
    FILE *data_file;
    long position=0, max_pos = -1;
    double buffer, maximum;
    if ( (data_file = fopen( file_name , "rb" ) ) != NULL )
    {
        while( fread( & buffer, sizeof(double), 1, data_file) == 1)
        {
            if(position == 0 )
            {
                maximum = buffer;
                max_pos = 0;
            }
            else
            if( ! buffer > maximum )
            {
                maximum = buffer;
                max_pos = position;
            }
            position ++;
        }
        fclose( data_file );
    }
    return max_pos ;
}
```