

Distributed Automatic Parameter Testing

Ben Duggan

October 17, 2018

1 Setup

1.1 Google Sheet

The Google Sheet can be have any name you wish. The first 6 columns are set but the remaining columns can be used to store any parameters you wish. They will be sent as a dictionary in main so make sure they are unique. The link to the Google Sheet is <https://docs.google.com/spreadsheets/d/17QJFFXto0Mb0X5dH9GFP3NevNHixj7eZf7Pevcg96U/edit?usp=sharing> but is read only. The first 6 columns are as following:

- id: the trial id and must be unique.
- status: the current status of the parameter set. It can be empty meaning not started, in progress or finished.
- start date
- end date
- performed by: the computer that performed the computation as defined by config.txt
- comment: any comments either added by the person entering values or main.py

After the first six columns you can add settings. The ‘PhysiCell_settings.xml’ file is created from ‘PhysiCell_settings_default.xml’ and the XML structure must already be present. The column names are the path to get to the XML variable and the value is what should be set. There are problems with Google Sheets formating so it’s best to set the columns to plain text.

1.2 sheet.py

Using the Google Sheets API Python Startup Guide and Google Spreadsheets and Python guide written by Greg Baugues.

Follow the following steps:

1. Run "pip install gspread oauth2client" to install the required libraries.
2. Create the credentials (this is only needed to create a new set of parameters).
 - (a) Go to <https://console.developers.google.com/>.
 - (b) Create a new project.

- (c) Click Enable API. Search for and enable the Google Drive API and the Google Sheets API.
 - (d) Create credentials for service account key. Create a service account and select a Key type of JSON.
 - (e) Name the service account and grant it a Project Role of Editor.
 - (f) Download the JSON file.
 - (g) Copy the JSON file into DistParam.
3. Go to the spreadsheet you wish to use, copy spreadsheet ID (The ID in <https://docs.google.com/spreadsheets/d/17QJFFXto0MbOX5dH9GFP3NevNHluxj7eZf7Pevcg96U/edit#gid=0> is **17QJF-FXto0MbOX5dH9GFP3NevNHluxj7eZf7Pevcg96U**) and set it equal to spreadsheetID in sheet.py

1.3 config.txt

This is the configuration file for the main file. It consists of key value pairs separated by a colon. There can't be a space between the key or value and the colon. It consists of the following fields:

- `userName` this is the user name of the system. It is not required but gets saved in the Google Sheet and allows for runs to be traced back to a particular system. Its default value is "default".
- `resetTime` is the time in seconds at which a parameter set will be added as available if the status hasn't changed from "in progress" to "finished". This is to ensure that if the computer shuts down or an error occurs the parameter set will still be run. The default value is "172800" or 2 days.
- `numOfRuns` is the number of trials you want main to run. If you set it to -1 it will run until there are no more parameters to run. The default value is "-1".
- `lastTest` is used by main.py to keep track of if a test didn't finish correctly. If it did not then it will try this set of parameters the next time. Its default value is "None".

2 Run Test

To run you must simply type `python main.py`