



Product data sheet

EVELUX M 48/450/730 DALI WR2
104755
TREVOS



Light fitting resistant to dust, humidity and spraying water, suitable for roads, residential areas, parking areas and open spaces; Light fitting suitable for lighting outdoor sports halls, certified for ball impact safety pursuant to DIN 18032-3; Wide range of optional versions of the light fitting's optical system for diverse applications; Digitally dimmable DALI driver (AC/DC); Body:aluminium alloy, black grey (RAL 7021); Diffuser:heat-strengthened safety glass; Connection:screw terminal block with disconnecter for conductors with maximum cross-section of 4 mm²; Power:65,3 W; Luminaire flux:9960 lm; Lifetime:L90/B10 100000 hours; Impact strength:IK10; Ambient temperature:-25|45 °C; Weight:7,2 kg

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	65.3 W	CRI	70
Total flux	9960 lm	LOR	100%
Luminous efficacy	153 lm/W	Total power	65.3 W

Mounting mode

Pole top mounted

Shape and measurements

Length: 28.35 in
Width: 12.20 in
Height: 3.94 in

Adjustability

Fixed

Design

Material impression: Aluminum
Color of housing: Anthracite / graphite
Designer: TREVOS

Electric

System power: 65.3 W
Ballast: ECG
Controller: DALI
Appliance Class: I

Protection

IP: 66
IK: 10
Designation labels: CE, ENEC

Other operating numbers

Ambient temperature range: -13...113°F