Binary Analysis – Emulation and Instrumentation

REVERSE ENGINEERING

João Paulo Barraca

deti universidade de aveiro
departamento de eletrónica, telecomunicações e informática

Binary Analysis Process

- Up to now we know how ELF files are structured, but the question remains: how do we analyse ELF files?
  - Or any other binary executable

- A possible flow can be:
  - File analysis (file, nm, ldd, content visualization, foremost, binwalk)
  - Static Analysis (disassemblers and decompilers
  - Behavioral Analysis (strace, LD_PRELOAD)
  - **Dynamic Analysis (debuggers and emulators)**

Dynamic Binary Analysis

- Allows capturing the dynamic behavior of some code
  - Behavior that depends on external input
  - Data structures and even code revealed during execution time

- Allows runtime validation/evaluation of binary code
  - A program, a firmware, part of a program, a sequence of instructions
  - Under a controlled context
  - On a different (more flexible, or controllable, or safe) environment

Dynamic Binary Analysis

How

- Load the binary and ***execute*** instructions of the target binary
  - The meaning of “Execute” is broad

- Allow some interaction with the binary while it is running
  - Break the execution at some point
  - Inspect memory and process it’s content
  - Change memory, either variables or code
  - Execute code in a controlled manner: step by step, in chunks, until a given point

Dynamic Binary Analysis

Approaches

- Analysis of an execution flow can either be **passive** or **active**.
  - Choosing either one or the other has consequences on the soundness, the coverage, etc. of the results

- **Passive analysis**: observation
  - **register values**: return value of functions (`rax`), program counter (`pc`), stack frame (`rbp, rsp`), etc.
  - **stack inspection**: local variables, input parameters (according to some calling conventions), return address, etc.
  - **heap inspection**: the number of allocated blocks, their content, etc

- **Active analysis**: modification
  - Easily explore paths without finding inputs that actually activate them

Dynamic Binary Analysis

caveats

- In android the focus was the simple analysis of java apps, binary applications **are more powerful and complex**
  - May not be written in java, and have code that runs in a VM
  - May consider code that changes the host system, or is a malware

- Binary analysis of complex applications requires a different toolset
  - The principles will be the same, but the tools will allow fine grained control and isolation
  - Side effects and execution impact may be subtle (remember Meltdown and Spectre)
  - Host systems may be more complex

Considerations

(Need for) Stability

- Reversing is significantly more difficult if execution is unstable.
  - Observations are affected by "random" factors, such as multithreaded execution, hardware behavior, user interactions with graphical interface and so on.
  - Applications being reversed should be isolated from external effects are much as possible.

- Determinism in a design results from stable execution of a program run
  - Thus it facilitates debugging and reversing.
  - State may also be deterministically altered for the entire program or for a specific function (fuzzing)

- Logs can be obtained from executions using monitor applications

Considerations

(Need for) Save and Replaying

- Reversing usually needs to trace from the current state to the line of code where a change was produced.
  - It implies moving "back in time".
  - To restore past program state, one must **re-run it** and try to find failure source.
  - This operation may be performed multiple times, **moving backward step-by-step, and then forward**.

- Deterministic replay reconstructs program execution using previously recorded input data.
  - The first program run is used to record these inputs into the log.
  - Then all following runs will reconstruct the same behavior, because the program uses only recorded inputs.
  - Should included all inputs (disk, network)

Considerations

(Need for) Safety

- Target binary **may be malicious (..they are always malicious until proven safe)**

- An important aspect of Reversing binaries is malware analysis
  - Malware is way to complex to be analyzed statically
  - But executing the malware may be dangerous
    - **Most important: dangerous in ways unknown to the reverse engineer**

- Solutions must create the adequate isolation boundaries between environments
  - If stability is required, no interactions with the software under analysis
  - Sometimes, isolation must be broken to trigger specific behavior
    - Network connection allowing contact with a C&C address or to download some payload
    - Disk or file presence
    - Whenever possible, such resource should be virtualized

Considerations

(Need for) Support of Heterogeneous Architectures

- Dynamic analysis requires the execution of the program under analysis.

- A system analyst will mostly run on an Intel x86 64bits computer (a COTS laptop/server)
  - Most embedded devices are ARM, which has several variants
  - Microcontrollers frequently use 8085, AVR or PIC architectures (MIPS)
  - Several specialty SOCs use custom architectures (the list is large…)
  - Several binary formats are popular: ELF, PE, DWARF and then many others from IoT

- Frameworks must be extensible in order to support a wide range of architectures
  - And the related interfaces and customizations
  - While minimizing the need for new tools

Considerations

(Need for) Support of Peripherals and external entities

- Reversing an application with external interactions may require the existence of the related entities
  - Web sites, servers in fixed/dynamic IP addresses
  - Common physical devices for user input, storage, …
  - Exotic external devices communicating through known or unknown buses
  - Hardware Dongles
- Need to recreate the set of devices/entities required to trigger a specific path
  - Frequently resorts to device emulation with mock software constructs

Considerations

(Need for) Context manipulation (instrumentation)

- The main limitation of a dynamic approach is **coverage**.
  - Every path that is not covered by the instrumented executions cannot be analyzed.
  - This limitation can be slightly reduced by performing active instrumentation, and in particular by **forcing conditional branching**



Example of Intel PIN coverage output provided to IDA

Considerations

(Need for) Context manipulation (instrumentation)

- A reversing task will need to observe **structure** and **behavior**
  - The analysis should have **enough coverage to recover the adequate level of detail**
  - But while static analysis aims for wide coverage, dynamic analysis aims for focus
  - What if a specific course of execution is not triggered?
  - **Results of dynamic analysis are dependent on the context of the execution**

- Context manipulation allows setting the adequate state to trigger a specific flow of execution, **increasing the reversing coverage**
  - Achieved by careful manipulation of execution state, registers and memory content
  - Problems:
    - May lead to the recovery of an incorrect design as the found flow may be a decoy!
    - May lead to the recovery of artificial vulnerabilities, that do not really exist

Considerations

Context manipulation (instrumentation)

- Live patching: modifying RAM in a debugger/controlled environment
- File Patching: alter binaries files to replace their content
- Binary Instrumentation: Real time, automated modification

Considerations

Design Fidelity

- If the program under analysis is executed, **it can detect and try to defend actively against analysis**.
  - For instance, it can hide a part of its behavior if it detects that it is being analyzed.
  - This anti-debugging and anti-instrumentation techniques are used by many malwares.

- So, when we achieve a hypothesis of a design, how correct it is?

The completely unrelated

In completely unrelated news, upcoming versions of Signal will be periodically fetching files to place in app storage. These files are never used for anything inside Signal and never interact with Signal software or data, but they look nice, and aesthetics are important in software. Files will only be returned for accounts that have been active installs for some time already, and only probabilistically in low percentages based on phone number sharding. We have a few different versions of files that we think are aesthetically pleasing, and will iterate through those slowly over time. There is no other significance to these files.

https://signal.org/blog/cellebrite-vulnerabilities/

Dynamic Binary Analysis of Binaries

Processes

- Tracing
- Debugging
- Sandboxing
- Emulation
- Instrumentation

Tracers

… Already briefly discussed in previous lectures

- **Tracers execute a binary, logging information about function and system calls**
- Binary is executed in the analyst's system
  - In a VM!
- Tracer adds hooks to application or kernel to gain information about execution
  - Access to files, packets sent, registry access
- No confinement or security measures in place
  - Actually, there may be no interaction between the tracer and the application
    - Tracer monitors system through kernel debug interfaces

Tracers

… Already briefly discussed in previous lectures

- **Limitations:**
  - No isolation, no capability to analyze malicious or harmful code
  - Can only inspect interactions between the application and the external environment
  - Host environment must be compatible with the target binary
    - No possibility of analyzing windows binaries on linux, vice-versa, embedded systems on windows, etc…

- **Linux**: `ltrace, strace (ptrace), wireshark, valgrind, cachegrind, callgrind, helgrind`

- **Windows**: `process monitor, wireshark`

```
$ ltrace -CfirS ./hello
[pid 3409]   0.000000 [0x7fb358d197b7] SYS_brk(0)                                                                = 0x7ffff030a000
[pid 3409]   0.001059 [0x7fb358d1a417] SYS_access("/etc/ld.so.preload", 04)                                      = -2
[pid 3409]   0.001796 [0x7fb358d1a4fd] SYS_openat(0xffffff9c, 0x7fb358d2090f, 0x80000, 0)                        = 3
[pid 3409]   0.000924 [0x7fb358d1a383] SYS_fstat(3, 0x7ffff878e030)                                              = 0
[pid 3409]   0.000634 [0x7fb358d1a6f3] SYS_mmap(0, 0xf607, 1, 2)                                                = 0x7fb358cf0000
[pid 3409]   0.000792 [0x7fb358d1a437] SYS_close(3)                                                             = 0
[pid 3409]   0.000497 [0x7fb358d1a4fd] SYS_openat(0xffffff9c, 0x7fb358d29df0, 0x80000, 0)                        = 3
[pid 3409]   0.000846 [0x7fb358d1a5c4] SYS_read(3, "\177ELF\002\001\001\003", 832)                               = 832
[pid 3409]   0.000734 [0x7fb358d1a383] SYS_fstat(3, 0x7ffff878e090)                                              = 0
[pid 3409]   0.000554 [0x7fb358d1a6f3] SYS_mmap(0, 8192, 3, 34)                                                 = 0x7fb358d30000
[pid 3409]   0.000698 [0x7fb358d1a6f3] SYS_mmap(0, 0x1c0800, 1, 2050)                                           = 0x7fb358b20000
[pid 3409]   0.000751 [0x7fb358d1a7a7] SYS_mprotect(0x7fb358b42000, 1658880, 0)                                 = 0
[pid 3409]   0.001054 [0x7fb358d1a6f3] SYS_mmap(0x7fb358b42000, 0x148000, 5, 2066)                              = 0x7fb358b42000
[pid 3409]   0.001092 [0x7fb358d1a6f3] SYS_mmap(0x7fb358c8a000, 0x4c000, 1, 2066)                               = 0x7fb358c8a000
[pid 3409]   0.000784 [0x7fb358d1a6f3] SYS_mmap(0x7fb358cd7000, 0x6000, 3, 2066)                                = 0x7fb358cd7000
[pid 3409]   0.000857 [0x7fb358d1a6f3] SYS_mmap(0x7fb358cdd000, 0x3800, 3, 50)                                  = 0x7fb358cdd000
[pid 3409]   0.000765 [0x7fb358d1a437] SYS_close(3)                                                             = 0
[pid 3409]   0.000598 [0x7fb358d01d9c] SYS_arch_prctl(4098, 0x7fb358d31500, 0x7fb358d31e30, 144)                = 0
[pid 3409]   0.000932 [0x7fb358d1a7a7] SYS_mprotect(0x7fb358cd7000, 16384, 1)                                   = 0
[pid 3409]   0.000606 [0x7fb358d1a7a7] SYS_mprotect(0x7fb358d3c000, 4096, 1)                                    = 0
[pid 3409]   0.000599 [0x7fb358d1a7a7] SYS_mprotect(0x7fb358d27000, 4096, 1)                                    = 0
[pid 3409]   0.000595 [0x7fb358d1a787] SYS_munmap(0x7fb358cf0000, 62983)                                        = 0
[pid 3409]   0.002566 [0x7fb358d3a165] printf("Hello " <unfinished ...>
[pid 3409]   0.000758 [0x7fb358c09af3] SYS_fstat(1, 0x7ffff878e670)                                             = 0
[pid 3409]   0.000635 [0x7fb358c0fb58] SYS_ioctl(1, 0x5401, 0x7ffff878e5d0, -3013)                              = 0
[pid 3409]   0.001205 [0x7fb358c10307] SYS_brk(0)                                                               = 0x7ffff030a000
[pid 3409]   0.000758 [0x7fb358c10307] SYS_brk(0x7ffff032b000)                                                  = 0x7ffff032b000
[pid 3409]   0.000574 [0x7fb358d3a165] <... printf resumed> )                                                   = 6
[pid 3409]   0.000436 [0x7fb358d3a171] puts("World" <unfinished ...>
[pid 3409]   0.000787 [0x7fb358c0a504] SYS_write(1, "Hello World\n", 12Hello World
)                                                 = 12
[pid 3409]   0.001037 [0x7fb358d3a171] <... puts resumed> )                                                     = 6
[pid 3409]   0.000496 [0x7fb358be69d6] SYS_exit_group(0 <no return ...>
[pid 3409]   0.000615 [0xffffffffffffffff] +++ exited (status 0) +++
```

Function calls
System calls


Process Monitor - Sysinternals: www.sysinternals.com
File Edit Event Filter Tools Options Help
Time of Day Process Name PID Operation Path Result Detail
6:20:34.4727264 PM dwm.exe 1744 RegQueryValue HKCU\SOFTWARE\Microsoft\Windows\DWM\ColorPrevalence SUCCESS Type: REG_DWORD, Length: 4, Data: 0
6:20:34.4733777 PM dwm.exe 1744 RegQueryValue HKCU\SOFTWARE\Microsoft\Windows\DWM\ColorPrevalence SUCCESS Type: REG_DWORD, Length: 4, Data: 0
6:20:34.4734050 PM dwm.exe 1744 RegQueryValue HKCU\SOFTWARE\Microsoft\Windows\DWM\ColorPrevalence SUCCESS Type: REG_DWORD, Length: 4, Data: 0
6:20:34.4745306 PM atieclxx.exe 4988 QueryNameInfo... C:\Programs\ProcessMonitor\Procmon64.exe SUCCESS Name: \Programs\ProcessMonitor\Procmon64.exe
6:20:34.4784765 PM FoxitReaderUpdateServic... 7072 CreateFile C:\ProgramData\Foxit Software\Foxit Reader\FoxitData.txt NAME NOT FOUND Desired Access: Read Attributes, Disposition: Open, Options: Open Reparse Point,
6:20:34.4806833 PM dwm.exe 1744 RegQueryValue HKCU\SOFTWARE\Microsoft\Windows\DWM\ColorPrevalence SUCCESS Type: REG_DWORD, Length: 4, Data: 0
6:20:34.4807006 PM dwm.exe 1744 RegQueryValue HKCU\SOFTWARE\Microsoft\Windows\DWM\ColorPrevalence SUCCESS Type: REG_DWORD, Length: 4, Data: 0
6:20:34.4814350 PM dwm.exe 1744 RegQueryValue HKCU\SOFTWARE\Microsoft\Windows\DWM\ColorPrevalence SUCCESS Type: REG_DWORD, Length: 4, Data: 0
6:20:34.4814669 PM dwm.exe 1744 RegQueryValue HKCU\SOFTWARE\Microsoft\Windows\DWM\ColorPrevalence SUCCESS Type: REG_DWORD, Length: 4, Data: 0
6:20:34.4829904 PM atieclxx.exe 4988 QueryNameInfo... C:\Programs\ProcessMonitor\Procmon64.exe SUCCESS Name: \Programs\ProcessMonitor\Procmon64.exe
6:20:34.4871868 PM dwm.exe 1744 RegQueryValue HKCU\SOFTWARE\Microsoft\Windows\DWM\ColorPrevalence SUCCESS Type: REG_DWORD, Length: 4, Data: 0
6:20:34.4872250 PM dwm.exe 1744 RegQueryValue HKCU\SOFTWARE\Microsoft\Windows\DWM\ColorPrevalence SUCCESS Type: REG_DWORD, Length: 4, Data: 0
6:20:34.4882720 PM dwm.exe 1744 RegQueryValue HKCU\SOFTWARE\Microsoft\Windows\DWM\ColorPrevalence SUCCESS Type: REG_DWORD, Length: 4, Data: 0
6:20:34.4883107 PM dwm.exe 1744 RegQueryValue HKCU\SOFTWARE\Microsoft\Windows\DWM\ColorPrevalence SUCCESS Type: REG_DWORD, Length: 4, Data: 0
6:20:34.4898183 PM atieclxx.exe 4988 QueryNameInfo... C:\Programs\ProcessMonitor\Procmon64.exe SUCCESS Name: \Programs\ProcessMonitor\Procmon64.exe
6:20:34.4946592 PM dwm.exe 1744 RegQueryValue HKCU\SOFTWARE\Microsoft\Windows\DWM\ColorPrevalence SUCCESS Type: REG_DWORD, Length: 4, Data: 0
6:20:34.4946777 PM dwm.exe 1744 RegQueryValue HKCU\SOFTWARE\Microsoft\Windows\DWM\ColorPrevalence SUCCESS Type: REG_DWORD, Length: 4, Data: 0
6:20:34.4954656 PM dwm.exe 1744 RegQueryValue HKCU\SOFTWARE\Microsoft\Windows\DWM\ColorPrevalence SUCCESS Type: REG_DWORD, Length: 4, Data: 0
6:20:34.4955028 PM dwm.exe 1744 RegQueryValue HKCU\SOFTWARE\Microsoft\Windows\DWM\ColorPrevalence SUCCESS Type: REG_DWORD, Length: 4, Data: 0
6:20:34.4967488 PM atieclxx.exe 4988 QueryNameInfo... C:\Programs\ProcessMonitor\Procmon64.exe SUCCESS Name: \Programs\ProcessMonitor\Procmon64.exe
6:20:34.5026921 PM dwm.exe 1744 RegQueryValue HKCU\SOFTWARE\Microsoft\Windows\DWM\ColorPrevalence SUCCESS Type: REG_DWORD, Length: 4, Data: 0
6:20:34.5027294 PM dwm.exe 1744 RegQueryValue HKCU\SOFTWARE\Microsoft\Windows\DWM\ColorPrevalence SUCCESS Type: REG_DWORD, Length: 4, Data: 0
6:20:34.5032906 PM dwm.exe 1744 RegQueryValue HKCU\SOFTWARE\Microsoft\Windows\DWM\ColorPrevalence SUCCESS Type: REG_DWORD, Length: 4, Data: 0
6:20:34.5033048 PM dwm.exe 1744 RegQueryValue HKCU\SOFTWARE\Microsoft\Windows\DWM\ColorPrevalence SUCCESS Type: REG_DWORD, Length: 4, Data: 0
6:20:34.5046926 PM atieclxx.exe 4988 QueryNameInfo... C:\Programs\ProcessMonitor\Procmon64.exe SUCCESS Name: \Programs\ProcessMonitor\Procmon64.exe
6:20:34.5104047 PM FoxitReaderUpdateServic... 7072 CreateFile C:\ProgramData\Foxit Software\Foxit Reader\FoxitData.txt NAME NOT FOUND Desired Access: Read Attributes, Disposition: Open, Options: Open Reparse Point,
6:20:34.5106292 PM dwm.exe 1744 RegQueryValue HKCU\SOFTWARE\Microsoft\Windows\DWM\ColorPrevalence SUCCESS Type: REG_DWORD, Length: 4, Data: 0
6:20:34.5106426 PM dwm.exe 1744 RegQueryValue HKCU\SOFTWARE\Microsoft\Windows\DWM\ColorPrevalence SUCCESS Type: REG_DWORD, Length: 4, Data: 0
6:20:34.5114190 PM dwm.exe 1744 RegQueryValue HKCU\SOFTWARE\Microsoft\Windows\DWM\ColorPrevalence SUCCESS Type: REG_DWORD, Length: 4, Data: 0
6:20:34.5114449 PM dwm.exe 1744 RegQueryValue HKCU\SOFTWARE\Microsoft\Windows\DWM\ColorPrevalence SUCCESS Type: REG_DWORD, Length: 4, Data: 0
6:20:34.5126114 PM atieclxx.exe 4988 QueryNameInfo... C:\Programs\ProcessMonitor\Procmon64.exe SUCCESS Name: \Programs\ProcessMonitor\Procmon64.exe
6:20:34.5187472 PM dwm.exe 1744 RegQueryValue HKCU\SOFTWARE\Microsoft\Windows\DWM\ColorPrevalence SUCCESS Type: REG_DWORD, Length: 4, Data: 0
6:20:34.5187896 PM dwm.exe 1744 RegQueryValue HKCU\SOFTWARE\Microsoft\Windows\DWM\ColorPrevalence SUCCESS Type: REG_DWORD, Length: 4, Data: 0
6:20:34.5196183 PM dwm.exe 1744 RegQueryValue HKCU\SOFTWARE\Microsoft\Windows\DWM\ColorPrevalence SUCCESS Type: REG_DWORD, Length: 4, Data: 0
6:20:34.5196579 PM dwm.exe 1744 RegQueryValue HKCU\SOFTWARE\Microsoft\Windows\DWM\ColorPrevalence SUCCESS Type: REG_DWORD, Length: 4, Data: 0
6:20:34.5208130 PM atieclxx.exe 4988 QueryNameInfo... C:\Programs\ProcessMonitor\Procmon64.exe SUCCESS Name: \Programs\ProcessMonitor\Procmon64.exe
6:20:34.5266925 PM dwm.exe 1744 RegQueryValue HKCU\SOFTWARE\Microsoft\Windows\DWM\ColorPrevalence SUCCESS Type: REG_DWORD, Length: 4, Data: 0
6:20:34.5267404 PM dwm.exe 1744 RegQueryValue HKCU\SOFTWARE\Microsoft\Windows\DWM\ColorPrevalence SUCCESS Type: REG_DWORD, Length: 4, Data: 0
6:20:34.5274177 PM dwm.exe 1744 RegQueryValue HKCU\SOFTWARE\Microsoft\Windows\DWM\ColorPrevalence SUCCESS Type: REG_DWORD, Length: 4, Data: 0
6:20:34.5274533 PM dwm.exe 1744 RegQueryValue HKCU\SOFTWARE\Microsoft\Windows\DWM\ColorPrevalence SUCCESS Type: REG_DWORD, Length: 4, Data: 0
6:20:34.5291568 PM atieclxx.exe 4988 QueryNameInfo... C:\Programs\ProcessMonitor\Procmon64.exe SUCCESS Name: \Programs\ProcessMonitor\Procmon64.exe
6:20:34.5346890 PM dwm.exe 1744 RegQueryValue HKCU\SOFTWARE\Microsoft\Windows\DWM\ColorPrevalence SUCCESS Type: REG_DWORD, Length: 4, Data: 0
6:20:34.5347068 PM dwm.exe 1744 RegQueryValue HKCU\SOFTWARE\Microsoft\Windows\DWM\ColorPrevalence SUCCESS Type: REG_DWORD, Length: 4, Data: 0
Showing 1,995,462 of 3,591,990 events (55%)
Backed by virtual memory

Debugging

- Applications that can control a target executing binary
  - Debuggers can **create a process** and analyze it or **attach to a running process**
    - Process usually executes in the host system
  - This is the “typical”, low tech way of dynamically analyzing a program
    - Reuses concepts/tools from the engineering process, applied to reverse engineering

- **What they provide:** extensive, interactive control over a process execution flow
  - Frequently at the level of opcodes and assembly
  - Can be integrated with static analysis tools
    - Combining execution information with decompiled code, CFGs, disassembly

Debugging

Limitations

- Debugging **can be detected** and subverted by the target application
  - Especially popular in malware and DRM systems
- Target application must be executed in a full hosted environment
  - Without isolation measures, this provides a serious security risk
  - Remote debugging may be used to circumvent this limitation
- Host system architecture must match the target binary architecture
  - Binary is loaded to the host system as a standard process
  - No debugging of windows in Linux, ARM or MIPS in x86
  - No direct way of debugging shellcode or a binary blob (e.g firmware).

Debugging

How debuggers work?

- Debuggers explore system calls provided by the operating system
  - Debuggers either:
    - create a child process, sharing the same address space
    - attach to an existing process given that the user has the correct permissions (e.g. root)
  - Linux: **`ptrace`**
  - Windows: provides API for process control
    - **`CreateProcess`** with specific **`dwCreationFlags`** (`DEBUG_PROCESS`)
    - **`OpenProcess`** with **`dwDesiredAccess`** (`PROCESS_VM_READ, PROCESS_VM_WRITE, PROCESS_VM_OPERATION`)
- Debuggers may attach to hardware devices providing external debugging
  - Used in embedded devices

Debugging



Debugger set breakpoints which Trigger SIGTRAP, returning control to the debugger.

Patching the code with **0xCC** or using Hardware breakpoints (through **PTRACE**)

Debugging

debugger.c

```c
int main(int argc, char** argv)
{
    pid_t child_pid;

    if (argc < 2) {
        fprintf(stderr, "Expected a program name as argument\n");
        return -1;
    }

    child_pid = fork();
    if (child_pid == 0)
        run_target(argv[1]);

    else if (child_pid > 0)

        run_debugger(child_pid);

    else {
        perror("fork");
        return -1;
    }

    return 0;
}

```

```c
void run_target(const char* programname)
{
    procmsg("target started. will run '%s'\n", programname);

    /* Allow tracing of this process */
    if (ptrace(PTRACE_TRACEME, 0, 0, 0) < 0) {
        perror("ptrace");
        return;
    }

    /* Replace this process's image with the given program */
    execl(programname, programname, 0);
}
```

`fork()` duplicates the current process. While sharing the same address space.

One (child) will execute **`run_target()`**
Other (parent) will execute **`run_debugger()`**

Debugging

debugger.c

Child process allows tracing

```c
int main(int argc, char** argv)
{
    pid_t child_pid;

    if (argc < 2) {
        fprintf(stderr, "Expected a program name as argument\n");
        return -1;
    }

    child_pid = fork();
    if (child_pid == 0)
        run_target(argv[1]);

    else if (child_pid > 0)

        run_debugger(child_pid);

    else {
        perror("fork");
        return -1;
    }

    return 0;
}
```

```c
void run_target(const char* programname)
{
    procmsg("target started. will run '%s'\n", programname);

    /* Allow tracing of this process */
    if (ptrace(PTRACE_TRACEME, 0, 0, 0) < 0) {
        perror("ptrace");
        return;
    }

    /* Replace this process's image with the given program */
    execl(programname, programname, 0);
}
```

`execl` will replace the current process image with the binary loaded from the storage.

In this moment, the processes become different.

Debugging

debugger.c

Wait for process to start

Get CPU registers

Single Step through one instruction (ASM)

Wait for instruction to finish

```
48  void run_debugger(pid_t child_pid)
49  {
50      int wait_status;
51      unsigned icounter = 0;
52      procmsg("debugger started\n");
53      struct user_regs_struct regs;
54
55      /* Wait for child to stop on its first instruction */
56      wait(&wait_status);
57
58      while (WIFSTOPPED(wait_status)) {
59          icounter++;
60          ptrace(PTRACE_GETREGS, child_pid, 0, &regs);
61          unsigned instr = ptrace(PTRACE_PEEKTEXT, child_pid, regs.rip, 0);
62
63          procmsg("icounter = %u.  RIP = 0x%08x.  instr = 0x%08x\n",
64                  icounter, regs.rip, instr);
65
66          /* Make the child execute another instruction */
67          if (ptrace(PTRACE_SINGLESTEP, child_pid, 0, 0) < 0) {
68              perror("ptrace");
69              return;
70          }
71
72          /* Wait for child to stop on its next instruction */
73          wait(&wait_status);
74      }
75
76      procmsg("the child executed %u instructions\n", icounter);
77  }
```

Sandboxing

- Sandboxing improves the control that debuggers provide
  - Creation of a distinct execution environment
    - Different libraries? Restricted view of the filesystem (minimal access to files)
  - Isolate some actions, providing some safety to analyze malicious applications
- Implementation: lightweight virtual machines or namespaces/containers
  - Supported my mechanisms of the Operating System or additional tools
  - Tools: `sandboxie, pyrebox, panda`
- An agent monitors interactions of the application inside the environment and may allow instrumentation
  - File access, network communication
  - Remote debugging

Emulators

- Emulators are the typical backends for sandboxes
  - May provide much better isolation as the guest and host environments are distinct
    - Kernel is not shared, hardware is emulated
  - Tools: **QEMU**, Virtualbox, Vmware

- Emulation types
  - Full system emulation
  - User mode emulation

Emulators

User Mode Emulation

- Launches **a processes** directly, but on a restricted environment
  - Process may be compiled for one CPU and executed on another CPU
  - Address space is restricted, such as filesystem and libraries available
  - Interaction with Host OS is mediated by the emulator

- Emulator process native CPU instructions (emulation/translation) and:
  - Provide means **to translate syscalls** from guest to host OS
  - Understand intrinsic characteristics such as clone
    - Clone is used to spawn new processes and will require the creation of a new emulation environment
  - Handle signals between analyzed binary and the host system

- May provide integration with debugging tools

Emulators

User Mode Emulation with QEMU

- QEMU allows user mode emulation **as long as the OS is kept the same**
- What it does:
  - Machine code translation from any CPU to any CPU
  - Syscall mapping
  - Data structure conversion (Bit-order and Bit-width conversions)
  - Extensive tracing capability to the level of Micro Ops
- Provides a **`gdbserver`** interface for interaction with GDB
- Usefulness: reverse engineering applications compiled to other architectures


System Overview
ARM Source Code
Arm-linux-gnueabihf-gcc
Compiler
ARM Binary
QEMU
JIT Compiler
Host Binary
Execution
Execution Results

Emulators

Full System Emulation

- Basically: a full-blown virtual machine
  - Emulates a highly configurable set of hardware, including embedded devices
  - Maps interactions to Host resources (screen, disk, network)
  - RE aware software tools expose debugging interfaces (usually to **gdb**)
- Provides the best level of isolation
  - All accesses are mediated by the emulator, reducing the attack surface to emulator components
  - Allows analyzing other binaries besides standard executable files
    - Firmware, MBR, UEFI
- Malware frequently try to detect Virtual Machines, emulators and debuggers…
  - With variable sofistication

Remote debugging with emulators

gdb and gdbserver

- **gdb** can debug remote applications
  - It can even debug remote kernels and firmware
  - Why? Consider embedded devices, software inside an emulator

- **gdbserver** is launched on the target system, with the arguments:
  - Either a device name (to use a serial line) or a TCP hostname and portnumber, and the path and filename of the executable to be debugged
  - It then waits passively for the host **gdb** to communicate with it.

- **gdb** is run on the host, with the arguments:
  - The path and filename of the executable (and any sources) on the host, and
  - A device name (for a serial line) or the IP address and port number needed for connection to the target system.

- **Alternative**: the remote application is compiled with a stub that provides a **gdbserver** interface when the application is launched

Example

Reversing an ARM binary

```
┌──(root💀pc)-[/tmp/er/arm]
└─# qemu-arm -L . -singlestep -g 1234  crackme-dyn-arm
```

```
┌──(user㉿pc)-[/tmp/er/arm]
└─$ gdb-multiarch ./crackme-dyn-arm
GNU gdb (Debian 10.1-1.7) 10.1.90.20210103-git
Copyright (C) 2021 Free Software Foundation, Inc.
License GPLv3+: GNU GPL version 3 or later <http://gnu.org/lic
enses/gpl.html>
This is free software: you are free to change and redistribute
 it.
There is NO WARRANTY, to the extent permitted by law.
Type "show copying" and "show warranty" for details.
This GDB was configured as "x86_64-linux-gnu".
Type "show configuration" for configuration details.
For bug reporting instructions, please see:
<https://www.gnu.org/software/gdb/bugs/>.
Find the GDB manual and other documentation resources online a
t:
    <http://www.gnu.org/software/gdb/documentation/>.

For help, type "help".
Type "apropos word" to search for commands related to "word"..
.
Reading symbols from ./crackme-dyn-arm...
(No debugging symbols found in ./crackme-dyn-arm)
(gdb) target remote localhost:1234
Remote debugging using localhost:1234
warning: remote target does not support file transfer, attempt
ing to access files from local filesystem.
Reading symbols from /tmp/er/arm/lib/ld-linux-armhf.so.3...
(No debugging symbols found in /tmp/er/arm/lib/ld-linux-armhf.
so.3)
0×3ffcea30 in ?? () from /tmp/er/arm/lib/ld-linux-armhf.so.3
(gdb) br main
Breakpoint 1 at 0×10574
(gdb)
```

Exercise

unknown.bin

- Remember the **`unknown.bin`** file?
  - Well… looks like a PDF (is a PDF)
  - but **`$ file unknown.bin`** returns "**`unknown.bin: DOS/MBR boot sector`**"

- What we may extrapolate from that:
  - Seems to be a DOS/Master Boot Record (Master boot record – Wikipedia)
  - DOS was only released for i386 (16bits and 32bits)
  - `qemu-system-i386` may boot it if used as a hard disk or floppy disk

Exercise

unknown.bin

- How to address such files?
  - Binary files other than ELFs (or PE or other similar) obey to a fixed set of rules
  - It is required to check the datasheets and gather information required to load the file.
  - Important:
    - CPU used, CPU mode, relevant or required peripherals: to know how to decode the binary instructions
    - Program Entry Point: to know where the program starts, and where disassembly should start

- From a Master Boot Record we may know:
  - MBR is loaded to address 0x7C00
  - MBR code runs in Intel x86 Real Mode (16bits)
  - There are quite a few limitations and assumptions: IBM DOS 2.00 Master Boot Record (pcministry.com)
  - There is no OS running. Input/Output must use BIOS Interrupts

Exercise

Loading the unknown.bin in ghidra



Exercise

Loading the unknown.bin in ghidra



Exercise

Loading the unknown.bin in ghidra

```
                        //
                        // RAM
                        // ram:0000:7c00-ram:0000:ac01
                        //
        assume DF = 0x0  (Default)
0000:7c00 25              ??         25h    %
0000:7c01 ff              ??         FFh
0000:7c02 ff              ??         FFh
0000:7c03 eb              ??         EBh
0000:7c04 57              ??         57h    W
0000:7c05 0a              ??         0Ah
0000:7c06 00              ??         00h
0000:7c07 00              ??         00h
0000:7c08 00              ??         00h
0000:7c09 00              ??         00h
0000:7c0a 00              ??         00h
0000:7c0b 00              ??         00h
0000:7c0c 00              ??         00h
0000:7c0d 00              ??         00h
0000:7c0e 00              ??         00h
0000:7c0f 00              ??         00h
0000:7c10 00              ??         00h
0000:7c11 00              ??         00h
0000:7c12 00              ??         00h
0000:7c13 00              ??         00h
0000:7c14 00              ??         00h
0000:7c15 00              ??         00h
0000:7c16 00              ??         00h
0000:7c17 00              ??         00h
0000:7c18 00              ??         00h
```

If we state that 0x7C00 has code, looks like we have something

```
                        //
                        // RAM
                        // ram:0000:7c00-ram:0000:ac01
                        //
        assume DF = 0x0  (Default)
0000:7c00 25 ff ff        AND        AX,0xffff
0000:7c03 eb 57           JMP        LAB_0000_7c5c
0000:7c05 0a              ??         0Ah
0000:7c06 00              ??         00h
0000:7c07 00              ??         00h
0000:7c08 00              ??         00h
0000:7c09 00              ??         00h
0000:7c0a 00              ??         00h
0000:7c0b 00              ??         00h
0000:7c0c 00              ??         00h
0000:7c0d 00              ??         00h
0000:7c0e 00              ??         00h
0000:7c0f 00              ??         00h
0000:7c10 00              ??         00h
0000:7c11 00              ??         00h
0000:7c12 00              ??         00h
0000:7c13 00              ??         00h
0000:7c14 00              ??         00h
0000:7c15 00              ??         00h
0000:7c16 00              ??         00h
0000:7c17 00              ??         00h
0000:7c18 00              ??         00h
0000:7c19 00              ??         00h
0000:7c1a 00              ??         00h
0000:7c1b 00              ??         00h
```

Exercise

Loading the unknown.bin in ghidra

Some check to int 13H (HDD or Floppy)

```
                        LAB_0000_7c5c                                   XREF[1]:     0000:7c03(j)
0000:7c5c 31 c0         XOR         AX,AX
0000:7c5e 8e d8         MOV         DS,AX
0000:7c60 30 d2         XOR         DL,DL
0000:7c62 cd 13         INT         0x13
0000:7c64 0f 82 1d 01   JC          LAB_0000_7d85
0000:7c68 31 c9         XOR         CX,CX

                        LAB_0000_7c6a                                   XREF[1]:     0000:7c7c(j)
0000:7c6a bb 85 7c      MOV         BX,0x7c85
0000:7c6d 01 cb         ADD         BX,CX
0000:7c6f 8b 07         MOV         AX,word ptr [BX]=>LAB_0000_7c85
0000:7c71 30 c8         XOR         AL,CL
0000:7c73 88 07         MOV         byte ptr [BX]=>LAB_0000_7c85,AL
0000:7c75 83 c1 01      ADD         CX,0x1
0000:7c78 81 fb fe 7d   CMP         BX,0x7dfe
0000:7c7c 7e ec         JLE         LAB_0000_7c6a
0000:7c7e eb 05         JMP         LAB_0000_7c85
```

A loop XORing data at 0x7C85.

XOR uses a variable key (register CL). It's both the index and the key.

Jumps to 0x7C85 but data at 0x7C85 is decrypted in real time. Static analysis cannot see it… ☹

Must use dynamic analysis ☺

```
for i in range(0x7dfe - 0x7c85):
    ram[0x7c85 + i] ^= i
```

Exercise

Loading the unknown.bin in qemu with gdb

Execute GDB
Connect to the gdbserver
Do some initialization to set the CPU and display layout

Launch qemu-system-i386 with a gdbserver socket and monitor socket

```
┌──(root💀 pc)-[/tmp/mbr]
└─# qemu-system-i386 -m 1M -fda unknown.bin -s -S  -monitor telnet:127.0.0.1:2222,server,nowait;
WARNING: Image format was not specified for 'unknown.bin' and probing guessed raw.
         Automatically detecting the format is dangerous for raw images, write operations on block 0 will be restricted.
```

```
QEMU [Paused]
Machine  View
SeaBIOS (version 1.14.0-2)

iPXE (http://ipxe.org) 00:03.0 CA00 PCI2.10 PnP PMM+00000000+00000000 CA00


Booting from Hard Disk...
Boot failed: could not read the boot disk

Booting from Floppy...
```

```
┌──(root💀 pc)-[/tmp/mbr]
└─# gdb  -ix gdb_init_real_mode.txt \
    -ex 'target remote localhost:1234' \
    -ex 'break *0x7c00' \
    -ex 'continue'
GNU gdb (Debian 10.1-1.7) 10.1.90.20210103-git
Copyright (C) 2021 Free Software Foundation, Inc.
License GPLv3+: GNU GPL version 3 or later <http://gnu.org/licenses/gpl.html>
This is free software: you are free to change and redistribute it.
There is NO WARRANTY, to the extent permitted by law.
Type "show copying" and "show warranty" for details.
This GDB was configured as "x86_64-linux-gnu".
Type "show configuration" for configuration details.
For bug reporting instructions, please see:
<https://www.gnu.org/software/gdb/bugs/>.
Find the GDB manual and other documentation resources online at:
    <http://www.gnu.org/software/gdb/documentation/>.

For help, type "help".
Type "apropos word" to search for commands related to "word".

warning: A handler for the OS ABI "GNU/Linux" is not built into this configuration
of GDB.  Attempting to continue with the default i8086 settings.

The target architecture is set to "i8086".

warning: A handler for the OS ABI "GNU/Linux" is not built into this configuration
of GDB.  Attempting to continue with the default i8086 settings.

Remote debugging using localhost:1234
warning: No executable has been specified and target does not support
determining executable automatically.  Try using the "file" command.
──────────────────────────[ STACK ]──
0000 0000 0000 0000 0000 0000 0000 0000
0000 0000 0000 0000 0000 0000 0000 0000
──────────────────────────[ DS:SI ]──
00000000: 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00  ................
00000010: 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00  ................
00000020: 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00  ....
00000030: 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00  ....
──────────────────────────[ ES:DI ]──
00000000: 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00  ....
00000010: 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00  ....
00000020: 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00  ....
00000030: 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00  ....
```

It runs and we have control in GDB

Exercise

Loading the unknown.bin in qemu with gdb

Approach:
- Set a breakpoint to 0x7c85
- Continue (let it decrypt)



Exercise

Loading the unknown.bin in qemu with gdb

Connect to the QEMU Control socket
Dump physical RAM (1MB)
This file can be loaded in ghidra and should contain the decrypted code! ☺

Can you recover the flags only with RE? (*)

```
┌──(user㉿pc)-[~]
└─$ telnet localhost 2222
Trying ::1...
Trying 127.0.0.1...
Connected to localhost.
Escape character is '^]'.
QEMU 5.2.0 monitor - type 'help' for more information
(qemu) pmemsave 0 1048576 mem-at-7c85
(qemu)
```

(*) there may be some additional steps involved. ☺
Analyze CFGs, rename, retype and combine with dynamic analysis whenever relevant
Enjoy the ASCII art and praise @zezadas for the great work with this binary.:

Dynamic Binary Instrumentation (DBI)

What are they

- DBI system as an application virtual machine that interprets the ISA of a specific platform
  - usually (but not always) coinciding with the one where the system runs
  - offering instrumentation capabilities to support monitoring and altering instructions and data from an analysis tool component
  - Up to the level of a single instruction

- DBI systems expand standard Dynamic Binary Analysis tasks by
  - Fine grained monitoring capabilities
  - Full control over data and instructions, potentially increasing Reverse Engineering Scope

- Uses
  - Measure performance, Detect vulnerabilities, Force code execution, Fuzz binary programs at the scale of a group of instructions

Dynamic Binary Instrumentation (DBI)

caveats

- DBI is vulnerable to specific attacks targeting the emulator
  - Purpose: avoid the use of emulators or induce incorrect results
  - Exploit the fact that DBI tools are slow
  - Exploit the fact that the system is emulated and differs from a real system

- Some approaches
  - Extensive loops Timing measurements
  - Timing measurements
  - Testing for system specific behavior

```
128  for ( n = 0; n < 2000000; ++n )
129  {
130    EnterCriticalSection(&CriticalSection);
131    mw_junk_0();
132    v6[1] = (int)v6;
133    v6[0] = 707220816;
134    *(_DWORD *)sz = dword_41A4F4;
135    CharUpperW(sz);
136    for ( ii = 0; ii < 5; ++ii )
137    {
138      v6[2] = -199066008;
139      v8 = 0;
140    }
141    LeaveCriticalSection(&CriticalSection);
142  }
143  DeleteCriticalSection(&CriticalSection);
```

Dynamic Binary Instrumentation (DBI)

What are they

- Instrumentation
  - Insert Code

- Dynamic Binary Instrumentation
  - “Running” Code



Dynamic Binary Instrumentation (DBI)

What are they

- Instrumentation
  - Insert Code

- Dynamic Binary Instrumentation
  - “Running” Code



Dynamic Binary Instrumentation (DBI)

What are they

- Instrumentation
  - Insert Code

- Dynamic Binary Instrumentation
  - “Running” Code



Dynamic Binary Instrumentation (DBI)

How they work?

- Rebuild a program binary code using some JIT technique
  - Insert trace points and hooks for inspection
  - Divert execution to **additional user specified functions**
  - Monitor access to memory regions
    - Potentially triggering callbacks on access
  - May reimplement access to IOs or even **`syscalls`** and interrupts
  - May create a fully Emulated Execution Environment
    - Can be combined with an Emulation platform such as QEMU or Unicorn (a fork from QEMU)
- Popular tools: valgrind, DynamoRIO, Intel PIN, DynInst, Qiling, Frida

Dynamic Binary Instrumentation (DBI)

APPLICATION DOMAIN	DBI PRIMITIVES								
	INSTRUCTIONS				SYSTEM CALLS	LIBRARY CALLS	THREADS & PROCESSES	CODE LOADING	EXCEPTIONS & SIGNALS
	MEMORY R/W	CALLS/RETS	BRANCHES	OTHER					
CRYPTOANALYSIS	✓	✓	✓	✓					
MALICIOUS SOFTWARE ANALYSIS	✓	✓	✓	✓	✓	✓	✓	✓	✓
VULNERABILITY DETECTION	✓	✓	✓	✓	✓	✓			
SOFTWARE PLAGIARISM	✓				✓				
REVERSE ENGINEERING	✓	✓	✓	✓	✓	✓			
INFORMATION FLOW TRACKING	✓	✓	✓	✓		✓			✓
SOFTWARE PROTECTION	✓	✓	✓	✓	✓	✓	✓	✓	✓

Daniele D'Elia et al, SoK: Using Dynamic Binary Instrumentation for Security, AsiaCCS, 2019

Dynamic Binary Instrumentation (DBI)

Why not FRIDA?

- Frida allows binary instrumentation of an executing binary
  - No emulation capabilities
  - Malicious code can de analyzed, but further care is required
- Landscape is wider with additional binaries
  - Firmwares
  - Shellcodes
  - DLLs
  - SOs

DBI with Qiling

DBI tool that can perform:

- **Emulation**: Executes binary code step by step, replacing instructions
- **Binary instrumentation**: allows injection of user specified code
- **Cross-platform and cross-architectural analysis**: analyze one architecture or OS on another
- **Sandboxing**: I/O is redirected to fake devices (files, sockets)
- **On raw binaries**: used to analyze blobs from binary devices or shellcode

DBI with Qiling

Emulation

- Syscalls and interrupt are implemented in python
  - Program calls syscall/interrupt
  - Qiling invokes handler in python, which mimics a standard system
  - Implementation can be overridden by the user

- Host OS is never called, and result is provided by Qiling
  - Advantages:
    - Great control over the execution
    - Great isolation
  - Disadvantages:
    - Not all calls are implemented
    - Behavior mimics an ideal system and may deviate from reality

DBI with Qiling

Instrumentation

- User can define hooks to triggering callbacks on an event
  - Because an emulator is translating code in real time, instruction level hooks are possible

- Example
  - Code execution reaches a specific address
  - An address is written or read
  - A function is called, or is leaving
  - An instruction is executed

DBI with Qiling

Cross Platform and Cross Architecture

- Binary code is emulated, allowing cross architecture execution
  - Target architecture instructions are compiled to native instructions

- Because all syscalls and interrupts are emulated, host platform can differ from target platform
  - As Qiling is based on Unicorn (Qemu), a wide range of possibilities is available

DBI with Qiling

Loading an Elf

- Qiling has several loaders
  - MBR
  - PE, ELF, MachO
  - Unstructured binary (shellcode)

```python
from qiling import *

def sandbox(path, rootfs):
    ql = Qiling(path, rootfs)
    ql.run()

if __name__ == '__main__':
    sandbox(['./hello'], '.')
```

- Loader will make code available to be **emulated** on a secure **rootfs**
  - Calls to interrupts and syscalls are implemented in python

```
[=]     brk(input = 0x0)
[=]     uname(address = 0x80000000d960)
[=]     access(path = 0x7ffff7dfa9b0, mode = 0x4)
[=]     openat(fd = 0xffffff9c, path = 0x7ffff7df7b67, flags = 0x80000, mode = 0x0)
[=]     openat(fd = 0xffffff9c, path = 0x80000000cef0, flags = 0x80000, mode = 0x0)
[=]     stat(path = 0x80000000cef0, buf_ptr = 0x80000000cfa0)
[=]     openat(fd = 0xffffff9c, path = 0x80000000cef0, flags = 0x80000, mode = 0x0)
[=]     stat(path = 0x80000000cef0, buf_ptr = 0x80000000cfa0)
[=]     openat(fd = 0xffffff9c, path = 0x80000000cef0, flags = 0x80000, mode = 0x0)
[=]     stat(path = 0x80000000cef0, buf_ptr = 0x80000000cfa0)
[=]     openat(fd = 0xffffff9c, path = 0x80000000cef0, flags = 0x80000, mode = 0x0)
[=]     stat(path = 0x80000000cef0, buf_ptr = 0x80000000cfa0)
[=]     openat(fd = 0xffffff9c, path = 0x80000000cef0, flags = 0x80000, mode = 0x0)
[=]     stat(path = 0x80000000cef0, buf_ptr = 0x80000000cfa0)
[=]     openat(fd = 0xffffff9c, path = 0x80000000cef0, flags = 0x80000, mode = 0x0)
[=]     stat(path = 0x80000000cef0, buf_ptr = 0x80000000cfa0)
[=]     openat(fd = 0xffffff9c, path = 0x80000000cef0, flags = 0x80000, mode = 0x0)
[=]     stat(path = 0x80000000cef0, buf_ptr = 0x80000000cfa0)
[=]     openat(fd = 0xffffff9c, path = 0x80000000cef0, flags = 0x80000, mode = 0x0)
[=]     read(fd = 0x3, buf = 0x80000000d0f8, len = 0x340)
[=]     fstat(fd = 0x3, buf_ptr = 0x80000000cfa0)
[=]     mmap(addr = 0x0, length = 0x1c4508, prot = 0x1, flags = 0x802, fd = 0x3, pgoffset = 0x0)
[=]     mprotect(start = 0x7fffb7dfb000, mlen = 0x196000, prot = 0x0)
[=]     mmap(addr = 0x7fffb7dfb000, length = 0x14b000, prot = 0x5, flags = 0x812, fd = 0x3, pgoffset = 0x25000)
[=]     mmap(addr = 0x7fffb7f46000, length = 0x4a000, prot = 0x1, flags = 0x812, fd = 0x3, pgoffset = 0x170000)
[=]     mmap(addr = 0x7fffb7f91000, length = 0x6000, prot = 0x3, flags = 0x812, fd = 0x3, pgoffset = 0x1ba000)
[=]     mmap(addr = 0x7fffb7f97000, length = 0x3508, prot = 0x3, flags = 0x32, fd = 0xffffffff, pgoffset = 0x0)
[=]     close(fd = 0x3)
[=]     mmap(addr = 0x0, length = 0x2000, prot = 0x3, flags = 0x22, fd = 0xffffffff, pgoffset = 0x0)
[=]     arch_prctl(ARCHX = 0x1002, ARCH_SET_FS = 0x7fffb7f9bf40)
[=]     mprotect(start = 0x7fffb7f91000, mlen = 0x3000, prot = 0x1)
[=]     mprotect(start = 0x555555557000, mlen = 0x1000, prot = 0x1)
[=]     mprotect(start = 0x7ffff7dff000, mlen = 0x1000, prot = 0x1)
[=]     fstat(fd = 0x1, buf_ptr = 0x80000000d630)
[=]     ioctl(fd = 0x1, cmd = 0x5401, arg = 0x80000000d590)
[=]     brk(input = 0x0)
[=]     brk(input = 0x55555557c000)
[=]     write(fd = 0x1, buf = 0x5555555b2a0, count = 0x6)
Hello [!]       0x7fffb7e9bc08: syscall ql_syscall_clock_nanosleep number = 0xe6(230) not implemented
[=]     write(fd = 0x1, buf = 0x5555555b2a0, count = 0x6)
World
[=]     exit_group(exit_code = 0x0)
```

DBI with Qiling

Overriding a library function

- Functions can be overridden with custom implementations
  - Code can access arguments of basic types (Strings, Ints, Floats)
  - Inside function, other external functions can be called
  - Entire set of registries and memory can be manipulated
  - Return is provided to the calling function to be **emulated** on a secure **rootfs**
  - Calls to interrupts and syscalls are implemented in python

```python
from qiling import *
from qiling.os.const import UINT
import time

def my_sleep(ql):
    args = ql.os.resolve_fcall_params({'seconds': UINT})
    seconds = args['seconds']
    print(f"Sleep: {seconds}")
    if seconds > 10:
        print("QL: Limiting sleep to 10s")
        time.sleep(10)
    else:
        time.sleep(seconds)

def sandbox(path, rootfs):
    ql = Qiling(path, rootfs, log_file="hello-2.log", verbose=0)
    ql.set_api('sleep', my_sleep)
    ql.run()

if __name__ == '__main__':
    sandbox(['./hello'], '.')
```