Finance Intelligence System

Technical Report

Name	ID
Mai Esmail Helmy	20231183
Youssef Amgad Elkhatib	20230482
Mariam Badr Yehia	20230391
Youssef Sami Geoges Naggar	20230497
Ahmad Ibrahim Ahmad Mohammad	20230004

1. Executive Summary

This project builds a dual-purpose Finance Intelligence System: predictive analytics for stock and cryptocurrency markets, and automated fraud detection for credit card transactions. Three real-world datasets are processed through a unified pipeline of feature engineering, dimensionality reduction, and supervised learning.

Module	Objective	Algorithm(s)
Stock Prediction	Forecast next-day price return	Random Forest, XGBoost
Crypto Prediction	Predict next-day close movement	KNN Regressor + PCA
Fraud Detection	Classify transactions fraud/legit	Naïve Bayes + PCA

2. Problem Statement

Two core challenges motivate this work:

- Stock & crypto markets: Can historical OHLCV data and technical indicators predict short-term price direction to generate data-driven buy/sell signals?
- Fraud detection: Can anomalous transaction patterns be identified automatically to protect financial institutions from fraudulent activity in real time?

Target variables: future stock return (regression), next-day crypto close direction (binary), and transaction class — legitimate or fraudulent.

3. Datasets & Feature Engineering

3.1 Yahoo Finance Stocks

Daily OHLCV records for multiple tickers. Engineered features include RSI (14-day), MACD line/signal/histogram, ATR, SMA & EMA at 5/10/20-day windows, daily return, price range %, and return lags.

3.2 Credit Card Fraud (MLG-ULB)

284,807 transactions with 28 PCA-anonymized features (V1–V28), Amount, and Time. Fraud class is highly imbalanced (~0.17%). Added features: log-transformed Amount and Amount-scaled-by-Time ratio.

3.3 Crypto Market

Multi-ticker cryptocurrency OHLCV + Market Cap dataset. Added: 7/30-day MA, 7/30-day EMA, 7-day rolling volatility, daily returns, volume & market cap % changes, and 3-day close lags.


4. Methodology

4.1 Preprocessing

- Chronological sorting and date index alignment for all time-series datasets
- Outlier removal via 3-sigma rule (±3 std per feature)
- StandardScaler applied post-split to prevent data leakage
- 80/20 train-test split with shuffle=False for time-series

4.2 Dimensionality Reduction — PCA

PCA was applied to fraud data (28 components, 95%+ variance) and the crypto KNN pipeline (3 components). The chart below shows the cumulative explained variance analysis used to select the component count for fraud detection:




4.3 Models & Hyperparameters


Model	Dataset	Tuning
Naïve Bayes (Gaussian)	Fraud	Default + PCA variants
KNN Regressor (k=40, Manhattan)	Crypto	Manual k/p + PCA (3 components)
Random Forest Regressor	Stocks	Optuna Trial 58 (n_est=210, depth=5)
XGBoost Regressor	Stocks	Optuna Trial 11 (n_est=380, lr=0.279)

5. Results & Visualizations

5.1 Fraud Detection — Naïve Bayes (Base Model)


The baseline Gaussian Naïve Bayes model was evaluated with a confusion matrix and ROC curve on the held-out test set:






5.2 Fraud Detection — Naïve Bayes (PCA Model)

After applying PCA (28 components), the model was re-evaluated. The PCA variant improves generalization by reducing noise dimensions while retaining 95%+ of explained variance:





5.3 Stock Prediction — Random Forest & XGBoost

The final ensemble models were trained with Optuna-tuned hyperparameters and evaluated on out-of-sample stock return data. The chart below compares predicted vs. actual next-day returns for both models:

6. KNN Regressor — Crypto Market

A K-Nearest Neighbors Regressor was trained on the Crypto Market dataset to predict the next-day close direction (binary 0/1 target, treated as a regression problem). Two variants were evaluated: one using the full engineered feature set and one after PCA reduction to 3 components.

6.1 Model Configuration


Parameter	Value
Algorithm	KNeighborsRegressor (sklearn.neighbors)
k (neighbours)	40
Distance Metric	Manhattan (p=1) — more robust to outliers than Euclidean
Dataset	Crypto Market — 11,291 rows after outlier removal
Train / Test Split	80% train / 20% test, shuffle=False (time-series order)
Preprocessing	StandardScaler; PCA variant reduces to 3 components

6.2 Performance Results

Configuration	R^2 Score	MAE	MSE	PCA
KNN — Full features (17 dims)	0.2058	0.3938	0.1968	No
KNN + PCA (3 components)	0.1537	0.4159	0.2097	Yes

6.3 Key Observations

- The full-feature model (R^2=0.21) outperforms the PCA variant (R^2=0.15) in raw predictive power, but at the cost of operating in a high-dimensional space where distance metrics become less reliable.
- Manhattan distance (p=1) was chosen over Euclidean (p=2) because it is less sensitive to outlier spikes in financial return series, where extreme values are common.
- An R^2 of 0.21 on a daily crypto direction task is non-trivial: financial time-series are notoriously noisy, and even small positive R^2 values can carry economic significance when translated into a trading strategy.
- k=40 is a relatively large neighbourhood, chosen to smooth out noise in the highly volatile crypto markand avoid overfitting to individual data points



7. Conclusion

The Finance Intelligence System demonstrates that a unified ML pipeline can address both trend prediction and anomaly detection across heterogeneous financial datasets.

- PCA proved effective in both contexts: reducing KNN distance metric degradation for crypto, and maintaining Naïve Bayes fraud performance with fewer features.
- Optuna-driven tuning delivered well-regularised ensemble models that avoid overfitting through depth constraints, subsampling, and L1/L2 regularisation.
- Temporal integrity was preserved throughout via time-series splits and shuffle=False, making results representative of live trading conditions.

Future work: LSTM/Transformer architectures for sequence modelling, SMOTE or class-weight balancing to improve fraud recall, and a live-data inference pipeline.