## BOM\_Ensor-384-32bit

Comment	Description	Designator	Footprint	Quantity	Suplier MOUSER
0.1uF	NON-POLARIZED CAP	C1, C2, C4, C17, C19, C21, C22	0603	7	80-C603C104K5RAC3121
10uF	NON-POLARIZED CAP	C3, C16, C20, C23, C24	0805	5	581-0805ZC106KAT2A
2.2uF	NON-POLARIZED CAP	C5	0805	1	581-08053C225JAT2A
.01uF	NON-POLARIZED CAP	C6	0603	1	80-C0603C103K2REAUTO
4.7uF	NON-POLARIZED CAP	C7, C8, C10, C11, C12, C13, C14, C15	0805	8	581-0805ZC475KAT2A
1uF	NON-POLARIZED CAP	C9, C18	0603	2	581-06033C105KAT2A
0.01uF	NON-POLARIZED CAP	C25	0603	1	80-C0603C103K2REAUTO
TPS73533QDRBRQ1	Automotive 500mA, Low Quiescent Current	IC1	SON65P300X300X100-9N	1	595-TPS73533DRBR
micro73A	Micrófono diferencial	MK1, MK2	micro73a	2	726-IM73A135V01XTSA1
	Socket (Female) Straight Through Hole 20 Position 2				
HDR2x20_2.54	Row 2.54	P1	HDR2X20	1	200-SSQ11001TD
Header 4	Header, 4-Pin	P2, P3	HDR1X4	2	NO MOUNT
10K	RESISTOR	R1	R0603	1	CRGCQ0603J10K
22	RESISTOR	R2	R0603	1	KTR03EZPF22R0
TLV320ADC6140IRTWR	ADC	U1	WQFN24_RTW_TEX	1	595-V320ADC6140IRTWT
24.576MHz	815-ASTX-H11-24.576T	X1	XT_3225_4	1	815-ASTX-H11-24.576T