```
7.19:           .ORIG x3005; start location
                LEA R2, DATA; takes address from x000B and offsets PC by that address, writes result to R2
                LDR R4, R2, #0; store value of address of R2 + 0 into R4 (data at address of result just written into R2 + 0  stored into R4)
LOOP            ADD R4, R4, #-3; R4: mem(R4-3), deincrements R4 by 3
                BRzp LOOP; loop if 0 or positive
                TRAP x25; stop process
DATA            .FILL x000B; any specified register will have value x000B (11)
                .END; end program
```

4 times

```
7.21:           .ORIG x3000; start location
                AND R0, R0, #0; initializing R0 to 0
                ADD R2, R0, #10; R2: mem(R0+10), stores value R0 plus 10 in R2
                LD R1, MASK; R1 is ptr, point to data starting at x8000
                LD R3, PTR1; R3 is ptr, point to data starting at x4000
LOOP            LDR R4, R3, #0; R4: mem(0 + R3), put into R4 data from address (R3+0)
                AND R4, R4, R1; AND R4 w/ R1, R4 set flag
                BRz NEXT; next line if zero
                ADD R0, R0, #1; R0: mem(R0+1), increments R0 by 1
NEXT            ADD R3, R3, #1; R3: mem(R3+1), increments ptr R3 by 1
                ADD R2, R2, #-1; R2: mem(R2-1), deincrements ptr R2 by 1
                BRp LOOP; loop if positive
                STI R0, PTR2; mem(mem(PTR2)) into R4 (storing this address into memory)
                HALT; stop
MASK            .FILL x8000; any specified register will have value in x8000
```

```
PTR1        .FILL x4000; any specified register will have value in x4000
PTR2        .FILL x5000; any specified register will have value in x5000
            .END; end program
```

See above for what the program does.

```
7.23:               .ORIG x3000; start location
                    LD R0, PTR; R0 is ptr, point to data in x4000
                    ADD R1, R0, #0; R1: mem(R0+0), stores value of R0 + 0 in R1
AGAIN               LDR R2, R1, #0; R4: mem(R1 + 0), put into R2 data from address R2+0
                    BRz CONT; go to "CONT" line if zero
                    ADD R1, R1, #1; R1: mem(R1+1), increments R1 by 1
                    BRnzp AGAIN; go to "AGAIN" line
CONT                ----------(a)
LOOP                LDR R3, R0, #0; R3: mem(0 + R0), put into R3 data from address (R0+0)
                    ----------(b)
                    NOT R4, R4; flip bits in R4 to make negative of R4, store in R4
                    ADD R4, R4, #1; R4: mem(R4+1), increments R4 by 1
                    ADD R3, R3, R4; add R3 with R4, store value in R3
                    BRnp NO; go to "NO" line if not 0
                    ----------(c)
                    ----------(d)
                    NOT R2, R0; flip bits in R0 to make negative of R0, store in R2
                    ADD R2, R2, #1; R2: mem(R2+1), increments R2 by 1
                    ADD R2, R1, R2; add R1 with R2, store value in R2
                    BRnz YES; go to "YES" line if negative or 0
                    ----------(e)
```

```
YES     AND R5, R5, #0; initialize R5 to 0
        ADD R5, R5, #1; R5: mem(R5+1), increments R5 by 1
        BRnzp DONE; if R3 = negative, 0, positive then stop program
NO      AND R5, R5, #0; initialize R5 to 0
DONE    HALT; stop
PTR     .FILL x4000; any specified register will have value in x4000
        .END; end program
```

a.:
b.:
c.:
d.:
e.:

```
7.24:   .ORIG x3000; start location
        AND R2, R2, #0; initialize R2 to 0
        ADD R2, R2, #4; R2: mem(R2+4), increments R2 by 4
LOOP    BRz DONE; halt program if R2 = 0
        ADD R2, R2, #-1; R2: mem(R2-1), deincrements ptr R2 by 1
        ADD R3, R3, R3; add R3 to itself, store value in R3 (double R3, store in R3)
        BR LOOP; loop regardless of register value
DONE    HALT; stop
        .END; end program
```

The error is that the ADD function on line 6 isn't adding the value in R2 to R3, and is instead just adding R3 to itself. To fix it, replace one of the last two R3s on that line with R2.