

-- Schéma SQL Complet - Brasil Burger

-- Base de données: PostgreSQL (Neon)

```
CREATE TYPE role_enum AS ENUM ('CLIENT', 'GESTIONNAIRE');
```

```
CREATE TYPE type_complement_enum AS ENUM ('BOISSON', 'FRITES');
```

```
CREATE TYPE type_commande_enum AS ENUM ('SUR_PLACE',  
'LIVRAISON', 'EMPORTE');
```

```
CREATE TYPE etat_commande_enum AS ENUM ('VALIDEE', 'ANNULEE');
```

```
CREATE TYPE type_produit_enum AS ENUM ('BURGER', 'MENU',  
'COMPLEMENT');
```

```
CREATE TYPE mode_paiement_enum AS ENUM ('WAVE', 'OM');
```

```
CREATE TABLE utilisateur (  
    id SERIAL PRIMARY KEY,  
    email TEXT NOT NULL UNIQUE,  
    mot_de_passe TEXT NOT NULL,  
    role role_enum NOT NULL,  
    created_at TIMESTAMPTZ DEFAULT now()  
);
```

```
CREATE TABLE client (  
    id INTEGER PRIMARY KEY REFERENCES utilisateur(id) ON DELETE  
    CASCADE,  
    nom TEXT NOT NULL,  
    prenom TEXT,
```

```
    telephone TEXT,  
    adresse TEXT  
);
```

```
CREATE TABLE gestionnaire (  
    id INTEGER PRIMARY KEY REFERENCES utilisateur(id) ON DELETE  
    CASCADE,  
    nom TEXT NOT NULL,  
    prenom TEXT  
);
```

-- Table burger

```
CREATE TABLE burger (  
    id SERIAL PRIMARY KEY,  
    nom TEXT NOT NULL,  
    description TEXT,  
    prix NUMERIC(10,2) NOT NULL CHECK (prix >= 0),  
    image TEXT,  
    archive BOOLEAN DEFAULT FALSE  
);
```

```
CREATE TABLE complement (  
    id SERIAL PRIMARY KEY,  
    nom TEXT NOT NULL,  
    type type_complement_enum NOT NULL,  
    image TEXT,  
    prix NUMERIC(10,2) NOT NULL CHECK (prix >= 0),
```

```
archive BOOLEAN DEFAULT FALSE  
);
```

```
CREATE TABLE menu (  
    id SERIAL PRIMARY KEY,  
    nom TEXT NOT NULL,  
    image TEXT,  
    archive BOOLEAN DEFAULT FALSE  
);
```

```
CREATE TABLE composition (  
    id SERIAL PRIMARY KEY,  
    menu_id INTEGER NOT NULL UNIQUE REFERENCES menu(id) ON  
DELETE CASCADE,  
    burger_id INTEGER NOT NULL REFERENCES burger(id) ON DELETE  
RESTRICT,  
    boisson_id INTEGER NOT NULL REFERENCES complement(id) ON  
DELETE RESTRICT,  
    frites_id INTEGER NOT NULL REFERENCES complement(id) ON  
DELETE RESTRICT  
);
```

```
CREATE TABLE zone (  
    id SERIAL PRIMARY KEY,  
    nom TEXT NOT NULL,  
    quartiers TEXT,  
    prix_livraison NUMERIC(10,2) NOT NULL DEFAULT 0 CHECK  
(prix_livraison >= 0)  
);
```

```
CREATE TABLE commande (  

```

```
id SERIAL PRIMARY KEY,  
date_commande TIMESTAMPTZ DEFAULT now(),  
type_commande type_commande_enum NOT NULL,  
etat etat_commande_enum NOT NULL DEFAULT 'VALIDEE',  
montant_total NUMERIC(12,2) NOT NULL DEFAULT 0 CHECK  
(montant_total >= 0),  
client_id INTEGER NOT NULL REFERENCES client(id) ON DELETE  
CASCADE,  
zone_id INTEGER REFERENCES zone(id),  
livreur_nom TEXT  
);
```

```
CREATE TABLE ligne_commande (  
id SERIAL PRIMARY KEY,  
commande_id INTEGER NOT NULL REFERENCES commande(id) ON  
DELETE CASCADE,  
type_produit type_produit_enum NOT NULL,  
produit_id INTEGER NOT NULL,  
quantite INTEGER NOT NULL DEFAULT 1 CHECK (quantite > 0),  
prix_unitaire NUMERIC(12,2) NOT NULL CHECK (prix_unitaire >= 0)  
);
```

```
CREATE TABLE paiement (  
id SERIAL PRIMARY KEY,  
date_paiement TIMESTAMPTZ DEFAULT now(),  
montant NUMERIC(12,2) NOT NULL CHECK (montant >= 0),  
mode_paiement mode_paiement_enum NOT NULL,  
commande_id INTEGER NOT NULL REFERENCES commande(id) ON  
DELETE CASCADE
```

);

CREATE INDEX idx_commande_client ON commande(client_id);

CREATE INDEX idx_commande_date ON commande(date_commande);

CREATE INDEX idx_ligne_commande_commande ON
ligne_commande(commande_id);

CREATE INDEX idx_burger_archive ON burger(archive);

CREATE INDEX idx_complement_type ON complement(type);

CREATE INDEX idx_complement_archive ON complement(archive);

CREATE INDEX idx_menu_archive ON menu(archive);