

Seaborn vs. Bokeh: A Comprehensive Guide to Python Visualization Libraries

OUTLINE :

- I. Introduction
- II. Seaborn Overview
- III. Bokeh Overview
- IV. Graph Types
 - 1. Seaborn Graphs
 - Line Plot
 - Scatter Plot
 - Bar Chart
 - Heatmap
 - 2. Bokeh Graphs
 - Line Plot
 - Scatter Plot
 - Bar Chart
 - Interactive Widgets
- V. Library Comparison
- VI. Conclusion

I. INTRODUCTION

This guide compares two prominent Python visualization libraries: **Seaborn** and **Bokeh**. Each is tailored to different use cases—Seaborn is a high-level interface for Matplotlib with a focus on statistical data visualization, while Bokeh excels in creating interactive, browser-based visualizations. By using examples from official sources, this guide helps you understand when and how to use these libraries effectively.

II. SEABORN OVERVIEW

Seaborn is designed to work seamlessly with **Pandas** and **Matplotlib**, offering a concise, high-level interface for generating informative and attractive statistical plots. Seaborn's core strength is its ability to handle complex datasets and automatically generate plots that are easy to interpret, making it particularly useful for exploratory data analysis and statistical modeling.

Key Features :

- **Integration with Pandas:** It directly supports DataFrames, making it easy to pass your data into visualization functions.
- **Automatic Estimation and Aggregation:** Automatically computes and visualizes summary statistics like means and confidence intervals.
- **Built-in Themes and Color Palettes:** Seaborn provides attractive default styles and color palettes that reduce the need for customization.
- **Statistical Plotting:** Built-in support for plots that visualize statistical relationships and distributions (e.g., box plots, violin plots, and pair plots).

III. BOKEH OVERVIEW

Bokeh, on the other hand, specializes in creating interactive, web-ready plots that can be embedded directly into websites or web applications. With its extensive customization and interactivity, Bokeh is ideal for users who need to build real-time dashboards or complex data applications.

Key Features :

- **Interactive Web Visualizations:** Bokeh enables you to create plots that are fully interactive, including hover tools, sliders, and panning.
- **Scalability:** Bokeh can efficiently render large datasets while maintaining smooth interactions, making it great for live streaming and real-time data dashboards.
- **Widgets and Custom Interactions:** Bokeh integrates with various UI widgets like sliders, buttons, and dropdowns to create rich interactive dashboards.
- **Integration with Flask/Django:** It can be integrated with web frameworks like Flask or Django, making it easy to embed visualizations into web applications.

IV. GRAPH TYPES


1. SEABORN GRAPHS

• LINE PLOT


Seaborn's line plot is ideal for visualizing continuous data or trends over time. It automatically handles the aggregation of data points and can display confidence intervals.

Use Case: Visualizing sales trends over time.

Code :

A screenshot of a code editor with a dark background. The code is written in Python and uses Seaborn and Pandas. It creates a DataFrame with 'day' and 'sales' columns and then plots a line graph titled 'Sales Over Time'.

```
import seaborn as sns
import pandas as pd
# Sample data
data = pd.DataFrame({
    'day': [1, 2, 3, 4, 5],
    'sales': [100, 150, 120, 180, 200]
})
# Create line plot
sns.lineplot(x='day', y='sales', data=data)
plt.title('Sales Over Time')
```



```
Text(0.5, 1.0, 'Sales Over Time')
```


• SCATTER PLOT

Scatter plots in Seaborn allow you to visualize the relationship between two continuous variables. Seaborn also supports built-in regression fitting for scatter plots using `regplot()`.

Use Case: Visualizing the relationship between advertising budget and sales revenue.

Code :

```
import seaborn as sns
import pandas as pd
# Sample data
data = pd.DataFrame({
    'budget': [1, 2, 3, 4, 5],
    'sales': [100, 150, 120, 180, 200]
})
# Create scatter plot
sns.scatterplot(x='budget', y='sales', data=data)
plt.title('Budget vs Sales')
```



```
Text(0.5, 1.0, 'Budget vs Sales')
```

• BAR CHART

Seaborn's bar plots are useful for visualizing categorical data and comparing multiple categories. They automatically aggregate data and provide error bars.


Use Case: Comparing sales performance across different regions.

Code :

```
import seaborn as sns
import pandas as pd
import matplotlib.pyplot as plt

# Sample data
data = pd.DataFrame({
    'region': ['North', 'South', 'East', 'West'],
    'sales': [100, 150, 180, 200]
})

# Create bar chart
sns.barplot(x='region', y='sales', data=data)
plt.title('Sales by Region')
```



```
Text(0.5, 1.0, 'Sales by Region')
```

+ Code + Markdown

• HEATMAP

Heatmaps in Seaborn are perfect for visualizing relationships between multiple variables by mapping their correlations or counts to colors.


Use Case: Visualizing a correlation matrix of a dataset's features.

Code :

```
import seaborn as sns
import pandas as pd
import matplotlib.pyplot as plt

# Sample correlation matrix
data = pd.DataFrame({
    'Feature1': [1, 2, 3, 4],
    'Feature2': [4, 3, 2, 1],
    'Feature3': [2, 3, 4, 5]
})
corr = data.corr()

# Create heatmap
sns.heatmap(corr, annot=True, cmap='coolwarm')
plt.title('Correlation Matrix')
```



```
Text(0.5, 1.0, 'Correlation Matrix')
```

+ Code + Markdown

2. BOKEH GRAPHS

- LINE PLOT

Bokeh's line plots allow users to create dynamic, interactive line charts with hover, zoom, and pan capabilities, making them suitable for real-time data visualizations.

Use Case: Visualizing the stock prices of a company over time in an interactive dashboard.

Code :



• SCATTER PLOT

Scatter plots in Bokeh enable interactive exploration of the relationships between variables, with tooltips displaying the exact values of data points on hover.

Use Case: Visualizing employee performance scores and their sales metrics interactively.

Code :

```
from bokeh.plotting import figure, show
from bokeh.io import output_notebook


output_notebook()

# Sample data
x = [1, 2, 3, 4, 5]
y = [6, 7, 8, 9, 10]

# Create figure
p = figure(title="Interactive Scatter Plot", x_axis_label='Budget', y_axis_label='Sales')

# Add scatter points
p.scatter(x, y, size=10)

# Show plot
show(p)
```



• BAR CHART

Bokeh's bar charts support interactivity and can be customized with hover tooltips and other interactive elements to enhance user experience.

Use Case: Creating an interactive bar chart to compare the sales of different products over time.

Code:



• INTERACTIVE WIDGETS

Bokeh's widgets enable dynamic user interaction, allowing users to modify plot elements such as sliders, buttons, and dropdowns.

Use Case: Creating an interactive slider to control data points dynamically.

Code :

```
from bokeh.layouts import column
from bokeh.models import Slider
from bokeh.plotting import figure, show
from bokeh.io import output_notebook

output_notebook()

# Sample data
categories = ['A', 'B', 'C']
values = [10, 20, 15]


# Create figure
p = figure(x_range=categories, title="Adjustable Bar Chart", y_axis_label='Values')

# Add bars
p.vbar(x=categories, top=values, width=0.9)

# Create slider widget
slider = Slider(start=0, end=50, value=10, step=1, title="Adjust Values")

# Create layout
layout = column(slider, p)

# Show plot
show(layout)
```



Column(id='p1512', ...)

+ Code + Markdown

V. LIBRARY COMPARISON

Aspect	Seaborn	Bokeh
Ease of Use	High-level abstraction with default styling, easy to get started.	Requires more configuration but highly customizable and interactive.
Customization	Offers pre-set themes but with limited fine-grain control.	Full control over styling and layout, with support for widgets.
Interactivity	Primarily for static plots; minimal interactivity.	Highly interactive, ideal for dashboards and real-time applications.
Performance	Handles large datasets well for static visualizations.	Efficient rendering of large datasets, especially in web-based applications.
Best Use Case	Ideal for creating polished, static plots for data exploration.	Best for interactive web applications and real-time visualizations.

VI. CONCLUSION

Both Seaborn and Bokeh are valuable tools in Python for data visualization. Seaborn simplifies the process of creating attractive, static statistical plots, making it perfect for exploratory analysis and reports. In contrast, Bokeh excels in interactivity, especially for real-time data visualizations and web-based applications.