



# Data analysis with the shell

Spring 2021  
PCfB Class 3  
January 29, 2021

## UNIX SHELL



# Outline

- Installing/running programs
- ‘for’ loops
- Shell scripts
- Assignment

**Installing/running  
programs**

**Computers only understand their  
native machine language**

# 2 types of programming languages

# Permissions ('ls -l')

permissions	user	group	size	date		file/directory
drwxr-xr-x	2 paul	users	1024	Jan	2 23:50	.
drwxr-xr-x	6 root	root	1024	Jan	2 22:51	..
drwxr-xr-x	3 paul	users	1024	Jan	8 11:42	grassdata
lrwxrwxrwx	1 paul	users	13	May	6 1998	latex -> /d2/lt
drwx-----	2 paul	users	1024	Mar	8 17:30	mail
drwx-----	2 paul	users	1024	Feb	4 01:09	projects
-rw-r--r--	1 paul	users	844344	Dec	9 1998	nations.ps
-rw-rw-r--	1 paul	users	21438	Mar	2 21:47	ps4mf.txt

↑

↑

↑

↑

other (world) permissions

group permissions

user permissions

d : directory

- : file

l : link (to other file/directory)

r : read permission

w : write permission

x : execute permission (programm)

- : permission not set

# Changing Permissions

chmod (change mode)

Add execute for User: `chmod u+x file.txt`

Add read and write for Group: `chmod g+rw file.txt`

Remove write and execute for Other: `chmod o-wx file.txt`

All three in one command: `chmod u+x,g+rw,o-wx file.txt`

# \$PATH

- A list of directories
  - Locations your computer looks for command-line software
- Searched in the order listed
- To view: `echo $PATH`
- To add a directory: `PATH="$PATH:path/to/new/dir"`



# Recommendation

- Create three directories in your home directory:
  - *scripts* (your own custom scripts, PCfB p. 85-88)
  - *programs* (ready-to-use code downloaded from others)
  - *source* (source code that needs to be compiled)
- Add *scripts* and *programs* to \$PATH

# Dependencies

Installing  
program  
demo

**‘for’ loops**

# for loop

- Simple, but powerful way to repeatedly execute the same commands for different files, parameter values, etc.
- Can be included in scripts or run directly on command line

# Basic syntax

```
for file in *.sh; do chmod u+x $file; done
```

# ‘for’ loop examples

```
for file in *.fasta;  
do print_fasta_seq_lengths.py $file;  
done
```

```
for file in *.txt; do cp $file copy_$file;  
mkdir dir_$file; mv $file dir_$file; done
```

**‘for’ loop**

**demo**



# Shell scripts

# Why use shell scripts?

- Automate a series of commands
  - particularly useful when each command takes a long time to run
- Creates a record of commands that have been run
- Easy format for rerunning commands

# Two ways to specify the interpreter to use

# Specify interpreter inside script

```
1  #!/bin/bash~  
2  ~  
3  mkdir test~  
4  cd test~
```

# File extensions

- Recommended (but not required) to save script with specific file extension
- Allows recognition from file name
- Syntax-specific coloring in text editors
- For shell script:

# Shell + Regexp method

1. Use the shell to generate a list of files/directories
2. Use regular expressions within your text editor to turn those file/directory names into a list of commands

# Shell script demo