

FEM Solver Pro — Report di Calcolo

1. Dati Struttura

Elemento	Parametri
Nodo N1	x=2.000 m, y=4.000 m
Nodo N2	x=-1.000 m, y=0.000 m
Nodo N3	x=5.000 m, y=4.000 m
Nodo N4	x=5.000 m, y=2.000 m
Nodo N5	x=5.000 m, y=0.000 m
Nodo N6	x=0.500 m, y=2.000 m
Trave T1	N2→N1, L=5.000m, EI=10000.0, EA=100000.0
Trave T2	N1→N3, L=3.000m, EI=10000.0, EA=100000.0
Trave T3	N3→N5, L=4.000m, EI=10000.0, EA=100000.0
Trave T4	N6→N4, L=4.500m, EI=10000.0, EA=100000.0
Vincolo @ N6	Carrello
Vincolo @ N5	Incastro
Vincolo @ N4	Cerniera
Vincolo @ N1	Cerniera
Vincolo @ N2	Carrello
Carico C1	uniforme su T1, val=10.0

2. Reazioni Vincolari

Nodo	Componente	Valore	Unità
N1	Rx	-41.724495	kN
N1	Ry	+4.123740	kN
N2	Ry	+34.548684	kN
N4	Rx	+0.000000	kN
N4	Ry	+0.000000	kN
N5	Rx	+1.724495	kN
N5	Ry	-8.672424	kN
N5	Mz	-2.234659	kN·m
N6	Ry	+0.000000	kN

3. Spostamenti Nodali

Nodo	ux [m]	uy [m]	ϕ [rad]
N1	+0.000000e+00	+0.000000e+00	+2.017861e-03
N2	+2.303246e-03	+0.000000e+00	-3.060318e-03
N3	+5.173486e-05	+3.468970e-04	-4.857329e-04
N4	+0.000000e+00	+0.000000e+00	+0.000000e+00

N5	+0.000000e+00	+0.000000e+00	+0.000000e+00
N6	+0.000000e+00	+0.000000e+00	+0.000000e+00

4. Azioni Interne (max per trave)

Trave	M _max [kNm]	V _max [kN]	N _max [kN]
T1	20.8333	13.9565	27.6389
T2	21.3539	15.1489	1.7245
T3	4.6633	1.7245	8.6724
T4	0.0000	0.0000	0.0000