LGKP AD 2.1 AERODROME LOCATION INDICATOR AND NAME

LGKP – KARPATHOS

LGKP AD 2.2 AERODROME GEOGRAPHICAL AND ADMINISTRATIVE DATA

1	ARP coordinates and site at AD	352516N 0270845E Centre of RWY 12/30
2	Direction and distance from (city)	BRG: 205º, 7 NM from the village.
3	Elevation/Reference temperature	20.20 M (66.27 FT) / 30.10°C.
4	Geoid undulation at AD ELEV PSN	NIL
5	MAG VAR/Annual change	5º E (JAN 2024) / 5'30"E.
6	AD Administration, address, telephone, telefax, telex, AFS	Hellenic Aviation Service Provider (HASP) Karpathos Airport GR 85700, KARPATHOS TEL: +30 22450 91120, 91047 FAX: +30 22450 91012 AFTN: LGKPYDYX e-mail: kakptl@hasp.gov.gr
7	Types of traffic permitted (IFR/VFR)	IFR - VFR
8	Remarks	NIL

LGKP AD 2.3 OPERATIONAL HOURS

1	AD Administration	HO
2	Customs and immigration	HO
3	Health and sanitation	HO
4	AIS Briefing Office	HO
5	ATS Reporting Office (ARO)	HO (TEL: +30 22450 91120)
6	MET Briefing Office	HO (MET)
7	ATS	HO
8	Fuelling	HO
9	Handling	HO
10	Security	HO
11	De-icing	NIL
12	Remarks	NIL

LGKP AD 2.4 HANDLING SERVICES AND FACILITIES

1	Cargo-handling facilities	NIL
2	Fuel/oil types	Fuel: JP8: by EKO and GISSCO. Oil: NIL
3	Fuelling facilities/capacity	EKO and GISSCO
4	De-icing facilities	NIL
5	Hangar space for visiting aircraft	NIL
6	Repair facilities for visiting aircraft	NIL
7	Remarks	NIL

LGKP AD 2.5 PASSENGER FACILITIES

1	Hotels	At the village.
2	Restaurants	At the village.
3	Transportation	Taxi.
4	Medical facilities	First aids, Motor ambulance.
5	Bank and Post Office	NIL
6	Tourist Office	NIL
7	Remarks	NIL

LGKP AD 2.6 RESCUE AND FIRE FIGHTING SERVICES

1	AD category for fire fighting	CIV CAT: 6
2	Rescue equipment	Equivalent for CAT 6 requirements.
3	Capability for removal of disabled aircraft	NIL
4	Remarks	NIL

LGKP AD 2.7 SEASONAL AVAILABILITY - CLEARING

1	Types of clearing equipment	NIL
2	Clearance priorities	NIL
3	Remarks	All seasons.

LGKP AD 2.8 APRONS, TAXIWAYS AND CHECK LOCATIONS/POSITIONS DATA

1	Apron surface and strength	Surface: Asphalt. Strength: PCN 53/F/D/X/U.
2	Taxiway designation width, surface and strength	Width: 28 M. Surface: Asphalt. Strength: NIL.
3	Altimeter checkpoint location and elevation	NIL
4	VOR checkpoints	NIL
5	INS checkpoints	NIL
6	Remarks	NIL

LGKP AD 2.9 SURFACE MOVEMENT GUIDANCE AND CONTROL SYSTEM AND MARKINGS

1	Use of aircraft stand ID signs, TWY guide lines and visual docking/parking guidance system of aircraft stands	Taxiing guidance by Marshaller.
2	RWY and TWY markings and LGT	LGT: RWY: Threshold, end, edge, RTIL. TWY: Edge (blue). Markings: RWY: CL and Threshold TWY: CL
3	Stop bars	NIL
4	Remarks	West parallel TWY marked and lighted as RWY. See also **LGKP AD chart ICAO**

LGKP AD 2.10 AERODROME OBSTACLES

In approach/TKOF areas			**In circling area and at AD**		**Remarks**
1			**2**		**3**
RWY NR/ Area affected	**Obstacle type Elevation Markings/LGT**	**Coordinates**	**Obstacle type Elevation Markings/LGT**	**Coordinates**	
a	**b**	**c**	**a**	**b**	
12	See relevant LGKP AOC chart-ICAO				NIL
30	See relevant LGKP AOC chart-ICAO				

LGKP AD 2.11 METEOROLOGICAL INFORMATION PROVIDED

1	Associated MET Office	KARPATHOS / III
2	Hours of service MET Office outside hours	HO HTAF REGIONAL METEOROLOGICAL CENTRE LARISSA
3	Office responsible for TAF preparation Periods of validity	HTAF REGIONAL METEOROLOGICAL CENTRE LARISSA 9 HR
4	Trend forecast Interval of issuance	NO TREND

5	Briefing/consultation provided	Personal consultation. Telephone.
6	Flight documentation Language(s) used	Tabular forms Greek, English
7	Charts and other information available for briefing or consultation	SWH, SWL, W, T, MW
8	Supplementary equipment available for providing information	Online data connection to the data Bank of the Hellenic National Meteorological Service.
9	ATS units provided with information	KARPATHOS AFIS.
10	Additional information (limitation of service, etc.)	All data over FL100 are issued by World Area Forecast Centres. TEL: +30 22450 91035, +30 6983526332.

LGKP AD 2.12 RUNWAY PHYSICAL CHARACTERISTICS

Designations RWY NR	TRUE BRG	Dimensions of RWY (M)	Strength (PCN) and surface of RWY and SWY	THR coordinates RWY end coordinates THR geoid undulation	THR elevation and highest elevation of TDZ of precision APP RWY
1	2	3	4	5	6
12	124.58º	2399 x 30	PCN 53/F/D/X/U Asphalt	352535.43N 0270810.36E	THR 11.13 M / 36.51 FT. TDZ: NIL
30	304.59º	2399 x 30	PCN 53/F/D/X/U Asphalt	352456.77N 0270918.86E	THR 18.92 M / 62.06 FT. TDZ: NIL

Designations RWY NR	Slope of RWY-SWY	SWY dimensions (M)	CWY dimensions (M)	Strip dimensions (M)	RESA dimensions (M)	OFZ	Remarks
1	7	8	9	10	11	12	13
12	NIL	NIL	NIL	2519 x 150	NIL	NIL	See also LGKP AD and AOC chart-ICAO. Shoulders 7.5 M on both sides. Arresting cable 352 M FM THR 30.
30	NIL	NIL	NIL	2519 x 150	NIL	NIL	

LGKP AD 2.13 DECLARED DISTANCES

RWY Designator	TORA (M)	TODA (M)	ASDA (M)	LDA (M)	Remarks
1	2	3	4	5	6
12	2399	2399	2399	2249	THR RWY 12 displaced 150 M
30	2399	2399	2399	2249	THR RWY 30 displaced 150 M

LGKP AD 2.14 APPROACH AND RUNWAY LIGHTING

RWY Designator	APCH LGT Type Length Intensity	THR LGT Colour Wingbars	PAPI VASIS Angle (MEHT)	TDZ, LGT Length	RWY Centre-line LGT Length Spacing, Colour Intensity	RWY edge LGT Length Spacing Colour Intensity	RWY End LGT Colour Wingbars	SWY LGT Length Colour	Remarks
1	2	3	4	5	6	7	8	9	10
12	NIL	Green - RTIL	PAPI LEFT / 3.1° (16.25 M)	NIL	NIL	White LIH	Red -	NIL	See LGKP AD chart-ICAO.
30	Simple Approach Lighting system	Green - RTIL	PAPI LEFT / 3° (19 M)	NIL	NIL	White LIH	Red -	NIL	

LGKP AD 2.15 OTHER LIGHTING, SECONDARY POWER SUPPLY

1	ABN/IBN location, characteristics and operational hours	ABN: NIL IBN: NIL
2	LDI location and LGT Anemometer location and LGT	LDI: NIL. WDI: 2 WDI. Anemometers: 2.
3	TWY edge and centre line lighting	Edge: Blue.
4	Secondary power supply/switch-over time	Available
5	Remarks	Apron: Flood lights. Short RWY 13/31 is used only as TWY, although lighted as RWY.

LGKP AD 2.16 HELICOPTER LANDING AREA

1	Coordinates TLOF or THR of FATO Geoid undulation	NIL
2	TLOF and/or FATO elevation M/FT	NIL
3	TLOF and FATO area dimensions, surface, strength, marking	NIL
4	True BRG of FATO	NIL
5	Declared distance available	NIL
6	APP and FATO lighting	NIL
7	Remarks	See **LGKP AD 2.20.4**

LGKP AD 2.17 ATS AIRSPACE

1	Designation and lateral limits	KARPATHOS CTR: Circle, 15 NM radius centred at 352516N 0270845E (ARP).
		KARPATHOS ATZ: Circle, 5 NM radius cent red at 352516N 0270845E (ARP).
2	Vertical limits	CTR: SFC to 7000 FT ALT.
		ATZ: SFC to 2000 FT ALT.
3	Airspace classification	CLASS D**
4	ATS unit call sign Language(s)	CTR: IRAKLION APPROACH (during KARPATHOS Airport Operational Hours) / ATHINAI CONTROL (when KARPATHOS airport is closed) Greek, English.
		ATZ: KARPATHOS TWR* KARPATHOS INFORMATION** Greek, English.
5	Transition altitude	6000 FT.
6	Hours of applicability	As ATS operational hours (see **AD 2.3**). Out of ATS operational hours, **ENR 1.4.2.1.3** applies.
7	Remarks	AFIS is provided to KARPATHOS airport at present. * When air traffic control is provided to KARPATHOS airport. ** When AFIS is provided to KARPATHOS airport, the airspace within the lateral and vertical limits of KARPATHOS CTR at and below 2000FT is designated as RMZ and is classified as CLASS G. Pilots shall establish radio contact and maintain continuous air-ground communication watch on the appropriate frequency in the RMZ KARPATHOS INFORMATION. Above 2000FT is classified as class D (see **ENR 2.1.5.4** IRAKLION TMA).

LGKP AD 2.18 ATS COMMUNICATION FACILITIES

Service designation	Call sign	Frequency/ VHF CH	Operational hours	Remarks
1	2	3	4	5
AFIS	KARPATHOS INFORMATION	123.200 122.100 257.800 MHz 121.500 243.000 MHz	HO HO HO HO HO	Primary freq. Coverage FL 030 / 15 NM. RGA. MIL RGA. Emergency. MIL Emergency.
G/A/G	KARPATHOS RADIO	5637 kHz 2989 kHz	HO: 0400 – 1700 HO: 1700 – 0400	Primary freq. Primary freq.
ATS Communication Facilities: HF & VHF under responsibility of HASP, MIL frequencies under responsibility of HAF.				

LGKP AD 2.19 RADIO NAVIGATION AND LANDING AIDS

Type of aid MAG VAR CAT of ILS/MLS (For VOR/ILS/MLS, give declination)	ID	Frequency (CH)	Hours of operation	Position of transmitting antenna coordinates	Elevation of DME transmitting antenna	Remarks
1	2	3	4	5	6	7
KARPATHOS VOR/DME (5°E/2024) (5°E)	KPC	111.40 MHz (CH 51X)	H24	352518.56N 0270848.88E	39 FT / 11.79 M	Coverage FL 500 / 50 NM, 120° – 190° 100 NM
KARPATHOS L (5°E/2024)	KRC	314 kHz	H24	352510.77N 0270900.91E	-	Coverage 25 NM
All Radio Navigation and Landing Aids under responsibility of HASP. See also **GEN 2.5** and **ENR 4**						

LGKP AD 2.20 LOCAL TRAFFIC REGULATIONS

2.20.1 Airport regulations

NIL

2.20.2 Taxiing to and from stands

2.20.2.1 Pilots of jet aircraft are requested to use low power when TAXIING on the Apron.

2.20.2.2 All aircraft entering the apron shall use the south apron TWY link unless otherwise communicated by Airport Authority via ATS. All aircraft exiting the apron shall use the TWY link as communicated by Airport Authority. In most case aircraft exiting the apron should use the north apron TWY link.

2.20.3 Parking area for small aircraft (General aviation)

NIL

2.20.4 Parking area for helicopters

2.20.4.1 An area in the Apron which, pending on the AD traffic and parking availability, is specified each time by the AD operator.

2.20.5 Apron - taxiing during winter conditions

NIL

2.20.6 Taxiing - limitations

NIL

2.20.7 School and training flights - technical test flights - use of runways

NIL

2.20.8 Helicopter traffic - limitation

NIL

2.20.9 Removal of disabled aircraft from runways

NIL

LGKP AD 2.21 NOISE ABATEMENT PROCEDURES
Part I

2.21.1 Noise abatement procedures for jet aeroplanes irrespective of weight, and for propeller and turboprop aeroplanes with MTOM of or above 11 000 KG

2.21.1.1 General provisions

NIL

2.21.1.2 Use of the runway system during the day period 0600-2200 (0500-2100)

NIL

2.21.1.3 Use of the runway system during the night period 2200-0600 (2100-0500)

NIL

2.21.1.4 Restrictions

NIL

2.21.1.5 Reporting

NIL

Part II

2.21.2 Noise abatement procedures for propeller and turboprop aeroplanes with MTOM below 11 000 KG

2.21.2.1 Use of the runway system during the day period 0600-2300 (0500-2200)

NIL

2.21.2.2 Use of the runway system during the night period 2300-0600 (2200-0500)

NIL

2.21.2.3 Reporting

NIL

Part III

2.21.3 Noise abatement procedures for helicopters

2.21.3.1 General provisions

NIL

2.21.3.2 Use of the runway system during the day period 0600-2300 (0500-2200)

NIL

2.21.3.3 Use of the runway system during the night period 2300-0600 (local time)

NIL

2.21.3.4 Reporting

NIL

LGKP AD 2.22 FLIGHT PROCEDURES

2.22.1 General

2.22.1.1 All aircraft within IRAKLION TMA KARPATHOS AREA shall contact IRAKLION APP for instructions (see **LGIR AD 2.18**).

2.22.1.2 RWY 12 / 30 not visible from AFIS site in the Terminal building.

2.22.1.3 For AFIS see **AD 1.1.6.2**.

2.22.2 Runway in use

2.22.2.1 RWY 12 / 30

2.22.2.2 ATTN: Previous and short RWY 13/31 is available only for TWY although marked and lighted as RWY

2.22.3 Procedures for IFR flights within IRAKLION TMA KARPATHOS AREA

2.22.3.1 See **LGIR AD 2.22** and relevant LGKP IAC charts-ICAO (**LGKP AD 2.24**).

2.22.4 Radar procedures within IRAKLION TMA KARPATHOS AREA

2.22.4.1 Within IRAKLION TMA KARPATHOS AREA (see **ENR 2.1.5.4**) radar service is not available below 4000ft.

2.22.4.2 Within IRAKLION TMA KARPATHOS AREA (see **ENR 2.1.5.4**) only radar monitoring will be provided from 4000-6000ft.

2.22.4.3 Within IRAKLION TMA KARPATHOS AREA (see **ENR 2.1.5.4**) radar vectoring can be provided above 6000ft (See **LGIR AD 2.22.4.3.2**).

2.22.5 Procedures for VFR flights within IRAKLION TMA KARPATHOS AREA

2.22.5.1 VFR flights entering IRAKLION TMA KARPATHOS AREA, shall follow VFR routes and altitudes, unless other clearance is provided by IRAKLION APP.

2.22.6 Procedures for VFR flights within KARPATHOS CTR

2.22.6.1 See relevant VFR routes KARPATHOS AREA chart (AD 2-LGKP-VFR).

2.22.7 Standard instrument departure procedure (SID)

2.22.7.1 See relevant LGKP SID charts-ICAO (LGKP AD 2.24).

LGKP AD 2.23 ADDITIONAL INFORMATION

2.23.1 Bird concentrations in the vicinity of the airport

2.23.1.1 No significant concentration of birds on and at the vicinity of airport during daylight hours. See also **ENR 5.6**.

LGKP AD 2.24 CHARTS RELATED TO AERODROME

Chart name	Date	Page
Aerodrome Chart – ICAO: - KARPATHOS Airport	02 JAN 20	AD 2-LGKP-ADC
Aircraft Parking/ Docking Chart – ICAO: -	NIL	NIL
Aerodrome Obstacle Chart (AOC) - ICAO, Type A: - RWY 12/30 / LGKP AOC	02 JAN 20	AD 2-LGKP-AOC A-1
Aerodrome Obstacle Chart (AOC) – ICAO, Type B: -	NIL	NIL
Precision Approach Terrain Chart – ICAO: -	NIL	NIL
Instrument Approach Chart (IAC) – ICAO: - VOR RWY 12	21 MAR 24	AD 2-LGKP-IAC-1
Instrument Approach Chart (IAC) – ICAO: - VOR RWY 30	21 MAR 24	AD 2-LGKP-IAC-2
Visual Approach Chart (VAC) – ICAO: -	NIL	NIL
Standard Departure Chart - Instrument (SID) – ICAO: - RWY 12	04 SEP 25	AD 2-LGKP-SID-1
Standard Departure Chart - Instrument (SID) – ICAO: - RWY 30	04 SEP 25	AD 2-LGKP-SID-2
Standard Arrival Chart - Instrument (STAR) – ICAO: -	NIL	NIL
TMA - VFR routes: - VFR routes KARPATHOS AREA (IRAKLION TMA)	16 APR 26	AD 2-LGKP-VFR
ATC Surveillance Minimum Altitude Chart (ASMAC) – ICAO: - IRAKLION TMA (KARPATHOS AREA)	21 MAR 24	AD 2-LGKP-ASMAC

LGKP AD 2.25 VISUAL SEGMENT SURFACE (VSS) PENETRATION