LGPA AD 2.1 AERODROME LOCATION INDICATOR AND NAME

LGPA – PAROS

LGPA AD 2.2 AERODROME GEOGRAPHICAL AND ADMINISTRATIVE DATA

1	ARP coordinates and site at AD	370115N 0250647E Centre of RWY.
2	Direction and distance from (city)	BRG 203°, 8 KM from Paros Port.
3	Elevation/Reference temperature	38 M (125 FT) / 31.13°C.
4	Geoid undulation at AD ELEV PSN	37 M.
5	MAG VAR/Annual change	5°E (JAN 2024) / 5´37´´E.
6	AD Administration, address, telephone, telefax, telex, AFS	Hellenic Aviation Service Provider (HASP) Paros Airport GR 84400, PAROS TEL: +30 22840 90500 AFTN: LGPAYDYX Email: kapa@hasp.gov.gr
7	Types of traffic permitted (IFR/VFR)	VFR
8	Remarks	NIL

LGPA AD 2.3 OPERATIONAL HOURS

1	AD Administration	HO
2	Customs and immigration	NIL
3	Health and sanitation	NIL
4	AIS Briefing Office	HO
5	ATS Reporting Office (ARO)	HO (TEL: +30 22840 90505).
6	MET Briefing Office	HO (MET)
7	ATS	HO
8	Fuelling	NIL
9	Handling	HO
10	Security	HO
11	De-icing	NIL
12	Remarks	NIL

LGPA AD 2.4 HANDLING SERVICES AND FACILITIES

1	Cargo-handling facilities	NIL
2	Fuel/oil types	Fuel: NIL Oil: NIL
3	Fuelling facilities/capacity	NIL
4	De-icing facilities	NIL
5	Hangar space for visiting aircraft	NIL
6	Repair facilities for visiting aircraft	NIL
7	Remarks	NIL

LGPA AD 2.5 PASSENGER FACILITIES

1	Hotels	At Paros town.
2	Restaurants	At Paros town.
3	Transportation	Taxis and Bus.
4	Medical facilities	Medical Centre at Paros town.
5	Bank and Post Office	At Paros town.
6	Tourist Office	NIL
7	Remarks	NIL

LGPA AD 2.6 RESCUE AND FIRE FIGHTING SERVICES

1	AD category for fire fighting	CIV CAT: 5
2	Rescue equipment	Equivalent for CAT 5 requirements.
3	Capability for removal of disabled aircraft	Tow bars available on request from Goldair Handling.
4	Remarks	NIL

LGPA AD 2.7 SEASONAL AVAILABILITY - CLEARING

1	Types of clearing equipment	NIL
2	Clearance priorities	NIL
3	Remarks	All seasons.

LGPA AD 2.8 APRONS, TAXIWAYS AND CHECK LOCATIONS/POSITIONS DATA

1	Apron surface and strength	Surface: Asphalt. Strength: PCN 50/F/B/X/U.
2	Taxiway designation, width, surface and strength	Width: 23 M Surface: Asphalt. Strength: PCN 50/F/B/X/U.
3	Altimeter checkpoint location and elevation	NIL
4	VOR checkpoints	NIL
5	INS checkpoints	NIL
6	Remarks	NIL

LGPA AD 2.9 SURFACE MOVEMENT GUIDANCE AND CONTROL SYSTEM AND MARKINGS

1	Use of aircraft stand ID signs, TWY guide lines and visual docking/parking guidance system of aircraft stands	Taxiing guidance on Marshaller instructions.
2	RWY and TWY markings and LGT	LGT: RWY 17: Threshold, edge, end, RTIL. RWY 35: Threshold, edge, end, RTIL. TWY: Edge. Markings: RWY: THR, designations, centre line, side stripes, touch down zones, fixed distance, turnpad marking. TWY: Centre line, holding position.
3	Stop bars	NIL
4	Remarks	Guidance on the apron by marshaller.

LGPA AD 2.10 AERODROME OBSTACLES

In approach/TKOF areas			In circling area and at AD		Remarks
1			2		3
RWY NR/Area affected	**Obstacle type Elevation Markings/LGT**	**Coordinates**	**Obstacle type Elevation Markings/LGT**	**Coordinates**	
a	**b**	**c**	**a**	**b**	
17	NIL		Not available		
35	NIL		Not available		

LGPA AD 2.11 METEOROLOGICAL INFORMATION PROVIDED

1	Associated MET Office	PAROS
2	Hours of service MET Office outside hours	HO NATIONAL METEOROLOGICAL CENTRE ATHINAI
3	Office responsible for TAF preparation Period of validity	NATIONAL METEOROLOGICAL CENTRE ATHINAI 9 HR
4	Trend forecast Interval of issuance	NO TREND
5	Briefing/consultation provided	Personal consultation, Telephone.
6	Flight documentation Language(s) used	Charts, Tabular forms Greek, English
7	Charts and other information available for briefing or consultation	SWH, SWL, W, T, MW
8	Supplementary equipment available for providing information	Online data connection to the data Bank of the Hellenic National Meteorological Service.
9	ATS units provided with information	PAROS AFIS, ATHINAI ACC
10	Additional information (limitation of service, etc.)	All data over FL100 are issued by World Area Forecast Centres. TEL: +30 22840 92052, +30 6983526350.

LGPA AD 2.12 RUNWAY PHYSICAL CHARACTERISTICS

Designations RWY NR	TRUE BRG	Dimensions of RWY (M)	Strength (PCN) and surface of RWY and SWY	THR coordinates RWY end coordinates THR geoid undulation	THR elevation and highest elevation of TDZ of precision APP RWY
1	2	3	4	5	6
17	169° 12’	1400 x 30	PCN 50/F/B/X/U Asphalt	370137.81N 0250641.72E 370053.18N 0250652.33E 37.60 M	THR: 36.29 M / 119.03 FT TDZ: NIL
35	349° 12‘	1400 x 30	PCN 50/F/B/X/U Asphalt	370053.18N 0250652.33E 370137.81N 0250641.72E 37.57 M	THR: 32.08 M / 105.22 FT TDZ: NIL

Designations RWY NR	Slope of RWY-SWY	SWY dimensions (M)	CWY dimensions (M)	Strip dimensions (M)	RESA dimensions (M)	OFZ	Remarks
1	7	8	9	10	11	12	13
17	+0.44% / -0.69% 480 M / 920 M	N/A	300 x 150	1520 x 150	240 x 150	N/A	See relevant LGPA-ADC and AOC chart-ICAO.
35	+0.69% / -0.44% 920 M / 480 M	N/A	300 x 150	1520 x 150	240 x 150	N/A	

LGPA AD 2.13 DECLARED DISTANCES

RWY Designator	TORA (M)	TODA (M)	ASDA (M)	LDA (M)	Remarks
1	2	3	4	5	6
17	1400	1700	1400	1400	NIL
35	1400	1700	1400	1400	NIL

LGPA AD 2.14 APPROACH AND RUNWAY LIGHTING

RWY Designator	APCH LGT Type Length Intensity	THR LGT Colour Wingbars	PAPI VASIS Angle (MEHT)	TDZ, LGT Length	RWY Centre-line LGT Length Spacing, Colour Intensity	RWY edge LGT Length Spacing Colour Intensity	RWY End LGT Colour Wingbars	SWY LGT Length Colour	Remarks
1	2	3	4	5	6	7	8	9	10
17	NIL	GREEN RTIL	APAPI LEFT/ 3° (12.8 M)	NIL	NIL	WHITE LIM	RED	NIL	See also LGPA AD chart-ICAO.
35	NIL	GREEN RTIL	APAPI LEFT/ 3° (12.8 M)	NIL	NIL	WHITE LIM	RED	NIL	

LGPA AD 2.15 OTHER LIGHTING, SECONDARY POWER SUPPLY

1	ABN/IBN location, characteristics and operational hours	ABN: At the Tower building, ALTN FLG WG EV 5 SEC. HO: HN and IMC. IBN: At the Tower building, FLG W, coding “PAS” EV 5 SEC. HO: HN and IMC.
2	LDI location and LGT Anemometer location and LGT	LDI: NIL WDI: 290 M from THR 17, lighted, 290 M from THR 35, lighted. Anemometer: 300 M from THR 17, lighted, 300 M from THR 35, lighted.
3	TWY edge and centre line lighting	Edge: Blue Centre Line: NIL
4	Secondary power supply/switch-over time	UPS / switch-over time 0 sec, diesel generator / switch-over time around 15 sec
5	Remarks	Apron: Flood lights.

LGPA AD 2.16 HELICOPTER LANDING AREA

1	Coordinates TLOF or THR of FATO Geoid undulation	NIL
2	TLOF and/or FATO elevation M/FT	NIL
3	TLOF and FATO area dimensions, surface, strength, marking	NIL
4	True BRG of FATO	NIL
5	Declared distance available	NIL
6	APP and FATO lighting	NIL
7	Remarks	See **LGPA AD 2.20.4**

LGPA AD 2.17 ATS AIRSPACE

1	Designation and lateral limits	PAROS CTR: a) 365400N 0245400E b) 370000N 0244900E c) 371800N 0244900E d) 371330N 0251100E. Last (d) and first (a) points are joined by an arc of circle 13 NM radius centre at (370037N 0250741E).
		PAROS ATZ: Circle, 5 NM radius centered at 370037N 0250741E.
2	Vertical limits	CTR: SFC to 8500 FT ALT.
		ATZ: SFC to 2000 FT ALT.
3	Airspace classification	CLASS D*
4	ATS unit call sign Language(s)	CTR: ATHINAI CONTROL* Greek, English
		ATZ: PAROS TWR* PAROS INFORMATION** Greek, English
5	Transition altitude	4000 FT
6	Remarks	AFIS is provided to PAROS airport at present. *When air traffic control is provided to PAROS airport. **When AFIS is provided to PAROS airport, the airspace within the lateral and vertical limits of PAROS CTR is designated as RMZ and is classified as CLASS G. Air Traffic Service provided is AFIS and unit providing service is PAROS INFORMATION. Pilots shall establish radio contact and maintain continuous air-ground communication watch on the appropriate frequency in the RMZ PAROS INFORMATION.

LGPA AD 2.18 ATS COMMUNICATION FACILITIES

Service designation	Call sign	Frequency/ VHF CH	Operational hours	Remarks
1	2	3	4	5
AFIS	PAROS INFORMATION	125.050 121.500	HO HO	Primary freq. Coverage FL 030 / 15 NM Emergency
G/A/G	PAROS RADIO	5637 kHz 2989 kHz	HO: 0400 – 1700 HO: 1700 – 0400	Primary freq. Primary freq.
All ATS Communication Facilities under responsibility of HASP.				

LGPA AD 2.19 RADIO NAVIGATION AND LANDING AIDS

Type of aid MAG VAR CAT of ILS/MLS (For VOR/ILS/MLS, give declination)	ID	Frequency (CH)	Hours of operation	Position of transmitting antenna coordinates	Elevation of DME transmitting antenna	Remarks
1	2	3	4	5	6	7
PAROS L (5°E/2024)	PAO	386 kHz	H24	370041.57N 0250744.68E	-	Coverage 25 NM
All Radio Navigation and Landing Aids under responsibility of HASP. See also **GEN 2.5**						

LGPA AD 2.20 LOCAL TRAFFIC REGULATIONS

2.20.1 Airport regulations

NIL

2.20.2 Taxiing to and from stands

NIL

2.20.3 Parking area for small aircraft (General aviation)

NIL

2.20.4 Parking area for helicopters

2.20.4.1 An area in the Apron, which depending on Aerodrome traffic and parking availability, is specified each time by the AD operator.

2.20.5 Apron - taxiing during winter conditions

NIL

2.20.6 Taxiing – limitations

NIL

2.20.7 School and training flights - technical test flights - use of runways

NIL

2.20.8 Helicopter traffic – limitation

NIL

2.20.9 Removal of disabled aircraft from runways

2.20.9.1 Tow bars available on request from Goldair Handling.

LGPA AD 2.21 NOISE ABATEMENT PROCEDURES

Part I

2.21.1 Noise abatement procedures for jet aeroplanes irrespective of weight, and for propeller and turboprop aeroplanes with MTOM of or above 11 000 KG

2.21.1.1 General provisions

NIL

2.21.1.2 Use of the runway system during the day period 0600-2200 (0500-2100)

NIL

2.21.1.3 Use of the runway system during the night period 2200-0600 (2100-0500)

NIL

2.21.1.4 Restrictions

NIL

2.21.1.5 Reporting

NIL

Part II

2.21.2 Noise abatement procedures for propeller and turboprop aeroplanes with MTOM below 11 000 KG

2.21.2.1 Use of the runway system during the day period 0600-2300 (0500-2200)

NIL

2.21.2.2 Use of the runway system during the night period 2300-0600 (2200-0500)

NIL

2.21.2.3 Reporting

NIL

Part III

2.21.3 Noise abatement procedures for helicopters

2.21.3.1 General provisions

2.21.3.2 Use of the runway system during the day period 0600-2300 (0500-2200)

NIL

2.21.3.3 Use of the runway system during the night period 2300-0600 (local time)

NIL

2.21.3.4 Reporting

NIL

LGPA AD 2.22 FLIGHT PROCEDURES

2.22.1 General

2.22.2 Runway in use

2.22.2.1 RWY 17/35

2.22.3 Procedures for IFR flights within ..... TMA

2.22.4 Radar procedures within ..... TMA

NIL

2.22.5 Procedures for VFR flights within ..... TMA

2.22.6 Procedures for VFR flights within ..... CTR

2.22.7 Standard instrument departure procedure (SID)

LGPA AD 2.23 ADDITIONAL INFORMATION

2.23.1 Bird concentrations in the vicinity of the airport

2.23.1.1 Caution advised to pilots due to bird concentration (mostly seagulls) on and at the vicinity of airport during daylight hours. See also **ENR 5.6.**

LGPA AD 2.24 CHARTS RELATED TO AERODROME

Chart name	Date	Page
Aerodrome Chart – ICAO: - PAROS / PAROS Airport	14 MAY 26	AD 2-LGPA-ADC
Aircraft Parking / Docking Chart – ICAO: -	NIL	NIL
Aerodrome Obstacle Chart (AOC) - ICAO, Type A: - PAROS Airport	02 MAR 17	AD 2-LGPA-AOC A
Aerodrome Obstacle Chart (AOC) – ICAO, Type B: -	NIL	NIL
Precision Approach Terrain Chart – ICAO: -	NIL	NIL
Instrument Approach Chart (IAC) – ICAO: -	NIL	NIL
Visual Approach Chart (VAC) – ICAO: -	NIL	NIL
Standard Departure Chart - Instrument (SID) – ICAO: -	NIL	NIL
Standard Arrival Chart - Instrument (STAR) – ICAO: -	NIL	NIL
TMA – VFR routes: - VFR routes PAROS CTR	20 MAR 25	AD 2-LGPA-VFR

LGPA AD 2.25 VISUAL SEGMENT SURFACE (VSS) PENETRATION