## LGSA AD 2.1 AERODROME LOCATION INDICATOR AND NAME

## LGSA – CHANIA / IOANNIS DASKALOGIANNIS

## LGSA AD 2.2 AERODROME GEOGRAPHICAL AND ADMINISTRATIVE DATA

| | | | |
|---|---|---|---|
| 1 | ARP coordinates and site at AD | 353153N 0240904E<br>Centre of RWY 11L/29R | |
| 2 | Direction and distance from (city) | BRG 080°, 6 NM from Chania town | |
| 3 | Elevation/Reference temperature | 149.40 M (490.16 FT) / 32.13°C | |
| 4 | Geoid undulation at AD ELEV PSN | NIL | |
| 5 | MAG VAR/Annual change | 5°E (JAN 2026) / 5′ 43″E | |
| 6 | AD Administration, address, telephone, telefax, telex, AFS | Chania / Ioannis Daskalogiannis Airport<br>Aerodrome operator: Fraport Greece SA<br>Germanikis Scholis 10<br>GR 15123, Maroussi<br>e-mail: chqaocc@fraport-greece.com<br>Website: https://www.chq-airport.gr | |
| | | Hellenic Aviation Service Provider (HASP)<br>GR 73100, CHANIA<br>TEL: +30 28210 83800-803-805<br>FAX: +30 28210 66100<br>AFTN: LGSAZDYX<br>e-mail: kaxndar@hasp.gov.gr | Hellenic Air Force (HAF)<br>115 Combat Wing<br>GR 73100, CHANIA<br>TEL: +30 28210 63218<br>AFTN: LGSAYXYX<br>e-mail: opsdir.115cw@haf.gr |
| 7 | Types of traffic permitted (IFR/VFR) | IFR – VFR. | |
| 8 | Remarks | For private flights special permission is required. (**GEN 1.2.5**). | |

## LGSA AD 2.3 OPERATIONAL HOURS

| | | |
|---|---|---|
| 1 | AD Administration | H24 (HAF)<br>H24 (HASP) |
| 2 | Customs and immigration | H24 (HAF)<br>H24 (HASP) |
| 3 | Health and sanitation | O/R (HASP) |
| 4 | AIS Briefing Office | H24 |
| 5 | ATS Reporting Office (ARO) | H24 (HAF TEL: +30 28210 05661, +30 28210 05656)<br>H24 (HASP TEL: +30 28210 83805) |
| 6 | MET Briefing Office | H24 |
| 7 | ATS | H24 (HAF) |
| 8 | Fuelling | Availability<br>H24 (HASP)<br>Summer time: On AD OPR HR<br>Winter time: On AD OPR HR with prior notice |
| 9 | Handling | H24 (HASP) |
| 10 | Security | H24 (HASP) |
| 11 | De-icing | NIL |
| 12 | Remarks | NIL |

## LGSA AD 2.4 HANDLING SERVICES AND FACILITIES

| | | |
|---|---|---|
| 1 | Cargo-handling facilities | One fork lift (2 tons), container loader (7 tons), conveyor belts. |
| 2 | Fuel/oil types | Fuel:<br>PF 100LL: NIL<br>TF JET A1: by GISSCO, EKO.<br>Oil : NIL |
| 3 | Fuelling facilities/capacity | GISSCO<br>2 tanks (207.000 Litres), 4 trucks<br>TEL/FAX: +30 28214 40155<br>Email: chq01@gissco.gr<br><br>EKO<br>5 tanks (594.000 Litres), 4 trucks<br>Payment: carnet, cash Visa, Mastercard<br>TEL: +30 28210 66440<br>FAX: +30 28214 40185<br>Email: c.airport@eko.gr, airport.chania2@eko.gr |
| 4 | De-icing facilities | NIL |
| 5 | Hangar space for visiting aircraft | NIL |
| 6 | Repair facilities for visiting aircraft | NIL |
| 7 | Remarks | NIL |

## LGSA AD 2.5 PASSENGER FACILITIES

| | | |
|---|---|---|
| 1 | Hotels | Available at AD vicinity and Chania town. |
| 2 | Restaurants | Snack-bar, cafeteria. Restaurants at AD vicinity and Chania town. |
| 3 | Transportation | Buses, taxis, car hire from the AD. |
| 4 | Medical facilities | First aid treatment, Ambulance vehicle O/R (HASP), Hospital in Chania town. |
| 5 | Bank and Post Office | ATM. |
| 6 | Tourist Office | NIL |
| 7 | Remarks | NIL |

## LGSA AD 2.6 RESCUE AND FIRE FIGHTING SERVICES

| | | |
|---|---|---|
| 1 | AD category for fire fighting | CIV CAT: 8<br>MIL CAT: 6 |
| 2 | Rescue equipment | Equivalent for CAT 8 and MIL CAT 6 requirements. |
| 3 | Capability for removal of disabled aircraft | CIV ACFT: Iron Tire aircraft recovery dolly with load capacity 4,500 kg and towing capacity of 9,000 kg / MIL: O/R (HAF). |
| 4 | Remarks | NIL |

## LGSA AD 2.7 SEASONAL AVAILABILITY - CLEARING

| | | |
|---|---|---|
| 1 | Types of clearing equipment | NIL |
| 2 | Clearance priorities | NIL |
| 3 | Remarks | All seasons. |

**LGSA AD 2.8 APRONS, TAXIWAYS AND CHECK LOCATIONS/POSITIONS DATA**

| | | |
|---|---|---|
| 1 | Apron surface and strength | Surface: Asphalt<br>Strength: PCN 100/F/A/X/T. |
| 2 | Taxiway designation, width, surface and strength | Width: - NORTH (N) 30.48 M.<br>- TWYs between RWY 11L/29R and TWY N: A: 22.5 M, B: 24.7 M, C: 24.6 M, D: 24.7 M, E: 22 M, F: 29.8 M, G: 22 M.<br>- TWYs between TWY N and Civil apron: P: 24 M, J: 26 M, E: 25 M.<br><br>Surface: - TWY N: Asphalt / Concrete.<br>- TWYs A, B, C, D, G: Concrete.<br>- TWYs E & F: Asphalt.<br><br>Strength: - TWYs P, J, E between TWY N and Civil apron: PCN 100/F/A/X/T. |
| 3 | Altimeter checkpoint location and elevation | NIL |
| 4 | VOR checkpoints | NIL |
| 5 | INS checkpoints | NIL |
| 6 | Remarks | NIL |

**LGSA AD 2.9 SURFACE MOVEMENT GUIDANCE AND CONTROL SYSTEM AND MARKINGS**

| | | |
|---|---|---|
| 1 | Use of aircraft stand ID signs, TWY guide lines and visual docking/parking guidance system of aircraft stands | Taxiing guidance by "FOLLOW ME" vehicle or marshal's instructions following guide lines at apron. |
| 2 | RWY and TWY markings and LGT | LGT: - RWY 11L/29R: Threshold, edge, end.<br>- RWY 11R/29L: Threshold, edge, end (used as RWY only by Hellenic Air Force (HAF) in emergency situations).<br>- TWY N: edge.<br>- TWY M: edge.<br><br>Markings: - RWY 11L/29R: Thresholds, designations, touchdown zone, centerline, side strips, aiming points.<br>- RWY 11R/29L: Thresholds, designations, touchdown zone, centerline, side strips, aiming points (used as RWY only by Hellenic Air Force (HAF) in emergency situations).<br>- TWY N: markings available.<br>- TWY M: centreline, holding positions, side strips. |
| 3 | Stop bars | NIL. |
| 4 | Remarks | Aircraft follow ATC instructions to a taxi-link and will then be guided by FOLLOW ME vehicle to the parking position. No visual guidance system is available, crew adhere at all times to the marshaller's signs.<br>Information signs according to EASA CS and LED lights, available only at civil apron. |

## LGSA AD 2.10 AERODROME OBSTACLES

| In approach/TKOF areas | | | In circling area and at AD | | Remarks |
|---|---|---|---|---|---|
| 1 | | | 2 | | 3 |
| RWY NR/Area affected | Obstacle type Elevation Markings/LGT | Coordinates | Obstacle type Elevation Markings/LGT | Coordinates | |
| a | b | c | a | b | |
| 11L | See relevant LGSA AOC chart-ICAO | | | | Main obstructions lighted. |
| 29R | See relevant LGSA AOC chart-ICAO | | | | |

## LGSA AD 2.11 METEOROLOGICAL INFORMATION PROVIDED

| | | |
|---|---|---|
| 1 | Associated MET Office | CHANIA / IOANNIS DASKALOGIANNIS / II |
| 2 | Hours of service<br>MET Office outside hours | H24<br>CHANIA / IOANNIS DASKALOGIANNIS |
| 3 | Office responsible for TAF preparation<br>Periods of validity | NATIONAL METEOROLOGICAL CENTRE ATHINAI<br>24 HR |
| 4 | Trend forecast Interval of issuance | NO TREND |
| 5 | Briefing/consultation provided | Personal consultation. Telephone. |
| 6 | Flight documentation<br>Language(s) used | Charts, Tabular forms<br>Greek, English |
| 7 | Charts and other information available for briefing or consultation | SWH, SWL, W, T, MW |
| 8 | Supplementary equipment available for providing information | Receiver for satellite cloud picture |
| 9 | ATS units provided with information | SOUDA TWR, SOUDA APP |
| 10 | Additional information (limitation of service, etc.) | All data over FL100 are issued by World Area Forecast Centres.<br>TEL: +30 28210 05677, +30 6983529715.<br>Email: meteo.chania@hnms.gr |

**LGSA AD 2.12 RUNWAY PHYSICAL CHARACTERISTICS**

| Designations RWY NR | TRUE BRG | Dimensions of RWY (M) | Strength (PCN) and surface of RWY and SWY | THR coordinates RWY end coordinates THR geoid undulation | THR elevation and highest elevation of TDZ of precision APP RWY |
|---|---|---|---|---|---|
| 1 | 2 | 3 | 4 | 5 | 6 |
| 11L | 112° | 3348 x 45 | PCN 53/F/B/X/U Asphalt (first 160 concrete) | 353212.75N 0240802.32E | THR: 130.93 M / 429.45 FT TDZ: NIL |
| 29R | 292° | 3348 x 45 | PCN 53/F/B/X/U Asphalt (first 215 concrete) | 353132.61N 0241005.81E | THR: 149.40 M / 490.03 FT TDZ: NIL |
| 11R | 112° | 3356 x 28.20 | PCN 54/R/A/W/T Asphalt | 353206.43N 0240758.85E | THR: 136.52 M / 447.79 FT TDZ: NIL |
| 29L | 292° | 3356 x 28.20 | PCN 54/R/A/W/T Asphalt (first 250 concrete) | 353126.19N 0241002.67E | THR: 155.72 M / 510.76 FT TDZ: NIL |

| Designations RWY NR | Slope of RWY-SWY | SWY dimensions (M) | CWY dimensions (M) | Strip dimensions (M) | RESA dimensions (M) | OFZ | Remarks |
|---|---|---|---|---|---|---|---|
| 1 | 7 | 8 | 9 | 10 | 11 | 12 | 13 |
| 11L | NIL | NIL | NIL | NIL | NIL | NIL | See relevant LGSA AD and AOC charts-ICAO.<br>Arresting system of both RWYs. Arrestor barriers (nets) 17 M before THR of RWY 29R, HGT 1.6 M, not lighted.<br>Arrestor gear wire under-floor type. |
| 29R | NIL | NIL | NIL | NIL | NIL | NIL | |
| 11R | NIL | NIL | NIL | NIL | NIL | NIL | RWY 11R/29L is used as RWY only by Hellenic Air Force (HAF) in emergency situations.<br>Arrestor gear wire of both RWYs (above ground type). |
| 29L | NIL | NIL | NIL | NIL | NIL | NIL | |

**LGSA AD 2.13 DECLARED DISTANCES**

| RWY Designator | TORA (M) | TODA (M) | ASDA (M) | LDA (M) | Remarks |
|---|---|---|---|---|---|
| 1 | 2 | 3 | 4 | 5 | 6 |
| 11L | 3248 | 3248 | 3248 | 3348 | Pilots of departing ACFT from RWY 11L should line up 100 M in front of THR. |
| 29R | 3248 | 3248 | 3248 | 3348 | Pilots of departing ACFT from RWY 29R should line up 100 M in front of net barriers. |
| 11R | 3356 | 3356 | 3356 | 3356 | RWY 11R used only by Hellenic Air Force (HAF) in emergency situations. |
| 29L | 3356 | 3356 | 3356 | 3356 | RWY 29L used only by Hellenic Air Force (HAF) in emergency situations. |

**LGSA AD 2.14 APPROACH AND RUNWAY LIGHTING**

| RWY Designator | APCH LGT Type Length Intensity | THR LGT Colour Wingbars | PAPI VASIS Angle (MEHT) | TDZ, LGT Length | RWY Centre-line LGT Length Spacing, Colour Intensity | RWY edge LGT Length Spacing Colour Intensity | RWY End LGT Colour Wingbars | SWY LGT Length Colour | Remarks |
|---|---|---|---|---|---|---|---|---|---|
| 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | 10 |
| 11L | Simple approach lighting system 360 M LIH | GREEN - | PAPI LEFT/3° (18 M) | NIL | NIL | 3348 M 60 M WHITE LIH | RED - | NIL | See also LGSA AD chart-ICAO.<br><br>RWY 11R/29L used only by Hellenic Air Force (HAF) in emergency situations. |
| 29R | Precision approach lighting system CAT I (Calvert). LIH | GREEN - | PAPI LEFT/3° (18 M) | NIL | NIL | 3348 M 60 M WHITE LIH | RED - | NIL | |
| 11R | NIL | GREEN - | PAPI LEFT/3° - | NIL | NIL | 3356 M 60 M WHITE LIM | RED - | NIL | |
| 29L | Simple approach lighting system 300 M LIH | GREEN - | PAPI LEFT/3° - | NIL | NIL | 3356 M 60 M WHITE LIM | RED - | NIL | |

**LGSA AD 2.15 OTHER LIGHTING, SECONDARY POWER SUPPLY**

| | | |
|---|---|---|
| 1 | ABN/IBN location, characteristics and operational hours | ABN: At the Tower building, ALTN FLG WG, every 12 SEC, H24: HN and IMC.<br>IBN: At the Tower building, FLG G coding "SUD", every 8 SEC, LED. H24: HN and IMC. |
| 2 | LDI location and LGT<br>Anemometer location and LGT | LDI: N/A.<br>WDI: 2 WDI lighted on left side of each RWY.<br>Anemometer: 300 M SE of THR 11L – lighted. 320 M SW of THR 29R – lighted. |
| 3 | TWY edge and centre line lighting | Edge:<br>- TWY A, B, C, D, E, F, G and N: Blue.<br>- TWY M: Blue LED. |
| 4 | Secondary power supply/switch-over time | Available / 10 seconds. |
| 5 | Remarks | Apron Flood lights LED. |

**LGSA AD 2.16 HELICOPTER LANDING AREA**

| | | |
|---|---|---|
| 1 | Coordinates TLOF or THR of FATO<br>Geoid undulation | NIL |
| 2 | TLOF and/or FATO elevation M/FT | NIL |
| 3 | TLOF and FATO area dimensions, surface, strength, marking | NIL |
| 4 | True BRG of FATO | NIL |
| 5 | Declared distance available | NIL |
| 6 | APP and FATO lighting | NIL |
| 7 | Remarks | See **LGSA AD 2.20.4** |

**LGSA AD 2.17 ATS AIRSPACE**

| | | |
|---|---|---|
| 1 | Designation and lateral limits | CHANIA / IOANNIS DASKALOGIANNIS MIL CTR:<br>A circle, 10 NM radius centred at 353153N 0240904E. |
| | | CHANIA / IOANNIS DASKALOGIANNIS MIL ATZ:<br>A circle, 5 NM radius centered at 353153N 0240904E. |
| 2 | Vertical limits | MIL CTR: SFC to 5000 FT ALT. |
| | | MIL ATZ: SFC to 2000 FT ALT. |
| 3 | Airspace classification | Class D.<br>See relevant LGSA **ENR 2.1.6.7** |
| 4 | ATS unit call sign<br>Language(s) | MIL CTR: SOUDA APPROACH<br>Greek, English. |
| | | MIL ATZ: SOUDA TOWER<br>Greek, English. |
| 5 | Transition altitude | 11000 FT. |
| 6 | Remarks | For SOUDA MTMA see **ENR 2.1.6.7.** |

**LGSA AD 2.18 ATS COMMUNICATION FACILITIES**

| Service designation | Call sign | Frequency/ VHF CH | Operational hours | Remarks |
|---|---|---|---|---|
| 1 | 2 | 3 | 4 | 5 |
| APP | SOUDA APPROACH | 118.125<br>362.300 MHZ<br>122.100<br>121.500<br>243.000 MHZ | H24<br>H24<br>H24<br>H24<br>H24 | Primary freq. coverage FL 250 / 50 NM.<br>MIL.<br>RGA.<br>Emergency.<br>MIL Emergency. |
| TWR | SOUDA TOWER | 118.125<br>122.100<br>257.800 MHZ<br>121.500<br>243.000 MHZ | H24<br>H24<br>H24<br>H24<br>H24 | Primary freq. Coverage FL 040/ 25 NM.<br>RGA.<br>MIL RGA.<br>Emergency.<br>MIL Emergency. |
| | SOUDA GROUND | 121.700 | H24 | Coverage 5NM / Aerodrome surface ACFT Start Up and TAXI Clearance. |
| G/A/G | CHANIA RADIO | 5637 kHz<br>2989 kHz | HO: 0400 – 1700<br>HO: 1700 – 0400 | Primary freq.<br>Primary freq. |
| ATIS (ARR / DEP) | CHANIA IOANNIS DASKALOGIANNIS AIRPORT INFORMATION | 130.180 | a. From 01 APR to 31 OCT daily 0400 – 2000.<br>b. From 01 NOV to 31 MAR daily 0500 – 2100. | Coverage FL 200 / 60 NM. |
| All ATS Communication Facilities under responsibility of HAF, except G/A/G service (HASP).<br>For ATIS see also **ENR 1.1** | | | | |

**LGSA AD 2.19 RADIO NAVIGATION AND LANDING AIDS**

| Type of aid<br>MAG VAR<br>CAT of ILS/MLS<br>(For VOR/ILS/MLS, give declination) | ID | Frequency (CH) | Hours of operation | Position of transmitting antenna coordinates | Elevation of DME transmitting antenna | Remarks |
|---|---|---|---|---|---|---|
| 1 | 2 | 3 | 4 | 5 | 6 | 7 |
| CHANIA VOR/DME<br>(5°E/2024)<br>(5°E) | SUD | 108.60 MHz<br>(CH 23X) | H24 | 353122.90N<br>0241029.83E | 518 FT / 157.95 M | Coverage FL 250 / 40 NM.<br>Note: At ALT MSL-9000 FT, sector R340-360 at a greater DIST than 18 DME and R010 at a DIST 18-29 DME, unreliable AZM guidance and loss of DME DIST. |
| PALEOCHORA VOR/DME<br>(5°E/2024)<br>(5°E) | PLH | 114.60 MHz<br>(CH 93X) | H24 | 351339.49N<br>0234051.04E | 120 FT / 36.45 M | Coverage FL 500 / 150 NM |
| CHANIA L<br>(5°E/2024) | SUD | 409 kHz | H24 | 353121.86N<br>0240930.98E | | Coverage 25 NM |
| CHANIA ILS/DME<br>CAT I, RWY 29R<br>(5°E/2024) | ISUD | | H24 | | | Note: Temporary not available for civil aircraft. |
| ILS/LLZ<br>(5°E) | | 110.90 MHz | | 353216.96N<br>0240749.42E | | Coverage FL 062.5 / 25 NM |
| GP | | 330.80 MHz | | 353139.41N<br>0240954.61E | | Coverage FL 023 / 10 NM<br>GP Angle 3°, RDH 49.2 FT<br>FLY LEFT GP coverage limited to 4° |
| DME | | (CH 46X) | | 353139.41N<br>0240954.61E | 528 FT / 162.50 M | Coverage FL 100 / 25 NM |
| Radio Navigation and Landing Aids under responsibility of HASP: SUD VOR/DME, PLH VOR/DME and SUD L.<br>Radio Navigation and Landing Aids under responsibility of HAF: ISUD ILS/DME.<br>See also **GEN 2.5** and **ENR 4.1.** | | | | | | |

## LGSA AD 2.20 LOCAL TRAFFIC REGULATIONS

### 2.20.1 Airport regulations

2.20.1.1 Flight Schedule Data Collection Process (Commercial Flights, excluding GA/BA)

All airlines planning to operate at the airport during winter season shall send their schedules preferably in IATA SSIM Chapter 6 or 7 format to the following e-mail address: flightscheduling@fraport-greece.com. More information and Guidelines for flight Schedule Data collection are also available at https://www.fraport-greece.com/en/our-expertise/aviation/flight-schedules.html.

2.20.1.2 GA/BA and non-commercial flights

a) Due to operational restrictions, prior permission (PPR) must be obtained through the FG PPR Platform for all GA/BA and non-commercial flights prior to departing airport of origin. Relevant requests should be communicated through a local representative or ground handler. Specific application guidelines are available on: https://www.fraport-greece.com/en/our-expertise/aviation/ppr-procedure-and-guidelines.html.
b) On the above restriction, the following categories are exempted:
- SAR flights and airplanes in state of emergency
- Ambulance flights operated with state aircraft
- Flights of aircraft rendering assistance or being on a mission in disasters.
c) Special permission is required (restrictions according to AIP **GEN 1.2.5.2.3**) for GA flights that do not operate under AOC. The Aircraft operator shall apply through its representative CAT 1 to D1 (HCAA) to grant the prerequisite permission.
d) For all foreign transit military flights:
- A 48-hour prior notice and approval (PPR number) by the Hellenic Air Force aerodrome authority (115 C.W.) is required even for aircraft planning to be served by the civil airport company (Fraport Greece SA).
- All requests should be submitted during working days: Monday to Friday hours 0430-1130. Special requests (VIP, HOSP etc.) are exempted.
- 115 C.W is unable to provide customs, immigration services, passenger transportation and hotel accommodation.
- 115 C.W tel.: +30 2821 005554, email: opsdir.115CW@haf.gr.
e) Aircraft up to 30 M wingspan and 31.2 M fuselage length are suggested to provide a suitable tow head and towbar for pushback. Limited roll-through positions are available. Towhead and towbar is mandatory for larger aircraft types. Towbar is not mandatory for light aircraft up to 2,000 Kg.
f) For PPR which are approved under the condition that there is appropriate towbar and towhead availability, the towbar and towhead is mandatory regardless of the aircraft dimensions stated in paragraph c) above, as it is a pre-requisite for the PPR granted.
g) Minimum ground time allowed is 20 min for all GA/BA aircraft excluding helicopters.
h) During adverse weather conditions with strong prevailing winds, all GA/BA aircraft shall be properly secured, under the responsibility of the aircraft operator. For Long Ground Times, all GA/BA aircraft shall be secured, regardless of the prevailing weather.

2.20.1.3 Higher code letter aircraft requests

To operate with a Higher Code Letter aircraft at LGSA Airport (Aerodrome reference code 4D, RFF category 8), aircraft carriers shall submit relevant request via e-mail to: anocdm@fraport-greece.com. The request shall be made at least 10 days before the date planned and shall contain the following data:
- Aircraft type.
- Required RFF category.
- Expected date and time.

2.20.1.4 Aircraft are permitted to taxi only at the indispensable minimum engine power.

2.20.1.5 In case of pilot request start-up engine in parking position should be initially communicated to the Airport Operations Control Center through the aircraft operator and/or the ground handler. In such cases, single engine start-up in idle power shall be performed. The aircraft operator and/or the ground handling provider are responsible to safeguard the area around the aircraft in order to prevent personnel or vehicle passing behind running engines.

2.20.1.6 Maintenance run-up tests above idle power require prior approval by the Airport Operator and may take place only in designated areas. The area will be indicated following Airport Operator and ATC communication and according to available apron space. Relevant request should be addressed to the Airport Operations Control Center through the aircraft operator or the ground handler.

### 2.20.2 Taxiing to and from stands

2.20.2.1 New Civilian Apron Layout

2.20.2.1.1 New Aircraft stand Taxilane M is extending from TWYL E to P and is suitable for aircraft up to ICAO category E (incl.).

#### 2.20.2.2 Procedures for arriving aircraft

2.20.2.2.1 All taxi instructions are issued by ATC via VHF frequency. ATC will advise aircraft to taxi to a TWYL in order to be guided by Follow Me vehicle to parking position. The Parking Stand allocation is the responsibility of the Airport Operations Control Center. Presence of Follow Me vehicle is mandatory.

2.20.2.2.2 No docking system available, crew shall adhere to marshaller's instructions. Marshalling services are under the responsibility of the ground handling agent.

2.20.2.2.3 Non-marked and non-published parking areas may also be assigned for parking, aircraft will be guided by Follow-Me vehicle and marshalling signals.

2.20.2.3 Procedures for departing aircraft

2.20.2.3.1 Aircraft may leave nose-in parking positions only by the aid of a towing truck. Power back using reverse thrust for jet-powered aircraft or reverse variable pitch for propeller aircraft shall not be used unless (and under extreme circumstances) prior approval has been obtained from the Airport Operator.

2.20.2.3.2 Push-back clearance shall be requested only if the tow-bar is fully connected to the aircraft and the pilot can perform the maneuver immediately. Unless otherwise instructed by ATC, push-back shall be executed with west facing in order to taxi-out via taxi-links P or J except when due to operational reasons or aircraft limitations pilot requests push-back facing east.

2.20.2.3.3 When crews request taxi-out or push-back, they shall indicate their parking position.

2.20.2.4 Push-Back and Engine start-up procedures

a) Pilot shall request start-up and push-back clearance by ATC.
b) Start-up of engines shall be performed either during push-back after the service road has been cleared or when the aircraft is aligned on the Aircraft stand taxilane.
c) Cross-bleeding start-up is not permitted on the parking stand and can only be performed on the Aircraft stand taxilane and/or RWY 11L/29R according to ATC instructions. The request for cross-bleeding start-up should be timely communicated to the Airport Operations Control Center through the aircraft operator and/or the ground handler.
d) During push-back procedure, aircraft from any parking position is aligned on the Aircraft stand taxilane M and positioned with the nose gear abeam the lead-in line of the position it is vacating unless otherwise instructed by ATC. Exceptionally:
   i. Pushback from parking stand 1A with default facing West. Aircraft will be positioned with the nose gear abeam the lead-in line of stand 1B.
   ii. Pushback from parking stand 1 with default facing West. Aircraft will be positioned with the nose gear abeam the lead-in line of stand 2A.
   iii. Pushback from parking stand 11, 12 with default facing East. Aircraft will be positioned with the nose gear abeam the lead-in line of stand 11.
e) In order to facilitate and/or expedite traffic, ATC may request from aircraft to perform a long / extended push-back or to be pulled forward with the nose gear positioned abeam the lead-in line of an adjacent parking position.
f) Push-back procedure cannot take place simultaneously in any adjacent positions.
g) Push-back clearance is permitted for one aircraft at a time or may be permitted simultaneously maximum for two (2) aircrafts regarding traffic demands and safety procedures.

2.20.2.5 Towing of aircraft

2.20.2.5.1 Towing of aircraft is executed only with the aid of a Follow Me vehicle and requires prior notice to the ATC.

**2.20.3 Parking area for small aircraft (General aviation)**

2.20.3.1 Follow-Me vehicle guidance and marshalling signals shall be provided to all aircraft taxiing to roll-through parking positions. For departing aircraft the presence of a marshaller is mandatory. Follow-Me guidance may also be provided.

**2.20.4 Parking area for helicopters**

2.20.4.1 No heliport available, helicopters will be advised to proceed to an area suitable for parking. The allocation of the parking area is the responsibility of the Airport Operator and will be communicated to arriving helicopters through ATC.

**2.20.5 Apron - taxiing during winter conditions**

NIL

**2.20.6 Taxiing – limitations**

2.20.6.1 Due to narrow width of intersections between RWY 11L/29R and RWY 11R/29L ACFT with wingspan equal or longer than 56 M should not use RWY 11R/29L for taxi.

2.20.6.2 Heavy ACFT should use minimum power during taxiing on the North (N) TWY, in order not to produce FOD cause by jet blast.

2.20.6.3 ACFT with outer engines placed at a distance more than 15 M from aircraft's centreline shall –if possible- taxi with these engines set at idle position.

2.20.6.4 Aircraft parked at LIMA AREA

- Aircraft taxiing to - from LIMA AREA shall be guided by Follow-Me vehicle. No visual guidance system is available crew adhere at all times to the marshaller's signs.
- Aircraft parked at LIMA AREA shall taxi to THR RWY 11L via intersection F or G.
- A holding position (Pattern B - as per EASA CS ADR-DSN L.575) is marked before entering intersection F, when taxiing eastwards from LIMA AREA.
- A holding position (Pattern A - as per EASA CS ADR-DSN.L.575) is marked before entering intersection G towards THR RWY 11L.
- No aircraft enter or leave LIMA AREA during night hour, due to insufficient lights. Aircraft serviced by the 115 Combat Wing (HAF) are excluded.

- TWY G: No markings and signs available. During taxiing via TWY G and while on extension of RWY 29R between intersections G and F, use minimum engine power. Follow-Me guidance is mandatory.

2.20.6.5 South segment of intersection G between RWY 11L/29R and RWY 11R/29L is closed.

**2.20.7 School and training flights - technical test flights - use of runways**

2.20.7.1 For School, Training and Test flights that require use of the apron, Prior Permission (PPR) by the airport operator is required prior departure from airport of origin. In addition prior approval from the ATC is required.

2.20.7.2 For runway use only (touch & go) prior approval from the ATC is required and approval by the airport operator via e-mail at CHQdm@fraport-greece.com

**2.20.8 Helicopter traffic - limitation**

NIL

**2.20.9 Removal of disabled aircraft from runways**

2.20.9.1 CIV ACFT: Iron Tire aircraft recovery dolly with load capacity 4,500 kg and towing capacity of 9,000 kg / MIL: O/R (HAF).

**2.20.10** Operation of advanced surveillance system

2.20.10.1 In order to cooperate with the Mode-S based Advanced Surveillance System, aircraft operators intending to use CHANIA / IOANNIS DASKALOGIANNIS airport shall ensure that the Mode S transponder is able to operate when the aircraft is on the ground.

2.20.10.1.1 Pilots shall:

a. Select AUTO mode and the assigned Mode A code.

b. If AUTO mode is not available, select ON (e.g. XPDR) and the assigned Mode A code:

- from the request for towed push-back or taxi, whichever is earlier

- after landing, continuously until the aircraft is fully parked in its stand

- when the aircraft is fully parked, they shall select STBY

2.20.10.1.2 Whenever the aircraft is capable of reporting Aircraft Identification (i.e. call sign used in flight), this should be entered

(through the FMS or the Transponder Control Panel) at the time of the request for towed push-back or taxi, whichever is earlier.

2.20.10.1.3 Air crew must use the ICAO defined format to enter the Aircraft Identification.

2.20.10.1.4 To ensure that the performance of systems based on SSR frequencies (including airborne TCAS units and SSR radars) is not compromised, TCAS should not be selected before receiving clearance to line up, and should be deselected after vacating the runway.

## LGSA AD 2.21 NOISE ABATEMENT PROCEDURES

### Part I

**2.21.1 Noise abatement procedures for jet aeroplanes irrespective of weight, and for propeller and turboprop aeroplanes with MTOM of or above 11 000 KG**

2.21.1.1 General provisions

NIL

2.21.1.2 Use of the runway system during the day period 0600-2200 (0500-2100)

NIL

2.21.1.3 Use of the runway system during the night period 2200-0600 (2100-0500)

NIL

2.21.1.4 Restrictions

NIL

2.21.1.5 Reporting

NIL

### Part II

**2.21.2 Noise abatement procedures for propeller and turboprop aeroplanes with MTOM below 11 000 KG**

2.21.2.1 Use of the runway system during the day period 0600-2300 (0500-2200)

NIL

2.21.2.2 Use of the runway system during the night period 2300-0600 (2200-0500)

NIL

2.21.2.3 Reporting

NIL

### Part III

**2.21.3 Noise abatement procedures for helicopters**

2.21.3.1 General provisions

NIL

2.21.3.2 Use of the runway system during the day period 0600-2300 (0500-2200)

NIL

2.21.3.3 Use of the runway system during the night period 2300-0600 (local time)

NIL

2.21.3.4 Reporting

NIL

## LGSA AD 2.22 FLIGHT PROCEDURES

### 2.22.1 General

2.22.1.1 Only procedural ATC service is provided within SOUDA MTMA.

2.22.1.2 Restricted area LGR 28 (1000 FT AMSL), see ENR 5.1.2.

2.22.1.3 SOUDA MTMA is affected by Controlled firing area LGC101, see ENR 5.1.4

2.22.1.4 Seasonal Phenomena

2.22.1.4.1 The following phenomena are usually observed during winter, spring and summer period in the vicinity of Chania / Ioannis Daskalogiannis airport:

a) Low Level Wind Shear (LLWS) observed in case of South - South East winds with main characteristics, 9-12 knots on the runway and severe upper winds (2000FT, South winds >40 KT). Also severe upper winds (>40 KT) 5-10 NM East and/or West of the airport.

b) When South – South East winds prevail, severe turbulence and high downdraughts are observed on final of RWY 11L severe cross wind (>40 KT) also appears during approach on RWY 29R.

c) Sea breeze (8-15 knots) during summer period at noon from both sides of Runway 11L/29R.

d) Tail wind from both sides of Runway 11L/29R in case of North winds (350-360 degrees) 8-15 knots (all year).

### 2.22.2 Runway in use

2.22.2.1 RWYs in use 11L/29R.

2.22.2.2 Traffic circuit

a) Right hand traffic circuit for RWY 11L applies.
b) Left hand traffic circuit for RWY 29R applies.

2.22.2.2.1 All flights unless otherwise instructed by ATC shall enter the traffic circuit at an altitude of 1500 FT for propeller ACFT and 2000 FT for jet ACFT.

### 2.22.3 Procedures for IFR flights within SOUDA MTMA

2.22.3.1 See relevant LGSA IAC charts-ICAO (**LGSA AD 2.24**).

### 2.22.4 Radar procedures within SOUDA MTMA

NIL

### 2.22.5 Procedures for VFR flights within SOUDA MTMA

2.22.5.1 See relevant LGSA VFR ROUTES-ICAO (**LGSA AD 2.24**).

2.22.5.2 All ACFT (including helicopters) flying under VFR and traversing SOUDA MTMA should establish RTF contact with SOUDA APP and proceed according to the given instructions.

2.22.5.3 General Aviation – aeroclub VFR local flights – including helicopters – shall contact local ATC (on tel. +3028210-05656) prior to the flight for coordination, so as to provide the specifics on their flight (route, ETO, reporting points, ETA, etc), in order to obtain the final approval.

2.22.5.4 Military VFR Training flights

2.22.5.4.1 The period from 01 MAY till 31 OCT no foreign military VFR training flights will be accepted within SOUDA MTMA due to heavy traffic. Flights which are conducted within LGC101 and LGR28 areas are exempted from the above restriction.

2.22. 5.4.2 The period from 01 NOV till 31 APR, for foreign military VFR training flights within SOUDA MTMA, a five (5) days prior coordination with local ATC is required.

### 2.22.6 Procedures for VFR flights within CHANIA / IOANNIS DASKALOGIANNIS MIL CTR

2.22.6.1 See relevant LGSA VFR ROUTES - ICAO (**LGSA AD 2.24**).

### 2.22.7 Standard instrument departure procedure (SID)

2.22.7.1 See relevant LGSA SID charts-ICAO (**LGSA AD 2.24**).

### 2.22.8 Procedures for departing aircraft

2.22.8.1 Start-up and ATC clearance

2.22.8.1.1 Aircraft may anticipate 5min delay for start-up until ATC clearance is obtained by ATHINAI ACC.

2.22.8.1.2 Pilot shall request ATC Clearance when ready for push back and start-up.

2.22.8.2 Intersection Take-offs

2.22.8.2.1 Intersection take-offs are permitted during aviation daytime only when visibility is not less than 5 KM.

2.22.8.2.2 An aircraft may be cleared to depart from an intersection take-off position:

a) Upon request of the pilot and acceptance by the ATC, or
b) If initiated by ATC and accepted by the pilot in command.

2.22.8.2.3 When a departure from an intersection take-off position is requested by the pilot, phraseology will be as follows:

<<REQUEST DEPARTURE FROM RUNWAY (number), INTERSECTION (name of intersection).>>.

2.22.8.2.4 The aircraft operator / pilot in command shall ensure that the reduced declared distances for an intersection take-off are sufficient and in compliance with the aircraft operations regulations.

2.22.8.2.5 Pilots in command shall state their position when contact tower for departure from a runway intersection as follows:

<<SOUDA TOWER (aircraft call sign), AT INTERSECTION (name), READY FOR DEPARTURE RUNWAY (name)>>.

2.22.8.2.6 Declared distances in case of intersection take-off are as follows:

| RWY | Intersection | Declared Distances | Distances (M) |
|---|---|---|---|
| 29R | B | TORA/TODA/ASDA | 2755 |
| 29R | C | TORA/TODA/ASDA | 2475 |
| 11L | E | TORA/TODA/ASDA | 2540 |

## LGSA AD 2.23 ADDITIONAL INFORMATION

### 2.23.1 Bird concentrations in the vicinity of the airport

2.23.1.1 Seagulls' concentration on the RWYs, TWYs and vicinity of the aerodrome. See also **ENR 5.6**.

### 2.23.2 Accepted deviations in aerodrome certificate

| Specification | Description of Non-Compliance | Deviation type |
|---|---|---|
| B.060 Longitudinal Slopes of RWYs | Longitudinal slopes exceeding requirements at various spots of runway. | Special Condition |
| B.080 Transverse Slopes on RWYs | According to new topographical plan slopes along northern side of RWY 11L/29R centerline exceed limitation. Specifically, 1080m from THR 29R is 2,5% and at about 950 m from THR 29 is 2,5%. 697 m from THR 11L up to about 2790 m from THR 11L slopes exceed 2%. | Special Condition |
| B.130 Longitudinal Slopes on RWY Strips | Surface is flush to RWY 11L/29R pavement, but slopes exceed partly >2,5% (northern side RWY 11L: at 320-400 m, 2200-2300 m, 2600-2680 m, 2870-3030 m, values -2,6 up to -4,3%) (southern side RWY 11L: at 200-300 m, 2200 m, 3300-3340 m, values -2,6 up to -4,0%). | Special Condition |
| B.165 Objects on RWY Strip | Military equipment (arresting gear, signs, etc.). | Special Condition |
| B.180 Longitudinal Slopes on RWY Strips | Longitudinal slopes exceeding requirements at various spots of runway strips . | Special Condition |
| D.265 Longitudinal Slopes on TWYs | Non-compliant: acc. to aerial survey data exceeding's of long. slope limitations: on TWY A (max value: 2,8%), on TWY C (max value: 2,6%), on TWY E (between TWY N & RWY 11L/29R) (max value: 2,9%), on TWY F (max value: -3,4%), on TWY G (max value: -2,7%). | Special Condition |

| Specification | Description of Non-Compliance | Deviation type |
|---|---|---|
| D.270 Longitudinal Slope changes on TWYs | Non-compliant: acc. to aerial survey data longitudinal slope changes exceed limitations on TWY C (max value: 2,7% / 30 m) and TWY E (max value: 2,4% / 30 m), no exceeding's on other TWYs ascertained. | Special Condition |
| D.280 Transverse Slope on TWYs | Non-compliant: based on aerial survey TWYs E and pre-threshold-area RWY 11L exceed the transverse slope limitation >1,5%: (max value 2,3% TWY E between RWY 11L/29R and TWY N east side). | Special Condition |
| D.330 Slopes on TWY Strips | Exceeded downward slope in strip of TWYs E, J, and near drainage channel (max value: -12%). | Special Condition |
| J.475 Non-Precision Approach RWYs | Infringement of Northern transitional (due to parking aircraft on military apron). | Special Condition |
| M.626 Simple Approach Lighting Systems | 1. 60m crossbar distance, 27 m crossbar width.<br>2. C/L lights spaced inhomogeneously at different intervals. | ELoS |
| M.630 Precision Approach Category I Lighting System | Precision approach at Cat 1<br><br>The system has single light source C/L up to 450 m from THR, changing into dual light source for the outer 450 m (no barrettes installed). | ELoS |
| M.735 Iterm Hold Position Lights | Intermediate holding positions at TWYs P/J/E are not equipped with IHPLs. | ELoS |
| M.745 RWY Guard Lights | No RWY guard lights installed on RWY 11L/29R. | ELoS |
| T.910 Equipment Frangibility Requirements | Various equipment installations do not provide frangibility features (WDI, bird scare cannons, sings, military equipment). | ELoS |
| T.915 Siting of Equipment & Installations on Operational Areas | 1. Several bird scare cannons are installed along the RWY 11L/29R, at the end of the RWY 11L/29R shoulder, endangering objects can be found within the RWY 11L/29R strip (see B.165).<br><br>2. Not all objects in this area are frangible (i.e. sings, military equipment), however no detailed information on obstacles are available<br><br>3. At both RWY 11L/29R ends, requirements cannot be met (installed military equipment, concrete foundations, etc.).<br><br>4. WDIs are not frangible. | ELoS |
| L.590 Aircraft stand marking | The stop line marking of the aircraft stands indicates the intended nose wheel position of the parked aircraft. | ELoS |

**2.23.3 Exchange of Data with Network Manager Operations Centre (NMOC) - Advanced ATC TWR**

2.23.3.1 LGSA exchanges information for departure flights by applying the Advanced ATC TWR procedures. Message exchange from the local system to the ATM network complies with the European standard for A-CDM airports, using the following message types:

- A-DPI: ATC departure planning information message, for all IFR departure flights
- C-DPI: Cancel DPI, cancellation of departure planning information, when required

When the aircraft is off-blocks and starts to exit the stand, the TTOT is calculated and transmitted to NMOC via an A-DPI message. After reception of the A-DPI message, DLA or CHG messages that change the flight plan data shall not be accepted. If the flight is regulated, the CTOT assigned before receiving the A-DPI shall be maintained. If an aircraft has to abort taxiing, a C-DPI message shall be sent to the NMOC. The result of the C-DPI is that the flight shall be suspended by informing the operator via an FLS (flight suspension message) with the comment "suspended by departure airport". The flight plan can be activated again by updating the EOBT with a DLA or CHG message.

**LGSA AD 2.24 CHARTS RELATED TO AERODROME**

| Chart name | Date | Page |
|---|---|---|
| | | |
| **Aerodrome Chart – ICAO:** - CHANIA / IOANNIS DASKALOGIANNIS Airport | 29 OCT 26 | AD 2-LGSA-ADC |
| **Aircraft Parking/ Docking Chart – ICAO:** - CHANIA / IOANNIS DASKALOGIANNIS Airport | 17 APR 25 | AD 2-LGSA-APDC |
| **Aerodrome Obstacle Chart (AOC) - ICAO, Type A:** - CHANIA / IOANNIS DASKALOGIANNIS | 15 AUG 19 | AD 2-LGSA-AOC A-1 |
| **Aerodrome Obstacle Chart (AOC) – ICAO, Type B: -** | NIL | NIL |
| **Precision Approach Terrain Chart – ICAO: -** | NIL | NIL |
| **Instrument Approach Chart (IAC) – ICAO:** - VOR x RWY 11L | 08 AUG 24 | AD 2-LGSA-IAC-1 |
| Instrument Approach Chart (IAC) – ICAO: - VOR w RWY 29R | 05 SEP 24 | AD 2-LGSA-IAC-2 |
| Instrument Approach Chart (IAC) – ICAO: - VOR z RWY 11L | 31 OCT 24 | AD 2-LGSA-IAC-3 |
| Instrument Approach Chart (IAC)-ICAO: - VOR y RWY 29R | 08 AUG 24 | AD 2-LGSA-IAC-4 |
| Instrument Approach Chart (IAC)-ICAO: - L RWY 11L | 08 AUG 24 | AD 2-LGSA-IAC-5 |
| Instrument Approach Chart (IAC)-ICAO: - L RWY 29R | 08 AUG 24 | AD 2-LGSA-IAC-6 |
| **Visual Approach Chart (VAC) – ICAO: -** | NIL | NIL |
| **Standard Departure Chart - Instrument (SID) – ICAO:** - RWY 11L | 06 AUG 26 | AD 2-LGSA-SID-1 |
| Standard Departure Chart - Instrument (SID) – ICAO: - RWY 29R | 06 AUG 26 | AD 2-LGSA-SID-2 |
| Standard Departure Chart - Instrument (SID) – ICAO: - RWY 11L | 06 AUG 26 | AD 2-LGSA-SID-3 |
| Standard Departure Chart - Instrument (SID) – ICAO: - RWY 11L | 06 AUG 26 | AD 2-LGSA-SID-4 |
| Standard Departure Chart - Instrument (SID) – ICAO: - RWY 29R | 06 AUG 26 | AD 2-LGSA-SID-5 |
| Standard Departure Chart - Instrument (SID) – ICAO: - RWY 29R | 06 AUG 26 | AD 2-LGSA-SID-6 |
| Standard Departure Chart - Instrument (SID) – ICAO: - RWY 11L | 06 AUG 26 | AD 2-LGSA-SID-7 |
| Standard Departure Chart - Instrument (SID) – ICAO: - RWY 29R | 06 AUG 26 | AD 2-LGSA-SID-8 |
| **Standard Arrival Chart - Instrument (STAR) – ICAO:** - RWY 11L | 06 AUG 26 | AD 2-LGSA-STAR-1 |
| Standard Arrival Chart - Instrument (STAR) – ICAO: - RWY 29R | 06 AUG 26 | AD 2-LGSA-STAR-2 |
| Standard Arrival Chart - Instrument (STAR) – ICAO: - RWY 11L | 06 AUG 26 | AD 2-LGSA-STAR-3 |
| Standard Arrival Chart - Instrument (STAR) – ICAO: - RWY 29R | 06 AUG 26 | AD 2-LGSA-STAR-4 |
| Standard Arrival Chart - Instrument (STAR) – ICAO: - RWY 29R | 06 AUG 26 | AD 2-LGSA-STAR-5 |
| Standard Arrival Chart - Instrument (STAR) – ICAO: - RWY 11L | 06 AUG 26 | AD 2-LGSA-STAR-6 |
| Standard Arrival Chart - Instrument (STAR) – ICAO: - RWY 11L | 06 AUG 26 | AD 2-LGSA-STAR-7 |
| Standard Arrival Chart - Instrument (STAR) – ICAO: - RWY 29R | 06 AUG 26 | AD 2-LGSA-STAR-8 |
| **TMA – VFR routes:** - VFR routes SOUDA MTMA | 06 AUG 26 | AD 2-LGSA-VFR |

**LGSA AD 2.25 VISUAL SEGMENT SURFACE (VSS) PENETRATION**