LGSM AD 2.1 AERODROME LOCATION INDICATOR AND NAME
LGSM - SAMOS / ARISTARCHOS OF SAMOS

LGSM AD 2.2 AERODROME GEOGRAPHICAL AND ADMINISTRATIVE DATA

1	ARP coordinates and site at AD	374121N 0265444E Centre of RWY 09/27.
2	Direction and distance from (city)	BRG 232°, 5.5 NM from centre of Samos town.
3	Elevation/Reference temperature	5.74 M (18.83 FT) / 34.27°C
4	Geoid undulation at AD ELEV PSN	NIL
5	MAG VAR/Annual change	5°E (JAN 2026) / 5'37"E
6	AD Administration, address, telephone, telefax, telex, AFS	Samos / Aristarchos of Samos Airport Aerodrome operator: Fraport Greece SA Germanikis Scholis 10 GR 15123, Maroussi TEL: +30 22734 40013 email: smiaocc@fraport-greece.com Website: https://www.smi-airport.gr Hellenic Aviation Service Provider (HASP) GR 83103, PYTHAGORIO TEL: +30 22734 40045 FAX: +30 22734 40099 AFTN: LGSMYDYX email: kasmaar@hasp.gov.gr
7	Types of traffic permitted (IFR/VFR)	IFR - VFR
8	Remarks	NIL

LGSM AD 2.3 OPERATIONAL HOURS

1	AD Administration	HO
2	Customs and immigration	HO
3	Health and sanitation	HO
4	AIS Briefing Office	HO
5	ATS Reporting Office (ARO)	HO (TEL: +30 22734 40078 & +30 22734 40079)
6	MET Briefing Office	H24 (MET)
7	ATS	HO
8	Fuelling	Availability Summer time: On AD OPR HR Winter time: On AD OPR HR with prior notice
9	Handling	HO
10	Security	HO
11	De-icing	NIL
12	Remarks	NIL

LGSM AD 2.4 HANDLING SERVICES AND FACILITIES

1	Cargo-handling facilities	NIL
2	Fuel/oil types	Fuel PF 100 LL: by GISSCO TF JET A1: by EKO, GISSCO Oil: NIL
3	Fuelling facilities/capacity	GISSCO TEL: +30 22734 40075, +30 6948685119 Email: smi01@gissco.gr EKO TEL: +30 22734 40088, +30 22734 40997, +30 6981682486 Email: A.samos@eko.gr
4	De-icing facilities	NIL
5	Hangar space for visiting aircraft	NIL
6	Repair facilities for visiting aircraft	NIL
7	Remarks	NIL

LGSM AD 2.5 PASSENGER FACILITIES

1	Hotels	Available at Pythagorio, Karlovasi, Kokari and Samos towns.
2	Restaurants	Available at Samos and Pythagorio towns, distance 3 KM.
3	Transportation	Charter airlines buses, taxis, buses.
4	Medical facilities	Hospital at Samos town. First aid / treatment / Motor ambulance.
5	Bank and Post Office	ATM / Postal box available at the airport.
6	Tourist Office	NIL
7	Remarks	NIL

LGSM AD 2.6 RESCUE AND FIRE FIGHTING SERVICES

1	AD category for fire fighting	CIV CAT: 7
2	Rescue equipment	Equivalent for CAT 7 requirements.
3	Capability for removal of disabled aircraft	Iron Tire aircraft recovery dolly with load capacity 4,500 kg and towing capacity 9,000 kg.
4	Remarks	NIL

LGSM AD 2.7 SEASONAL AVAILABILITY - CLEARING

1	Types of clearing equipment	NIL.
2	Clearance priorities	NIL.
3	Remarks	NIL.

LGSM AD 2.8 APRONS, TAXIWAYS AND CHECK LOCATIONS/POSITIONS DATA

1	Apron surface and strength	Surface: Asphalt Strength: PCN 59/F/A/X/T			
2	Taxiway designation, width, surface and strength	TWY	Width	Surface	Strength
		A1	23 M	Asphalt	PCN 84/F/B/X/T
		A2	40 M	Asphalt	PCN 100/F/B/X/T.
		A3	36 M	Asphalt	PCN 84/F/B/X/T
		D	15 M	Asphalt	NIL
		E	15 M	Asphalt	NIL
3	Altimeter checkpoint location and elevation	NIL			
4	VOR checkpoints	NIL			
5	INS checkpoints	NIL			
6	Remarks	NIL			

LGSM AD 2.9 SURFACE MOVEMENT GUIDANCE AND CONTROL SYSTEM AND MARKINGS

1	Use of aircraft stand ID signs, TWY guide lines and visual docking/parking guidance system of aircraft stands	Guidance to stands by Marshaler. Follow me guidance available as per **LGSM AD 2.20** or upon request.
2	RWY and TWY markings and LGT	LGT: RWY 09: Threshold, edge, end. RWY 27: Threshold, edge, end, Runway Threshold Identification Lights (RTIL). TWY: Edge. Markings: RWY: Thresholds, designations, centre line, TDZ, Aiming points. TWY: Centre line, RWY holding positions.
3	Stop bars	NIL.
4	Remarks	See also LGSM AD chart – ICAO.

LGSM AD 2.10 AERODROME OBSTACLES

In approach/TKOF areas			In circling area and at AD		Remarks
1			2		3
RWY NR/ Area affected	Obstacle type Elevation Markings/LGT	Coordinates	Obstacle type Elevation Markings/LGT	Coordinates	
a	b	c	a	b	
09/APPROACH 27/TAKE-OFF	High Ground, 665 M NIL/LGTD LIM R	374122.15N 0264838.20E	High Ground, 300 M NIL/LGTD LIM R	373848.29N 0265217.88E	
09/APPROACH 27/TAKE-OFF	High Ground, 342 M NIL/LGTD LIM R	374125.26N 0265014.52E	High Ground, 195 M NIL/LGTD LIM R	373958.49N 0265150.37E	
09/APPROACH 27/TAKE-OFF	High Ground, 361 M NIL/LGTD LIM R	374136.71N 0265013.10E	High Ground, 765 M NIL/LGTD LIM R	374002.55N 0264820.59E	
27/APPROACH 09/TAKE-OFF	High Ground, 17 M NIL/LGTD LIL R	374121.80N 0265618.62E	High Ground, 729 M NIL/LGTD LIM R	374056.70N 0264818.95E	
27/APPROACH 09/TAKE-OFF	High Ground, 42 M NIL/LGTD LIL R	374124.89N 0265701.67E	High Ground, 167 M NIL/LGTD LIM R	374206.01N 0265154.50E	
09/APPROACH 27/TAKE-OFF	Military emplacement 8.43 M NIL	374126.18N 0265359.30E	High Ground, 250 M NIL/LGTD LIM R	374232.86N 0265353.56E	
09/APPROACH 27/TAKE-OFF	Military emplacement 9.68 M NIL	374126.39N 0265359.65E	High Ground, 185 M NIL/LGTD LIM R	374236.14N 0265435.77E	
27/APPROACH 09/TAKE-OFF	Military stronghold 3.85 M NIL	374116.30N 0265527.58E	High Ground, 227 M NIL/LGTD LIM R	374152.42N 0265557.86E	
09/APPROACH 27/TAKE-OFF	Fence airport 7.38 M NIL	374126.20N 0265356.50E	Old Label Base 4.66 M NIL	374122.75N 0265433.45E	
			RVR RWY 09 8.03 Marked/ lighted	374120.22N 0265416.78E	
			RVR RWY 09 8.03 M Marked/ lighted	374120.13N 0265418.02E	
			RVR RWY 27 7.56 M Marked/ lighted	374116.94N 0265511.50E	
			RVR RWY 27 7.56 M Marked/ lighted	374116.86N 0265512.75E	
			Antenna 30.88 M NIL	374127.33N 0265452.75E	

In approach/TKOF areas			In circling area and at AD		Remarks
1			2		3
RWY NR/ Area affected	Obstacle type Elevation Markings/LGT	Coordinates	Obstacle type Elevation Markings/LGT	Coordinates	
a	b	c	a	b	
			Control Tower 28.22 M NIL/lighted	374127.16N 0265452.80E	
			Light Pole Apron 25.85 M Marked/ lighted	374127.41N 0265439.46E	
			Light Pole Apron 26.99 M Marked/ lighted	374127.00N 0265445.97E	
			Light Pole Apron 26.67 M Marked/ lighted	374126.80N 0265449.14E	
			Windsock RWY 27 9.66 M Marked/ lighted	374115.82N 0265516.32E	
			Windsock RWY 09 10.64 M Marked/ lighted	374126.12N 0265413.23E	

LGSM AD 2.11 METEOROLOGICAL INFORMATION PROVIDED

1	Associated MET Office	SAMOS / ARISTARCHOS OF SAMOS / III
2	Hours of service MET Office outside hours	H24 SAMOS / ARISTARCHOS OF SAMOS
3	Office responsible for TAF preparation Period of validity	HTAF REGIONAL METEOROLOGICAL CENTRE LARISSA 9 HR
4	Trend forecast Interval of issuance	NO TREND
5	Briefing/consultation provided	Personal consultation.
6	Flight documentation Language(s) used	Charts, Tabular forms Greek, English
7	Charts and other information available for briefing or consultation	SWH, SWL, W, T, MW
8	Supplementary equipment available for providing information	Online data connection to the data Bank of the Hellenic National Meteorological Service.
9	ATS units provided with information	SAMOS TWR, SAMOS APP
10	Additional information (limitation of service, etc.)	All data over FL100 are issued by World Area Forecast Centres. TEL: +30 22730 61477, +30 6983526355. Email: meteo.samos@hnms.gr

LGSM AD 2.12 RUNWAY PHYSICAL CHARACTERISTICS

Designations RWY NR	TRUE BRG	Dimensions of RWY (M)	Strength (PCN) and surface of RWY and SWY	THR coordinates RWY end coordinates THR geoid undulation	THR elevation and highest elevation of TDZ of precision APP RWY
1	2	3	4	5	6
09	094°	2044 x 45	PCN 68/F/B/X/T Asphalt	374123.24N 0265404.88E 374118.44N 0265525.20E 36.91 M	THR: 5.75 M / 18.87 FT TDZ: NIL
27	274°	2044 x 45	PCN 68/F/B/X/T Asphalt	374118.44N 0265525.20E 374123.41N 0265402.02E 36.91 M	THR: 3.38 M / 11.07 FT TDZ: NIL

Designations RWY NR	Slope of RWY-SWY	SWY dimensions (M)	CWY dimensions (M)	Strip dimensions (M)	RESA dimensions (M)	OFZ	Remarks
1	7	8	9	10	11	12	13
09	-0.19%/+0.13%/-0.21% (720M) (520M) (804M)	NIL	NIL	2164 x 150	NIL	NIL	See relevant LGSM AD and AOC charts-ICAO
27	+0.21%/-0.13%/+0.19% (804M) (520M) (720M)	NIL	NIL	2164 x 150	NIL	NIL	

LGSM AD 2.13 DECLARED DISTANCES

RWY Designator	TORA (M)	TODA (M)	ASDA (M)	LDA (M)	Remarks
1	2	3	4	5	6
09	2044	2044	2044	1974	THR RWY 09 displaced 70 M.
27	2044	2044	2044	2044	NIL

LGSM AD 2.14 APPROACH AND RUNWAY LIGHTING

RWY Designator	APCH LGT Type Length Intensity	THR LGT Colour Wingbars	PAPI VASIS Angle (MEHT)	TDZ, LGT Length	RWY Centre-line LGT Length Spacing, Colour Intensity	RWY edge LGT Length Spacing Colour Intensity	RWY End LGT Colour Wingbars	SWY LGT Length Colour	Remarks
1	2	3	4	5	6	7	8	9	10
09	Simple approach lighting system. 420 M with a crossbar at 300 M LIH	- Green	PAPI / Left 3° 28.5' (17.18 M)	NIL	NIL	2164 M, 60 M spacing, White (last 600 M Yellow), LIH	Red -	NIL	Blue LED TWY edge lights on both RWY turn pads. PAPI both RWYs slewed 5 DEG to the South. PAPI Range limited to 2 NM due to high terrain
27	NIL	Green -	PAPI / Left 3° 30' (17.16 M)	NIL	NIL	2164 M, 60 M spacing, White (last 600 M Yellow), LIH	Red -	NIL	

LGSM AD 2.15 OTHER LIGHTING, SECONDARY POWER SUPPLY

1	ABN/IBN location, characteristics and operational hours	ABN: At the Tower building, ALTN FLG green and white, every 6 SEC, HO: HN and IMC. IBN: At the Tower building, FLG green, coding "SAM", every 30 SEC, LED. HO: HN and IMC.
2	LDI location and LGT Anemometer location and LGT	LDI: NIL. WDI: 2 WDI, lighted, LED. Anemometer: Two anemometers, one abeam each RWY threshold - lighted.
3	TWY edge and centre line lighting	TWY Edge A1, A2, A3: Blue LED. TWY Edge D, E: NIL.
4	Secondary power supply/switch-over time	Available / 0 SEC (UPS available).
5	Remarks	Apron: Flood lights LED. Flares in extraordinary cases.

LGSM AD 2.16 HELICOPTER LANDING AREA

1	Coordinates TLOF or THR of FATO Geoid undulation	NIL
2	TLOF and/or FATO elevation M/FT	NIL
3	TLOF and FATO area dimensions, surface, strength, marking	NIL
4	True BRG of FATO	NIL
5	Declared distance available	NIL
6	APP and FATO lighting	NIL
7	Remarks	See **LGSM AD 2.20.4**

LGSM AD 2.17 ATS AIRSPACE

1	Designation and lateral limits	SAMOS / ARISTARCHOS OF SAMOS CTR: Circle, 10 NM radius centred at 374121N 0265444E, limited to East by ATHINAI - ISTANBUL FIR boundaries.
		SAMOS / ARISTARCHOS OF SAMOS ATZ: Circle, 5 NM radius centred at 374121N 0265444E, limited to East by ATHINAI - ISTANBUL FIR boundaries.
2	Vertical limits	CTR: SFC to 5000 FT ALT.
		ATZ: SFC to 2000 FT ALT.
3	Airspace classification	Class D.
4	ATS unit call sign Language(s)	CTR: SAMOS APPROACH Greek, English.
		ATZ: SAMOS TOWER Greek, English.
5	Transition altitude	7000 FT.
6	Remarks	For SAMOS TMA see **ENR 2.1.5.13**

LGSM AD 2.18 ATS COMMUNICATION FACILITIES

Service designation	Call sign	Frequency/ VHF CH	Operational hours	Remarks
1	**2**	**3**	**4**	**5**
APP	SAMOS APPROACH	124.100 122.100 257.800 MHz 121.500 243.000 MHz	HO HO HO HO HO	Primary freq. Coverage FL 100 / 25 NM. RGA. MIL RGA. Emergency. MIL Emergency.
TWR	SAMOS TOWER	129.850 122.100 257.800 MHz 121.500 243.000 MHz	HO HO HO HO HO	Primary freq. Coverage FL 040 / 25 NM. RGA. MIL RGA. Emergency. MIL Emergency.
G/A/G	SAMOS RADIO	5637 kHz 2989 kHz	HO: 0400 – 1700 HO: 1700 – 0400	Primary freq. Primary freq.
ATIS (ARR / DEP)	SAMOS ARISTARCHOS OF SAMOS AIRPORT INFORMATION	127.055	HO	Coverage FL 200 / 60 NM.
ATS Communication Facilities: HF & VHF under responsibility of HASP, MIL frequencies under responsibility of HAF. For ATIS see also **ENR 1.1**				

LGSM AD 2.19 RADIO NAVIGATION AND LANDING AIDS

Type of aid MAG VAR CAT of ILS/MLS (For VOR/ILS/MLS, give declination)	ID	Frequency (CH)	Hours of operation	Position of transmitting antenna coordinates	Elevation of DME transmitting antenna	Remarks
1	2	3	4	5	6	7
SAMOS VOR/DME (5°E/2024) (5°E)	SAM	111.60 MHz (CH 53X)	H24	374111.85N 0265425.48E	36 FT / 10.93 M	Coverage FL 200 / 25 NM
SAMOS NDB (5°E/2024)	SMO	375 kHz	H24	374118.52N 0265423.20E	-	Coverage 25 NM
All Radio Navigation and Landing Aids under responsibility of HASP. See also **GEN 2.5** and **ENR 4.1**.						

LGSM AD 2.20 LOCAL TRAFFIC REGULATIONS

2.20.1 Airport regulations

2.20.1.1 Flight Schedule Data Collection Process (Commercial Flights, excluding GA/BA)

All airlines planning to operate at the airport shall send their schedules preferably in IATA SSIM Chapter 6 or 7 format to the following e-mail address: flightscheduling@fraport-greece.com. More information and Guidelines for flight Schedule Data collection are also available at https://www.fraport-greece.com/en/our-expertise/aviation/flight-schedules.html.

2.20.1.2 GA/BA and non-commercial flights

a) Due to operational reasons, prior permission (PPR) must be obtained through the FG PPR Platform for all GA/BA and non-commercial flights before the scheduled departure of the flight. PPR must match with the scheduled times of the flight otherwise it must be updated accordingly. PPRs that will not be used must be immediately cancelled. PPR requests should be communicated through a Ground Handling Services Provider or a Local Representative. Detailed guidelines are available on: https://www.fraport-greece.com/en/our-expertise/aviation/ppr-procedure-and-guidelines.html.
b) On the above restriction, the following categories are exempted:
   - SAR flights and airplanes in state of emergency
   - Ambulance flights operated with state aircraft
   - Flights of aircraft rendering assistance or being on a mission in disasters.
c) Suitable tow head and towbar for pushback is mandatory for all aircraft types. Towbar is not mandatory for light aircraft up to 2000Kgs
d) Minimum ground time allowed is 20 min for all GA/BA aircraft excluding helicopters
e) During adverse weather conditions with strong prevailing winds, all GA/BA aircraft shall be properly secured, under the responsibility of the aircraft operator. For Long Ground Times all GA/BA aircrafts shall be secured, regardless of the prevailing weather.

2.20.1.3 Higher code letter aircraft requests

To operate with a Higher Code Letter aircraft at LGSM Airport (Aerodrome reference code 4D, RFF category 7), aircraft carriers shall submit relevant request via e-mail to: anocdm@fraport-greece.com. The request shall be made at least 10 days before the date planned and shall contain the following data:
- Aircraft type.
- Required RFF category.
- Expected date and time.

2.20.1.4 ATC may request engine start-up on the parking position in order to expedite traffic. Also a pilot may request engine start-up on the parking position for operational reasons. Prior of clearance, ATC shall inform airport operator to monitor the procedure. In such cases, single engine start-up in idle power shall be performed. During engine start up at parking stand the aircraft operator and/or the ground service provider are responsible to safeguard the area around the aircraft in order to prevent personnel and/or vehicle passing behind running engine.

2.20.1.5 Maintenance run-up tests above idle require prior permission by the airport operator. No designated area available. Suitable area will be allocated subject to space availability.

2.20.1.6 During winter season (NOV-APR) aircraft may be parked in a roll-through manner parallel to the terminal disregarding parking position markings, following marshaller instructions. Aircraft are allowed to taxi only at the indispensable engine power and speed. A relevant NOTAM will be issued. Follow Me guidance shall be provided.

2.20.2 Taxiing to and from stands

2.20.2.1 Procedures for arriving aircraft

2.20.2.1.1 All taxiing instructions are issued by ATC via VHF communication

2.20.2.1.2 The parking stand allocation is the responsibility of the Airport Operations Control Center and is communicated to crew through ATC along with taxi instructions.

2.20.2.1.3 No docking system available, parking is permitted only under the instructions of a marshaller. If marshaller is not in sight, aircraft shall hold position until the marshaller is present. Crew shall adhere to marshaller's instructions. Marshalling is under the responsibility of the ground service provider.

2.20.2.1.4 Non-published and unmarked parking areas may also be assigned for parking. In such cases aircraft will be guided by Follow Me and marshalling signals.

2.20.2.2 Procedures for departing aircraft

2.20.2.2.1 Aircraft may leave nose-in parking positions only with the aid of a towing truck. Power back using reverse thrust for jet-powered aircraft or reverse variable pitch for propeller aircraft shall not be used unless (and under extreme circumstances) prior approval has been obtained by the airport operator.

2.20.2.2.2 Taxi-out or pushback clearance may be requested only if the pilot can perform the manoeuver immediately. ATC may cancel taxi-out or pushback clearance if the procedure has been delayed and this delay affects other traffic.

2.20.2.2.3 When pilot request taxi-out or pushback they shall indicate the parking position.

2.20.2.2.4 Pushback and engine start procedure

a) Pilot shall request start-up clearance and pushback by ATC. Following pilot request for push-back clearance, ATC will provide permission and instructions regarding the direction (facing) of the aircraft. Default facing according to RWY in use is given to the below table:

RWY in use	Facing
09	West
27	East

b) Start-up of engines shall be performed either during pushback after the service road has been cleared or when the aircraft is aligned on the Aircraft Stand Taxilane A.
c) Cross-bleeding start-up is not permitted on the parking stand and can only be performed on the Aircraft Stand Taxilane A and/or RWY according to ATC instructions. The request for cross-bleeding start-up should be timely communicated to the Airport Operations Control Center through the aircraft operator and/or the ground service provider.
d) During pushback procedure, aircraft from any parking position is aligned on the Aircraft Stand Taxilane A and positioned with the nose gear abeam the lead-in line of the position it is vacating.
e) In order to facilitate and/or expedite traffic, ATC may request from aircraft to perform long / extended pushback or to be pulled forward with the nose gear positioned abeam the lead-in line of any adjacent parking position.
f) For parking position 1, default facing is west. When east winds of more than 15kt prevail at the airport, pilot may request engine start-up on the parking position. The aircraft operator and/or the ground service provider is responsible to safeguard the area around the aircraft in order to prevent personnel or vehicle to pass behind running engines.

2.20.2.2.5 Push-back procedure cannot take place simultaneously in any adjacent positions.

20.2.2.2.6 Aircraft parked at roll-through positions or in a roll-through manner in an area of the apron, shall use own power (idle power) to taxi-out and shall adhere to marshaller's instructions. Follow Me vehicle guidance may be provided upon Pilot or ATC request.

2.20.2.3 Towing of aircraft

2.20.2.3.1 Towing of aircraft is executed only with the aid of a Follow Me vehicle and requires prior coordination and permission by ATC

2.20.3 Parking area for small aircraft (General aviation)

2.20.3.1 Follow Me vehicle guidance and marshalling signals shall be provided to all aircraft taxiing to general aviation parking area.

2.20.3.2 For departing aircraft from general aviation parking positions the presence of a marshaller is mandatory. Aircraft shall adhere to the marshaller's instructions

2.20.4 Parking area for helicopters

2.20.4.1 No heliport available, helicopters will be advised to proceed to an area suitable for parking. The allocation of the parking area is the responsibility of the airport operator, subject to apron space availability and will be communicated to arriving helicopters through ATC.

2.20.5 Apron - taxiing during winter conditions

NIL

2.20.6 Taxiing – limitations

NIL

2.20.7 School and training flights - technical test flights - use of runways

2.20.7.1 For School, Training and Test flights that require use of the apron, Prior Permission (PPR) by the airport operator is required prior departure from the airport of origin. In addition, prior approval from the ATC is required.

2.20.7.2 For runway use only (touch & go) prior approval from the ATC is required and approval by the airport operator via e-mail at SMIdm@fraport-greece.com.

2.20.8 Helicopter traffic – limitation

NIL

2.20.9 Removal of disabled aircraft from runways

2.20.9.1 Iron Tire aircraft recovery dolly with load capacity 4,500 kg and towing capacity 9,000 kg.

2.20.10 Operation of advanced surveillance system

2.20.10.1 In order to cooperate with the Mode-S based Advanced Surveillance System, aircraft operators intending to use LGSM airport shall ensure that the Mode S transponder is able to operate when the aircraft is on the ground.

2.20.10.1.1 Pilots shall:

a) Select AUTO mode and the assigned Mode A code.

b) If AUTO mode is not available, select ON (e.g. XPDR) and the assigned Mode A code:

i. from the request for towed push-back or taxi, whichever is earlier

ii. after landing, continuously until the aircraft is fully parked in its stand;

iii. when the aircraft is fully parked, they shall select STBY

2.20.10.1.2 Whenever the aircraft is capable of reporting Aircraft Identification (i.e. call sign used in flight), this should be entered (through the FMS or the Transponder Control Panel) at the time of the request for towed push-back or taxi, whichever is earlier.

2.20.10.1.3 Air crew must use the ICAO defined format to enter the Aircraft Identification.

2.20.10.1.4 To ensure that the performance of systems based on SSR frequencies (including airborne TCAS units and SSR radars) is not compromised, TCAS should not be selected before receiving clearance to line up, and should be deselected after vacating the runway.

LGSM AD 2.21 NOISE ABATEMENT PROCEDURES

Part I

2.21.1 Noise abatement procedures for jet aeroplanes irrespective of weight, and for propeller and turboprop aeroplanes with MTOM of or above 11 000 KG

2.21.1.1 General provisions

NIL

2.21.1.2 Use of the runway system during the day period 0600-2200 (0500-2100)

NIL

2.21.1.3 Use of the runway system during the night period 2200-0600 (2100-0500)

NIL

2.21.1.4 Restrictions

NIL

2.21.1.5 Reporting

NIL

Part II

2.21.2 Noise abatement procedures for propeller and turboprop aeroplanes with MTOM below 11 000 KG

2.21.2.1 Use of the runway system during the day period 0600-2300 (0500-2200)

NIL

2.21.2.2 Use of the runway system during the night period 2300-0600 (2200-0500)

NIL

2.21.2.3 Reporting

NIL

Part III

2.21.3 Noise abatement procedures for helicopters

2.21.3.1 General provisions

NIL

2.21.3.2 Use of the runway system during the day period 0600-2300 (0500-2200)

NIL

2.21.3.3 Use of the runway system during the night period 2300-0600 (local time)

NIL

2.21.3.4 Reporting

NIL

LGSM AD 2.22 FLIGHT PROCEDURES

2.22.1 General

2.22.1.1 Local flights not permitted.

2.22.1.2 All manoeuvres to the South due to high terrain north of airport.

2.22.1.3 Pilots should exercise caution when North winds of 20 - 25 KT speed prevail as it is certain that moderate or severe turbulence will be experienced when approaching RWY 09 or RWY 27 respectively. This phenomenon coincides with that of a tail wind component during descent on either RWY approach area. When the wind speed is increased an aggravation of the above conditions should be expected with possible vertical wind shear during landing or take-off. Especially for RWY 27, when north wind above 20 KT prevails, unpredictable and dangerous conditions should be expected during the approach procedure, due to severe wind shear and turbulence.

2.22.2 Runway in use

NIL

2.22.3 Procedures for IFR flights within SAMOS TMA

2.22.3.1 See relevant LGSM IAC charts – ICAO (LGSM AD 2.24)

2.22.4 Radar procedures within SAMOS TMA

NIL

2.22.5 Procedures for VFR flights within SAMOS TMA

2.22.5.1 See relevant LGSM VFR routes chart (LGSM AD 2.24).

2.22.6 Procedures for VFR flights within SAMOS ARISTARCHOS OF SAMOS CTR

2.22.6.1 See relevant LGSM VFR chart (LGSM AD 2.24).

2.22.7 Standard instrument departure procedure (SID)

2.22.7.1 See relevant LGSM SID charts (LGSM AD 2.24).

LGSM AD 2.23 ADDITIONAL INFORMATION

2.23.1 Wildlife Hazard Management

a. A diversity of wildlife species may be found at LGSM airport and its close vicinity. Currently, 99 bird species (either resident or migratory bird species) and 2 mammal species have been recorded at LGSM airport.

b. The presence and behavior of wildlife species at LGSM airport is monitored in regular intervals, daily, from dawn to dusk. Some of the wildlife control methods applied at LGSM airport are: distress calls (bioacoustics), digital sounds, anti-bird laser, etc. Preventive long-term actions that are mainly related to habitat management measures (e.g. grass cutting, water body management) are also taken to further reduce the presence of species constituting a risk to flight safety. In addition, a NOTAM is published and regularly updated.

c. **Yellow-legged gull (*Larus michahellis*),** is the most common bird species monitored and controlled at LGSM airport. Yellow-legged gull is a large gull species with a mass of 1.5kg. It is resident on Samos island, but its presence at LGSM airport is more intense in spring and during rainy weather conditions. Flocks of 30-50 Yellow-legged gulls are usually observed at the maneuvering area. They mainly fly north upon the application of wildlife control methods.

d. **Golden jackals (*Canis aureus*),** may be observed all over the year at LGSM airport. They mainly move south or north upon the application of wildlife control methods and they are rarely involved in wildlife strikes.

e. **Yellow-legged gulls** suffered strikes on aircraft at a height of 0-35ft above ground level in the period 17 April 2017-2022.

2.23.2 Accepted deviations in aerodrome certificate

Specification	Description of Non-Compliance	Deviation type
B.015 Runways Number, siting and orientation of runways	SMI has a single RWY 09/27 Wind data show a general wind direction North significant crosswind conditions prevail occasionally	Special Condition
B.065 Longitudinal slopes changes on RWYs	(c)(1) non-compliant: multiple areas exceed slope changes of 0,1%/30m (max. value on RWY 09: 1065-1080m 0.8%), 345-375m average 0.4%/30m, 720-750m average 0.34%/30m, 795-960m average 0.38%/30m, 1050-1140m average 0.57%/30m, 1800-1875m average 0.3%/30m	Special Condition
B.080 Transverse slopes on RWYs	(b)(1) non-compliant: acc to aerial survey data marginal exceedings of trans slope limitation ascertained mostly on southern side RWY 09 ascertained (min.-max. value: -0.8% up to -2.1% 800-2044m), marginal exceeding north side 1800-2044m (average value: 1.8%)	Special Condition
B.095 Runway turn pads	The turn pads of Runway 09/27 do not conform to the typical turn pad layout. As a consequence, the straight portion of the runway turn pad marking is not parallel to the outer edge of the runway turn pad.	ELoS
B.130 Runways Slopes on runway shoulders	According to new topographical plan, transverse slopes on southern side of RWY 09 exceed limitations (max. value 4.3% at about 500m from RWY 09, value of 3.7% at several spots such as 570m, 710m, 750m from RWY 09 etc.) At northern side of RWY 09 the max. value is 3.2% at about 970m. Limitations are being exceeded with a value of 2.7% at about 1120m, 1929m and at 1500m.	Special Condition
B.160 Runways Width of runway strip	(c)(1) non-compliant: 75m wide (laterally measured from RWY C/L) RWY strip is published within the AIP ADC. RWY is classified as 4D, which requires 150m wide (laterally measured from RWY C/L) RWY strip.	Special Condition
B.180 Longitudinal slopes on RWY strips	(b)(1) non-compliant: longitudinal slopes exceed the limitation at the north-west edge RWY strip near drainage channel behind motorway (max value: -2.5%)	Special Condition
C.210 Runway End Safety Areas	No RESA established at both RWY ends	Special Condition
D.260 TWY Minimum separation Distance	(b) non-compliant: Aircraft stand taxilane is too close to RWY (approx. 100m) instead of 176m	Special Condition
L.590 Aircraft stand marking	The stop line marking of the aircraft stands indicates the intended nose wheel position of the parked aircraft.	ELoS
M.615 General	(c) non-compliant: at intersection with TWYs A2 and A3 RELs are inset but not flush with the surface (approx. 5cm)	ELoS
M.670 Runway threshold identification lights	(a) non-compliant: RTILs for THR 27 are installed at distance from line of RELs approx. 23m (instead of 10m)	ELoS

Specification	Description of Non-Compliance	Deviation type
M.675 RWY Edge lights	(b)(4) non-compliant: acc. to aerial survey data and onsite visit, distance between THRs and first light unit is approx. 86m instead of 60m, which is the distance of the other light units.	ELoS
M.680 RWY Threshold and wing bar lights	(b)(4) (ii) non-compliant: lights are symmetrically disposed about the runway centre line in two groups; gap is too large (approx. 24m instead of 18m (gauge of TDZ marking).	ELoS
M.745 Visual Aids for Navigation - Lights RWY Guard lights	(b)(2) non-compliant: no RWY guard lights installed.	ELoS

2.23.3 Exchange of Data with Network Manager Operations Center (NMOC) - Advanced ATC TWR

2.23.3.1 LGSM exchanges information for departure flights by applying the Advanced ATC TWR procedures. Message exchange from the local system to the ATM network complies with the European standard for A-CDM airports, using the following message types:

- A-DPI: ATC departure planning information message, for all IFR departure flights.
- C-DPI: Cancel DPI, cancellation of departure planning information, when required.

When the aircraft is off-blocks and starts to exit the stand, the TTOT is calculated and transmitted to NMOC via an A-DPI message. After reception of the A-DPI message, DLA or CHG messages that change the flight plan data shall not be accepted. If the flight is regulated, the CTOT assigned before receiving the A-DPI shall be maintained. If an aircraft has to abort taxiing, a C-DPI message shall be sent to the NMOC. The result of the C-DPI is that the flight shall be suspended by informing the operator via an FLS (flight suspension message) with the comment “suspended by departure airport”. The flight plan can be activated again by updating the EOBT with a DLA or CHG message.

LGSM AD 2.24 CHARTS RELATED TO AERODROME

Chart name	Date	Page
Aerodrome Chart – ICAO: - SAMOS / ARISTARCHOS OF SAMOS Airport	29 OCT 26	AD 2-LGSM-ADC
Aircraft Parking/ Docking Chart – ICAO: - SAMOS / ARISTARCHOS OF SAMOS	13 JUN 24	AD 2- LGSM-APDC
Aerodrome Obstacle Chart (AOC) - ICAO, Type A: - RWY 09/27 / LGSM AOC A	17 SEP 15	AD 2-LGSM-AOC A
Aerodrome Obstacle Chart (AOC) – ICAO, Type B: -	NIL	NIL
Precision Approach Terrain Chart – ICAO: -	NIL	NIL
Instrument Approach Chart (IAC) – ICAO: VOR/DME	11 JUL 24	AD 2-LGSM-IAC-1
Visual Approach Chart (VAC) – ICAO: -	NIL	NIL
Standard Departure Chart - Instrument (SID) – ICAO: - RWY 09/27	11 JUL 24	AD 2-LGSM-SID-1
Standard Arrival Chart - Instrument (STAR) – ICAO: - RWY 09/27	11 JUL 24	AD 2-LGSM-STAR-1
TMA – VFR routes: - VFR routes SAMOS TMA	17 APR 25	AD 2-LGSM-VFR

LGSM AD 2.25 VISUAL SEGMENT SURFACE (VSS) PENETRATION