

Non-Native Arithmetic via CRT Codes

Devcon 7

Liam Eagen
Alpen Labs

November 14, 2024

Recap SNARKs

- Succinct Non-interactive ARgument of Knowledge

Recap SNARKs

- Succinct Non-interactive ARgument of Knowledge
- Allow a Prover to convince a Verifier they *know* some witness

Recap SNARKs

- Succinct Non-interactive ARgument of Knowledge
- Allow a Prover to convince a Verifier they *know* some witness
- Witness satisfies some relation $C(x, w) = 1$

Recap SNARKs

- Succinct Non-interactive ARgument of Knowledge
- Allow a Prover to convince a Verifier they *know* some witness
- Witness satisfies some relation $C(x, w) = 1$
- For example, x chain state, w transaction, $C(x, w) = 1$ iff valid

Recap SNARKs

- Succinct Non-interactive ARgument of Knowledge
- Allow a Prover to convince a Verifier they *know* some witness
- Witness satisfies some relation $C(x, w) = 1$
- For example, x chain state, w transaction, $C(x, w) = 1$ iff valid
- Relation defined via a circuit over some *finite field* \mathbb{F}_p

Recap SNARKs

- Succinct Non-interactive ARgument of Knowledge
 - Allow a Prover to convince a Verifier they *know* some witness
 - Witness satisfies some relation $C(x, w) = 1$
 - For example, x chain state, w transaction, $C(x, w) = 1$ iff valid
 - Relation defined via a circuit over some *finite field* \mathbb{F}_p
- Field is sometimes a “free” parameter (e.g. FRI), sometimes fixed (e.g. KZG)

Non-native Arithmetic

- What if the relation is over the wrong field?

Non-native Arithmetic

- What if the relation is over the wrong field?
- For example, w is a secp256k1 signature, but F_p is BN254?

Non-native Arithmetic

- What if the relation is over the wrong field?
- For example, w is a secp256k1 signature, but F_p is BN254?
- Secp signatures defined over $F_r \neq F_p$

Non-native Arithmetic

- What if the relation is over the wrong field?
- For example, w is a secp256k1 signature, but F_p is BN254?
-
- Secp signatures defined over $F_r \neq F_p$

Need to *simulate* F_r arithmetic in F_p

Non-native Arithmetic

- What if the relation is over the wrong field?
- For example, w is a secp256k1 signature, but F_p is BN254?
-
- Secp signatures defined over $F_r \neq F_p$
- Need to *simulate* F_r arithmetic in F_p
Very simple example: let $p = 5$ and $r = 7$

Non-native Arithmetic

- What if the relation is over the wrong field?
 - For example, w is a secp256k1 signature, but F_p is BN254?
 - Secp signatures defined over $F_r \neq F_p$
 - Need to *simulate* F_r arithmetic in F_p
- Very simple example: let $p = 5$ and $r = 7$
- Want to check $4 \times 5 = 20 \equiv 6 \pmod{7}$ in F_r

Non-native Arithmetic

- What if the relation is over the wrong field?
 - For example, w is a secp256k1 signature, but F_p is BN254?
 - Secp signatures defined over $F_r \neq F_p$
 - Need to *simulate* F_r arithmetic in F_p
- Very simple example: let $p = 5$ and $r = 7$
- Want to check $4 \times 5 = 20 \equiv 6 \pmod{7}$ in F_r
 - Naive approach fails $4 \times 5 = 20 \equiv 0 \not\equiv 6 \pmod{5}$

Non-native Arithmetic

Is it possible?

- What can we do?

Non-native Arithmetic

Is it possible?

- What can we do?
- Arithmetic circuits are NP-complete, so it is possible

Non-native Arithmetic

Is it possible?

- What can we do?
- Arithmetic circuits are NP-complete, so it is possible
- For example, encode as binary digits

Non-native Arithmetic

Is it possible?

- What can we do?
- Arithmetic circuits are NP-complete, so it is possible
- For example, encode as binary digits
 - In any field we can check $x = 0, 1$ via $x^2 - x = 0$

Non-native Arithmetic

Is it possible?

- What can we do?
- Arithmetic circuits are NP-complete, so it is possible
- For example, encode as binary digits
 - In any field we can check $x = 0, 1$ via $x^2 - x = 0$
 - Can check bitwise operations

Non-native Arithmetic

Is it possible?

- What can we do?
- Arithmetic circuits are NP-complete, so it is possible
- For example, encode as binary digits
 - In any field we can check $x = 0, 1$ via $x^2 - x = 0$
 - Can check bitwise operations
 - Can we do this more efficiently?

Reduction to Integer Relations

- If we can check (bounded) *integer* relations, can check *modular* relations

Reduction to Integer Relations

- If we can check (bounded) *integer* relations, can check *modular* relations
- $ab \equiv c \pmod{r} \iff \exists q \in \mathbb{Z} : ab - c = rq$

Reduction to Integer Relations

- If we can check (bounded) *integer* relations, can check *modular* relations
- $ab \equiv c \pmod{r} \Leftrightarrow \exists q \in \mathbb{Z} : ab - c = rq$
- Thus, sufficient to check integer relations

Reduction to Integer Relations

- If we can check (bounded) *integer* relations, can check *modular* relations
 - $ab \equiv c \pmod{r} \Leftrightarrow \exists q \in \mathbb{Z} : ab - c = rq$
 - Thus, sufficient to check integer relations
- In some cases, this is sufficient to simulate F' directly

Reduction to Integer Relations

- If we can check (bounded) *integer* relations, can check *modular* relations
- $ab \equiv c \pmod r \iff \exists q \in \mathbb{Z} : ab - c = rq$
- Thus, sufficient to check integer relations
- In some cases, this is sufficient to simulate F' directly
- “Small” elements of F behave like \mathbb{Z}

Reduction to Integer Relations

- If we can check (bounded) *integer* relations, can check *modular* relations
- $ab \equiv c \pmod{r} \Leftrightarrow \exists q \in \mathbb{Z} : ab - c = rq$
- Thus, sufficient to check integer relations
- In some cases, this is sufficient to simulate F' directly
- “Small” elements of F behave like \mathbb{Z}

If $|ab - c - rq| < p$ and $ab - c - rq = 0 \pmod{p}$ then $ab = c \pmod{r}$

Reduction to Integer Relations

- If we can check (bounded) *integer* relations, can check *modular* relations
- $ab \equiv c \pmod r \iff \exists q \in \mathbb{Z} : ab - c = rq$
- Thus, sufficient to check integer relations
- In some cases, this is sufficient to simulate F' directly
- “Small” elements of F behave like \mathbb{Z}
- If $|ab - c - rq| < p$ and $ab - c - rq = 0 \pmod p$ then $ab = c \pmod r$
If $r < \sqrt{p/2}$, sufficient for $|a|, |b|, |c|, |q| < \sqrt{p/2}$

Residue Number Systems

- What if $r > \sqrt{p}$? Or even $r > p$?

Residue Number Systems

- What if $r > \sqrt{p}$? Or even $r > p$?
- Encodings of “mod r ” values into \mathbb{F}_p no longer behave like \mathbb{Z}

Residue Number Systems

- What if $r > \sqrt{p}$? Or even $r > p$?
- Encodings of “mod r ” values into \mathbb{F}_p no longer behave like \mathbb{Z}
Might not even be possible at all (when $r > p$)

Residue Number Systems

- What if $r > \sqrt{p}$? Or even $r > p$?
-
- Encodings of “mod r ” values into F_p no longer behave like Z
- Might not even be possible at all (when $r > p$)

Solution: use the Chinese Remainder Theorem (CRT)

Residue Number Systems

- What if $r > \sqrt{p}$? Or even $r > p$?
- Encodings of “mod r ” values into \mathbb{F}_p no longer behave like \mathbb{Z}
- Might not even be possible at all (when $r > p$)
- Solution: use the Chinese Remainder Theorem (CRT)
Says $\mathbb{Z}/(ab)\mathbb{Z} \approx \mathbb{Z}/a\mathbb{Z} \times \mathbb{Z}/b\mathbb{Z}$ if $\gcd(a, b) = 1$

Residue Number Systems

- What if $r > \sqrt{p}$? Or even $r > p$?
-
- Encodings of “mod r ” values into F_p no longer behave like Z
- Might not even be possible at all (when $r > p$)
- Solution: use the Chinese Remainder Theorem (CRT)
- Says $Z/(ab)Z \approx Z/aZ \times Z/bZ$ if $\gcd(a, b) = 1$

Can represent a number via a set of residues $x = x_i \bmod p_i$

Residue Number Systems

- What if $r > \sqrt{p}$? Or even $r > p$?
- Encodings of “mod r ” values into \mathbb{F}_p no longer behave like \mathbb{Z}
- Might not even be possible at all (when $r > p$)
- Solution: use the Chinese Remainder Theorem (CRT)
- Says $\mathbb{Z}/(ab)\mathbb{Z} \approx \mathbb{Z}/a\mathbb{Z} \times \mathbb{Z}/b\mathbb{Z}$ if $\gcd(a, b) = 1$
- Can represent a number via a set of residues $x = x_i \bmod p_i$
Use CRT to uniquely recover x

Residue Number Systems

- What if $r > \sqrt{p}$? Or even $r > p$?
- Encodings of “mod r ” values into \mathbb{F}_p no longer behave like \mathbb{Z}
- Might not even be possible at all (when $r > p$)
- Solution: use the Chinese Remainder Theorem (CRT)
- Says $\mathbb{Z}/(ab)\mathbb{Z} \approx \mathbb{Z}/a\mathbb{Z} \times \mathbb{Z}/b\mathbb{Z}$ if $\gcd(a, b) = 1$
- Can represent a number via a set of residues $x = x_i \bmod p_i$
Use CRT to uniquely recover x

Now, just need x small compared to $M = \prod_i p_i$

Reed-Solomon Codes

- Recall Reed-Solomon (RS) codes

Reed-Solomon Codes

- Recall Reed-Solomon (RS) codes
- Treat k vector as a degree $k - 1$ polynomial $f(X)$

Reed-Solomon Codes

- Recall Reed-Solomon (RS) codes
- Treat k vector as a degree $k - 1$ polynomial $f(X)$
- Encode by evaluating at $n > k$ distinct points

Reed-Solomon Codes

- Recall Reed-Solomon (RS) codes
- Treat k vector as a degree $k - 1$ polynomial $f(X)$
- Encode by evaluating at $n > k$ distinct points
- Given these n points, can recover $f(X)$

Reed-Solomon Codes

- Recall Reed-Solomon (RS) codes
- Treat k vector as a degree $k - 1$ polynomial $f(X)$
- Encode by evaluating at $n > k$ distinct points
- Given these n points, can recover $f(X)$
- Can even recover $f(X)$ if some of the points are wrong

CRT Codes

- Evaluating a polynomial $f(r_i)$ is equivalent to reducing $f(X) = f(r_i) \bmod X - r_i$

CRT Codes

- Evaluating a polynomial $f(r_i)$ is equivalent to reducing $f(X) = f(r_i) \bmod X - r_i$
- This lets us generalize RS codes to other ideal domains

CRT Codes

- Evaluating a polynomial $f(r_i)$ is equivalent to reducing $f(X) = f(r_i) \bmod X - r_i$
- This lets us generalize RS codes to other ideal domains
- For example, Algebraic Geometry codes

CRT Codes

- Evaluating a polynomial $f(r_i)$ is equivalent to reducing $f(X) = f(r_i) \bmod X - r_i$
- This lets us generalize RS codes to other ideal domains
- For example, Algebraic Geometry codes

Also CRT codes

CRT Codes

- Evaluating a polynomial $f(r_i)$ is equivalent to reducing $f(X) = f(r_i) \bmod X - r_i$
- This lets us generalize RS codes to other ideal domains
- For example, Algebraic Geometry codes
- Also CRT codes

Treat our message as a bounded integer $x < M$

CRT Codes

- Evaluating a polynomial $f(r_i)$ is equivalent to reducing $f(X) = f(r_i) \bmod X - r_i$
- This lets us generalize RS codes to other ideal domains
- For example, Algebraic Geometry codes
- Also CRT codes
- Treat our message as a bounded integer $x < M$
Encode by reducing modulo many small p_i

Protocol Sketch

- Suppose we want to verify some non-native arithmetic
- That is $f(x_1, \dots, x_k) = 0$ over \mathbb{Z} where $\max_i f_i = d$ and $|x_j| < B$
 - 1 Fix some p_1, \dots, p_ℓ where $M = \prod_a p_a > B^d$
 - 2 Commit to $x_j = y_{j,a} \bmod p_a$
 - 3 Commit to $q_{i,a}$ such that $f_i(y_{1,a}, \dots, y_{k,a}) = p_a q_{i,a}$
 - 4 Prove each $(y_{i,a})_{a=1}^\ell$ corresponds to $|x_i| < B$
 - 5 Choose a random subset of primes and test
- Assuming the primes similar size, easy to compute success probability of dishonest prover
- Spiritually similar to STARKs like FRI, Ligerio, etc.

Protocol Sketch

- Suppose we want to verify some non-native arithmetic
- That is $f(x_1, \dots, x_k) = 0$ over \mathbb{Z} where $\max_i f_i = d$ and $|x_j| < B$
 - 1 Fix some p_1, \dots, p_a where $M = \prod_a p_a > B^d$
 - 2 Commit to $x_j = y_j \bmod p_a$
 - 3 Commit to $q_{i,a}$ such that $f_i(y_1, \dots, y_k) = p_a q_{i,a}$
 - 4 Prove each $(y_{i,a})_i$ corresponds to $|x_j| < B$

Protocol Sketch

- Suppose we want to verify some non-native arithmetic
- That is $f(x_1, \dots, x_k) = 0$ over \mathbb{Z} where $\max_i f_i = d$ and $|x_j| < B$
 - 1 Fix some p_1, \dots, p_a where $M = \prod_a p_a > B^{d^d}$
 - 2 Commit to $x_j = y_j \bmod p_a$
 - 3 Commit to $q_{j,a}$ such that $f_j(y_1, \dots, y_k) = p_a q_{j,a}$
 - 4 Prove each $(y_{j,a})^d$ corresponds to $|x_j| < B$
 - 5 Choose a random subset of primes and test

Protocol Sketch

- Suppose we want to verify some non-native arithmetic
- That is $f(x_1, \dots, x_k) = 0$ over \mathbb{Z} where $\max_i f_i = d$ and $|x_j| < B$
 - 1 Fix some p_1, \dots, p_a where $M = \prod_a p_a > B^{d^k}$
 - 2 Commit to $x_j = y_{j,a} \bmod p_a$
 - 3 Commit to $q_{j,a}$ such that $f_j(y_{1,a}, \dots, y_{k,a}) = p_a q_{j,a}$
 - 4 Prove each $(y_{j,a})^k$ corresponds to $|x_j| < B$
 - 5 Choose a random subset of primes and test
- Assuming the primes similar size, easy to compute success probability of dishonest prover

Protocol Sketch

- Suppose we want to verify some non-native arithmetic
- That is $f(x_1, \dots, x_k) = 0$ over \mathbb{Z} where $\max_i f_i = d$ and $|x_j| < B$
 - 1 Fix some p_1, \dots, p_a where $M = \prod_a p_a > B^{d^d}$
 - 2 Commit to $x_j = y_j \bmod p_a$
 - 3 Commit to $q_{i,a}$ such that $f_i(y_1, \dots, y_k) = p_a q_{i,a}$
 - 4 Prove each $(y_{j,a})^d$ corresponds to $|x_j| < B$
 - 5 Choose a random subset of primes and test
- Assuming the primes similar size, easy to compute success probability of dishonest prover
- Spiritually similar to STARKs like FRI, Ligerio, etc.

Ongoing Work: Proximity Gaps

- Step 4 of the protocol tests each $(y_{i,a})$ is a valid codeword

Ongoing Work: Proximity Gaps

- Step 4 of the protocol tests each $(y_{i,a})$ is a valid codeword
- STARKs used to do this, now use a batched proximity test

Ongoing Work: Proximity Gaps

- Step 4 of the protocol tests each $(y_{i,a})$ is a valid codeword
- STARKs used to do this, now use a batched proximity test
- Remarkably, if a *random linear combination* (RLC) of codewords is *close* to a code word, all the combined codewords are *also close*

Ongoing Work: Proximity Gaps

- Step 4 of the protocol tests each $(y_{i,a})$ is a valid codeword
- STARKs used to do this, now use a batched proximity test
- Remarkably, if a *random linear combination* (RLC) of codewords is *close* to a code word, all the combined codewords are *also close*
- Idea: can we take a RLC of the x_j ?

Ongoing Work: Proximity Gaps

- Step 4 of the protocol tests each $(y_{i,a})$ is a valid codeword
- STARKs used to do this, now use a batched proximity test
- Remarkably, if a *random linear combination* (RLC) of codewords is *close* to a code word, all the combined codewords are *also close*
- Idea: can we take a RLC of the x_j ?
- Yes! but more complex

What I Haven't Discussed

- Subtleties of CRT code distance since p_i different sizes

What I Haven't Discussed

- Subtleties of CRT code distance since p_i different sizes
- Decoding to rationals of bounded height rather than integers

What I Haven't Discussed

- Subtleties of CRT code distance since p_i different sizes
- Decoding to rationals of bounded height rather than integers
- Using number fields instead of rationals

What I Haven't Discussed

- Subtleties of CRT code distance since p_i different sizes
- Decoding to rationals of bounded height rather than integers
- Using number fields instead of rationals
- Technicalities related to this like size, etc.

What I Haven't Discussed

- Subtleties of CRT code distance since p_i different sizes
 - Decoding to rationals of bounded height rather than integers
 - Using number fields instead of rationals
 - Technicalities related to this like size, etc.
- Applications of techniques to STARKs over small fields (i.e. without extensions)

Thanks!